

The Photos of SAR test

No. I15Z42559-SEM01

For

TCT Mobile Limited HSUPA/HSDPA/UMTS tribands / GSM quadbands/LTE 6-band mobile phone

Model name: 7048W

With

Hardware Version: PIO

Software Version: v7F1V_2

FCC ID: RAD558

Issued Date: 2015-11-04




Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.


Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191 Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504


Email: cttl terminals@catr.cn, website: www.chinattl.com




Picture 1: Constituents of the sample




Picture 2: Left Hand Touch Cheek Position



Picture 3: Left Hand Tilt 15° Position




Picture 4: Right Hand Touch Cheek Position




Picture 5: Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 6 test positions all with the distance =10mm between the EUT and the phantom bottom:



Picture 6: Front




Picture 7: Rear




Picture 8: Left Edge



Picture 9: Right Edge



Picture 10: Bottom Edge



Picture 11: Top Edge