## Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at device output terminal:		(dBm)	
Cable and Jumper loss		(dB)	
Maximum peak output power at antenna input terminal:		(dBm)	
Maximum peak output power at antenna input terminal:		• • •	
Single Antenna gain(typical):	12	(dBi)	See note below
Number of Antennae	2	_	
Total Antenna gain(typical):	15.01029996	(dBi)	
Maximum antenna gain:	31.69786385	(numeric)	)
Prediction distance:	20	(cm)	
Prediction frequency:	5570	(MHz)	
MPE limit for uncontrolled exposure at prediction frequency:		(mW/cm^2)	
Power density at prediction frequency:	0.198957	(mW/cm^	2)
	1.989574	(W/m^2)	
Tx On time:	1.000000	. ,	
Tx period time:	1.000000		
Average Factor:			
Average Power density at prediction frequency:	1.989574	(W/m^2)	
Maximum allowable antenna gain:	22.02269855	· · ·	
ganne ga		()	
Margin of Compliance:	7.012398597	dB	

Note: Antenna gain: 12 dBi + 10 × log10 (2) dB = 15 dBi