

FCC Test Report

Report No.: RFBCMA-WTW-P21010371

FCC ID: RAXCM4642342

Test Model: CM4642342XXX

Series Model: CG4634XXXXXX

(where X character can be replaced by either alphanumeric character between A and Z and between 0 and 9 or “-“ or “.” or “blank”)

Received Date: Dec. 22, 2020

Test Date: Dec. 22, 2020 to Feb. 02, 2021

Issued Date: Feb. 24, 2021

Applicant: Arcadyan Technology Corporation

Address: No.8, Sec.2, Guangfu Rd., Hsinchu City 30071, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	10
3.2.1 Test Mode Applicability and Tested Channel Detail.....	11
3.3 Duty Cycle of Test Signal	13
3.4 Description of Support Units	14
3.4.1 Configuration of System under Test	15
3.5 General Description of Applied Standards and References	16
4 Test Types and Results	17
4.1 Radiated Emission and Bandedge Measurement.....	17
4.1.1 Limits of Radiated Emission and Bandedge Measurement	17
4.1.2 Test Instruments	18
4.1.3 Test Procedures.....	20
4.1.4 Deviation from Test Standard	21
4.1.5 Test Setup.....	21
4.1.6 EUT Operating Conditions.....	22
4.1.7 Test Results	23
4.2 Conducted Emission Measurement	37
4.2.1 Limits of Conducted Emission Measurement	37
4.2.2 Test Instruments	37
4.2.3 Test Procedures.....	38
4.2.4 Deviation from Test Standard	38
4.2.5 Test Setup.....	38
4.2.6 EUT Operating Conditions.....	38
4.2.7 Test Results	39
4.3 6dB Bandwidth Measurement	41
4.3.1 Limits of 6dB Bandwidth Measurement	41
4.3.2 Test Setup.....	41
4.3.3 Test Instruments	41
4.3.4 Test Procedure	41
4.3.5 Deviation from Test Standard	41
4.3.6 EUT Operating Conditions.....	41
4.3.7 Test Result.....	42
4.4 Conducted Output Power Measurement.....	44
4.4.1 Limits of Conducted Output Power Measurement	44
4.4.2 Test Setup.....	44
4.4.3 Test Instruments	44
4.4.4 Test Procedures.....	44
4.4.5 Deviation from Test Standard	44
4.4.6 EUT Operating Conditions.....	44
4.4.7 Test Results	45
4.5 Power Spectral Density Measurement.....	49
4.5.1 Limits of Power Spectral Density Measurement	49
4.5.2 Test Setup.....	49
4.5.3 Test Instruments	49
4.5.4 Test Procedure	49
4.5.5 Deviation from Test Standard	49
4.5.6 EUT Operating Condition	49

4.5.7 Test Results	50
4.6 Conducted Out of Band Emission Measurement.....	52
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	52
4.6.2 Test Setup.....	52
4.6.3 Test Instruments	52
4.6.4 Test Procedure	52
4.6.5 Deviation from Test Standard	52
4.6.6 EUT Operating Condition	52
4.6.7 Test Results	52
5 Pictures of Test Arrangements.....	65
Annex A - Band-Edge Measurement.....	66
Appendix – Information of the Testing Laboratories	70

Release Control Record

Issue No.	Description	Date Issued
RFBCMA-WTW-P21010371	Original release.	Feb. 24, 2021

1 Certificate of Conformity

Product: DOCSIS® 3.1 Dual-Band AX5660 Wi-Fi 6 Cable Gateway

Brand: XTREAM

Test Model: CM4642342XXX

Series Model: CG4634XXXXXX

(where X character can be replaced by either alphanumeric character between A and Z and between 0 and 9 or “-“ or “.” or “blank”)

Sample Status: ENGINEERING SAMPLE

Applicant: Arcadyan Technology Corporation

Test Date: Dec. 22, 2020 to Feb. 02, 2021

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Cherry Chuo, **Date:** Feb. 24, 2021
Cherry Chuo/ Specialist

Approved by : Clark Lin, **Date:** Feb. 24, 2021
Clark Lin / Technical Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -18.18dB at 0.34141MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2484.86MHz, 2484.09MHz and 2386.56MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

Note:

- For 2.4GHz band compliance with rule 15.247(d) of the band-edge items, the test plots were recorded in Annex A. Test Procedures refer to report 4.1.3.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.9 dB
Conducted Emissions	-	2.5 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.1 dB
	30MHz ~ 1GHz	5.1 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.1 dB
	18GHz ~ 40GHz	5.3 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	DOCSIS® 3.1 Dual-Band AX5660 Wi-Fi 6 Cable Gateway
Brand	XTREAM
Test Model	CM4642342XXX
Series Model	CG4634XXXXXX (where X character can be replaced by either alphanumeric character between A and Z and between 0 and 9 or “-“ or “.” or “blank”)
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	12Vdc from power adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT20/40 in 2.4GHz 1024QAM for OFDMA in 11ax HE mode
Modulation Technology	DSSS,OFDM, OFDMA
Transfer Rate	802.11b: up to 11 Mbps 802.11a/g: up to 54 Mbps 802.11n: up to 600 Mbps 802.11ac: up to 1733.3 Mbps 802.11ax: up to 2401.9 Mbps
Operating Frequency	2.4GHz: 2.412GHz ~ 2.462GHz 5GHz: 5.18 ~ 5.24GHz, 5.745 ~ 5.825GHz
Number of Channel	2.4GHz: 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7 5GHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 9 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 4 802.11ac (VHT80), 802.11ax (HE80): 2
Output Power	CDD Mode: 2.412 ~ 2.462 GHz: 986.76 mW 5.18 ~ 5.24 GHz: 990.208 mW 5.745 ~ 5.825 GHz: 972.881 mW Beamforming Mode: 2.412 ~ 2.462 GHz: 935.568 mW 5.18 ~ 5.24 GHz: 567.847 mW 5.745 ~ 5.825 GHz: 567.273 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x1
Data Cable	NA

Note:

1. The EUT has two radios as following table:

Radio 1	Radio 2
WLAN 2.4GHz	WLAN 5GHz

2. Simultaneously transmission condition.

Condition	Technology	
1	WLAN 2.4GHz	WLAN 5GHz

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The EUT has below model names, which are identical to each other in all aspects except for the following information:

Brand	Model No.	Differences
XTREAM	CM4642342XXX	NA
	CG4634XXXXXX (where X character can be replaced by either alphanumeric character between A and Z and between 0 and 9 or “-“ or “.” or “blank”)	For marketing reason the same product will be covered by different name.

From the above models, model: **CM4642342XXX** was selected as representative model for the test and its data was recorded in this report.

4. The EUT must be supplied with a power adapter as following table:

Brand	Model No.	Spec.
HONOTO	ADS-36FKJ-12 12036EPCU	AC Input: 100-240Vac, 1A, 50/60Hz DC Output: 12V, 3.0A DC Output Cable: 1.5m unshielded

5. The antennas provided to the EUT, please refer to the following table:

Ant. No	RF Chain No.	Ant. Net Gain (dBi)	Freq. Range (GHz)	Ant. Type	Connector Type
1	2.4GHz Chain 0	1.83	2.4~2.4835	PCB	none
2	2.4GHz Chain 1	0.03	2.4~2.4835	PCB	none
3	2.4GHz Chain 2	1.97	2.4~2.4835	PCB	none
4	5GHz Chain 0	1.81	5.15~5.85	PCB	none
5	5GHz Chain 1	3.32	5.15~5.85	PCB	none
6	5GHz Chain 2	2.37	5.15~5.85	PCB	none
7	5GHz Chain 3	2.07	5.15~5.85	PCB	none

6. The EUT incorporates a MIMO function:

MODULATION MODE	2.4GHz Band	
	TX & RX CONFIGURATION	
802.11b	3TX	3RX
802.11g	3TX	3RX
802.11n (HT20)	3TX	3RX
802.11n (HT40)	3TX	3RX
VHT20	3TX	3RX
VHT40	3TX	3RX
802.11ax (HE20)	3TX	3RX
802.11ax (HE40)	3TX	3RX
5GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
	4TX	4RX
802.11a	4TX	4RX
802.11n (HT20)	4TX	4RX
802.11n (HT40)	4TX	4RX
802.11ac (VHT20)	4TX	4RX
802.11ac (VHT40)	4TX	4RX
802.11ac (VHT80)	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
802.11ax (HE80)	4TX	4RX

Note:

1. All of modulation mode support beamforming function except 802.11a/b/g modulation mode.
 2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
 3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz), VHT mode for 20MHz (40MHz) and 802.11ax mode for 20MHz (40MHz), therefore the manufacturer will control the power for 802.11n/ VHT mode is the same as the 802.11ax mode or more lower than it and investigated worst case to representative mode in test report. (Final test mode refer to section 3.2.1)
7. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.
 8. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20 and 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40), VHT40 and 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE≥1G: Radiated Emission above 1GHz &
Bandedge Measurement RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of laying-flat and Standing Plane. The worst case was found when positioned of on **Standing Plane**.

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11g	1 to 11	6	OFDM	BPSK	6Mb/s

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11g	1 to 11	6	OFDM	BPSK	6Mb/s

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
VHT20 (Output power only)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40 (Output power only)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0
Beamforming Mode (output power only)					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
VHT20	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 68%RH	120Vac, 60Hz	Benson Chao
RE<1G	22deg. C, 66%RH	120Vac, 60Hz	Benson Chao
PLC	25deg. C, 71%RH	120Vac, 60Hz	Sampson Chen
APCM	25deg. C, 60%RH	120Vac, 60Hz	Eric Peng

3.3 Duty Cycle of Test Signal


If duty cycle of test signal is $\geq 98\%$, duty factor is not required.

802.11b: Duty cycle = 2.974 ms / 3.001 ms=0.991

802.11g: Duty cycle = 2.969 ms / 3.004 ms=0.988

802.11ax (HE20): Duty cycle = 2.317 ms / 2.353 ms=0.985

802.11ax (HE40): Duty cycle = 2.399 ms / 2.436 ms=0.985



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E6420	482T3R1	FCC DoC	Provided by Lab
B.	Laptop	DELL	E5430	GM1SKV1	FCC DoC	Provided by Lab
C.	Switch	D-Link	DGS-1005D	DR8WC92000523	NA	Provided by Lab
D.	Telephone	ROMEO	TE-812	97280903	NA	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	1.5	No	0	Supplied by client
2.	RJ-11 Cable	1	10	No	0	Provided by Lab
3.	Coaxial Cable	1	10	Yes	0	Provided by Lab
4.	RJ-45 Cable	1	10	No	0	Provided by Lab
5.	RJ-45 Cable	1	10	No	0	Provided by Lab
6.	RJ-45 Cable	1	10	No	0	Provided by Lab

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{uV}/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

**4.1.2 Test Instruments
For Radiated emission test**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESR7	102026	Apr. 22, 2020	Apr. 21, 2021
Spectrum Analyzer Keysight	N9030B	MY57141948	May 22, 2020	May 21, 2021
Pre-Amplifier EMCI	EMC001340	980142	May 25, 2020	May 24, 2021
Loop Antenna Electro-Metrics	EM-6879	264	Feb. 18, 2020	Feb. 17, 2021
RF Cable	5D-FB	LOOPCAB-001	Jan. 07, 2021	Jan. 06, 2022
RF Cable	5D-FB	LOOPCAB-002	Jan. 07, 2021	Jan. 06, 2022
Pre-Amplifier EMCI	EMC330N	980538	Apr. 28, 2020	Apr. 27, 2021
Trilog Broadband Antenna SCHWARZBECK	VULB9168	9168-0842	Nov. 03, 2020	Nov. 02, 2021
RF Cable	8D	966-5-1	Apr. 29, 2020	Apr. 28, 2021
RF Cable	8D	966-5-2	Apr. 29, 2020	Apr. 28, 2021
RF Cable	8D	966-5-3	Apr. 29, 2020	Apr. 28, 2021
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-02	Jan. 11, 2021	Jan. 10, 2022
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-1819	Nov. 22, 2020	Nov. 21, 2021
Pre-Amplifier EMCI	EMC12630SE	980509	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-1500	180503	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-2000	180501	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-6000	180506	Apr. 29, 2020	Apr. 28, 2021
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 11, 2021	Jan. 10, 2022
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 22, 2020	Nov. 21, 2021
RF Cable	EMC102-KM-KM-1200	160924	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC-KM-KM-4000	200214	Mar. 11, 2020	Mar. 10, 2021
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 5.
3. Tested Date: Jan. 18 to Feb. 01, 2021

For Bandedge test

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESR7	102026	Apr. 22, 2020	Apr. 21, 2021
Spectrum Analyzer Keysight	N9030B	MY57141948	May 22, 2020	May 21, 2021
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-1819	Nov. 22, 2020	Nov. 21, 2021
Pre-Amplifier EMCI	EMC12630SE	980509	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-1500	180503	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-2000	180501	Apr. 29, 2020	Apr. 28, 2021
RF Cable EMCI	EMC104-SM-SM-6000	180506	Apr. 29, 2020	Apr. 28, 2021
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 15, 2020	Jan. 14, 2021
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 22, 2020	Nov. 21, 2021
RF Cable	EMC102-KM-KM-1200	160924	Jan. 15, 2020	Jan. 14, 2021
RF Cable	EMC-KM-KM-4000	200214	Mar. 11, 2020	Mar. 10, 2021
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 5.
3. Tested Date: Dec. 22, 2020

For other test

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	May 29, 2020	May 28, 2021
Power meter Anritsu	ML2495A	1529002	July 22, 2020	July 21, 2021
Power sensor Anritsu	MA2411B	1339443	July 22, 2020	July 21, 2021
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 14, 2020	Apr. 13, 2021
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Feb. 02, 2021

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Connected the EUT with the Laptop which is placed on remote site.
- Controlling software (CM4642342_MM.rtf) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

ABOVE 1GHz DATA

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.5 PK	74.0	-8.5	1.05 H	220	68.5	-3.0
2	2390.00	53.8 AV	54.0	-0.2	1.05 H	220	56.8	-3.0
3	*2412.00	122.7 PK			1.05 H	220	125.6	-2.9
4	*2412.00	119.3 AV			1.05 H	220	122.2	-2.9
5	4824.00	43.8 PK	74.0	-30.2	1.50 H	117	42.4	1.4
6	4824.00	38.4 AV	54.0	-15.6	1.50 H	117	37.0	1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.58	62.3 PK	74.0	-11.7	3.38 V	142	65.3	-3.0
2	2387.58	51.8 AV	54.0	-2.2	3.38 V	142	54.8	-3.0
3	*2412.00	118.2 PK			3.38 V	142	121.1	-2.9
4	*2412.00	115.8 AV			3.38 V	142	118.7	-2.9
5	4824.00	46.9 PK	74.0	-27.1	3.81 V	69	45.5	1.4
6	4824.00	42.7 AV	54.0	-11.3	3.81 V	69	41.3	1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	62.4 PK	74.0	-11.6	1.26 H	325	65.4	-3.0
2	2390.00	50.0 AV	54.0	-4.0	1.26 H	325	53.0	-3.0
3	*2437.00	122.9 PK			1.26 H	325	125.8	-2.9
4	*2437.00	119.5 AV			1.26 H	325	122.4	-2.9
5	2483.50	63.1 PK	74.0	-10.9	1.26 H	325	66.1	-3.0
6	2483.50	50.7 AV	54.0	-3.3	1.26 H	325	53.7	-3.0
7	4874.00	45.5 PK	74.0	-28.5	1.50 H	110	44.2	1.3
8	4874.00	37.8 AV	54.0	-16.2	1.50 H	110	36.5	1.3
9	7311.00	43.9 PK	74.0	-30.1	1.78 H	307	37.0	6.9
10	7311.00	35.4 AV	54.0	-18.6	1.78 H	307	28.5	6.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.2 PK	74.0	-12.8	2.13 V	175	64.2	-3.0
2	2390.00	48.5 AV	54.0	-5.5	2.13 V	175	51.5	-3.0
3	*2437.00	114.6 PK			2.13 V	175	117.5	-2.9
4	*2437.00	112.3 AV			2.13 V	175	115.2	-2.9
5	2483.50	60.9 PK	74.0	-13.1	2.13 V	175	63.9	-3.0
6	2483.50	48.6 AV	54.0	-5.4	2.13 V	175	51.6	-3.0
7	4874.00	48.2 PK	74.0	-25.8	1.87 V	85	46.9	1.3
8	4874.00	45.0 AV	54.0	-9.0	1.87 V	85	43.7	1.3
9	7311.00	45.8 PK	74.0	-28.2	2.13 V	181	38.9	6.9
10	7311.00	38.7 AV	54.0	-15.3	2.13 V	181	31.8	6.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	123.1 PK			1.00 H	218	126.1	-3.0
2	*2462.00	119.5 AV			1.00 H	218	122.5	-3.0
3	2483.80	65.0 PK	74.0	-9.0	1.00 H	218	68.0	-3.0
4	2483.80	53.1 AV	54.0	-0.9	1.00 H	218	56.1	-3.0
5	4924.00	45.3 PK	74.0	-28.7	1.44 H	116	43.8	1.5
6	4924.00	37.6 AV	54.0	-16.4	1.44 H	116	36.1	1.5
7	7386.00	43.5 PK	74.0	-30.5	1.81 H	297	36.3	7.2
8	7386.00	35.4 AV	54.0	-18.6	1.81 H	297	28.2	7.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	118.6 PK			2.64 V	356	121.6	-3.0
2	*2462.00	116.3 AV			2.64 V	356	119.3	-3.0
3	2488.67	64.0 PK	74.0	-10.0	2.64 V	356	67.0	-3.0
4	2488.67	52.9 AV	54.0	-1.1	2.64 V	356	55.9	-3.0
5	4924.00	46.3 PK	74.0	-27.7	1.96 V	88	44.8	1.5
6	4924.00	42.8 AV	54.0	-11.2	1.96 V	88	41.3	1.5
7	7386.00	45.0 PK	74.0	-29.0	2.04 V	176	37.8	7.2
8	7386.00	38.7 AV	54.0	-15.3	2.04 V	176	31.5	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2388.50	73.4 PK	74.0	-0.6	1.16 H	221	76.4	-3.0
2	2388.50	53.1 AV	54.0	-0.9	1.16 H	221	56.1	-3.0
3	*2412.00	117.8 PK			1.16 H	221	120.7	-2.9
4	*2412.00	107.6 AV			1.16 H	221	110.5	-2.9
5	4824.00	43.4 PK	74.0	-30.6	1.44 H	111	42.0	1.4
6	4824.00	39.3 AV	54.0	-14.7	1.44 H	111	37.9	1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2388.97	70.7 PK	74.0	-3.3	1.74 V	355	73.7	-3.0
2	2388.97	51.8 AV	54.0	-2.2	1.74 V	355	54.8	-3.0
3	*2412.00	114.8 PK			1.74 V	355	117.7	-2.9
4	*2412.00	105.5 AV			1.74 V	355	108.4	-2.9
5	4824.00	44.8 PK	74.0	-29.2	1.94 V	102	43.4	1.4
6	4824.00	40.8 AV	54.0	-13.2	1.94 V	102	39.4	1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.7 PK	74.0	-8.3	1.12 H	330	68.7	-3.0
2	2390.00	50.8 AV	54.0	-3.2	1.12 H	330	53.8	-3.0
3	*2437.00	123.7 PK			1.12 H	330	126.6	-2.9
4	*2437.00	113.2 AV			1.12 H	330	116.1	-2.9
5	2483.50	68.2 PK	74.0	-5.8	1.12 H	330	71.2	-3.0
6	2483.50	52.0 AV	54.0	-2.0	1.12 H	330	55.0	-3.0
7	4874.00	43.5 PK	74.0	-30.5	1.47 H	118	42.2	1.3
8	4874.00	37.6 AV	54.0	-16.4	1.47 H	118	36.3	1.3
9	7311.00	41.3 PK	74.0	-32.7	1.80 H	320	34.4	6.9
10	7311.00	35.7 AV	54.0	-18.3	1.80 H	320	28.8	6.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.5 PK	74.0	-10.5	1.67 V	356	66.5	-3.0
2	2390.00	48.6 AV	54.0	-5.4	1.67 V	356	51.6	-3.0
3	*2437.00	120.5 PK			1.67 V	356	123.4	-2.9
4	*2437.00	109.9 AV			1.67 V	356	112.8	-2.9
5	2483.50	65.0 PK	74.0	-9.0	1.67 V	356	68.0	-3.0
6	2483.50	50.2 AV	54.0	-3.8	1.67 V	356	53.2	-3.0
7	4874.00	45.3 PK	74.0	-28.7	3.35 V	79	44.0	1.3
8	4874.00	40.8 AV	54.0	-13.2	3.35 V	79	39.5	1.3
9	7311.00	43.3 PK	74.0	-30.7	2.13 V	172	36.4	6.9
10	7311.00	37.9 AV	54.0	-16.1	2.13 V	172	31.0	6.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	119.9 PK			1.07 H	219	122.9	-3.0
2	*2462.00	109.5 AV			1.07 H	219	112.5	-3.0
3	2483.77	72.7 PK	74.0	-1.3	1.07 H	219	75.7	-3.0
4	2483.77	53.5 AV	54.0	-0.5	1.07 H	219	56.5	-3.0
5	4924.00	43.9 PK	74.0	-30.1	1.46 H	117	42.4	1.5
6	4924.00	37.1 AV	54.0	-16.9	1.46 H	117	35.6	1.5
7	7386.00	41.9 PK	74.0	-32.1	1.76 H	311	34.7	7.2
8	7386.00	35.6 AV	54.0	-18.4	1.76 H	311	28.4	7.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	116.8 PK			1.59 V	358	119.8	-3.0
2	*2462.00	107.5 AV			1.59 V	358	110.5	-3.0
3	2484.86	70.7 PK	74.0	-3.3	1.59 V	358	73.7	-3.0
4	2484.86	51.6 AV	54.0	-2.4	1.59 V	358	54.6	-3.0
5	4924.00	45.8 PK	74.0	-28.2	1.91 V	103	44.3	1.5
6	4924.00	42.6 AV	54.0	-11.4	1.91 V	103	41.1	1.5
7	7386.00	43.7 PK	74.0	-30.3	2.05 V	172	36.5	7.2
8	7386.00	37.8 AV	54.0	-16.2	2.05 V	172	30.6	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.38	70.6 PK	74.0	-3.4	1.03 H	220	73.6	-3.0
2	2387.38	53.2 AV	54.0	-0.8	1.03 H	220	56.2	-3.0
3	*2412.00	118.5 PK			1.03 H	220	121.4	-2.9
4	*2412.00	106.0 AV			1.03 H	220	108.9	-2.9
5	4824.00	43.6 PK	74.0	-30.4	1.40 H	123	42.2	1.4
6	4824.00	39.3 AV	54.0	-14.7	1.40 H	123	37.9	1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2388.78	67.5 PK	74.0	-6.5	1.41 V	8	70.5	-3.0
2	2388.78	52.3 AV	54.0	-1.7	1.41 V	8	55.3	-3.0
3	*2412.00	115.2 PK			1.41 V	8	118.1	-2.9
4	*2412.00	105.7 AV			1.41 V	8	108.6	-2.9
5	4824.00	44.3 PK	74.0	-29.7	1.91 V	104	42.9	1.4
6	4824.00	40.5 AV	54.0	-13.5	1.91 V	104	39.1	1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	67.4 PK	74.0	-6.6	1.12 H	218	70.4	-3.0
2	2390.00	52.7 AV	54.0	-1.3	1.12 H	218	55.7	-3.0
3	*2437.00	124.8 PK			1.12 H	218	127.7	-2.9
4	*2437.00	112.2 AV			1.12 H	218	115.1	-2.9
5	2483.50	68.5 PK	74.0	-5.5	1.12 H	218	71.5	-3.0
6	2483.50	51.7 AV	54.0	-2.3	1.12 H	218	54.7	-3.0
7	4874.00	43.5 PK	74.0	-30.5	1.44 H	108	42.2	1.3
8	4874.00	37.4 AV	54.0	-16.6	1.44 H	108	36.1	1.3
9	7311.00	40.1 PK	74.0	-33.9	1.75 H	313	33.2	6.9
10	7311.00	35.8 AV	54.0	-18.2	1.75 H	313	28.9	6.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	69.6 PK	74.0	-4.4	1.68 V	6	72.6	-3.0
2	2390.00	51.7 AV	54.0	-2.3	1.68 V	6	54.7	-3.0
3	*2437.00	125.0 PK			1.68 V	6	127.9	-2.9
4	*2437.00	113.1 AV			1.68 V	6	116.0	-2.9
5	2483.50	68.1 PK	74.0	-5.9	1.68 V	6	71.1	-3.0
6	2483.50	51.5 AV	54.0	-2.5	1.68 V	6	54.5	-3.0
7	4874.00	45.2 PK	74.0	-28.8	1.86 V	118	43.9	1.3
8	4874.00	42.3 AV	54.0	-11.7	1.86 V	118	41.0	1.3
9	7311.00	42.9 PK	74.0	-31.1	2.04 V	172	36.0	6.9
10	7311.00	38.2 AV	54.0	-15.8	2.04 V	172	31.3	6.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	119.4 PK			1.00 H	216	122.4	-3.0
2	*2462.00	107.3 AV			1.00 H	216	110.3	-3.0
3	2484.86	73.7 PK	74.0	-0.3	1.00 H	216	76.7	-3.0
4	2484.86	53.9 AV	54.0	-0.1	1.00 H	216	56.9	-3.0
5	4924.00	43.6 PK	74.0	-30.4	1.49 H	118	42.1	1.5
6	4924.00	37.7 AV	54.0	-16.3	1.49 H	118	36.2	1.5
7	7386.00	41.2 PK	74.0	-32.8	1.71 H	319	34.0	7.2
8	7386.00	35.9 AV	54.0	-18.1	1.71 H	319	28.7	7.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	119.0 PK			1.45 V	9	122.0	-3.0
2	*2462.00	106.6 AV			1.45 V	9	109.6	-3.0
3	2484.09	73.1 PK	74.0	-0.9	1.45 V	9	76.1	-3.0
4	2484.09	53.9 AV	54.0	-0.1	1.45 V	9	56.9	-3.0
5	4924.00	45.2 PK	74.0	-28.8	1.91 V	124	43.7	1.5
6	4924.00	40.8 AV	54.0	-13.2	1.91 V	124	39.3	1.5
7	7386.00	43.2 PK	74.0	-30.8	2.06 V	172	36.0	7.2
8	7386.00	38.9 AV	54.0	-15.1	2.06 V	172	31.7	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 3 : 2422 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.56	68.4 PK	74.0	-5.6	1.03 H	219	71.4	-3.0
2	2386.56	53.9 AV	54.0	-0.1	1.03 H	219	56.9	-3.0
3	*2422.00	113.4 PK			1.03 H	219	116.3	-2.9
4	*2422.00	101.0 AV			1.03 H	219	103.9	-2.9
5	4844.00	42.2 PK	74.0	-31.8	1.51 H	110	40.8	1.4
6	4844.00	36.5 AV	54.0	-17.5	1.51 H	110	35.1	1.4
7	7266.00	40.7 PK	74.0	-33.3	1.72 H	315	33.7	7.0
8	7266.00	35.0 AV	54.0	-19.0	1.72 H	315	28.0	7.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.57	67.1 PK	74.0	-6.9	1.32 V	15	70.1	-3.0
2	2386.57	53.6 AV	54.0	-0.4	1.32 V	15	56.6	-3.0
3	*2422.00	113.0 PK			1.32 V	15	115.9	-2.9
4	*2422.00	100.8 AV			1.32 V	15	103.7	-2.9
5	4844.00	44.8 PK	74.0	-29.2	1.90 V	125	43.4	1.4
6	4844.00	39.2 AV	54.0	-14.8	1.90 V	125	37.8	1.4
7	7266.00	43.6 PK	74.0	-30.4	2.00 V	166	36.6	7.0
8	7266.00	36.2 AV	54.0	-17.8	2.00 V	166	29.2	7.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	73.2 PK	74.0	-0.8	1.12 H	330	76.2	-3.0
2	2390.00	53.7 AV	54.0	-0.3	1.12 H	330	56.7	-3.0
3	*2437.00	117.8 PK			1.12 H	330	120.7	-2.9
4	*2437.00	105.2 AV			1.12 H	330	108.1	-2.9
5	2483.50	67.8 PK	74.0	-6.2	1.12 H	330	70.8	-3.0
6	2483.50	51.3 AV	54.0	-2.7	1.12 H	330	54.3	-3.0
7	4874.00	43.6 PK	74.0	-30.4	1.49 H	108	42.3	1.3
8	4874.00	36.5 AV	54.0	-17.5	1.49 H	108	35.2	1.3
9	7311.00	40.5 PK	74.0	-33.5	1.77 H	308	33.6	6.9
10	7311.00	34.9 AV	54.0	-19.1	1.77 H	308	28.0	6.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	71.2 PK	74.0	-2.8	1.77 V	10	74.2	-3.0
2	2390.00	53.4 AV	54.0	-0.6	1.77 V	10	56.4	-3.0
3	*2437.00	117.3 PK			1.77 V	10	120.2	-2.9
4	*2437.00	104.6 AV			1.77 V	10	107.5	-2.9
5	2483.50	67.9 PK	74.0	-6.1	1.77 V	10	70.9	-3.0
6	2483.50	50.5 AV	54.0	-3.5	1.77 V	10	53.5	-3.0
7	4874.00	44.6 PK	74.0	-29.4	1.93 V	130	43.3	1.3
8	4874.00	38.7 AV	54.0	-15.3	1.93 V	130	37.4	1.3
9	7311.00	41.3 PK	74.0	-32.7	2.03 V	152	34.4	6.9
10	7311.00	36.6 AV	54.0	-17.4	2.03 V	152	29.7	6.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 9 : 2452 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	116.7 PK			1.04 H	218	119.6	-2.9
2	*2452.00	103.4 AV			1.04 H	218	106.3	-2.9
3	2483.70	66.2 PK	74.0	-7.8	1.04 H	218	69.2	-3.0
4	2483.70	53.1 AV	54.0	-0.9	1.04 H	218	56.1	-3.0
5	4904.00	43.2 PK	74.0	-30.8	1.55 H	104	41.8	1.4
6	4904.00	36.9 AV	54.0	-17.1	1.55 H	104	35.5	1.4
7	7356.00	39.9 PK	74.0	-34.1	1.77 H	299	32.8	7.1
8	7356.00	34.7 AV	54.0	-19.3	1.77 H	299	27.6	7.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	116.5 PK			1.35 V	8	119.4	-2.9
2	*2452.00	103.7 AV			1.35 V	8	106.6	-2.9
3	2484.41	70.6 PK	74.0	-3.4	1.35 V	8	73.6	-3.0
4	2484.41	53.6 AV	54.0	-0.4	1.35 V	8	56.6	-3.0
5	4904.00	44.3 PK	74.0	-29.7	1.96 V	141	42.9	1.4
6	4904.00	38.5 AV	54.0	-15.5	1.96 V	141	37.1	1.4
7	7356.00	41.0 PK	74.0	-33.0	2.03 V	141	33.9	7.1
8	7356.00	36.8 AV	54.0	-17.2	2.03 V	141	29.7	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	81.17	30.0 QP	40.0	-10.0	2.50 H	89	47.9	-17.9
2	132.10	32.4 QP	43.5	-11.1	2.50 H	68	46.2	-13.8
3	291.53	36.9 QP	46.0	-9.1	1.00 H	140	49.2	-12.3
4	363.79	32.3 QP	46.0	-13.7	1.00 H	360	42.9	-10.6
5	622.46	29.7 QP	46.0	-16.3	1.00 H	153	34.4	-4.7
6	740.95	34.9 QP	46.0	-11.1	1.00 H	157	37.8	-2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	45.76	32.7 QP	40.0	-7.3	1.00 V	360	45.3	-12.6
2	72.88	34.4 QP	40.0	-5.6	1.50 V	106	50.1	-15.7
3	170.22	26.9 QP	43.5	-16.6	1.00 V	37	40.2	-13.3
4	288.47	32.0 QP	46.0	-14.0	2.00 V	148	44.3	-12.3
5	349.97	32.8 QP	46.0	-13.2	1.00 V	59	44.0	-11.2
6	625.71	31.6 QP	46.0	-14.4	1.00 V	68	36.3	-4.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 20, 2020	Oct. 19, 2021
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 27, 2020	Oct. 26, 2021
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 19, 2020	Mar. 18, 2021
50 ohms Terminator	50	3	Oct. 26, 2020	Oct. 25, 2021
RF Cable	5D-FB	COCCAB-001	Sep. 26, 2020	Sep. 25, 2021
Fixed attenuator EMCI	STI02-2200-10	005	Aug. 29, 2020	Aug. 28, 2021
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3. Tested Date: Jan. 30, 2021

4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1. Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)		Detector Function		Quasi-Peak (QP) / Average (AV)	
-------	----------	--	-------------------	--	--------------------------------	--

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.96	31.07	21.84	41.03	31.80	66.00	56.00	-24.97	-24.20
2	0.19297	9.99	27.57	17.24	37.56	27.23	63.91	53.91	-26.35	-26.68
3	0.22422	9.99	27.51	16.27	37.50	26.26	62.66	52.66	-25.16	-26.40
4	0.31797	10.01	28.76	18.24	38.77	28.25	59.76	49.76	-20.99	-21.51
5	5.77734	10.41	23.20	17.37	33.61	27.78	60.00	50.00	-26.39	-22.22
6	16.81641	11.23	18.28	11.48	29.51	22.71	60.00	50.00	-30.49	-27.29

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)		Detector Function		Quasi-Peak (QP) / Average (AV)	
-------	-------------	--	-------------------	--	--------------------------------	--

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.18125	9.97	31.26	19.70	41.23	29.67	64.43	54.43	-23.20	-24.76
2	0.34141	10.00	30.08	20.99	40.08	30.99	59.17	49.17	-19.09	-18.18
3	0.81406	10.05	21.10	14.39	31.15	24.44	56.00	46.00	-24.85	-21.56
4	2.94531	10.19	19.78	11.51	29.97	21.70	56.00	46.00	-26.03	-24.30
5	5.96484	10.37	23.36	17.47	33.73	27.84	60.00	50.00	-26.27	-22.16
6	16.55078	10.99	17.30	10.96	28.29	21.95	60.00	50.00	-31.71	-28.05

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	7.12	7.1	7.09	0.5	PASS
6	2437	7.1	7.1	6.61	0.5	PASS
11	2462	7.08	7.1	7.09	0.5	PASS

802.11g


Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	16.43	16.45	16.44	0.5	PASS
6	2437	16.43	16.41	16.43	0.5	PASS
11	2462	16.46	16.42	16.44	0.5	PASS

802.11ax (HE20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	19.07	18.97	19.01	0.5	PASS
6	2437	19.05	18.89	18.98	0.5	PASS
11	2462	19.04	18.93	19.03	0.5	PASS

802.11ax (HE40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
3	2422	37.89	37.54	37.71	0.5	PASS
6	2437	37.79	37.61	37.77	0.5	PASS
9	2452	37.81	37.52	37.73	0.5	PASS



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

CDD Mode

802.11b

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	24.87	25.29	25.10	968.561	29.86	30	Pass
6	2437	24.60	25.20	24.97	933.585	29.70	30	Pass
11	2462	24.71	25.09	24.84	923.44	29.65	30	Pass

802.11g

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	22.03	21.83	22.31	482.209	26.83	30	Pass
6	2437	25.04	24.86	25.58	986.76	29.94	30	Pass
11	2462	23.42	23.58	24.21	711.453	28.52	30	Pass

VHT20

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	20.17	20.25	20.53	322.897	25.09	30	Pass
6	2437	24.40	24.36	25.33	889.514	29.49	30	Pass
11	2462	22.61	21.74	22.35	503.46	27.02	30	Pass

VHT40

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	18.33	18.20	18.36	202.695	23.07	30	Pass
6	2437	21.54	21.69	21.93	446.087	26.49	30	Pass
9	2452	20.81	20.79	21.23	373.193	25.72	30	Pass

802.11ax (HE20)

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	20.41	20.47	20.74	339.907	25.31	30	Pass
6	2437	24.60	24.61	25.54	935.568	29.71	30	Pass
11	2462	22.86	21.97	22.58	531.729	27.26	30	Pass

802.11ax (HE40)

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	18.56	18.43	18.59	213.719	23.30	30	Pass
6	2437	21.79	21.92	22.16	471.042	26.73	30	Pass
9	2452	21.03	21.02	21.48	393.844	25.95	30	Pass

Beamforming Mode

VHT20

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	20.17	20.25	20.53	322.897	25.09	29.91	Pass
6	2437	24.40	24.36	25.33	889.514	29.49	29.91	Pass
11	2462	22.61	21.74	22.35	503.46	27.02	29.91	Pass

Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 30-(6.09-6) = 29.91dBm.

VHT40

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	18.33	18.20	18.36	202.695	23.07	29.91	Pass
6	2437	21.54	21.69	21.93	446.087	26.49	29.91	Pass
9	2452	20.81	20.79	21.23	373.193	25.72	29.91	Pass

Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 30-(6.09-6) = 29.91dBm.

802.11ax (HE20)

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	20.41	20.47	20.74	339.907	25.31	29.91	Pass
6	2437	24.60	24.61	25.54	935.568	29.71	29.91	Pass
11	2462	22.86	21.97	22.58	531.729	27.26	29.91	Pass

Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 30-(6.09-6) = 29.91dBm.

802.11ax (HE40)

Chan.	Frequency (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	18.56	18.43	18.59	213.719	23.30	29.91	Pass
6	2437	21.79	21.92	22.16	471.042	26.73	29.91	Pass
9	2452	21.03	21.02	21.48	393.844	25.95	29.91	Pass


Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 30-(6.09-6) = 29.91dBm.

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)			Total PSD (mW/3kHz)	Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	-6.67	-6.77	-6.84	0.6327	-1.99	7.91	PASS
6	2437	-7.28	-7.21	-6.76	0.588	-2.31	7.91	PASS
11	2462	-7.54	-6.89	-7.25	0.5692	-2.45	7.91	PASS

Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 8-(6.09-6) = 7.91dBm.

802.11g

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)			Total PSD (mW/3kHz)	Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	-11.62	-11.74	-11.08	0.21384	-6.70	7.91	PASS
6	2437	-8.74	-7.90	-7.95	0.4562	-3.41	7.91	PASS
11	2462	-9.48	-9.71	-9.28	0.3377	-4.71	7.91	PASS

Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 8-(6.09-6) = 7.91dBm.

802.11ax (HE20)


Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)			Total PSD (mW/3kHz)	Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	-13.96	-13.31	-13.77	0.12882	-8.90	7.91	PASS
6	2437	-8.76	-8.99	-9.05	0.3837	-4.16	7.91	PASS
11	2462	-12.33	-11.32	-10.67	0.21797	-6.62	7.91	PASS

Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 8-(6.09-6) = 7.91dBm.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)			Total PSD (mW/3kHz)	Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	-18.92	-18.68	-18.99	0.03899	-14.09	7.91	PASS
6	2437	-15.11	-14.98	-15.12	0.09336	-10.30	7.91	PASS
9	2452	-16.84	-16.45	-15.78	0.06977	-11.56	7.91	PASS

Note: 1. Directional gain=10 log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20})² / 3] = 6.09dBi > 6dBi, so the power density limit shall be reduced to 8-(6.09-6) = 7.91dBm.



4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.


4.6.6 EUT Operating Condition

Same as Item 4.3.6


4.6.7 Test Results

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b




Chain 0




Chain 1


CH 1





CH 6



CH 11




CH 11 Band edge




Chain 2


CH 1





CH 6




CH 11




CH 1 Band edge








802.11g




Chain 0




Chain 1
CH 1

CH 6

CH 11

CH 11 Band edge

CH 11 Band edge


Chain 2


CH 1





CH 6




CH 11




CH 1 Band edge



802.11ax (HE20)




Chain 0




Chain 1


CH 1





CH 6



CH 11




CH 11 Band edge




Chain 2


CH 1





CH 6




CH 11




CH 1 Band edge













802.11ax (HE40)



Chain 0





Chain 1
CH 3

CH 6

CH 9

CH 9 Band edge

CH 9 Band edge



Chain 2
CH 3

CH 6

CH 9

CH 9 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Annex A - Band-Edge Measurement








Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---