




# SPORTON International Inc.

No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.  
Ph: 886-3-656-9065 / FAX: 886-3-656-9085 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	Arcadyan Technology Corporation
Applicant Address	4F, No.9, Park Avenue II, Science-based Industrial Park Hsinchu 300, Taiwan, ROC
FCC ID	RAXWN8522D10

Product Name	IEEE Dual Band 802.11n USB2.0 Module
Brand Name	Arcadyan Technology Corporation
Model Name	WN8522D 10-CP
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Nov. 17, 2011
Final Test Date	Dec. 05, 2011
Submission Type	Original Equipment



### Statement

**Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a (5725 ~ 5850MHz) of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies .....	7
3.5. Table for Test Modes .....	8
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units .....	9
3.8. Table for Parameters of Test Software Setting .....	10
3.9. Test Configurations .....	11
<b>4. TEST RESULT .....</b>	<b>13</b>
4.1. AC Power Line Conducted Emissions Measurement.....	13
4.2. Peak Output Power Measurement .....	17
4.3. Average Output Power Measurement .....	20
4.4. Power Spectral Density Measurement .....	23
4.5. 6dB Spectrum Bandwidth Measurement .....	33
4.6. Radiated Emissions Measurement .....	40
4.7. Band Edge Emissions Measurement .....	66
4.8. Antenna Requirements .....	78
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>79</b>
<b>6. TEST LOCATION.....</b>	<b>81</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>82</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A6</b>
<b>APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE( .....</b>	<b>B1 ~ B3</b>
<b>APPENDIX C. PHOTOGRAPH OF EUT.....</b>	<b>C1 ~ C5</b>



## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR1N1716AB	Rev. 01	Initial issue of report	Dec. 29, 2011



## 1. CERTIFICATE OF COMPLIANCE

Product Name : IEEE Dual Band 802.11n USB2.0 Module  
Brand Name : Arcadyan Technology Corporation  
Model Name : WN8522D 10-CP  
Applicant : Arcadyan Technology Corporation  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 17, 2011 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Jordan Hsiao'.

Jordan Hsiao

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	13.91 dB
4.2	15.247(b)(3)	Peak Output Power	Complies	1.0 dB
4.3	-	Average Output Power	-	-
4.4	15.247(e)	Power Spectral Density	Complies	10.49 dB
4.5	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.6	15.247(d)	Radiated Emissions	Complies	1.38 dB
4.7	15.247(d)	Band Edge Emissions	Complies	1.01 dB
4.8	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: MCS0 (20MHz): 16.64 MHz ; MCS0 (40MHz): 36.24 MHz For 5GHz Band: MCS0 (20MHz): 16.76 MHz ; MCS0 (40MHz): 36.24 MHz
Peak Output Power	For 2.4GHz Band: MCS0 (20MHz): 27.94 dBm ; MCS0 (40MHz): 26.89 dBm For 5GHz Band: MCS0 (20MHz): 27.10 dBm ; MCS0 (40MHz): 25.79 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**802.11a/b/g**

Items	Description
Product Type	802.11b: WLAN ( 1TX, 1RX ) 802.11g: WLAN ( 2TX, 2RX ) 802.11a: WLAN ( 2TX, 2RX )
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 10.12 MHz ; 11g: 14.76 MHz ; 11a: 15.64 MHz
Peak Output Power	11b: 20.28 dBm ; 11g: 27.90 dBm ; 11a: 27.08 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**Antenna & Band width**

Antenna	Single (TX)		Two (TX)	
	20 MHz	40 MHz	20 MHz	40 MHz
Band width Mode				
IEEE 802.11a	X	X	V	X
IEEE 802.11b	V	X	X	X
IEEE 802.11g	X	X	V	X
IEEE 802.11n	X	X	V	V

## IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPS	NCBPS		NDBPS		Datarate(Mbps)			
					20MHz	40MHz	20MHz	40MHz	800nsGI		400nsGI	
									20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

## 3.2. Accessories

N/A



### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)		Remark
					2.4G	5G	
1	-	-	PCB Antenna	NA	4.18	4.62	TX/RX
2	-	-	PCB Antenna	NA	3.99	4.06	TX/RX

Note: The EUT has two Antennas.

**For IEEE 802.11n mode (2TX/2RX) for 5G band:**

Ant. 1 & Ant. 2 could transmit/receive simultaneously.

**For IEEE 802.11a mode (2TX/2RX):**

Ant. 1 & Ant. 2 could transmit/receive simultaneously.

**For IEEE 802.11n mode (2TX/2RX) for 2.4G band:**


Ant. 1 and Ant. 2 could transmit/receive simultaneously.

**For IEEE 802.11g mode (2TX/2RX):**

Ant. 1 and Ant. 2 could transmit/receive simultaneously.

**For IEEE 802.11b mode (1TX/1RX)**

Only Ant. 1 can be use as transmit and receive antenna.



### 3.4. Table for Carrier Frequencies

#### For 2.4GHz Band:

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

#### For 5GHz Band:

For IEEE 802.11a, use Channel 149, 153, 157, 161, 165.

There are two bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	159	5795 MHz
	151	5755 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

#### For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Peak Output Power	MCS0/20MHz	7.2 Mbps	1/6/11	1/2/1+2
Average Output Power	MCS0/40MHz	15 Mbps	3/6/9	1/2/1+2
Power Spectral Density	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1/2/1+2
6dB Spectrum Bandwidth	MCS0/20MHz	7.2 Mbps	1/6/11	1+2
	MCS0/40MHz	15 Mbps	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1+2
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	MCS0/20MHz	7.2 Mbps	1/6/11	1+2
	MCS0/40MHz	15 Mbps	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1/ 2/1+2
Band Edge Emissions	MCS0/20MHz	7.2 Mbps	1/11	1+2
	MCS0/40MHz	15 Mbps	3/9	1+2
	11b/CCK	1 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1/ 2/1+2

**For 5GHz Band**

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Peak Output Power	MCS0/20MHz	7.2 Mbps	149/157/165	1/2/1+2
Average Output Power	MCS0/40MHz	15 Mbps	151/159	1/2/1+2
Power Spectral Density	11a/BPSK	6 Mbps	149/157/165	1/2/1+2
6dB Spectrum Bandwidth	MCS0/20MHz	7.2 Mbps	149/157/165	1+2
	MCS0/40MHz	15 Mbps	151/159	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	MCS0/20MHz	7.2 Mbps	149/157/165	1+2
	MCS0/40MHz	15 Mbps	151/159	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Band Edge Emissions	MCS0/20MHz	7.2 Mbps	149/157/165	1+2
	MCS0/40MHz	15 Mbps	151/159	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2

**3.6. Table for Testing Locations**

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

**3.7. Table for Supporting Units**

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	E2K24GBRL
Notebook	DELL	1340	E2K4965AGNM
Mouse	iCooky	AMS0706W	DoC
Keyboard	BTC	7932	-

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### For 2.4GHz Band

##### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	DOS		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	56	56	56

##### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	DOS		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	50	50	50

##### Power Parameters of IEEE 802.11b/g

Test Software Version	DOS		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	60	60	60
IEEE 802.11g	54	60	56

#### For 5GHz Band

##### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	DOS		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	60	60	60

##### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	DOS	
Frequency	5755 MHz	5795 MHz
MCS0 40MHz	50	50

##### Power Parameters of IEEE 802.11a



Test Software Version	DOS		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	60	60	60

During the test, "DOS" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.


### 3.9. Test Configurations

#### 3.9.1. Radiation Emissions Test Configuration



<30MHz~ 1GHZ>



<Above GHZ>



### 3.9.2. AC Power Line Conduction Emissions Test Configuration



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.



#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	56%
Test Engineer	Sin Chang	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17215	50.60	-14.26	64.86	50.20	0.20	0.20	QP
2	0.17215	38.87	-15.99	54.86	38.47	0.20	0.20	AVERAGE
3	0.23162	42.41	-19.98	62.39	42.08	0.13	0.20	QP
4	0.23162	34.48	-17.91	52.39	34.15	0.13	0.20	AVERAGE
5	0.28782	37.05	-23.53	60.59	36.75	0.10	0.20	QP
6	0.28782	28.93	-21.65	50.59	28.63	0.10	0.20	AVERAGE
7	0.34646	35.28	-23.77	59.05	35.00	0.08	0.20	QP
8	0.34646	27.75	-21.30	49.05	27.47	0.08	0.20	AVERAGE
9	1.961	30.52	-25.48	56.00	30.29	0.04	0.19	QP
10	1.961	28.21	-17.79	46.00	27.98	0.04	0.19	AVERAGE
11	3.806	31.67	-24.33	56.00	31.32	0.05	0.30	QP
12	3.806	20.98	-25.02	46.00	20.63	0.05	0.30	AVERAGE

Temperature	25°C	Humidity	56%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.17384	50.86	-13.91	64.77	50.48	0.18	0.20	QP
2	0.17384	40.40	-14.37	54.77	40.02	0.18	0.20	AVERAGE
3	0.23162	42.89	-19.50	62.39	42.57	0.12	0.20	QP
4	0.23162	32.56	-19.83	52.39	32.24	0.12	0.20	AVERAGE
5	0.28935	42.02	-18.53	60.54	41.72	0.10	0.20	QP
6	0.28935	33.10	-17.45	50.54	32.80	0.10	0.20	AVERAGE
7	0.34683	33.68	-25.36	59.04	33.40	0.08	0.20	QP
8	0.34683	25.74	-23.30	49.04	25.46	0.08	0.20	AVERAGE
9	0.40400	33.81	-23.96	57.77	33.55	0.06	0.20	QP
10	0.40400	27.00	-20.77	47.77	26.74	0.06	0.20	AVERAGE
11	3.749	34.10	-21.90	56.00	33.76	0.04	0.30	QP
12	3.749	23.01	-22.99	46.00	22.67	0.04	0.30	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss

## 4.2. Peak Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the peak power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak

### 4.2.3. Test Procedures

Spectrum Parameter	Setting
RF Output Power Method	<input checked="" type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Peak Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Sean Ku	Configurations	IEEE 802.11n
Test Date	Dec. 05, 2011		

##### For 2.4GHz Band

##### Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
1	2412 MHz	24.59	24.81	27.71	30.00	Complies
6	2437 MHz	24.87	24.99	27.94	30.00	Complies
11	2462 MHz	24.51	24.41	27.47	30.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
3	2422 MHz	24.02	23.42	26.74	30.00	Complies
6	2437 MHz	23.95	23.81	26.89	30.00	Complies
9	2452 MHz	22.81	23.91	26.41	30.00	Complies

##### For 5GHz Band

##### Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
149	5745 MHz	24.27	23.91	27.10	30.00	Complies
157	5785 MHz	24.24	23.68	26.98	30.00	Complies
165	5825 MHz	24.24	23.61	26.95	30.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
151	5755 MHz	23.01	22.41	25.73	30.00	Complies
159	5795 MHz	22.95	22.61	25.79	30.00	Complies

Temperature	25°C	Humidity	56%
Test Engineer	Sean Ku	Configurations	IEEE 802.11a/b/g
Test Date	Dec. 05, 2011		

**Configuration IEEE 802.11b / Ant. 1**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	20.28	30.00	Complies
6	2437 MHz	20.12	30.00	Complies
11	2462 MHz	20.02	30.00	Complies

**Configuration IEEE 802.11g**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
1	2412 MHz	24.55	24.01	27.30	28.90	Complies
6	2437 MHz	24.77	25.01	27.90	28.90	Complies
11	2462 MHz	24.12	24.94	27.56	28.90	Complies

Note: Directional gain =  $10\log [(10^{4.18/20} + 10^{3.99/20})^2 / 2] = 7.1 \text{ dBi} > 6\text{dBi}$ , so the conducted power limit =  $30 - (7.1 - 6) = 28.9 \text{ dBm}$ .

**Configuration IEEE 802.11a**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
149	5745 MHz	24.32	23.81	27.08	28.65	Complies
157	5785 MHz	23.85	23.73	26.80	28.65	Complies
165	5825 MHz	23.88	23.69	26.80	28.65	Complies

Note: Directional gain =  $10\log [(10^{4.62/20} + 10^{4.06/20})^2 / 2] = 7.35 \text{ dBi} > 6\text{dBi}$ , so the conducted power limit =  $30 - (7.35 - 6) = 28.65 \text{ dBm}$ .

### 4.3. Average Output Power Measurement

#### 4.3.1. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

#### 4.3.2. Test Procedures

Spectrum Parameter	Setting
RF Output Power Method	<input checked="" type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging

#### 4.3.3. Test Setup Layout



#### 4.3.4. Test Deviation

There is no deviation with the original standard.

#### 4.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.6. Test Result of Average Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Sean Ku	Configurations	IEEE 802.11n
Test Date	Dec. 05, 2011		

For 2.4GHz Band

Configuration IEEE 802.11n MCS8 20MHz

Channel	Frequency	Average Conducted Power (dBm)		
		Ant. 1	Ant. 2	Total
1	2412 MHz	15.61	15.01	18.33
6	2437 MHz	15.66	15.41	18.55
11	2462 MHz	14.66	14.07	17.39

Configuration IEEE 802.11n MCS8 40MHz

Channel	Frequency	Average Conducted Power (dBm)		
		Ant. 1	Ant. 2	Total
3	2422 MHz	13.22	12.91	16.08
6	2437 MHz	13.31	12.85	16.10
9	2452 MHz	12.9	12.79	15.86

For 5GHz Band

Configuration IEEE 802.11n MCS8 20MHz

Channel	Frequency	Average Conducted Power (dBm)		
		Ant. 1	Ant. 2	Total
149	5745 MHz	16.49	16.22	19.37
157	5785 MHz	16.55	15.69	19.15
165	5825 MHz	16.63	15.88	19.28

Configuration IEEE 802.11n MCS8 40MHz

Channel	Frequency	Average Conducted Power (dBm)		
		Ant. 1	Ant. 2	Total
151	5755 MHz	13.83	13.37	16.62
159	5795 MHz	13.81	13.48	16.66



<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Sean Ku	<b>Configurations</b>	IEEE 802.11a/b/g
<b>Test Date</b>	Dec. 05, 2011		

**Configuration IEEE 802.11b / Ant. 1**

Channel	Frequency	Average Conducted Power (dBm)
1	2412 MHz	16.33
6	2437 MHz	16.20
11	2462 MHz	16.04

**Configuration IEEE 802.11g**

Channel	Frequency	Average Conducted Power (dBm)		
		Ant. 1	Ant. 2	Total
1	2412 MHz	15.50	14.10	17.87
6	2437 MHz	15.83	15.53	18.69
11	2462 MHz	14.70	15.50	18.13

**Configuration IEEE 802.11a**

Channel	Frequency	Average Conducted Power (dBm)		
		Ant. 1	Ant. 2	Total
149	5745 MHz	16.42	15.86	19.16
157	5785 MHz	16.03	15.97	19.01
165	5825 MHz	16.25	15.94	19.11

## 4.4. Power Spectral Density Measurement

### 4.4.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30 kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.
5. When measuring power spectral density with multiple antenna systems, add every result of the values by mathematic formula.

### 4.4.4. Test Setup Layout



### 4.4.5. Test Deviation

There is no deviation with the original standard.

### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of Power Spectral Density

Temperature	25°C%	Humidity	56%
Test Engineer	Sean Ku	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
1	2412 MHz	-7.27	-10.20	-5.48	8.00	Complies
6	2437 MHz	-9.25	-9.73	-6.47	8.00	Complies
11	2462 MHz	-8.27	-10.16	-6.10	8.00	Complies

Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
3	2422 MHz	-14.47	-13.85	-11.14	8.00	Complies
6	2437 MHz	-13.52	-12.55	-10.00	8.00	Complies
9	2452 MHz	-13.83	-13.58	-10.69	8.00	Complies

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
149	5745 MHz	-8.12	-9.25	-5.64	8.00	Complies
157	5785 MHz	-8.27	-7.56	-4.89	8.00	Complies
165	5825 MHz	-6.62	-8.65	-4.51	8.00	Complies

Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
151	5755 MHz	-10.71	-13.47	-8.86	8.00	Complies
159	5795 MHz	-12.27	-12.92	-9.57	8.00	Complies

Temperature	25°C	Humidity	56%
Test Engineer	Sean Ku	Configurations	IEEE 802.11a/b/g

**Configuration IEEE 802.11b / Ant. 1**

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-6.33	8.00	Complies
6	2437 MHz	-4.67	8.00	Complies
11	2462 MHz	-6.51	8.00	Complies

**Configuration IEEE 802.11g**

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
1	2412 MHz	-10.12	-8.23	-6.06	6.90	Complies
6	2437 MHz	-7.07	-9.11	-4.96	6.90	Complies
11	2462 MHz	-9.22	-8.98	-6.09	6.90	Complies

Note: Directional gain =  $10 \log [(10^{4.18/20} + 10^{3.99/20})^2 / 2] = 7.1 \text{ dBi} > 6 \text{ dBi}$ , so the conducted power density limit =  $8 - (\text{Directional gain} \rightarrow 7.1 - 6) = 6.9 \text{ dBm/3KHz}$ .

**Configuration IEEE 802.11a**


Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
149	5745 MHz	-10.12	-8.23	-3.84	6.65	Complies
157	5785 MHz	-7.07	-9.11	-5.70	6.65	Complies
165	5825 MHz	-9.22	-8.98	-5.18	6.65	Complies

Note 1: Directional gain =  $10 \log [(10^{4.62/20} + 10^{4.06/20})^2 / 2] = 7.35 \text{ dBi} > 6 \text{ dBi}$ , so the conducted power density limit =  $4 - (\text{Directional gain} \rightarrow 7.35 - 6) = 6.65 \text{ dBm/3KHz}$ .

Note 2: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / 2412 MHz**




Date: 5.DEC.2011 17:47:36

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / 2412 MHz**




Date: 5.DEC.2011 17:45:19

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / 2437 MHz**




Date: 5.DEC.2011 18:04:37


**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 2 / 2437 MHz**



Date: 5.DEC.2011 18:04:37


**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / 5825 MHz**

Date: 5.DEC.2011 18:55:13

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / 5825 MHz**


Date: 5.DEC.2011 18:53:32

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / 5755 MHz



Date: 5.DEC.2011 18:58:15


### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 2 / 5755 MHz



Date: 5.DEC.2011 19:00:01




**Power Density Plot on Configuration IEEE 802.11b / Ant. 1 / 2437 MHz**




Date: 5.DEC.2011 17:26:54

**Power Density Plot on Configuration IEEE 802.11g / Ant. 1 / 2437 MHz**




Date: 5.DEC.2011 17:38:50

### Power Density Plot on Configuration IEEE 802.11g / Ant. 2 / 2437 MHz




Date: 5.DEC.2011 17:37:10

### Power Density Plot on Configuration IEEE 802.11a / Ant. 1 / 5745 MHz



Date: 5.DEC.2011 18:31:17

### Power Density Plot on Configuration IEEE 802.11a / Ant. 2 / 5745 MHz



Date: 5.DEC.2011 18:34:16

## 4.5. 6dB Spectrum Bandwidth Measurement

### 4.5.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

### 4.5.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

### 4.5.4. Test Setup Layout



### 4.5.5. Test Deviation

There is no deviation with the original standard.

### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Test Result of 6dB Spectrum Bandwidth

Temperature	25°C%	Humidity	56%
Test Engineer	Sean Ku	Configurations	IEEE 802.11n
Test Date			

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.12	16.64	500	Complies
6	2437 MHz	15.12	16.64	500	Complies
11	2462 MHz	15.12	16.64	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.12	36.24	500	Complies
6	2437 MHz	32.96	36.16	500	Complies
9	2452 MHz	30.16	36.24	500	Complies

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	15.72	16.72	500	Complies
157	5785 MHz	15.48	16.76	500	Complies
165	5825 MHz	15.72	16.76	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.76	36.24	500	Complies
159	5795 MHz	35.44	36.24	500	Complies

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Sean Ku	<b>Configurations</b>	IEEE 802.11 a/b/g
<b>Test Date</b>			

**Configuration IEEE 802.11b / Ant. 1**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.56	10.08	500	Complies
6	2437 MHz	8.00	10.08	500	Complies
11	2462 MHz	8.08	10.12	500	Complies


**Configuration IEEE 802.11g / Ant. 1 + Ant. 2**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.32	14.72	500	Complies
6	2437 MHz	12.60	14.56	500	Complies
11	2462 MHz	12.36	14.76	500	Complies

**Configuration IEEE 802.11a / Ant. 1 + Ant. 2**


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	12.32	15.64	500	Complies
157	5785 MHz	12.32	15.60	500	Complies
165	5825 MHz	12.32	15.64	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 2412 MHz




Date: 5.DEC.2011 18:15:15

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 / 2452 MHz




Date: 5.DEC.2011 18:10:52

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 5785MHz



Date: 5.DEC.2011 19:08:08


6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 / 5795 MHz



Date: 5.DEC.2011 19:05:47




6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 1 / 2437 MHz




Date: 5.DEC.2011 17:25:25

6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 1+ Ant. 2 / 2412 MHz



Date: 5.DEC.2011 18:17:42

6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5745 MHz



Date: 5.DEC.2011 19:10:51

## 4.6. Radiated Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.6.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



#### 4.6.5. Test Deviation

There is no deviation with the original standard.

#### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Results of Radiated Emissions (9kHz~30MHz)

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	Normal Link
<b>Test Date</b>	Dec. 03, 2011		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25°C	Humidity	56%
Test Engineer	Denis Su	Configurations	Normal Link

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	31.94	33.84	40.00	-6.16	43.45	0.50	17.69	27.80	Peak	100	0 HORIZONTAL
2	304.51	41.30	46.00	-4.70	52.63	2.11	13.49	26.93	Peak	100	0 HORIZONTAL
3	344.28	41.39	46.00	-4.61	51.84	2.19	14.57	27.21	Peak	100	0 HORIZONTAL
4	425.76	36.75	46.00	-9.25	45.55	2.46	16.47	27.73	Peak	100	0 HORIZONTAL
5	796.30	42.11	46.00	-3.89	46.67	3.32	19.74	27.62	Peak	100	0 HORIZONTAL
6	829.28	42.60	46.00	-3.40	46.79	3.36	19.99	27.54	Peak	100	0 HORIZONTAL

**Vertical**



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	31.94	29.05	40.00	-10.95	38.66	0.50	17.69	27.80	Peak	400	0	VERTICAL
2	74.62	29.24	40.00	-10.76	49.16	0.90	6.88	27.70	Peak	400	0	VERTICAL
3	304.51	34.25	46.00	-11.75	45.58	2.11	13.49	26.93	Peak	400	0	VERTICAL
4	532.46	37.03	46.00	-8.97	44.37	2.76	18.00	28.10	Peak	400	0	VERTICAL
5	796.30	36.38	46.00	-9.62	40.94	3.32	19.74	27.62	Peak	400	0	VERTICAL
6	839.95	37.08	46.00	-8.92	41.15	3.38	20.07	27.52	Peak	400	0	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



#### 4.6.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

##### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.98	40.94	74.00	-33.06	39.60	3.31	33.06	35.03	Peak	100	115	HORIZONTAL
2	4824.18	28.80	54.00	-25.20	27.46	3.31	33.06	35.03	Average	100	115	HORIZONTAL

##### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4824.01	42.21	74.00	-31.79	40.87	3.31	33.06	35.03	Peak	100	200	VERTICAL
2	4824.09	30.58	54.00	-23.42	29.24	3.31	33.06	35.03	Average	100	200	VERTICAL

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.06	29.20	54.00	-24.80	27.74	3.33	33.16	35.03	Average	100	122	HORIZONTAL
2	4874.08	42.19	74.00	-31.81	40.73	3.33	33.16	35.03	Peak	100	122	HORIZONTAL
3	7306.28	40.28	54.00	-13.72	35.70	4.06	35.92	35.40	Average	134	325	HORIZONTAL
4	7308.88	57.11	74.00	-16.89	52.49	4.06	35.96	35.40	Peak	134	325	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.01	42.79	74.00	-31.21	41.33	3.33	33.16	35.03	Peak	100	200	VERTICAL
2	4874.04	32.03	54.00	-21.97	30.57	3.33	33.16	35.03	Average	100	200	VERTICAL
3	7305.84	54.71	74.00	-19.29	50.13	4.06	35.92	35.40	Peak	100	71	VERTICAL
4	7306.32	37.62	54.00	-16.38	33.04	4.06	35.92	35.40	Average	100	71	VERTICAL

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.86	29.28	54.00	-24.72	27.68	3.35	33.26	35.01	Average	100	132	HORIZONTAL
2	4924.02	42.27	74.00	-31.73	40.67	3.35	33.26	35.01	Peak	100	132	HORIZONTAL
3	7381.70	40.22	54.00	-13.78	35.47	4.06	36.09	35.40	Average	112	328	HORIZONTAL
4	7381.70	57.74	74.00	-16.26	52.99	4.06	36.09	35.40	Peak	112	328	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.89	42.91	74.00	-31.09	41.31	3.35	33.26	35.01	Peak	100	346	VERTICAL
2	4923.91	33.06	54.00	-20.94	31.46	3.35	33.26	35.01	Average	100	346	VERTICAL
3	7386.10	55.27	74.00	-18.73	50.52	4.06	36.09	35.40	Peak	100	318	VERTICAL
4	7386.30	37.89	54.00	-16.11	33.14	4.06	36.09	35.40	Average	100	318	VERTICAL

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4844.06	28.43	54.00	-25.57	27.05	3.32	33.09	35.03	Average	100	171	HORIZONTAL
2	4844.43	40.91	74.00	-33.09	39.53	3.32	33.09	35.03	Peak	100	171	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4843.70	41.81	74.00	-32.19	40.43	3.32	33.09	35.03	Peak	100	321	VERTICAL
2	4844.00	30.78	54.00	-23.22	29.40	3.32	33.09	35.03	Average	100	321	VERTICAL

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.86	29.01	54.00	-24.99	27.55	3.33	33.16	35.03	Average	100	132	HORIZONTAL
2	4874.23	42.46	74.00	-31.54	41.00	3.33	33.16	35.03	Peak	100	132	HORIZONTAL
3	7308.44	51.39	74.00	-22.61	46.77	4.06	35.96	35.40	Peak	116	354	HORIZONTAL
4	7309.04	36.04	54.00	-17.96	31.42	4.06	35.96	35.40	Average	116	354	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.97	31.95	54.00	-22.05	30.49	3.33	33.16	35.03	Average	100	212	VERTICAL
2	4874.05	42.64	74.00	-31.36	41.18	3.33	33.16	35.03	Peak	100	212	VERTICAL
3	7305.72	48.62	74.00	-25.38	44.04	4.06	35.92	35.40	Peak	100	75	VERTICAL
4	7306.24	34.36	54.00	-19.64	29.78	4.06	35.92	35.40	Average	100	75	VERTICAL

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4903.92	29.14	54.00	-24.86	27.63	3.34	33.19	35.02	Average	100	91	HORIZONTAL
2	4904.29	41.74	74.00	-32.26	40.23	3.34	33.19	35.02	Peak	100	91	HORIZONTAL
3	7346.60	50.67	74.00	-23.33	45.99	4.06	36.02	35.40	Peak	117	327	HORIZONTAL
4	7348.90	35.80	54.00	-18.20	31.12	4.06	36.02	35.40	Average	117	327	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4903.98	32.31	54.00	-21.69	30.80	3.34	33.19	35.02	Average	100	208	VERTICAL
2	4904.08	43.04	74.00	-30.96	41.53	3.34	33.19	35.02	Peak	100	208	VERTICAL
3	7338.40	48.54	74.00	-25.46	43.89	4.06	35.99	35.40	Peak	100	323	VERTICAL
4	7341.10	35.41	54.00	-18.59	30.76	4.06	35.99	35.40	Average	100	323	VERTICAL

<b>Temperature</b>	24°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz CH 149 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11488.60	44.80	54.00	-9.20	36.19	5.11	38.78	35.28	Average	130	360	HORIZONTAL
2	11490.60	58.08	74.00	-15.92	49.47	5.11	38.78	35.28	Peak	130	360	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11490.40	47.82	54.00	-6.18	39.21	5.11	38.78	35.28	Average	109	6	VERTICAL
2	11490.60	61.52	74.00	-12.48	52.91	5.11	38.78	35.28	Peak	109	6	VERTICAL

<b>Temperature</b>	24°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz CH 157 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11568.80	44.01	54.00	-9.99	35.35	5.13	38.83	35.30	Average	122	5	HORIZONTAL
2	11571.30	58.05	74.00	-15.95	49.38	5.14	38.83	35.30	Peak	122	5	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11563.60	54.99	74.00	-19.01	46.34	5.13	38.82	35.30	Peak	100	301	VERTICAL
2	11568.40	41.56	54.00	-12.44	32.90	5.13	38.83	35.30	Average	100	301	VERTICAL



<b>Temperature</b>	24°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz CH 165 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11651.40	43.67	54.00	-10.33	34.95	5.16	38.86	35.30	Average	116	15	HORIZONTAL
2	11656.32	57.54	74.00	-16.46	48.82	5.16	38.86	35.30	Peak	116	15	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11650.40	44.35	54.00	-9.65	35.63	5.16	38.86	35.30	Average	120	318	VERTICAL
2	11651.00	57.69	74.00	-16.31	48.97	5.16	38.86	35.30	Peak	120	318	VERTICAL

<b>Temperature</b>	24°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz CH 151 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11508.40	41.95	54.00	-12.05	33.32	5.12	38.79	35.28	Average	119	361	HORIZONTAL
2	11510.70	56.72	74.00	-17.28	48.09	5.12	38.79	35.28	Peak	119	361	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11510.00	53.28	74.00	-20.72	44.65	5.12	38.79	35.28	Peak	112	342	VERTICAL
2	11510.40	40.37	54.00	-13.63	31.74	5.12	38.79	35.28	Average	112	342	VERTICAL

<b>Temperature</b>	24°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz CH 159 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11586.60	54.77	74.00	-19.23	46.10	5.14	38.83	35.30	Peak	122	20	HORIZONTAL
2	11591.30	40.81	54.00	-13.19	32.14	5.14	38.83	35.30	Average	122	20	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11588.90	52.36	74.00	-21.64	43.69	5.14	38.83	35.30	Peak	100	301	VERTICAL
2	11595.80	38.53	54.00	-15.47	29.85	5.15	38.83	35.30	Average	100	301	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11b CH 1 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.96	45.23	54.00	-8.77	43.89	3.31	33.06	35.03	Average	100	190	HORIZONTAL
2	4823.96	50.22	74.00	-23.78	48.88	3.31	33.06	35.03	Peak	100	190	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.99	54.64	74.00	-19.36	53.30	3.31	33.06	35.03	Peak	103	40	VERTICAL
2	4824.00	52.11	54.00	-1.89	50.77	3.31	33.06	35.03	Average	103	40	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11b CH 6 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.90	48.98	74.00	-25.02	47.52	3.33	33.16	35.03	Peak	100	189	HORIZONTAL
2	4873.99	44.06	54.00	-9.94	42.60	3.33	33.16	35.03	Average	100	189	HORIZONTAL
3	7310.22	47.35	54.00	-6.65	42.73	4.06	35.96	35.40	Average	115	323	HORIZONTAL
4	7311.45	52.92	74.00	-21.08	48.30	4.06	35.96	35.40	Peak	115	323	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.97	51.63	54.00	-2.37	50.17	3.33	33.16	35.03	Average	103	27	VERTICAL
2	4874.00	54.45	74.00	-19.55	52.99	3.33	33.16	35.03	Peak	103	27	VERTICAL
3	7310.22	46.71	54.00	-7.29	42.09	4.06	35.96	35.40	Average	100	46	VERTICAL
4	7311.43	52.83	74.00	-21.17	48.21	4.06	35.96	35.40	Peak	100	46	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11b CH 11 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.96	42.18	54.00	-11.82	40.58	3.35	33.26	35.01	Average	100	336	HORIZONTAL
2	4924.00	47.64	74.00	-26.36	46.04	3.35	33.26	35.01	Peak	100	336	HORIZONTAL
3	7385.24	47.79	54.00	-6.21	43.04	4.06	36.09	35.40	Average	123	223	HORIZONTAL
4	7386.33	53.67	74.00	-20.33	48.92	4.06	36.09	35.40	Peak	123	223	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.92	54.87	74.00	-19.13	53.27	3.35	33.26	35.01	Peak	102	150	VERTICAL
2	4923.96	52.62	54.00	-1.38	51.02	3.35	33.26	35.01	Average	102	150	VERTICAL
3	7385.22	45.95	54.00	-8.05	41.20	4.06	36.09	35.40	Average	107	46	VERTICAL
4	7386.69	52.99	74.00	-21.01	48.24	4.06	36.09	35.40	Peak	107	46	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11g CH 1 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.93	42.80	74.00	-31.20	41.46	3.31	33.06	35.03	Peak	100	217	HORIZONTAL
2	4824.02	29.30	54.00	-24.70	27.96	3.31	33.06	35.03	Average	100	217	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.77	42.91	74.00	-31.09	41.57	3.31	33.06	35.03	Peak	100	34	VERTICAL
2	4824.02	31.26	54.00	-22.74	29.92	3.31	33.06	35.03	Average	100	34	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11g CH 6 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.69	41.59	74.00	-32.41	40.13	3.33	33.16	35.03	Peak	100	277	HORIZONTAL
2	4874.15	29.61	54.00	-24.39	28.15	3.33	33.16	35.03	Average	100	277	HORIZONTAL
3	7307.60	57.08	74.00	-16.92	52.46	4.06	35.96	35.40	Peak	105	349	HORIZONTAL
4	7311.80	41.31	54.00	-12.69	36.69	4.06	35.96	35.40	Average	105	349	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.01	43.31	74.00	-30.69	41.85	3.33	33.16	35.03	Peak	101	214	VERTICAL
2	4874.02	32.59	54.00	-21.41	31.13	3.33	33.16	35.03	Average	101	214	VERTICAL
3	7306.40	41.57	54.00	-12.43	36.99	4.06	35.92	35.40	Average	100	76	VERTICAL
4	7310.84	56.15	74.00	-17.85	51.53	4.06	35.96	35.40	Peak	100	76	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11g CH 11 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.98	29.61	54.00	-24.39	28.01	3.35	33.26	35.01	Average	100	231	HORIZONTAL
2	4924.12	41.87	74.00	-32.13	40.27	3.35	33.26	35.01	Peak	100	231	HORIZONTAL
3	7382.28	41.05	54.00	-12.95	36.30	4.06	36.09	35.40	Average	140	192	HORIZONTAL
4	7387.92	57.49	74.00	-16.51	52.74	4.06	36.09	35.40	Peak	140	192	HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.92	44.49	74.00	-29.51	42.89	3.35	33.26	35.01	Peak	101	190	VERTICAL
2	4923.99	33.82	54.00	-20.18	32.22	3.35	33.26	35.01	Average	101	190	VERTICAL
3	7387.64	39.80	54.00	-14.20	35.05	4.06	36.09	35.40	Average	123	196	VERTICAL
4	7392.96	57.42	74.00	-16.58	52.63	4.06	36.13	35.40	Peak	123	196	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11a CH 149 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11487.20	60.07	74.00	-13.93	51.46	5.11	38.78	35.28	Peak	113	357	HORIZONTAL
2	11487.52	44.68	54.00	-9.32	36.07	5.11	38.78	35.28	Average	113	357	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11490.36	48.09	54.00	-5.91	39.48	5.11	38.78	35.28	Average	122	0	VERTICAL
2	11490.44	62.74	74.00	-11.26	54.13	5.11	38.78	35.28	Peak	122	0	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11a CH 157 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11562.36	58.29	74.00	-15.71	49.64	5.13	38.82	35.30	Peak	124	17	HORIZONTAL
2	11567.72	44.24	54.00	-9.76	35.58	5.13	38.83	35.30	Average	124	17	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11566.32	41.55	54.00	-12.45	32.90	5.13	38.82	35.30	Average	105	298	VERTICAL
2	11566.80	56.42	74.00	-17.58	47.77	5.13	38.82	35.30	Peak	105	298	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11a CH 165 / Ant. 1 + Ant. 2
<b>Test Date</b>	Dec. 03, 2011		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11643.60	58.30	74.00	-15.70	49.58	5.16	38.86	35.30	Peak	123	38	HORIZONTAL
2	11648.92	43.76	54.00	-10.24	35.04	5.16	38.86	35.30	Average	123	38	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11645.36	61.31	74.00	-12.69	52.59	5.16	38.86	35.30	Peak	124	337	VERTICAL
2	11650.40	45.66	54.00	-8.34	36.94	5.16	38.86	35.30	Average	124	337	VERTICAL

## 4.7. Band Edge Emissions Measurement

### 4.7.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

### 4.7.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.7.5. Test Deviation

There is no deviation with the original standard.

### 4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.7.7. Test Result of Band Edge and Fundamental Emissions

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 1 + Ant. 2

##### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.52	69.30	74.00	-4.70	38.92	2.21	28.17	0.00	Peak	100	187	HORIZONTAL
2	2389.68	51.39	54.00	-2.61	21.01	2.21	28.17	0.00	Average	100	187	HORIZONTAL
3	2411.68	93.94				2.22	28.21	0.00	Average	100	187	HORIZONTAL
4	2411.68	106.03				2.22	28.21	0.00	Peak	100	187	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	45.73	54.00	-8.27	15.34	2.22	28.17	0.00	Average	161	190	HORIZONTAL
2	2390.00	59.13	74.00	-14.87	28.74	2.22	28.17	0.00	Peak	161	190	HORIZONTAL
3	2435.72	107.40				2.23	28.29	0.00	Peak	161	190	HORIZONTAL
4	2435.88	93.77				2.23	28.29	0.00	Average	161	190	HORIZONTAL
5	2483.50	38.82	54.00	-15.18	8.18	2.26	28.38	0.00	Average	161	190	HORIZONTAL
6	2484.74	49.47	74.00	-24.53	18.83	2.26	28.38	0.00	Peak	161	190	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

##### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2456.87	95.79				2.24	28.33	0.00	Average	100	150	VERTICAL
2	2457.03	109.98				2.24	28.33	0.00	Peak	100	150	VERTICAL
3	2483.50	52.25	54.00	-1.75	21.62	2.26	28.37	0.00	Average	100	150	VERTICAL
4	2484.30	72.99	74.00	-1.01	42.36	2.26	28.37	0.00	Peak	100	150	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 1 + Ant. 2

**Channel 3**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2385.19	70.19	74.00	-3.81	39.81	2.21	28.17	0.00	Peak	100	150	VERTICAL
2	2389.36	51.74	54.00	-2.26	21.36	2.21	28.17	0.00	Average	100	150	VERTICAL
3	2419.44	86.97				2.23	28.25	0.00	Average	100	150	VERTICAL
4	2419.76	104.12				2.23	28.25	0.00	Peak	100	150	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.40	46.94	54.00	-7.06	16.56	2.21	28.17	0.00	Average	127	189	HORIZONTAL
2	2388.72	64.74	74.00	-9.26	34.36	2.21	28.17	0.00	Peak	127	189	HORIZONTAL
3	2425.72	103.07				2.23	28.25	0.00	Peak	127	189	HORIZONTAL
4	2425.78	86.23				2.23	28.25	0.00	Average	127	189	HORIZONTAL
5	2483.50	40.23	54.00	-13.77	9.59	2.26	28.38	0.00	Average	127	189	HORIZONTAL
6	2483.50	54.93	74.00	-19.07	24.29	2.26	28.38	0.00	Peak	127	189	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

**Channel 9**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2446.87	105.23				2.24	28.29	0.00	Peak	100	152	VERTICAL
2	2449.44	89.02				2.24	28.29	0.00	Average	100	152	VERTICAL
3	2484.78	49.71	54.00	-4.29	19.08	2.26	28.37	0.00	Average	100	152	VERTICAL
4	2487.35	69.33	74.00	-4.67	38.66	2.26	28.41	0.00	Peak	100	152	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11b CH 1, 6, 11 / Ant. 1 + Ant. 2
<b>Test Date</b>	Sep. 29, 2008		

**Channel 1**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.20	45.33	54.00	-8.67	14.95	2.21	28.17	0.00	Average	100	148	VERTICAL
2	2389.84	56.89	74.00	-17.11	26.50	2.22	28.17	0.00	Peak	100	148	VERTICAL
3	2411.20	104.16				2.22	28.21	0.00	Average	100	148	VERTICAL
4	2411.20	108.16				2.22	28.21	0.00	Peak	100	148	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2387.28	45.84	54.00	-8.16	15.46	2.21	28.17	0.00	Average	100	150	VERTICAL
2	2387.60	57.60	74.00	-16.40	27.22	2.21	28.17	0.00	Peak	100	150	VERTICAL
3	2436.04	109.53				2.23	28.29	0.00	Peak	100	150	VERTICAL
4	2436.20	105.40				2.23	28.29	0.00	Average	100	150	VERTICAL
5	2486.39	39.95	54.00	-14.05	9.28	2.26	28.41	0.00	Average	100	150	VERTICAL
6	2486.55	49.79	74.00	-24.21	19.12	2.26	28.41	0.00	Peak	100	150	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2461.20	101.83				2.24	28.33	0.00	Average	124	204	HORIZONTAL
2	2461.20	105.89				2.24	28.33	0.00	Peak	124	204	HORIZONTAL
3	2483.50	44.51	54.00	-9.49	13.87	2.26	28.38	0.00	Average	124	204	HORIZONTAL
4	2483.50	54.10	74.00	-19.90	23.46	2.26	28.38	0.00	Peak	124	204	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.



<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Denis Su	<b>Configurations</b>	IEEE 802.11g CH 1, 6, 11 / Ant. 1 + Ant. 2

**Channel 1**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.72	72.18	74.00	-1.82	41.80	2.21	28.17	0.00	Peak	100	154	VERTICAL
2	2390.00	50.47	54.00	-3.53	20.08	2.22	28.17	0.00	Average	99	154	VERTICAL
3	2411.52	95.62				2.22	28.21	0.00	Average	99	154	VERTICAL
4	2412.48	108.80				2.22	28.21	0.00	Peak	100	154	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2387.00	47.50	54.00	-6.50	17.12	2.21	28.17	0.00	Average	129	191	HORIZONTAL
2	2388.08	62.16	74.00	-11.84	31.78	2.21	28.17	0.00	Peak	129	191	HORIZONTAL
3	2435.08	108.07				2.23	28.29	0.00	Peak	129	191	HORIZONTAL
4	2435.24	95.06				2.23	28.29	0.00	Average	129	191	HORIZONTAL
5	2483.50	39.12	54.00	-14.88	8.48	2.26	28.38	0.00	Average	129	191	HORIZONTAL
6	2483.82	52.10	74.00	-21.90	21.46	2.26	28.38	0.00	Peak	129	191	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.


**Channel 11**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2456.71	96.80				2.24	28.33	0.00	Average	100	157	VERTICAL
2	2456.87	110.10				2.24	28.33	0.00	Peak	100	157	VERTICAL
3	2483.50	50.24	54.00	-3.76	19.61	2.26	28.37	0.00	Average	100	157	VERTICAL
4	2485.10	72.52	74.00	-1.48	41.85	2.26	28.41	0.00	Peak	100	157	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 2412 MHz




Date: 3.DEC.2011 12:39:56

High Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 2462 MHz




Date: 3.DEC.2011 12:55:13

**Low Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 / 2422 MHz**




Date: 3.DEC.2011 12:35:55

**High Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 / 2452 MHz**




Date: 3.DEC.2011 12:29:50

**Low Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 5745 MHz**




Date: 3.DEC.2011 17:11:22

**High Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 5825 MHz**




Date: 3.DEC.2011 17:18:02

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 / 5755 MHz




Date: 3.DEC.2011 17:03:43

High Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 / 5795 MHz




Date: 3.DEC.2011 17:01:01

**Low Band Edge Plot on Configuration IEEE 802.11b / Ant. 1 + Ant. 2 / 2412 MHz**




Date: 3.DEC.2011 12:44:57

**High Band Edge Plot on Configuration IEEE 802.11b / Ant. 1 + Ant. 2 / 2462 MHz**




Date: 3.DEC.2011 12:49:01

**Low Band Edge Plot on Configuration IEEE 802.11g / Ant. 1 + Ant. 2 / 2412 MHz**




Date: 3.DEC.2011 12:42:22

**High Band Edge Plot on Configuration IEEE 802.11g / Ant. 1 + Ant. 2 / 2462 MHz**




Date: 3.DEC.2011 12:52:02

### Low Band Edge Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5745 MHz



Date: 3.DEC.2011 17:13:23

### High Band Edge Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5825 MHz



Date: 3.DEC.2011 17:15:53



## 4.8. Antenna Requirements

### 4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.8.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 14, 2011	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 14, 2011	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Nov. 30, 2011	Conduction (CO01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Sep. 26, 2011	Conducted (TH01-CB)
Thermo-Hygro Meter	N/A	HC 520	#1	15~70 degree	Nov. 02, 2010	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 01, 2011	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 01, 2011	Conducted (TH01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Oct. 29, 2011	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 25, 2011	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 22, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 29, 2011	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 29, 2011	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 03, 2011	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 22, 2011	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2011	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Note: "\*" Calibration Interval of instruments listed above is two years.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110702

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Road, Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

<b>Accreditation Criteria</b>	: ISO/IEC 17025:2005
<b>Accreditation Number</b>	: 1190
<b>Originally Accredited</b>	: December 15, 2003
<b>Effective Period</b>	: January 10, 2010 to January 09, 2013
<b>Accredited Scope</b>	: Testing Field, see described in the Appendix
<b>Specific Accreditation Program</b>	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

  
Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : July 02, 2011

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix