

# **CBSD-EUD Test Report**

Report No.: RFBCMA-WTW-P24070713

FCC ID: RAXXC46BE

Test Model: XC46BE

Received Date: Sep. 27, 2024

Test Date: Oct. 22 ~ Oct. 25, 2024

**Issued Date:** Nov. 19, 2024

**Applicant:** Arcadyan Technology Corporation

Address: No.8, Sec.2, Guangfu Rd., Hsinchu City 30071, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

FCC Registration/

**Designation Number:** 281270 / TW0032





This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Report No.: RFBCMA-WTW-P24070713 Page No. 1 / 13 Report Format Version: 6.1.1



## **Table of Contents**

Relea	se Control Record	3
1	Certificate of Conformity	4
2	Summary of Test Results	5
2.1	Modification Record	5
3	General Information	6
3.1	General Description of EUT	6
4	Measurement	7
4.1 4.2 4.3 4.4 4.5 4.6	End User Device additional requirements Test Procedure Test Environment Test Equipment Test Setup Test Result	7 8 8
5	Pictures of Test Arrangements	12
Appe	ndix – Information of the Testing Laboratories	13



## **Release Control Record**

Issue No.	Description	Date Issued
RFBCMA-WTW-P24070713	Original release	Nov. 19, 2024



1	Certificate	of Conformity
---	-------------	---------------

**Product:** Dragon

Brand: Verizon

Test Model: XC46BE

Sample Status: Engineering sample

**Applicant:** Arcadyan Technology Corporation

**Test Date:** Oct. 22 ~ Oct. 25, 2024

Standards: FCC Part 96.47

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: \_\_\_\_\_\_, Date: \_\_\_\_\_\_, Nov. 19, 2024

Jeremy Lin , Date: Nov. 19, 2024 Approved by:

Jeremy Lin / Project Engineer



# 2 Summary of Test Results

Applied Standard : FCC Part 96.47			
FCC Clause	Test Item	Result	Remarks
96.47(a)(1)	End User Device additional requirements	Pass	Meet the requirement

## 2.1 Modification Record

There were no modifications required for compliance.



## 3 General Information

## 3.1 General Description of EUT

Product	Dragon
Brand	Verizon
Test Model	XC46BE
Status of EUT	Engineering sample
Accessory Device	Refer to note
Data Cable Supplied	NA

### Note:

- 1. This report is for LTE Band 48 test.
- 2. The EUT uses following accessories.

Adapter		
Brand	verizon	
Model	1A105-1235	
Input Power	105-125 Vac, 60Hz, 1.2A	
Output Power	12.0Vdc, 3.5A, 42.0W	
DC Output Cable	1.8meter unshielded cable, w/o ferrite core	

Battery	
Brand	Atemitech
Model	XC46BE224T-F100
Power Rating	7.2Vdc, 9800mAh (70.56Wh)

3. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.



#### 4 Measurement

#### 4.1 End User Device additional requirements

FCC Part 96.47

- (a) End User Devices may operate only if they can positively receive and decode an authorization signal transmitted by a CBSD, including the frequencies and power limits for their operation.
- (1) An End User Device must discontinue operations, change frequencies, or change its operational power level within 10 seconds of receiving instructions from its associated CBSD.

#### 4.2 Test Procedure

Following test procedure can be done by WINNF-TS-0122 CBRS CBSD Test Specification, use the certified CBSD(FCC ID: P27P208) as CBSD device to show compliance with FCC Part 96.47 requirements for End User Device(EUD):

#### Test #1:

- a) Setup WINNF.PT.C.HBT.1 with 3615 ~ 3635 MHz and MaxEIRP at 10 dBm/MHz.
- b) Enable CBSD service from EPC management.
- c) Check EUD Tx Frequency and connection successful.
- d) Disable AP service from EPC management.
- e) Check if EUT stop transmission within 10s.

#### Test #2:

- a) Setup WINNF.PT.C.HBT.1 with 3595 ~ 3615 MHz and MaxEIRP at 15 dBm/MHz.
- b) Enable CBSD service from EPC management.
- c) Check EUD Tx Frequency and connection successful.
- d) Change power to 10 dBm/MHz.
- e) Check EUD Tx output power.
- f) Disable AP service from EPC management.
- g) Check if EUT stop transmission within 10s.

Note: Test #1 and #2 to show compliance with the handshake testing under Part 96.



### 4.3 Test Environment

## **Test Condition**

Test Item	Environmental Conditions	Input Power	Tested By
End User Device additional requirements	25deg. C, 70%RH	120Vac, 60Hz	Matthew Yang


## 4.4 Test Equipment

Description & Manufacturer	Model no.	Serial No.	Calibrated Date	Calibrated Until
CBSD	P208-TP	1801BVV000034	NA	NA
Sercomm	(FCCID: P27P208)	100121100001	100	1 17 1
Laptop DELL	Inspiron 15 3000	D67MYN2	NA	NA
Spectrum Analyzer KEYSIGHT	MXA	E2-010823	Mar. 19, 2024	Mar. 18, 2025
2WAY DIV WOKEN	0.5-8GHz 2Way SMA	DCMACMW1E4	Jan. 09, 2024	Jan. 08, 2025

NOTE: 1. The test was performed in WM OVEN 1 Test Room

- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 3. Tested Date: Oct. 22 ~ Oct. 25, 2024

## 4.5 Test Setup



NOTE: The CBSD device is certified CBSD(FCC ID: P27P208). Where the CBSD device connection with EUD is by radiated method. The EUD device connection with Spectrum Analyzer is by conducted method.




#### 4.6 **Test Result**

Step Test #1-(c)

EUD follow instruction from associate CBSD and successfully operate at assigned 3615-3635 MHz


channel.



Plot 5-1 EUD frequency of operations

#### Step Test #1(e)

EUD discontinues the operation within 10 seconds after CBSD terminates the service:



Note:

Marker 1: CBSD sends instructions to discontinues operations.


Marker 2: EUD discontinues operation.

Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUD.



### Test #2(c)

following plots demonstrate that EUD response to the associated CBSD instruction and operate at a new assigned channel ( $3595 \sim 3615 \text{ MHz}$  and MaxEIRP at -8 dBm/MHz)



Plot 5-3 EUD frequency of operations

## Test #2(e)

following plot demonstrates that EUD response to the associated CBSD power reduce instruction and reduce the power for 5 dB.



Plot 5-4 EUD changed output power



## Step Test #2(g)

EUD discontinues the operation within 10 seconds after CBSD terminates the service:



Plot 5-5 EUD discontinues operations within 10s.

## Note:

Marker 1: CBSD sends instructions to discontinues operations.

Marker 2: EUD discontinues operation.

Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUD.



5 Pictures of Test Arrangements	
Please refer to the attached file (Test Setup Photo).	

Report No.: RFBCMA-WTW-P24070713 Page No. 12 / 13 Report Format Version: 6.1.1



## **Appendix – Information of the Testing Laboratories**

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Hsin Chu EMC/RF Lab/Telecom Lab

Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a> Web Site: <a href="http://ee.bureauveritas.com.tw">http://ee.bureauveritas.com.tw</a>

The address and road map of all our labs can be found in our web site also.

--- END ---