

Specifications

Specifications	
General Operating voltage: DC5V Operating voltage range: DC10.8–16.0V Maximum operation current: 2.5A Grounding system: car battery negative pole AC Adapter Operating voltage range: AC85-265V Maximum operation current: 2.5A Car adapter Operating voltage: DC12V Operating voltage range: DC8–24V Maximum operation current: 2.5A TFT Monitor Screen diagonal: 4 inches (105mm) Usable display area: 87.84mm (W) x 49.8mm (H) Resolution: WQVGA 480 (W) x 272 (H) pixels Brightness: 180cd/m (centre brightness after 30 minutes) Top viewing angle: 58° Bottom viewing angle: 52° Horizontal viewing angle: +66° Dimensions Dimensions: 136mm (W) x 77mm (H) x 31mm (D) Net weight: 300g	Remote Control Frequency range: 2.4 – 2.483GHz Nominal output power: 0 dBm Modulation: FSK Camera Effective Pixels: 1.3 M Resolution: 1304 x 968 SXGA Aperture range: F 4.9mm Battery Capacity: 1350mAH Type: Lithium-ion Hardware Processor: Intel PXA270 416Mhz RAM: 64MB ROM: 64MB HDD: 4GB (iCN750) Internal CF card: 512MB (iCN720) SD/MMC Memory Expansion Environment Operating temperature: -10°C–+60°C Storage temperature: -30°C–+70°C Operating humidity: 45%–80% RH Storage humidity: 30%–90% RH EMC: e-Mark, FCC, CE, C Tick, RSS-210 Operating shock: 4G Non-operating shock: 75G