



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR 352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	NAVICO AUCKLAND LTD
	44 ARRENWAY DRIVE, ROSEDALE P.O. Box 331146 TAKAPUNA, AUCKLAND 0632 New Zealand
FCC ID	RAYHALO
MODEL NUMBER	HALO
PRODUCT DESCRIPTION	MARINE PULSE COMPRESSION RADAR
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Sid Sanders

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Sid Sanders

Engineering Project Manager

Date: 4/7/2015

RF Exposure Requirements

General information

Device type: MARINE PULSE COMPRESSION RADAR

Devices that operate under Part 80, 90 of this chapter are subject to RF exposure evaluation prior to equipment authorization or use.

Antenna

Configuration	Antenna p/n	Type	Max. Gain (dBi)
6 ft. Halo	000-11466-001	Halo	29 dBi

Operating configuration and exposure conditions:

The conducted output power is shown in the table below. Typical use qualifies for a maximum duty cycle factor of 100%.

Operation: A typical installation consists of an antenna system with a 10 meter coaxial cable of the type RG 213/ U type which has a loss as follows;

Nom. Attenuation for RG 213/U:

Frequency MHz	Attenuation per 100ft. dB
1	.27
10	.55
50	1.3
100	1.9
200	2.7
400	4.1
700	6.5
900	7.6
1000	8.0
4000	21.5

MPE Calculation:

The minimum separation distance is calculated as follows:

$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d}$	Power density: $P_d(mW/cm^2) = \frac{E^2}{3770}$
--	--

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

**Minimum Separation Distance for Mobile or Fixed Devices
General Population/Uncontrolled Exposure**

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	1 W	<i>equals</i>	Max Power	1000 mW
Duty Cycle	10 %	<i>equals</i>	Duty Factor	0.1 numeric
Antenna Gain	29 dBi	<i>equals</i>	Gain numeric	794.3282 numeric
Coax Loss	0 dB		Gain - Coax Loss	794.3282 numeric
Power Density	1 mW/cm ²			
Frequency	9495 MHz			

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1

Frequency range	Power der	Enter this value
MHz	mW/cm ²	mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	6.3
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	80 cm	0.80 m
------------------------------------	--------------	---------------

Minimum Separation in Inches 31.27731 Inches

Applicant: NAVICO AUCKLAND LTD

FCC ID: RAYHALO

Report: N\NAVICO AUCKLAND_RAY\268ZAUT15\268ZAUT15TestReport.docx