

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: RB8A5A

EUT Specification

EUT	Android TV Box
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	12.60dBm (18.20mW)
Antenna gain	2.9 dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale ; $P_i = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Channel Frequency (MHz)	Output Peak power (mW)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
802.11b					
Lowest	2412	14.69	2.9	0.005698	1
Middle	2437	16.18	2.9	0.006276	1
Highest	2462	16.90	2.9	0.006556	1
802.11g					
Lowest	2412	14.96	2.9	0.005803	1
Middle	2437	16.71	2.9	0.006482	1
Highest	2462	17.42	2.9	0.006757	1
802.11n(HT20)					
Lowest	2412	15.52	2.9	0.006020	1
Middle	2437	17.18	2.9	0.006664	1
Highest	2462	18.20	2.9	0.007060	1
802.11n(HT40)					
Lowest	2422	13.68	2.9	0.005307	1
Middle	2437	14.36	2.9	0.005570	1
Highest	2452	14.86	2.9	0.005764	1

Sincerely,

(signature)

Jack Gao/ Manager

Tel: +86-755-23981801 Fax: +86-755-23981800

E-mail: jack@measy.com.cn