

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: RB8U4AU4BU4C

EUT Specification

EUT	Android Mini PC
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☒ WLAN: 2.402GHz ~ 2.480GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	For BT: 3.55dBm (2.26mW) For WIFI:20.70dBm(117.49mW)
Antenna gain	0.8 dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale ; $\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Channel Frequency (MHz)	Output Peak power (mW)	Antenna Gain (dBi)	Power density at 20cm (mW/ cm ²)	Power density Limits (mW/cm ²)
802.11b					
Lowest	2412	43.75	0.8	0.010464	1
Middle	2437	35.65	0.8	0.008527	1
Highest	2462	31.12	0.8	0.007443	1
802.11g					
Lowest	2412	117.49	0.8	0.028102	1
Middle	2437	102.80	0.8	0.024588	1
Highest	2462	87.90	0.8	0.021024	1
802.11n(HT20)					
Lowest	2412	85.51	0.8	0.020452	1
Middle	2437	77.27	0.8	0.018482	1
Highest	2462	65.01	0.8	0.015549	1
GFSK					
Lowest	2402	2.26	0.8	5.4055e-4	1
Middle	2442	1.85	0.8	4.4249e-4	1
Highest	2480	1.54	0.8	3.6834e-4	1

Sincerely,



(signature)

Jack Gao/ Manager

Tel: +86-755-23981801

Fax: +86-755-23981800

E-mail: jack@measy.com.cn