



Report No: FCC 1705010-02 File reference No: 2017-05-03

Applicant: Shenzhen Jingwah Information Technology Co., Ltd.

Product: VR Headset

Model No: CVR-155, FV200

Trademark: N/A

Test Standards: FCC Part 15.247

It is herewith confirmed and found to comply with the Test result:

requirements set up by ANSI C63.10, FCC Part 15 Subpart C, the evaluation for

15.247 regulations

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: May 03, 2017

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TESTING LABORATORIES

Room 512-519, 5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen, Guangdong, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Date: 2017-05-03



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

Page 2 of 84

The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

## **CNAS-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

# FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.:899988.

Page 3 of 84

Report No.: FCC1705010-02

Date: 2017-05-03



# **Test Report Conclusion** Content

	* * * · · · · · · · · · · · · · · · · ·	
1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details.	7
3.1	Summary of Test Results.	7
3.2	Test Standards.	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT.	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT.	12
6.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit.	13
7.0	20dB Bandwidth	22
8.0	Maximum Output Power	34
9.0	Carrier Frequency Separation.	37
10.0	Number of Hopping Channel	41
11.0	Time of Occupancy (Dwell Time).	45
12.0	Out of Band Measurement.	52
13.0	Antenna Requirement.	65
14.0	FCC ID Label.	66
15.0	Photo of Test Setup and EUT View.	67

Report No.: FCC1705010-02 Page 4 of 84

Date: 2017-05-03



## 1.0 General Details

### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Room 512-519,5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen,

Guangdong China

(755) 83448688 Telephone: Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

## 1.2 Applicant Details

Shenzhen Jingwah Information Technology Co., Ltd. Applicant:

Address: 4F, Bldg 4, Jinghua Square, No.1 Huafa North Road, Futian District, Shenzhen, China

Telephone: Fax:

### 1.3 Description of EUT

Product: VR Headset

Manufacturer: Shenzhen Jingwah Information Technology Co., Ltd.

Address: 4F, Bldg 4, Jinghua Square, No.1 Huafa North Road, Futian District,

Shenzhen, China

Brand Name: N/A

Model Number: CVR-155

Additional Model Number: FV200

Power Adapter Model No.: AV-ASC-USB-002

AC Input: 100-240V~1.3A 50/60Hz; Output: DC5V, 2.4A\*5 or DC5V 1A\*10

Type of Modulation GFSK, JI/4DQPSK, 8DPSK for Bluetooth

Frequency range 2402-2480MHz for Bluetooth

Channel Spacing 1MHz for Bluetooth

Frequency Selection By software

Channel Number 79 channel for Bluetooth

Antenna: Integral Antenna and the maximum Gain of this antenna is 2.0dBi; Report No.: FCC1705010-02 Page 5 of 84

Date: 2017-05-03



Submitted Sample: 2 Samples

1.5 Test Duration 2017-04-26 to 2017-05-03

1.6 Test Uncertainty Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Report No.: FCC1705010-02 Page 6 of 84

Date: 2017-05-03



2.0 Test Equipments							
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date		
ESPI Test Receiver	R&S	ESPI 3	100379	2016-08-22	2017-08-21		
TWO Line-V-NETW	R&S	EZH3-Z5	100294	2016-08-22	2017-08-21		
TWO Line-V-NETW	R&S	EZH3-Z5	100253	2016-08-22	2017-08-21		
Ultra Broadband ANT	R&S	HL562	100157	2016-08-23	2017-08-22		
ESDV Test Receiver	R&S	ESDV	100008	2016-08-22	2017-08-21		
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2016-08-22	2017-08-21		
System Controller	CT	SC100	-				
Printer	EPSON	РНОТО ЕХЗ	CFNH234850				
Computer	IBM	8434	1S8434KCE99BLXLO*	-	-		
Loop Antenna	EMCO	6502	00042960	2016-08-23	2017-08-22		
ESPI Test Receiver	R&S	ESI26	838786/013	2016-08-22	2017-08-21		
3m OATS			N/A	2016-08-24	2017-08-23		
Horn Antenna	R&S	BBHA 9170	BBHA9170265	2016-08-24	2017-08-23		
Horn Antenna	R&S	BBHA 9120D	9120D-631	2016-08-24	2017-08-23		
Power meter	Anritsu	ML2487A	6K00003613	2016-08-22	2017-08-21		
Power sensor	Anritsu	MA2491A	32263	2016-08-22	2017-08-21		
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2016-08-23	2017-08-21		
LISN	AFJ	LS16C	10010947251	2016-08-22	2017-08-21		
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2016-08-23	2017-08-22		
9*6*6 Anechoic			N/A	2016-08-24	2017-08-23		
EMI Test Receiver	RS	ESCS30	100139	2016-08-22	2017-08-21		

Date: 2017-05-03



Page 7 of 84

### 3.0 **Technical Details**

### **Summary of test results** 3.1

The EUT has been tested according to the following specifications:

Requirement	CFR 47 Section	Result	Notes
Antenna Requirement	15.203, 15.247(b)(4)	PASS	Complies
Maximum Peak Out Power	15.247 (b)(1), (4)	PASS	Complies
Carrier Frequency Separation	15.247(a)(1)	PASS	Complies
20dB Channel Bandwidth	15.247 (a)(1)	PASS	Complies
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	PASS	Complies
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS	Complies
Spurious Emission, Band Edge, and Restricted bands	15.247(d),15.205(a), 15.209 (a),15.109	PASS	Complies
<b>Conducted Emissions</b>	15.207(a), 15.107	PASS	Complies
RF Exposure	15.247(i), 1.1307(b)(1)	PASS	Complies

#### 3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247 and ANSI C63.4:2014 AND ANSI C63.10:2013

### 4.0 **EUT Modification**

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES


Date: 2017-05-03



Page 8 of 84

### 5. **Power Line Conducted Emission Test**

#### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2014. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 -2014.

Test Voltage: 120V~60Hz Block diagram of Test setup



### 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2014. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

Date: 2017-05-03



Page 9 of 84

## A. EUT

Device	Manufacturer	Model	FCC ID	
VR Headset	Shenzhen Jingwah Information	CVR-155, FV200	RBD-CVR155	
VIX Headset	Technology Co., Ltd.	C v K-133, F v 200	KBD-CVK155	

#### B. Internal Device

Device	Manufacturer	Model	Rating

### C. Accessory

Device	Manufacturer	Model	FCC ID/DOC	Rating

### 5.4 **EUT Operating Condition**

Operating condition is according to ANSI C63.4 -2014.

- A Setup the EUT and simulators as shown on follow
- В Enable AF signal and confirm EUT active to normal condition

### 5.5 Power line conducted Emission Limit according to Paragraph 15.107, 15.207

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

#### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2017-05-03



Page 10 of 84

## A: Conducted Emission on Live Terminal (150kHz to 30MHz)

**EUT Operating Environment** 

Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa


**EUT set Condition: Keep Bluetooth Transmitting** 

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual





No. Mk.	Freq.			Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.4712	33.90	11.34	45.24	56.49	-11.25	QP	
2	0.4712	10.20	11.34	21.54	46.49	-24.95	AVG	

Date: 2017-05-03



Page 11 of 84

## B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

**EUT Operating Environment** 

Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa


**EUT set Condition: Keep Bluetooth Transmitting** 

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual

# 80.0 dBuV



No.	Mk.	Freq.	_		Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.4684	28.00	11.34	39.34	56.54	-17.20	QP	
2		0.4684	12.00	11.34	23.34	46.54	-23.20	AVG	

Date: 2017-05-03




# Page 12 of 84

#### 6 **Radiated Emission Test**

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- The EUT, peripherals were put on the turntable which table size is 1 m x 1.5 m, table high 0.8 m. All set up (2) is according to ANSI C63.10-2013.
- The frequency spectrum from 30 MHz to 25GHz was investigated. All readings from 30 MHz to 1 GHz (3) are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with (5) all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

## Block diagram of Test setup



- 6.2 Configuration of The EUT Same as section 5.3 of this report
- 6.3 **EUT Operating Condition** Same as section 5.4 of this report.

Date: 2017-05-03



Page 13 of 84

### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

## Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

Frequency Range (MHz)	Distance (m)	Field strength (dB $\mu$ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. All modulation have been tested GFSK was found as the worst case and only reported

Date: 2017-05-03



Page 14 of 84

## Test result

## General Radiated Emission Data and Harmonics Radiated Emission Data

# Radiated Emission In Horizontal/Vertical (30MHz----1000MHz)

**EUT set Condition:** Keep Bluetooth Transmitting

**Results:** Pass


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
30.200	31.79	Н	40.00
346.520	43.51	Н	46.00
594.000	42.82	Н	46.00
297.040	41.48	Н	46.00
159.520	30.20	V	43.50
396.000	42.45	V	46.00
937.120	40.54	V	46.00
30.600	37.37	V	40.00

Report No.: FCC1705010-02 Page 15 of 84

Date: 2017-05-03



# Test Figure:




Report No.: FCC1705010-02 Page 16 of 84

Date: 2017-05-03



## Test Figure:



Report No.: FCC1705010-02 Page 17 of 84

Date: 2017-05-03



## **Operation Mode: Transmitting under Low Channel (2402MHz)**

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4804	-	Н	74(Peak)/ 54(AV)
4804		V	74(Peak)/ 54(AV)
7206		H/V	74(Peak)/ 54(AV)
9608		H/V	74(Peak)/ 54(AV)
12010		H/V	74(Peak)/ 54(AV)
14412		H/V	74(Peak)/ 54(AV)
16814		H/V	74(Peak)/ 54(AV)
19216		H/V	74(Peak)/ 54(AV)
21618		H/V	74(Peak)/ 54(AV)
24020		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

## Operation Mode: Transmitting g under Middle Channel (2441MHz)

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4882		Н	74(Peak)/ 54(AV)
4882		V	74(Peak)/ 54(AV)
7323		H/V	74(Peak)/ 54(AV)
9764		H/V	74(Peak)/ 54(AV)
12205		H/V	74(Peak)/ 54(AV)
14646		H/V	74(Peak)/ 54(AV)
17087		H/V	74(Peak)/ 54(AV)
19528		H/V	74(Peak)/ 54(AV)
21969		H/V	74(Peak)/ 54(AV)
24410		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Report No.: FCC1705010-02 Page 18 of 84

Date: 2017-05-03



## **Operation Mode: Transmitting under High Channel (2480MHz)**

1	0 0	,	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4960		Н	74(Peak)/ 54(AV)
4960		V	74(Peak)/ 54(AV)
7440		H/V	74(Peak)/ 54(AV)
9920		H/V	74(Peak)/ 54(AV)
12400		H/V	74(Peak)/ 54(AV)
14880		H/V	74(Peak)/ 54(AV)
17360		H/V	74(Peak)/ 54(AV)
19840		H/V	74(Peak)/ 54(AV)
22320		H/V	74(Peak)/ 54(AV)
24800		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

<sup>2.</sup> Remark "---" means that the emissions level is too low to be measured

Page 19 of 84


Report No.: FCC1705010-02

Date: 2017-05-03



Please refer to the following test plots for details:

### Low Channel: Horizontal



## Low Channel: Vertical

107.0 dBuV/m

7.0

1000.000 2700.00



6100.00

7800.00

4400.00

9500.00

11200.00

14600.00

12900.00


18000.00 MHz

Date: 2017-05-03




## Middle Channel: Horizontal





## Middle Channel: Vertical

## 107.0 dBuV/m



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


adopt any other remedies which may be appropriate.

Date: 2017-05-03



## **High Channel: Horizontal**





## **High Channel: Vertical**

107.0 dBuV/m



Note: for the radiated emissions above 18G, it is the floor noise.

Date: 2017-05-03



Page 22 of 84

## 7.0 20dB Bandwidth Measurement

## 7.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

## 7.2 Limits of 20dB Bandwidth Measurement

N/A

## 7.3 Test Procedure.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span =3MHz, RBW =30 kHz, VBW=100 kHz, Sweep = auto Detector function = peak, Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. 6. Repeat above procedures until all frequencies measured were complete.

### 7.4 Test Result

## **Type of Modulation: GFSK**

EUT	UT VR Headset		Model		CVR-155						
Mode	9	Keep Tran	smitting Inpu		Input Voltage		Input Voltage		t Voltage		DC3.7V
Tempera	ture	24 de	g. C,	Humidity		nidity 56% RH					
Channel	Cha	nnel Frequency (MHz)	20 dB Bar (kH:		vidth Maximum (kHz		Pass/ Fail				
Low		2402	878	8			Pass				
Middle		2441	878	3			Pass				
High		2480	860	)			Pass				


Report No.: FCC1705010-02 Page 23 of 84

Date: 2017-05-03



## Test Figure:

# 1. Condition: Low Channel




Report No.: FCC1705010-02 Page 24 of 84

Date: 2017-05-03



## 2. Condition: Middle Channel




Report No.: FCC1705010-02 Page 25 of 84

Date: 2017-05-03



## 3. High Channel



Report No.: FCC1705010-02 Page 26 of 84

Date: 2017-05-03



## **Test Result**

Type of Modulation:  $\sqrt{J}/4DQPSK$ 

EUT		VR Headset		Model			CVR-155			
Mode	;	Keep Tra	insmitting	smitting Input Voltage		Input Voltage		smitting Input Voltage DC3.7		DC3.7V
Temperat	ture	24 de	eg. C,	Humidity			56% RH			
Channel	Cha	nnnel Frequency (MHz)	<b>2</b> 0 <b>a</b> B B a	B Bandwidth (kHz)		num Limit kHz)	Pass/ Fail			
Low		2402	121	1214			Pass			
Middle		2441	121	4			Pass			
High		2480	121	4			Pass			


Report No.: FCC1705010-02 Page 27 of 84

Date: 2017-05-03



## Test Figure:

# 1. Condition: Low Channel




Report No.: FCC1705010-02 Page 28 of 84

Date: 2017-05-03



## 2. Condition: Middle Channel




Report No.: FCC1705010-02 Page 29 of 84

Date: 2017-05-03



## 3. High Channel



Date: 2017-05-03



Page 30 of 84

## **Test Result**

**Type of Modulation: 8DPSK** 

EUT		VR Headset Model				CVR-155					
Mode		Keep Tra	nsmitting Input Voltage		g Input Voltage		mitting Input Voltage		smitting Input Voltage		DC3.7V
Tempera	ture	24 de	g. C,	Humidity	Humidity		56% RH				
Channel	Cha	nnel Frequency (MHz)		20dB Bandwidth (kHz)		imum Limit (kHz)	Pass/ Fail				
Low		2402	12	1214			Pass				
Middle		2441	1220 Pa				Pass				
High		2480	1214				Pass				


Report No.: FCC1705010-02 Page 31 of 84

Date: 2017-05-03



# Test Figure:

# 1. Condition: Low Channel




Report No.: FCC1705010-02 Page 32 of 84

Date: 2017-05-03



## 2. Condition: Middle Channel




Report No.: FCC1705010-02 Page 33 of 84

Date: 2017-05-03



## 3. High Channel



Date: 2017-05-03



Page 34 of 84

## 8. Maximum Output Power

### 8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

## 8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

### 8.3 Test Procedure

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW = 10MHz, RBW=3MHz; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4. Repeat above procedures until all frequencies measured were complete.

Date: 2017-05-03



Page 35 of 84

## **8.4Test Results**

Type of Modulation: GFSK

EUT	VR Headset			Model	Model		CVR-155	
Mode		Keep Transmitting Input Voltage			ge DC3.7V			
Temperature	e	24 deg	g. C,	Humidity	У		56% RH	
Channel	Cł	nannel Frequency (MHz)	Max. Power (dBm)	-		er Limit Bm)	Pass/ Fail	
Low		2402	2.08	· ·		30	Pass	
Middle		2441	2.31		30		Pass	
High		2480	2.20		30		Pass	

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

2. The worse case was recorded

EUT	EUT VR Heads		adset	Model		CVR-155	
Mode		Keep Tran	smitting	Input Voltage		DC3.7V	
Temperature	e	24 de	g. C,	Humidit	y		56% RH
Channel	Cł	hannel Frequency (MHz)	Max. Power (dBm)	Output	Peak Power Limit (dBm)		Pass/ Fail
Low		2402	1.19		30		Pass
Middle		2441	1.33		30		Pass
High		2480	1.19	· ·	3	30	Pass

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

2. The worse case was recorded

Date: 2017-05-03



Page 36 of 84

## **Type of Modulation: 8DPSK**

-5 P · · · · · · · · · · · · · · · · · ·								
EUT	EUT VR Headset		Model			CVR-155		
Mode		Keep Tran	Keep Transmitting Input Voltage			DC3.7V		
Temperature	Э	24 deş	g. C,	Humid	ity		56% RH	
Channel	Cl	nannel Frequency (MHz)	Max. Power C (dBm)	Output	Peak Power Limit (dBm)		Pass/ Fail	
Low		2402	1.39	3		0	Pass	
Middle		2441	1.44		30		Pass	
High		2480	1.40		30		Pass	

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

2. The worse case was recorded

Date: 2017-05-03



Page 37 of 84

# 9. Carrier Frequency Separation

#### 9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 9.2 Limits of Carrier Frequency Separation

The Maximum Power Spectral Density Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

#### 9.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span; Video (or Average) Bandwidth (VBW) ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.

Report No.: FCC1705010-02 Page 38 of 84

Date: 2017-05-03




#### 9.4Test Result

#### **Type of Modulation: GFSK**

EUT	VR Headset		Model	CVR-155	
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Carrier Frequency Separation			Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2/3 of the 20 dB bandwidth		Pass	

#### **Test Plots**



Report No.: FCC1705010-02 Page 39 of 84


Date: 2017-05-03



# Type of Modulation: $\sqrt{J}/4DQPSK$

EUT	VR Headset		Model	CVR-155	
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Carrier Frequency Separation			Limit		Pass/ Fail
1.000MHz		≥ 25 kHz or 2/3 of 20 dB bandwidth			Pass

# **Test Plots**



Report No.: FCC1705010-02 Page 40 of 84


Date: 2017-05-03



### **Type of Modulation: 8DPSK**

EUT	VR Headset	Model	CVR-155		
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Carrier Frequency Separation			Limit		Pass/ Fail
	1.000MHz	≥ 2	5 kHz or 2/3 of 2	0 dB bandwidth	Pass

# **Test Plots**



Date: 2017-05-03



Page 41 of 84

# 10. Number of Hopping Channels

#### 10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

#### 10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

#### **10.3 Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW=100 kHz, VBW=300 kHz; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Record the number of hopping channels.

Report No.: FCC1705010-02 Page 42 of 84

Date: 2017-05-03




#### 10.4Test Result

#### Type of Modulation: GFSK

EUT	VR Headset		Model	CVR-155		
Mode	Hopping On		Input Voltage	DC3.7V		
Temperature		24 deg. C,	Humidity	56% RH		
Operating Frequen	quency Number of hopping channels		oing channels	Limit	Pass/ Fail	
2402-2480MHz	79			≥ 15	Pass	

### **Test Plot**



Report No.: FCC1705010-02 Page 43 of 84


Date: 2017-05-03



Type of Modulation: Л/4DQPSK

EUT	VR Headset		Model		CVR-155	
Mode	Hopping On		Input Voltage			DC3.7V
Temperature	24 deg. C,		Humidity		56% RH	
Operating Frequen	Frequency Number of hopp channels		oing	Liı	nit	Pass/ Fail
2402-2480MHz		79		≥ 15		Pass

### **Test Plot**



Report No.: FCC1705010-02 Page 44 of 84


Date: 2017-05-03



**Type of Modulation: 8DPSK** 

EUT	VR Headset		Model			CVR-155	
Mode	Hopping On		Input V	Voltage DC3.7V		DC3.7V	
Temperature	24 deg. C,		Humidi	ity	56% RH		
Operating Frequer	ncy	Number of hopp channels		Liı	mit	Pass/ Fail	
2402-2480MHz	80MHz 79			≥	≥ 15 Pass		

### **Test Plot**



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2017-05-03



Page 45 of 84

### 11. Time of Occupancy (Dwell Time)

#### 11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

#### 11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

#### 11.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold
- 3. Measure the dwell time using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Date: 2017-05-03



Page 46 of 84

#### 11.4 Test Result

**Type of Modulation: GFSK** 

EUT	VRI	VR Headset		CVR-155			
Mode	Keep Tr	ansmitting	Input Voltage	oltage DC3.7V			
Temperatur	re 24 c	leg. C,	Humidity	5	56% RH		
Channel	Reading	Hoping	g Rate	Actual	Limit		
	DH5						
Middle	2.99ms	266.66	7 hop/s	0.319s	0.4s		

Actual = Reading  $\times$  (Hopping rate / Number of channels)  $\times$  Test period, Test period = 0.4 [seconds / channel]  $\times$  79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: DH5 was the worst case.

Report No.: FCC1705010-02 Page 47 of 84


Date: 2017-05-03



Test Plots:

DH5

Middle Channel:



Date: 2017-05-03



Page 48 of 84

### **Test Result**

Type of Modulation:  $\sqrt{1/4}$ DOPSK

-340 00 00 00 00 00 00 00 00 00 00 00 00 0							
EUT	VR Headset		Model	CVR-155			
Mode	Keep Tr	ansmitting	Input Voltage	DC3.7V			
Temperatur	e 24 d	leg. C,	Humidity	imidity 56% RH			
Channel	Reading	Hoping	g Rate	Actual	Limit		
	2DH5						
Middle	3.01ms	266.66	7 hop/s	0.321s	0.4s		

Actual = Reading  $\times$  (Hopping rate / Number of channels)  $\times$  Test period, Test period = 0.4 [seconds / channel]  $\times$  79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: 2DH5 was the worst case.


Report No.: FCC1705010-02 Page 49 of 84

Date: 2017-05-03



Test Plots:

#### **2DH5**



Date: 2017-05-03



Page 50 of 84

### Type of Modulation: 8DPSK

EUT	VR I	VR Headset		C	VR-155
Mode	Keep Tr	ansmitting	Input Voltage	DC3.7V	
Temperatur	e 24 d	leg. C,	Humidity	56% RH	
Channel	Reading	Hoping	g Rate	Actual	Limit
3DH5					
Middle	2.99ms	266.667	7 hop/s	0.319s	0.4s

Actual = Reading  $\times$  (Hopping rate / Number of channels)  $\times$  Test period, Test period = 0.4 [seconds / channel]  $\times$  79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: 3DH5 was the worst case.


Report No.: FCC1705010-02 Page 51 of 84

Date: 2017-05-03



Test Plots:

#### **3DH5**




Date: 2017-05-03



Page 52 of 84

### 12 Out of Band Measurement

### 12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

### 12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### 12.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. Peak values with RBW=VBW=1MHz and PK detector.

For bandage test, the spectrum set as follows: RBW=100kHz, VBW=300 kHz. A conducted measurement used

- Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.
- 2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No.: FCC1705010-02 Page 53 of 84


Date: 2017-05-03



# **Type of Modulation: GFSK**

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature		24 deg. C	Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBµV/m)	48.5		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	AV(dBμV/m)		54(dBμV/m)
2390MHz				



Report No.: FCC1705010-02 Page 54 of 84


Date: 2017-05-03



# Type of Modulation: GFSK

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	43.7		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	AV(dBμV/m)		54(dBµV/m)
2483.5MHz				



Report No.: FCC1705010-02 Page 55 of 84


Date: 2017-05-03



# Type of Modulation: GFSK

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature		24 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	46.3		$74(dB\mu V/m)$
Restrict Band	$AV(dB\mu V/m)$		Limit	54(dBµV/m)
2390MHz				



Report No.: FCC1705010-02 Page 56 of 84


Date: 2017-05-03



# Type of Modulation: GFSK

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 42.9			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBµV/m)
2483.5MHz				



Report No.: FCC1705010-02 Page 57 of 84


Date: 2017-05-03



# Type of Modulation: $\sqrt{J}/4DQPSK$

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 47.7			74(dBμV/m)
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				



Report No.: FCC1705010-02 Page 58 of 84


Date: 2017-05-03



# Type of Modulation: JI/4DQPSK

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 43.6			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				



Report No.: FCC1705010-02 Page 59 of 84


Date: 2017-05-03



# Type of Modulation: $\sqrt{J}/4DQPSK$

#### 12.4 Out of Band Test Result

Product:		VR Headset	Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 45.4			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				



Report No.: FCC1705010-02 Page 60 of 84


Date: 2017-05-03



# Type of Modulation: $\sqrt{J}/4DQPSK$

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	42.6		74(dBμV/m)
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				



Report No.: FCC1705010-02 Page 61 of 84


Date: 2017-05-03



# **Type of Modulation: 8DPSK**

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	45.9		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				



Report No.: FCC1705010-02 Page 62 of 84


Date: 2017-05-03



# **Type of Modulation: 8DPSK**

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 43.0			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				



Report No.: FCC1705010-02 Page 63 of 84


Date: 2017-05-03



# **Type of Modulation: 8DPSK**

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 44.9			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				



Report No.: FCC1705010-02 Page 64 of 84


Date: 2017-05-03



# **Type of Modulation: 8DPSK**

#### 12.4 Out of Band Test Result

Product:	VR Headset		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 42.3			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBµV/m)
2483.5MHz				



Date: 2017-05-03



Page 65 of 84

# 13.0 Antenna Requirement

# 13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 13.2 Antenna Connected constructions

Integral antenna used. The maximum Gain of the antennas is 2.0dBi.

Report No.: FCC1705010-02 Page 66 of 84

Date: 2017-05-03




#### 14.0 FCC ID Label

#### FCC ID: RBD-CVR155

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### **Mark Location:**



Page 67 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



#### 15.0 Photo of testing


Conducted Emission Test Setup:



Date: 2017-05-03



### Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Date: 2017-05-03



# Photographs - EUT

Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Page 70 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Page 71 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Page 72 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Report No.: FCC1705010-02 Page 73 of 84

Date: 2017-05-03



## Outside view



Report No.: FCC1705010-02 Page 74 of 84

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Page 75 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Report No.: FCC1705010-02 Page 76 of 84

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Page 77 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Page 78 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Page 79 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Page 80 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Page 81 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Page 82 of 84

Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Page 83 of 84 Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate


Page 84 of 84


Report No.: FCC1705010-02

Date: 2017-05-03



Inside view





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate