







ISO/IEC17025Accredited Lab.

Report No: FCC 1304100-02 File reference No: 2013-04-26

Applicant: Shenzhen Jingwah Information Technology Co., Ltd.

Product: Tablet PC

Model No: M727, M728HD, PMID708X

Trademark: Polaroid

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4 and FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: April 26, 2013

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

5/F, Block 4, Anhua Industrial Zone., No.8 TaiRan Rd.CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1304100-02 Page 2 of 87

Date: 2013-04-26



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC-Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.

Page 3 of 87

Report No: 1304100-02

Date: 2013-04-26



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	9
3.1	Summary of Test Results	9
3.2	Test Standards.	9
4.0	EUT Modification.	9
5.0	Power Line Conducted Emission Test.	10
5.1	Schematics of the Test.	10
5.2	Test Method and Test Procedure.	10
5.3	Configuration of the EUT	10
5.4	EUT Operating Condition.	11
5.5	Conducted Emission Limit.	11
5.6	Test Result.	11
6.0	Radiated Emission test.	14
6.1	Test Method and Test Procedure.	14
6.2	Configuration of the EUT	14
6.3	EUT Operation Condition.	14
6.4	Radiated Emission Limit.	15
7.0	6dB Bandwidth Measurement.	34
8.0	Maximum Peak Output Power.	50
9.0	Power Spectral Density Measurement.	53
10.0	Out of Band Measurement.	68
11.0	Antenna Requirement.	77
12.0	FCC ID Label	78
13.0	Photo of Test Setup and EUT View.	79

Report No: 1304100-02 Date: 2013-04-26



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Shenzhen Jingwah Information Technology Co., Ltd.

Address: 4F, Bldg 4, Jinghua Square, No.1 Huafa North Road, Futian District, Shenzhen, China

Telephone: 0755-83976295 Fax: 0755-83204874

1.3 Description of EUT

Product: Tablet PC

Manufacturer: Shenzhen Jingwah Information Technology Co., Ltd.

Address: 4F, Bldg 4, Jinghua Square, No.1 Huafa North Road, Futian District,

Shenzhen, China

Brand Name: Polaroid Model Number: M727

Additional Model Number: M728HD, PMID708X

Additional Trade Name: N/A

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20): OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20) : 2412-2462MHz;

Channel Spacing IEEE 802.11b/g/n (HT20) : 5MHz Air Data Rate IEEE 802.11b : 11, 5.5, 2, 1 Mbps

IEEE 802.11g : 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1304100-02 Page 5 of 87

TIMEWAY

Antenna: Integral Antenna with maximum gain 3.0dBi

Power Supply: Model No.: K-A70501500U

Input: 100-240V, 50/60Hz, 0.45A MAX; Output: 5V, 1500mA

1.4 Submitted Sample: 2 Samples

1.5 Test Duration

Date: 2013-04-26

2013-04-19 to 2013-04-26

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 87

Report No: 1304100-02

Date: 2013-04-26



2.0		Test Equip	ments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2012-08-21	2013-08-20
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2012-08-21	2013-08-20
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2012-08-21	2013-08-20
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2012-08-21	2013-08-20
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2012-08-21	2013-08-20
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2012-08-21	2013-08-20
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-
Loop Antenna	EMCO	6502	00042960	2012-08-21	2013-08-20
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2012-08-21	2013-08-20
3m OATS			N/A	2012-08-21	2013-08-20
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2012-08-21	2013-08-20
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2012-08-21	2013-08-20
Power meter	Anritsu	ML2487A	6K00003613	2012-08-21	2013-08-20
Power sensor	Anritsu	MA2491A	32263	2012-08-21	2013-08-20
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2012-08-21	2013-08-20
LISN	AFJ	LS16C	10010947251	2012-08-21	2013-08-20
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2012-08-21	2013-08-20
9*6*6 Anechoic			N/A	2012-08-21	2013-08-20
EMI Test Receiver	RS	ESCS30	100139	2012-08-21	2013-08-20
LISN	AFJ	LS16C	10010947251	2012-08-21	2013-08-20
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2012-08-21	2013-08-20

Report No: 1304100-02 Page 7 of 87



2.1 **Auxiliary Equipment**

Date: 2013-04-26

Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
	Wiodel Ivo.	Beriui 110.		Cuote	Тесть/вос
TF Card			Kingston		
Earphone					

Date: 2013-04-26



Page 8 of 87

3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 54Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 65Mbps data rate (worst case) were chosen for full testing

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.

Date: 2013-04-26



3.0 **Technical Details**

3.1 **Summary of test results**

Standard	Test Type	Result	Notes
CCC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

EUT Modification 4.0

No modification by Shenzhen Timeway Technology Consulting Co., Ltd


Page 10 of 87

Report No: 1304100-02 Date: 2013-04-26



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Manufacturer Model	
Tablet PC	Shenzhen Jingwah Information Technology Co., Ltd.	M727, M728HD, PMID708X	RBD-M727

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1304100-02 Page 11 of 87

Date: 2013-04-26



C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207.

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)	
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0
$5.00 \sim 30.00$	73.0	60.0	60.0	50.0

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2013-04-26



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging and Keep Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



Frequency	Lina	Reading(dBμV)		Limit(dBµV)	
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.469	Live	27.44	14.44	56.53	46.53
0.601	Live	49.91	36.90	56.00	46.00
0.832	Live	36.82	20.72	56.00	46.00
1.480	Live	50.89	31.19	56.00	46.00
1.997	Live	51.50	38.30	56.00	46.00
2.635	Live	51.05	39.85	56.00	46.00
4.390	Live	46.76	38.36	56.00	46.00
5.585	Live	44.65	36.45	60.00	50.00
25.388	Live	43.59	34.59	60.00	50.00

Date: 2013-04-26



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging and Keep Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



Frequency	Line	Reading(dBμV)	Limit(dBµV)	
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.614	Neutral	51.39	38.69	56.00	46.00
0.908	Neutral	49.20	34.90	56.00	46.00
1.563	Neutral	49.63	37.13	56.00	46.00
2.200	Neutral	49.08	38.88	56.00	46.00
2.706	Neutral	43.58	33.38	56.00	46.00
3.363	Neutral	41.05	30.25	56.00	46.00
3.982	Neutral	38.49	27.09	56.00	46.00
4.616	Neutral	42.35	27.95	56.00	46.00
5.112	Neutral	48.05	40.95	60.00	50.00
28.428	Neutral	40.63	31.93	60.00	50.00

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1304100-02 Page 14 of 87

Date: 2013-04-26



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

Block diagram of Test setup Distance = 3m Computer Pre -Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT
 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: 1304100-02 Page 15 of 87

Date: 2013-04-26



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209

	-	E 1
Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: 1304100-02 Page 16 of 87

Date: 2013-04-26



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/ In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Transmitting

Results: Pass

Frequency (MHz)	Frequency (MHz) Level@3m (dB \(\mu \) V/m)		Limit@3m (dB \u03b4 V/m)	
123.800	32.98	Н	43.50	
30.560	31.85	Н	40.00	
247.520	247.520 36.73		46.00	
148.520	148.520 35.79		43.50	
123.800	123.800 38.26		43.50	
31.3220	35.95	V	40.00	
346.5602	46.5602 42.61		46.00	
36.200	36.98	V	40.00	


Page 17 of 87

Report No: 1304100-02

Date: 2013-04-26



Test Figure:



Date: 23.APR.2013 16:30:52


Page 18 of 87

Report No: 1304100-02

Date: 2013-04-26



Test Figure:



Date: 23.APR.2013 16:38:41

Report No: 1304100-02 Page 19 of 87

Date: 2013-04-26



Operation Mode: Transmitting & Receiving under CH01 for 11g at 54Mbps

			_
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2412.00	91.19 (PK)	Н	Fundamental Frequency
2412.00	91.39 (PK)	V	Fundamental Frequency
4824.00		Н	74(Peak)/ 54(AV)
4824.00		V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16884		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54Mbps

Date: 2013-04-26



Operation Mode: Transmitting & Receiving under CH06 for 11g at 54Mbps

	8		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2437.00	91.44 (PK)	Н	Eundomontal Eroquanov
2437.00	91.47 (PK)	V	Fundamental Frequency
4874.00		Н	74(Peak)/ 54(AV)
4874.00		V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54 Mbps

Operation Mode: Transmitting & Receiving under CH11 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)	
2462.00	91.25 (PK)	Н	Fundamental Frequency	
2462.00	90.84 (PK)	V	Fundamental Frequency	
4924	1	Н	74(Peak)/ 54(AV)	
4924	•	V	74(Peak)/ 54(AV)	
7368	-	H/V	74(Peak)/ 54(AV)	
9848	1	H/V	74(Peak)/ 54(AV)	
12310	•	H/V	74(Peak)/ 54(AV)	
14772	1	H/V	74(Peak)/ 54(AV)	
17234	1	H/V	74(Peak)/ 54(AV)	
19696	1	H/V	74(Peak)/ 54(AV)	
22158		H/V	74(Peak)/ 54(AV)	
24620		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 54 Mbps

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2013-04-26




Please refer to the following test plots for details:

CH01 for 11g at 54Mbps: Horizontal



CH01 for 11g at 54Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-04-26



CH06 for 11g at 54Mbps: Vertical



CH06 for 11g at 54Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-04-26



CH11 for 11g at 54Mbps: Vertical



CH11 for 11g at 54Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2013-04-26



Operation Mode: Transmitting & Receiving under CH01 for 11b at 11Mbps

	0 0		•
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
2412.00	90.26 (PK)	Н	Even domental Engavenery
2412.00	91.36 (PK)	V	Fundamental Frequency
4824.00		Н	74(Peak)/ 54(AV)
4824.00		V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)
12060 14472 16684 19296 21708	 	H/V H/V H/V H/V	74(Peak)/ 54(AV) 74(Peak)/ 54(AV) 74(Peak)/ 54(AV) 74(Peak)/ 54(AV) 74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Operation Mode: Transmitting & Receiving under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2437.00	2437.00 90.15 (PK)		Eundomontal Eroguanay
2437.00	91.63 (PK)	V	Fundamental Frequency
4874.00	1	Н	74(Peak)/ 54(AV)
4874.00	1	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185	-	H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1304100-02 Page 25 of 87

Date: 2013-04-26



Operation Mode: Transmitting & Receiving under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)	
2462.00	91.45 (PK)	Н	Fundamental Frequency	
2462.00	91.38 (PK)	V	rundamental riequency	
4924		Н	74(Peak)/ 54(AV)	
4924		V	74(Peak)/ 54(AV)	
7368		H/V	74(Peak)/ 54(AV)	
9848		H/V	74(Peak)/ 54(AV)	
12310		H/V	74(Peak)/ 54(AV)	
14772		H/V	74(Peak)/ 54(AV)	
17234		H/V	74(Peak)/ 54(AV)	
19696		H/V	74(Peak)/ 54(AV)	
22158		H/V	74(Peak)/ 54(AV)	
24620		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps

Date: 2013-04-26




Please refer to the following test plots for details:

CH01 for 11b at 11Mbps: Horizontal



CH01 for 11b at 11Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-04-26



CH06 for 11b at 11Mbps: Vertical



CH06 for 11b at 11Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-04-26



CH11 for 11b at 11Mbps: Vertical



CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2013-04-26



Operation Mode: Transmitting & Receiving under CH01 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2412.00	92.36 (PK)	Н	Eundomontal Eroguanov
2412.00	90.92 (PK)	V	Fundamental Frequency
4824.00		Н	74(Peak)/ 54(AV)
4824.00		V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

Operation Mode: Transmitting & Receiving under CH06 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2437.00	91.55 (PK)	Н	Fundamental Frequency
2437.00	91.01 (PK)	V	Fundamental Frequency
4874.00	1	Н	74(Peak)/ 54(AV)
4874.00	1	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00	1	H/V	74(Peak)/ 54(AV)
12185	1	H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059	1	H/V	74(Peak)/ 54(AV)
19496	1	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370	-	H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1304100-02 Page 30 of 87

Date: 2013-04-26



Operation Mode: Transmitting & Receiving under CH11 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2462.00	91.12 (PK)	Н	Fundamental Frequency
2462.00	90.81 (PK)	V	Fundamental Frequency
4924		Н	74(Peak)/ 54(AV)
4924		V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

Date: 2013-04-26




Please refer to the following test plots for details:

CH01 for 11n HT20 at 65Mbps: Horizontal



CH01 for 11n HT20 at 65Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-04-26



CH06 for 11n HT20 at 65Mbps: Vertical



CH06 for 11n HT20 at 65Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Date: 2013-04-26



CH11 for 11n HT20 at 65Mbps: Vertical



CH11 for 11n HT20 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No: 1304100-02 Page 34 of 87

Date: 2013-04-26



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Report No: 1304100-02 Page 35 of 87

Date: 2013-04-26



6dB Occupied Bandwidth


EUT	UT Tablet PC Model		M727, M728HD, PMID708X				
Mode 802.11b)	Input Voltage		AC 120V		
Temperati	ure	24 deg.	C,	Humidity	lumidity 56% RH		56% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)		mum Limit MHz)	Pass/ Fail
1		2412	1	10.08		0.5	Pass
6		2437	1	10.08		0.5	Pass
11		2462	1	10.08		0.5	Pass
1		2412	11	8.52		0.5	Pass
6		2437	11	9.84		0.5	Pass
11		2462	11	9.84		0.5	Pass

Report No: 1304100-02 Page 36 of 87

Date: 2013-04-26



1. 802.11b at 1Mbps of CH01




Date: 22.APR.2013 10:38:50

Report No: 1304100-02 Page 37 of 87

Date: 2013-04-26



2. 802.11b at 1Mbps of CH06



Date: 22.APR.2013 10:39:45


Page 38 of 87

Report No: 1304100-02

Date: 2013-04-26



3. 802.11b at 1Mbps of CH11




Date: 22.APR.2013 10:40:58

Report No: 1304100-02 Page 39 of 87

Date: 2013-04-26



4. 802.11b at 11Mbps of CH01




Date: 22.APR.2013 10:44:07

Report No: 1304100-02 Page 40 of 87

Date: 2013-04-26



5. 802.11b at 11Mbps of CH06




Date: 22.APR.2013 10:43:10

Report No: 1304100-02 Page 41 of 87

Date: 2013-04-26



6. 802.11b at 11Mbps of CH11



Date: 22.APR.2013 10:42:11

Report No: 1304100-02 Page 42 of 87

Date: 2013-04-26



6dB Occupied Bandwidth

EUT	UT Tablet PC M		Model		M727, M728HD, PM	41D708X		
Mode		802.11g	Input Voltag	nput Voltage AC 120V				
Temperat	ure	24 deg. C,	Humidity			56% RH		
Channel		nel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass/ Fail	
1		2412	6		16.38	0.5	Pass	
6	2437		6	16.38		0.5	Pass	
11		2462	6		16.38	0.5	Pass	


Report No: 1304100-02 Page 43 of 87

Date: 2013-04-26



Test Plots:

1. 802.11g at 6Mbps of CH01




Date: 22.APR.2013 10:45:37

Report No: 1304100-02 Page 44 of 87

Date: 2013-04-26



2. 802.11g at 6Mbps of CH06




Date: 22.APR.2013 10:46:46

Report No: 1304100-02 Page 45 of 87

Date: 2013-04-26



3. 802.11g at 6Mbps of CH11



Date: 22.APR.2013 10:47:45

Report No: 1304100-02 Page 46 of 87

Date: 2013-04-26



6dB Occupied Bandwidth

EUT		Tablet PC			Model		M727, M728HD, PMID708X		
Mode			802.11n		Input Vol	tage		AC 120V	
Temperat	ure		24 deg. C,		Humidity	•		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)				num Limit MHz) Pass/ Fail		
1	2412		HT20	17.64			0.5	Pass	
6	2437 HT20		17	7.64		0.5	Pass		
11		2462	HT20	17.64			0.5	Pass	

Page 47 of 87


Report No: 1304100-02

Date: 2013-04-26



Test Plots:

1. 802.11n at HT20 of CH01




Date: 22.APR.2013 11:27:34

Report No: 1304100-02 Page 48 of 87

Date: 2013-04-26



2. 802.11n at HT20 of CH06




Date: 22.APR.2013 11:29:27

Report No: 1304100-02 Page 49 of 87

Date: 2013-04-26



3. 802.11n at HT20 of CH11



Date: 22.APR.2013 11:30:59

Report No: 1304100-02


Date: 2013-04-26



Page 50 of 87

8. Maximum Peak Output Power

8.1 Test Setup



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Report No: 1304100-02 Page 51 of 87

Date: 2013-04-26



8.4Test Results

EUT		Tablet PC	C Model			M727, M728HD, PMID708X	
Mode	Mode 802.11b		Input Voltage		ge	AC 120V	
Temperat	Temperature 24 deg. C,		·,	, Humidity		56% RH	
Channel	Cha	Channel Frequency Per (MHz)		ower Output dBm) Lim		Peak Power Limit (dBm)	Pass/ Fail
1		2412		6.85		30	Pass
6		2437		7.43		30	Pass
11		2462		7.31		30	Pass

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The test voltage varied from AC102V-138V. The worse case was recorded

EUT	EUT Tablet PC Model			Model		M727, M728HD, PMID708X		
Mode	Mode 802.11g Input Voltage					AC 120V		
Temperati	ure	24 deg. C,	leg. C, Humidity			56% RH		
Channel	Cha	Channel Frequency (MHz)		Peak Power Output (dBm)	Peak Pow (dB)		Pass/ Fail	
1		2412		4.13	30)	Pass	
6	·	2437		4.49	30)	Pass	
11	2462			4.63	30)	Pass	

Note: 1. At finial test to get the worst-case emission at 54Mbps for CH01, CH06 and CH11

- 2. The result basic equation calculation as follow:Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The test voltage varied from AC102V-138V. The worse case was recorded

Report No: 1304100-02 Page 52 of 87

Date: 2013-04-26



EUT	EUT Tablet PC			Model	M727,	M727, M728HD, PMID708X		
Mode	Mode 802.11n (HT20)) Input Voltage			AC 120V		
Temperati	ure	24 deg. C,		Humidity	Humidity 56% I			
Channel	Cha	Channel Frequency (MHz)		ak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail		
1		2412		3.10	30	Pass		
6		2437		3.26	30	Pass		
11		2462		3.43	30	Pass		

Note: 1. At finial test to get the worst-case emission at 11n HT20 for CH01, CH06 and CH11

- 2. The result basic equation calculation as follow:Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The test voltage varied from AC102V-138V. The worse case was recorded


Report No: 1304100-02 Page 53 of 87

Date: 2013-04-26



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = \max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be ≤ 8 dBm.

Report No: 1304100-02 Page 54 of 87

Date: 2013-04-26



9.4Test Result

EUT	EUT Tablet PC		C Model		M	M727, M728HD, PMID708X	
Mode	Mode 802.11b 11Ml		Ibps Input Voltage		е	AC 120V	
Temperati	Temperature 24 deg. C,		,	Humidity		56% RH	
Channel	Channel Frequency (MHz)			RF Power	Maximum Limit (dBm)	Pass/ Fail	
				11Mbps			
1		2412		-15.66	8	Pass	
6		2437 -		-15.71	8	Pass	
11		2462		-15.48	8	Pass	

EUT	EUT Tablet PC		C Model		M7	M727, M728HD, PMID708X		
Mode	Mode 802.11b 1Ml		bps Input Voltage			AC 120V		
Temperati	Temperature 24 c		C, Humidity			56% RH		
Channel	Channel Freque (MHz)			RF Power rel (dBm)	Maximum Limit (dBm)	Pass/ Fail		
				1Mbps				
1		2412		-18.28	8	Pass		
6		2437 -		-16.97	8	Pass		
11		2462	-	-17.08	8	Pass		

Report No: 1304100-02 Page 55 of 87

Date: 2013-04-26



EUT	EUT		Tablet PC Model		M727, M728HD, PMID708X	
Mode		802.11g 6Mbps	Input Voltage		AC 120V	
Temperature	;	24 deg. C,	Humidity		56% RH	
Channel	Ch	annel Frequency (MHz)	Final RF Power Level (dBm)	Maximum el Limit (dBm)		Pass/ Fail
			6Mbps			
1	2412		-23.61		8	Pass
6	2437		-24.11		8	Pass
11		2462	-23.99		8	Pass

EUT	Tablet PC		Model		M727, M728HD, PMID708X		
Mode		802.11n HT20	Input Voltage		AC 120V		
Temperat	ure	24 deg. C,	Humidity		56% RH		
Channel	Ch	annel Frequency (MHz)	Final RF Power Level (dBm)	M	(dBm)	Pass/ Fail	
			HT20				
1		2412	-25.38		8	Pass	
6		2437	-23.95		8	Pass	
11		2462	-24.54		8 Pass		

Page 56 of 87


Report No: 1304100-02

Date: 2013-04-26



9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01




Date: 22.APR.2013 10:58:12

Report No: 1304100-02 Page 57 of 87

Date: 2013-04-26



2. 802.11b at 11Mbps at CH06




Date: 22.APR.2013 10:59:05

Report No: 1304100-02 Page 58 of 87

Date: 2013-04-26



3. 802.11b at 11Mbps of CH11



Date: 22.APR.2013 11:00:06


Page 59 of 87

Report No: 1304100-02

Date: 2013-04-26



4. 802.11b at 1Mbps of CH1



Date: 22.APR.2013 10:52:19


Page 60 of 87

Report No: 1304100-02

Date: 2013-04-26



5. 802.11b at 1Mbps of CH6



Date: 22.APR.2013 10:54:47


Page 61 of 87

Report No: 1304100-02

Date: 2013-04-26



6. 802.11b at 1Mbps of CH11




Date: 22.APR.2013 10:54:04

Report No: 1304100-02 Page 62 of 87

Date: 2013-04-26



7. 802.11g at 6Mbps of CH1




Date: 22.APR.2013 10:51:11

Report No: 1304100-02 Page 63 of 87

Date: 2013-04-26



8. 802.11g at 6 Mbps of CH6



Date: 22.APR.2013 10:55:46


Page 64 of 87

Report No: 1304100-02

Date: 2013-04-26



9. 802.11g at 6 Mbps of CH11



Date: 22.APR.2013 10:48:52


Page 65 of 87

Report No: 1304100-02

Date: 2013-04-26



10. 802.11n at HT20 of CH01



Date: 22.APR.2013 11:33:30


Page 66 of 87

Report No: 1304100-02

Date: 2013-04-26



11. 802.11n at HT20 of CH06



Date: 22.APR.2013 11:32:50


Page 67 of 87

Report No: 1304100-02

Date: 2013-04-26



12. 802.11n at HT20 of CH11



Date: 22.APR.2013 11:32:10


Report No: 1304100-02 Page 68 of 87

Date: 2013-04-26



10 Out of Band Measurement

10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. this is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), after pre-test. It was found that the worse radiated emission was get at the lying position. the worse case was recorded

2. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Report No: 1304100-02

Date: 2013-04-26




For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge and Restricted band Measurement

	Band dage and recontrolled band frombaroniem									
EUT	Ta	ablet PC	Model	M727, M728HD, PMID708X						
Mode	Keeping	g Transmitting	Input Voltage	AC 120V						
Temperature	24	l deg. C,	Humidity	56% RH						
Test Result:		Pass	Detector	PK						
2400	PK (dBµV/m)	43.73	T ::4	$74(dB\mu V/m)$						
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$						
2390	PK (dBμV/m)	37.12	Limit	74(dBμV/m)						
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$						

Test Figure:



Date: 22.APR.2013 11:05:35

Note: The Max. FS in Restrict Band are measured in conventional method.

Page 70 of 87

Report No: 1304100-02

Date: 2013-04-26




CH11 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Ta	ablet PC	Model	M727, M728HD, PMID708X
Mode	Keeping	g Transmitting	Input Voltage	AC 120V
Temperature	24	4 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2483.5	PK (dBμV/m)	/		74(dBμV/m)
	AV (dBμV/m)			54(dBμV/m)

Test Figure:



Date: 22.APR.2013 11:09:49

Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1304100-02

Date: 2013-04-26




For 802.11b mode

CH01 at 1Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Ta	ablet PC	Model	M727, M728HD, PMID708X					
Mode	Keeping	g Transmitting	Input Voltage	AC 120V					
Temperature	24	deg. C,	Humidity	56% RH					
Test Result:		Pass	Detector	PK					
2400	PK (dBμV/m)	44.13	T ::4	$74(dB\mu V/m)$					
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$					
2390	PK (dBμV/m)	37.16	Limit	74(dBμV/m)					
	AV (dBμV/m)		Limit	54(dBμV/m)					

Test Figure:



Date: 22.APR.2013 11:05:57

Note: The Max. FS in Restrict Band are measured in conventional method.

Page 72 of 87

Report No: 1304100-02

Date: 2013-04-26




CH11 at 1Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	M727, M728HD, PMID708X
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	42.92	Limit	74(dBμV/m)
	AV (dBμV/m)			54(dBμV/m)

Test Figure:



Date: 22.APR.2013 11:07:38

Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2013-04-26




For 802.11g mode

CH01 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	M727, M728HD, PMID708X
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass	Detector	PK
2400	PK (dBµV/m)	43.69	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$
2390	PK (dBµV/m)	37.06	Limit	74(dBμV/m)
	AV (dBμV/m)		Lillit	54(dBµV/m)

Test Figure:



Date: 22.APR.2013 11:05:10

Page 74 of 87

Report No: 1304100-02

Date: 2013-04-26




CH11 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Ta	ablet PC	Model		M727, M728HD, PMID708X
Mode	Keeping Transmitting		Input Voltage		AC 120V
Temperature	24 deg. C,		Humidity		56% RH
Test Result:	Pass		Detec	ctor	PK
2483.5	PK (dBµV/m)	43.26	T 1 14	$74(dB\mu V/m)$ $54(dB\mu V/m)$	
	AV (dBμV/m)		Limit		

Test Figure:



Date: 22.APR.2013 11:08:48

Date: 2013-04-26




For 802.11n (HT20) mode

CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	M727, M728HD, PMID708X
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBμV/m)	43.92	T tout	74(dBμV/m)
	AV (dBμV/m)		Limit	54(dBµV/m)
2390	PK (dBμV/m)	37.27	Limit	74(dBμV/m)
	AV (dBμV/m)		- Limit	54(dBμV/m)

Test Figure:



Date: 22.APR.2013 11:36:05

Page 76 of 87

Report No: 1304100-02

Date: 2013-04-26




CH11 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	M727, M728HD, PMID708X
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	42.86	T 10014	74(dBμV/m)
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 22.APR.2013 11:38:51

Date: 2013-04-26



Page 77 of 87

11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

Integral Antenna used. The maximum Gain of the antennas is 3.0dBi.

Report No: 1304100-02 Page 78 of 87

Date: 2013-04-26




12.0 FCC ID Label

FCC ID: RBD-M727

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Report No: 1304100-02 Page 79 of 87

Date: 2013-04-26



13.0 Photo of testing

Conducted Emission Test Setup:



Date: 2013-04-26



Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2013-04-26



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Date: 2013-04-26



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Date: 2013-04-26



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: 1304100-02 Page 84 of 87

Date: 2013-04-26



Photo for the EUT



Page 85 of 87

Report No: 1304100-02

Date: 2013-04-26



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Date: 2013-04-26



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2013-04-26



Photo for the EUT





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to