



10. RADIATED EMISSION

10.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



The following table is the setting of spectrum analyzer and receiver.


| Spectrum Parameter | Setting |
|-----------------------|---|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |
| Start ~Stop Frequency | 1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average |

| Receiver Parameter | Setting |
|-----------------------|--------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |




10.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





10.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

10.4. TEST RESULT


Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55% |
| Pressure | 985hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 8 | Antenna | Horizontal |

Radiated emission from 30MHz to 1000MHz



| No. | Mk | . Freq. | Reading Level | Correct Factor | Measure- ment | Limit | Over | |
|-----|----|----------|------------------|-------------------|------------------|--------|-------|----------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | Detector |
| 1 | * | 63.9500 | 24.63 | 11.73 | 36.36 | 40.00 | -3.64 | peak |
| 2 | | 114.0666 | 25.44 | 11.99 | 37.43 | 43.50 | -6.07 | peak |
| 3 | | 233.6999 | 31.61 | 8.21 | 39.82 | 46.00 | -6.18 | peak |
| 4 | ! | 295.1333 | 26.38 | 14.86 | 41.24 | 46.00 | -4.76 | peak |
| 5 | ! | 356.5667 | 24.34 | 17.71 | 42.05 | 46.00 | -3.95 | peak |
| 6 | ! | 380.8167 | 22.31 | 18.25 | 40.56 | 46.00 | -5.44 | peak |

RESULT: PASS



| EUT | Portable Conf Microphone | erence | Model Name Relative Humidity Test Voltage | | PSE05 | 40 |
|---|-----------------------------|--------|---|---------|-----------------------|----------|
| Temperature | 25°C | | | | Relative Humidity 55% | |
| Pressure | 985hPa | | | | Normal | Voltage |
| Test Mode | Mode 8 | | Antenna | | Vertical | |
| 80.0 dBuV/m 40 40 1 2 40 1 2 40 1 2 40 1 2 40 1 2 40 1 2 40 1 40 1 | 50 60 70 80 Read | | 300 Measure- ment | 400 500 | | |
| NO. WK. | MHz dBu | | dBuV/m | dBuV/m | dB | Detector |
| 1 ! 3 | 31.6167 28.0 | | 35.28 | 40.00 | -4.72 | peak |

| | 1 | | 31.6167 | 28.06 | 7.22 | 35.28 | 40.00 | -4.72 | peak |
|---|---|---|----------|-------|-------|-------|-------|-------|------|
| _ | 2 | 1 | 42.9333 | 26.08 | 9.59 | 35.67 | 40.00 | -4.33 | peak |
| | 3 | * | 63.9500 | 24.94 | 11.96 | 36.90 | 40.00 | -3.10 | peak |
| | 4 | ! | 120.5580 | 26.16 | 12.98 | 39.14 | 43.50 | -4.36 | peak |
| | 5 | ! | 233.6999 | 28.62 | 12.58 | 41.20 | 46.00 | -4.80 | peak |
| | 6 | 1 | 495.6000 | 25.02 | 16.86 | 41.88 | 46.00 | -4.12 | peak |

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

2. All test modes had been pre-tested. The mode 8 is the worst case and recorded in the report.



Radiated emission above 1GHz

| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55% |
| Pressure | 985hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | | |
|---------------|-------------------|---------------|----------------|----------|--------|------------|--|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type | |
| 4804.000 | 48.32 | 0.08 | 48.4 | 74 | -25.6 | peak | |
| 4804.000 | 34.79 | 0.08 | 34.87 | 54 | -19.13 | AVG | |
| 7206.000 | 41.67 | 2.21 | 43.88 | 74 | -30.12 | peak | |
| 7206.000 | 29.76 | 2.21 | 31.97 | 54 | -22.03 | AVG | |
| | | | | | | | |
| Remark: | | | | | | | |
| actor = Anter | nna Factor + Cabl | e Loss – Pre- | amplifier. | | | | |

racio AILEINA FACIOI + CADIE LUSS Fie-ampliner.

| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55% |
| Pressure | 985hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | |
|---|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 4804.000 | 47.25 | 0.08 | 47.33 | 74 | -26.67 | peak |
| 4804.000 | 35.16 | 0.08 | 35.24 | 54 | -18.76 | AVG |
| 7206.000 | 40.81 | 2.21 | 43.02 | 74 | -30.98 | peak |
| 7206.000 | 30.74 | 2.21 | 32.95 | 54 | -21.05 | AVG |
| | | | | | | |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |



| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 8 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | |
|---------------|------------------|--------------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 4882.000 | 48.65 | 0.14 | 48.79 | 74 | -25.21 | peak |
| 4882.000 | 35.42 | 0.14 | 35.56 | 54 | -18.44 | AVG |
| 7323.000 | 42.73 | 2.36 | 45.09 | 74 | -28.91 | peak |
| 7323.000 | 30.27 | 2.36 | 32.63 | 54 | -21.37 | AVG |
| | | | | | | |
| Remark: | 1 | | 1 | | • | - |
| actor - Anter | na Factor + Cabl | eloss – Pre- | amplifier | | | |

Factor = Antenna Factor + Cable Loss -<u>- Pre-amplifier.</u>

| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 8 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | |
|---------------|-------------------|----------------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 4882.000 | 45.32 | 0.14 | 45.46 | 74 | -28.54 | peak |
| 4882.000 | 35.54 | 0.14 | 35.68 | 54 | -18.32 | AVG |
| 7323.000 | 40.16 | 2.36 | 42.52 | 74 | -31.48 | peak |
| 7323.000 | 30.17 | 2.36 | 32.53 | 54 | -21.47 | AVG |
| | | | | | | |
| Remark: | | | | | | |
| actor = Anter | nna Factor + Cabl | e Loss – Pre-a | amplifier | | | |



| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 4960.000 | 47.54 | 0.22 | 47.76 | 74 | -26.24 | peak |
| 4960.000 | 35.64 | 0.22 | 35.86 | 54 | -18.14 | AVG |
| 7440.000 | 41.37 | 2.64 | 44.01 | 74 | -29.99 | peak |
| 7440.000 | 31.43 | 2.64 | 34.07 | 54 | -19.93 | AVG |
| | | | | | | |
| emark: | | | | | | |

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 4960.000 | 47.94 | 0.22 | 48.16 | 74 | -25.84 | peak |
| 4960.000 | 36.12 | 0.22 | 36.34 | 54 | -17.66 | AVG |
| 7440.000 | 42.77 | 2.64 | 45.41 | 74 | -28.59 | peak |
| 7440.000 | 32.67 | 2.64 | 35.31 | 54 | -18.69 | AVG |
| | | | | | | |
| emark: | | | | | | |

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Emission Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


All test modes had been tested. The 8DPSK modulation is the worst case and recorded in the report.




| | i oot i oouit i oi baila oago olillool | | |
|-------------|--|-------------------|----------------|
| EUT | Portable Conference Microphone | Model Name | PSE0540 |
| Temperature | 25°C | Relative Humidity | 55% |
| Pressure | 985hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Horizontal |

Test result for band edge emission at restricted bands

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd



Report No.: AGC00484220202FE03 Page 56 of 69

| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55% |
| Pressure | 985hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86–755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




Report No.: AGC00484220202FE03 Page 57 of 69

| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55% |
| Pressure | 985hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: PASS




Report No.: AGC00484220202FE03 Page 58 of 69

| EUT | Portable Conference Microphone | Model Name | PSE0540 |
|-------------|-----------------------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55% |
| Pressure | 985hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer. The 8DPSK modulation is the worst case and recorded in the report.



11. NUMBER OF HOPPING FREQUENCY

11.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may

be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.

2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

3. VBW \geq RBW. Sweep: Auto. Detector function: Peak. Trace: Max hold.

4. Allow the trace to stabilize.

11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

11.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

11.4. LIMITS AND MEASUREMENT RESULT

| Test Data of Number of Hopping Frequency | | | | |
|--|----|------|------|--|
| Test Mode Number of Hopping Frequency Limits Pass or Fai | | | | |
| GFSK Hopping | 79 | >=15 | Pass | |

02:56:50 PM Mar 01, 2022 Frequency TRACE 1 2 3 4 5 TYPE MWWW DET P NNNN Avg Type: Log-Pw Avg|Hold: 100/100 2.441750000 GHz Center Frea Trig: Free Run PNO: Fast 🔸 IFGain:Low Auto Tune Ref 30.00 dBm Center Frea 2.441750000 GHz Start Fred 2.40000000 GHz Stop Freq 2.483500000 GHz **CF** Step 8.350000 MHz Auto Man Freg Offset 0 Hz Start 2.40000 GHz Stop 2.48350 GHz #VBW 620 kHz #Res BW 200 kHz Sweep 1.998 ms (1000 pts) 1h Test_Graph_BR_HOP_ANT1_NA_1Mbps_Number of Hopping

Test Graphs of Number of Hopping Frequency

Note: The GFSK modulation is the worst case and recorded in the report.



12. TIME OF OCCUPANCY (DWELL TIME)

12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Zero span, centered on a hopping channel.

2. RBW shall be \leq channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.

3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

4. Detector function: Peak. Trace: Max hold.

5. Use the marker-delta function to determine the transmit time per hop.

6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) \times (period specified in the requirements / analyzer sweep time).

7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2


12.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6


12.4. LIMITS AND MEASUREMENT RESULT

| Test Data of Dwell Time | | | | | | | | |
|-------------------------|----------------------------------|--|--------------------|---------------|--------------|--|--|--|
| Channel | Time of Pulse for DH5 (ms) | Number of hops in the period specified in the requirements | Sweep Time (ms) | Limit (ms) | Pass or Fail | | | |
| 2402 | 2.866 | 26.0*4 | 298.064 | 400 | Pass | | | |
| 2441 | 2.866 | 27.0*4 | 309.528 | 400 | Pass | | | |
| 2480 | 2.866 | 27.0*4 | 309.528 | 400 | Pass | | | |

Note: The GFSK modulation is the worst case and recorded in the report.









Test Graphs of Dwell Time











13. FREQUENCY SEPARATION

13.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Wide enough to capture the peaks of two adjacent channels.

2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

3. Video (or average) bandwidth (VBW) \geq RBW.

4. Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)


Same as described in section 6.2

13.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.3

13.4. LIMITS AND MEASUREMENT RESULT

| Test Data of Frequency Separation | | | | | | |
|-----------------------------------|--------------------------|-----------------|--------------|--|--|--|
| Test Mode | Channel Separation (MHz) | Limits | Pass or Fail | | | |
| GFSK Hopping | 1.005 | >= 2/3 -20dB BW | Pass | | | |



Test Graphs of Number of Hopping Frequency

Note: The GFSK modulation is the worst case and recorded in the report.



14. LINE CONDUCTED EMISSION TEST


14.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Frequency | Maximum RF Line Voltage | | | | |
|---------------|-------------------------|----------------|--|--|--|
| Frequency | Q.P. (dBµV) | Average (dBµV) | | | |
| 150kHz~500kHz | 66-56 | 56-46 | | | |
| 500kHz~5MHz | 56 | 46 | | | |
| 5MHz~30MHz | 60 | 50 | | | |

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST


- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.





14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



MEASUREMENT RESULT: "agc fin"

| 2022/3/5 11:19 Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|--|--|--|----------------------------|---|----------------------------------|----------------------------------|--|
| 0.150000 0.602000 18.666000 19.290000 19.926000 20.566000 | 57.20 45.40 47.30 44.30 49.00 49.10 | 6.9 5.4 8.7 8.7 8.8 8.8 | 66 56 60 60 60 | 8.8 10.6 12.7 15.7 11.0 10.9 | QP QP QP QP QP QP | L1 L1 L1 L1 L1 L1 | GND GND GND GND GND GND |

MEASUREMENT RESULT: "agc fin2"

| 2022/3/5 11:19 Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|---|--|--|----------------------------------|--|----------------------------|----------------------------------|--|
| 0.602000 18.026000 18.666000 19.294000 19.614000 19.930000 | 39.10 35.80 40.00 39.10 39.00 40.40 | 5.4 8.6 8.7 8.7 8.8 8.8 | 46 50 50 50 50 50 | 6.9 14.2 10.0 10.9 11.0 9.6 | AV AV AV AV AV | L1 L1 L1 L1 L1 L1 | GND GND GND GND GND GND |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



LINE CONDUCTED EMISSION TEST-N



MEASUREMENT RESULT: "agc fin"

| 2022/3/5 11:07 Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|--|--|--|----------------------------|--|----------------------------------|-----------------------|--|
| 0.154000 0.618000 19.222000 19.858000 20.170000 20.490000 | 60.20 46.40 46.40 49.40 46.20 48.90 | 6.9 5.4 8.7 8.8 8.8 8.8 | 66 56 60 60 60 | 5.6 9.6 13.6 10.6 13.8 11.1 | QP QP QP QP QP QP | N N N N N | GND GND GND GND GND GND |

MEASUREMENT RESULT: "agc_fin2"

| 2022/3/5 11:08 Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line | PE |
|------------------------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.606000 | 42.00 | 5.4 | 46 | 4.0 | AV | N | GND |
| 18.590000 | 37.30 | 8.7 | 50 | 12.7 | AV | N | GND |
| 19.222000 | 38.50 | 8.7 | 50 | 11.5 | AV | N | GND |
| 19.854000 | 35.50 | 8.8 | 50 | 14.5 | AV | N | GND |
| 20.166000 | 36.60 | 8.8 | 50 | 13.4 | AV | N | GND |
| 20.486000 | 36.90 | 8.8 | 50 | 13.1 | AV | N | GND |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC00484220202AP03

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC00484220202AP04

----END OF REPORT----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.