

客戶名稱 : **Qisda**
CUSTOMER

Document No.: ENS000103820

Approval Sheet Rev.: A0

Spec. Rev. : P0

承認書

APPROVAL SHEET

產品品名/Product Model No. : WA-P-LB-02-485
Model:PUCK

客戶料號/Customer No. : 2E.93Q70.001

發行日期/ Issue Date : 2017/09/29

承認日期/ Approved Date : _____

Approved by customer: (signing or stamping here)



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

■ 350 苗栗縣竹南鎮公義里11鄰科義街11號 □ 428 台中市大雅區科雅路27號4樓

電話：037-585-555

電話：04-2560-6555

傳真：037-585-511

傳真：04-2560-5151

No. 11, Ke-Yi St., Chunan, Miaoli 350,
Taiwan, R.O.C.

4F, No. 27, Keya Road, Daya Dist., Taichung City
428, Taiwan, R.O.C.

Tel. : +886-37-585-555


Tel. : +886-4-25606555

Fax : +886-37-585-511

Fax : +886-4-25605151

Embedded WiFi-Band Antenna for WA-P-LB-02-485

1. Explanation of part number :



- (1) Product type : WIFI Antenna
- (2) Antenna type : PCB type
- (3) Frequency : 2400~2500 MHz 5150~5850 MHz
- (4) Coaxial Cable Type : Black (length : 90 mm)
- (5) Suffix : 485

2. Electrical Specification :

Electrical Specification	
Frequency Range	2400~2500 MHz 5150~5850 MHz
Antenna Type	PCB
Impedance	50 ohm
Efficiency	≥ 40 %
Antenna Size	57.1 x12.3 x 0.8 mm ³
Cable	I-PEX 1.13, Black, 90 mm


Those specifications were specially defined for model, and all characteristics were measured with the fixture.

UNLESS OTHER SPECIFIED TOLERANCES ON : X=N/A X.X=N/A X.XX=N/A ANGLES=N/A HOLEDIA=N/A			INPAQ TECHNOLOGY CO., LTD.	
SCALE : N/A	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY:吳政達	CHECKED BY:林純正			
DESIGNED BY:林亨倫	APPROVED BY:陳彥銘			
TITLE : Embedded WiFi-Band Antenna for WA-P-LB-02-485		DOCUMENT NO.	ENS000103820	SPEC REV. P0

3. Mechanical Specification :

3. Mechanical Configuration :

ASSY DRAWING(成品图, 球标尺寸为重点尺寸)




未标注公差±0.15mm

T=0.8±0.1mm

接头方向依图档

Cable Length:



Connector : I-PEXMHF ; Cable : RF Cable 1.13 (黑色)

L : 90±2mm A : 1.5±0.5 mm B : 2.0±0.5mm C : 1.0±0.5m

ITEM	DESCRIPTION	MATERIAL SPECIFICATION	QUANTITY	UNIT
1	PCB	57.1 x12.3 x 0.8 mm ³	1	PCS
2	Cable	φ 1.13	1	PCS
3	Connector	I-PEX MHF 1	1	PCS

UNLESS OTHER SPECIFIED TOLERANCES ON :
 X=N/A X.X=N/A X.XX=N/A
 ANGLES=N/A HOLEDIA=N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A UNIT : mm
 DRAWN BY: 吳政達 CHECKED BY: 林純正
 DESIGNED BY: 林亨倫 APPROVED BY: 陳彥銘

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded WiFi-Band Antenna for
 WA-P-LB-02-485

DOCUMENT NO.

ENS000103820

SPEC REV.
 P0

4. VSWR :

6/22/2017 9:44:01 AM
1311.6010K42-106416-gr

Trc2 S11 SWR 1 U/ Ref 1 U Cal int Offs

1



5. Gain and Radiation Pattern

5.1 Measure method

1. Using a coaxial cable to link a standard fixture
2. Fixed this fixture on chamber's rotator plane
3. Linking fixture into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

UNLESS OTHER SPECIFIED TOLERANCES ON :
X=N/A X.X=N/A X.XX=N/A
ANGLES=N/A HOLEDIA=N/A



INPAQ TECHNOLOGY CO., LTD.


SCALE : N/A UNIT : mm
DRAWN BY:吳政達 CHECKED BY:林純正
DESIGNED BY:林亨倫 APPROVED BY:陳彥銘

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded WiFi-Band Antenna for
WA-P-LB-02-485

DOCUMENT NO.	ENS000103820	SPEC REV.
		P0

5.2 Chamber definition :



1. An anechoic chamber (10mx3mx3m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 50cmx50cmx50cm at the center of rotator
3. The distance between DUT and standard antenna is 9.14m
4. Two measurement antennas is 3164-06 (300MHz - 6GHz) and 3164-05 (2 - 18GHz)

UNLESS OTHER SPECIFIED TOLERANCES ON :
 X=N/A X.X=N/A X.XX=N/A
 ANGLES=N/A HOLEDIA=N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A UNIT : mm
 DRAWN BY:吳政達 CHECKED BY:林純正
 DESIGNED BY:林亨倫 APPROVED BY:陳彥銘

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded WiFi-Band Antenna for
 WA-P-LB-02-485

DOCUMENT NO.

ENS000103820

SPEC REV.
P0

5.3 Gain data and radiation pattern :

Antenna gain is marked [dBi] and is based on STANDARD HORN antenna. The data shows Peak-Gain and Average-Gain.

Frequency(MHz)	Peak Gain(dBi)	Average Gain(dBi)	Efficiency (%)
2400	2.8	-2.87	51.7
2410	2.71	-2.82	52.26
2420	2.95	-2.65	54.37
2430	3.26	-2.45	56.86
2440	3.41	-2.37	57.92
2450	3.38	-2.41	57.46
2460	3.44	-2.34	58.37
2470	3.68	-2.12	61.34
2480	3.66	-2.17	60.71
2490	3.43	-2.30	58.83
2500	2.74	-3.06	49.41
5150	3.13	-2.37	57.92
5200	3.23	-2.27	59.34
5250	2.39	-3.16	48.34
5300	2.38	-3.19	47.94
5350	3.35	-2.37	57.92
5400	3.03	-2.87	51.66
5450	3.17	-2.69	53.83
5500	3.42	-2.62	54.71
5550	3.5	-2.65	54.27
5600	3.46	-2.73	53.39
5650	3.7	-2.42	57.3
5700	3.39	-2.55	55.61
5750	3.66	-2.20	60.31
5800	3.69	-1.92	64.3
5850	3.63	-1.99	63.28

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=N/A X.X=N/A X.XX=N/A

ANGLES=N/A HOLEDIA=N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:吳政達

CHECKED BY:林純正

DESIGNED BY:林亨倫

APPROVED BY:陳彥銘

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded WiFi-Band Antenna for
WA-P-LB-02-485

DOCUMENT
NO.

ENS000103820


SPEC REV.
P0

Radiation pattern


PUCK WIFI ANTENNA DESIGN PERFORMANCE | RADIATION PATTERN

2450 MHz




X-Y Plane



X-Y Plane




Y-Z Plane




5500 MHz


X-Y Plane



X-Y Plane



Y-Z Plane



UNLESS OTHER SPECIFIED TOLERANCES ON :
 X=N/A X.X=N/A X.XX=N/A
 ANGLES=N/A HOLEDIA=N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:吳政達

CHECKED BY:林純正

DESIGNED BY:林亨倫

APPROVED BY:陳彥銘

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded WiFi-Band Antenna for
 WA-P-LB-02-485


DOCUMENT NO.

ENS000103820

SPEC REV.
 P0

PCB,T0.8MM,WA-P-LB-03-073

1. 品名: PCB, T0. 8MM, WA-P-LB-03-073
2. 檔名: PCB, T0. 8mm WA-P-LB-03-073 V1 20170221
3. 外观等级: Class2
4. 规格:



未标注公差±0.15mm

项次	项目	验收规格
A	Item	PCB
B	Material	FR4
C	Layer	SS
D	Copper	0.5oz
E	W	12.3 ± 0.15mm
F	L	57 ± 0.15mm
G	T	0.80 ± 0.10mm

备注 : 1. 表面为 OSP 处理 , 绿油油墨, 白字印字

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLE DIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY : 余骏

CHECKED BY : 李志强

DESIGNED BY : 张冲

APPROVED BY : 胡志清

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: PCB,T0.8MM,WA-P-LB-03-073 材规

DOCUMENT NO.

PAGE REV.
A0

5. 储存条件:


5.1 储存环境: 5 ~ 30°C

5.2 有限期限: 一年

5.2.1 开封后限期缩短 无 有 ___ (拆封后剩余物料仍需继续真空包装)

5.2.2 暴露空气存储期限: 48 小时 (环境温度较高时需尽快用完)

6. 实物图:



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
ANGLES=± HOLE DIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY : 余骏

CHECKED BY : 李志强

DESIGNED BY : 张冲

APPROVED BY : 胡志清

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE: PCB,T0.8MM,WA-P-LB-03-073 材规

DOCUMENT
NO.

PAGE REV.
A0

1. 品名: **CNC I-PEX MHF+RF CABLE 1.13_90mm ,1.5/2.0/1.0 (Black)**

2. Cable Dimension :



Connector : I-PEX MHF , Cable : RF Cable 1.13 (Black)

- | | |
|---------------|-----------------|
| L : 90±2.0mm | D : 0.84±0.2mm |
| A : 1.5±0.5mm | E : 1.25±0.2mm |
| B : 2.0±0.5mm | F : 1.16±0.2mm |
| C : 1.0±0.5mm | G : 88.75±2.0mm |

3. 電性規格 :


(1)

尺寸規格	Signal Loss
90±2.0mm	≤ 2.0dB

(2) 短路/斷路測試 : (使用三用電表量測)

- 心線與 Braidwires 間不可短路。
- Connector 之 Ground 與線路另一端之 Braidwires 間不可斷路。
- Connector 之心線與線路另一端之心線間不可斷路。

4. Connector appearance :



UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX =
 ANGLES = ± HOLE DIA = ±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY: 吳政達

CHECKED BY: 林純正

DESIGNED BY: 林亨倫

APPROVED BY: 陳彥銘

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : CNC I-PEX MHF+RF CABLE 1.13_90
 mm ,1.5/2.0/1.0 (Balck)

DOCUMENT
 NO.

SPEC REV.
 P0

5. 儲存條件：

5.1 儲存環境：5 ~ 30℃，≤60%RH。

5.2 有限期限：一年

5.2.1 開封後限期縮短 無 有 _____

6. 過期重驗：

是：項次 3

否

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX =
ANGLES = ± HOLE DIA = ±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY: 吳政達

CHECKED BY: 林純正

DESIGNED BY: 林亨倫

APPROVED BY: 陳彥銘

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE : CNC I-PEX MHF+RF CABLE 1.13_90
mm ,1.5/2.0/1.0 (Balck)

DOCUMENT
NO.


SPEC REV.
P0



正面
圖片



反面
圖片



If you have any inquiry, please do not hesitate to ask.