



ISO9001 ISO14001 IATF16949 CHILISIN ELECTRONICS CORP.

RoHS & Halogen Free & REACH Compliance.

SPECIFICATION FOR APPROVAL

Customer :

Customer P/N :

Drawing No :

Quantity :

Pcs.

Date :

2020/11/10

Chilisin P/N :

BTPA00460725GC1A05

SPECIFICATION

ACCEPTED BY:

COMPONENT ENGINEER	
ELECTRICAL ENGINEER	
MECHANICAL ENGINEER	
APPROVED	
REJECTED	

奇力新電子股份有限公司

Chilisin Electronics Corp
No. 29, Alley 301, Tehsin Rd.,
Hukou, Hsinchu 303, Taiwan
TEL : +886-3- 599-2646
FAX : +886-3- 599-9176
E-mail : sales@chilisin.com
http : //www.chilisin.com

東莞奇力新電子(東莞廠)有限公司

Chilisin Electronics (Dongguan) Co., Ltd.
No. 78, Puxing Rd., Yuliangwei Administration Area,
Qingxi Town, Dongguan City, Guangdong, China
TEL : +86-769-8773-0251~3
FAX : +86-769-8773-0232
E-mail : cect@chilisin.com

奇力新電子(越南廠)有限公司

Chilisin Electronics (Vietnam) Limited
No 143 - 145, Road No 10, VSIP Hai
Phong, Lap Le Commune, Thuy Nguyen
Dist, Haiphong City, Vietnam
Tel : 84-316 255 688 Fax : 84-316 255 689
E-mail : sales@chilisin.com

奇力新電子(湖南廠)有限公司

HuNan Chilisin Electronics Technology Co., Ltd
No. 8, Shaziao Liangshuijing Town, Yuanling County,
Huaihua City, Hunan Province 419601, China
Tel : 86-745-867-5882
E-mail : cect@chilisin.com

Drawn by

Checked by

Approved by




ISO9001 ISO14001 IATF16949 CHILISIN ELECTRONICS CORP.

Contents

Item	Description	Page
1.	Mechanical Specification 4
2.	RF Specification 5
3.	TEST REPORT 6~10

Mechanical Specification

RoHS COMPLIANT



備註:

1. 電氣特性必須100%測試以及標註 * 的尺寸須做重點檢驗(SPC)
2. 此產品及其附屬包裝材料的均質成份須滿足無鹵管制要求:
Br<900ppm, Cl<900ppm, Br+Cl<1500ppm

△	MODIFY_DRAWING	11/10/'20	ALLEN
△	MODIFY_CABLE_LENGTH_&_PATTERN	09/10/'20	ALLEN
△	MODIFY_CABLE_LENGTH	05/26/'20	ALLEN
△	NEW_DRAWING	04/30/'20	ALLEN
LTR	DESCRIPTION	DATE	REQ. BY


6			1	
5			1	
4			1	
3	PCB	FR4 46mm x 7.5mm x 0.8mm	1	
2	Cable	1.13MM COAXIAL CABLE(白色)	1	
1	Connector	I-PEX一代端子	1	
NO	DESCRIPTION		QTY	REMARK

設計 DR. ALLEN 2020/11/10	核准 APPD. TASON 2020/11/10
版本說明 REVISION NOTE	

容許公差	TOLERANCE
.XXX	±0.20
.XX	±0.35
.X	±0.50
X	±1.00
ANG	±5

品名
ASM, ANTENNA-2(左)
BTPA00460725GC1A05

CHILISIN



單位 UNIT	比例 SCALE	張數 SHEET	版本 REV.
mm	1:1	1/1	D



ISO9001 ISO14001 IATF16949 CHILISIN ELECTRONICS CORP.

RF Specification


Electrical		
Item		Ant2
Test Environment		Free Space
Antenna Type		PF
Frequency Range		2400~2500MHz 5150~5850MHz
Returnloss		2400~2500MHz <-10 5150~5850MHz <-10
Polarization		Linear
Gain(Peak Gain)		<4.23
Efficiency		≥53%
Input Impedance		50 ohm



ISO9001 ISO14001 IATF16949 CHILISIN ELECTRONICS CORP.

Test Report

S- Parameter_ Return Loss_Ant2






ISO9001 ISO14001 IATF16949 CHILISIN ELECTRONICS CORP.

S- Parameter Isolation




3D Peak Gain & Efficiency List Table




Ant2		
Frequency (MHz)	Efficiency	Total Gain (dBi)
2400	55	3.39
2412	56	3.38
2437	57	3.50
2450	56	3.53
2462	56	3.50
2500	53	3.13
5150	62	4.23
5180	61	4.20
5320	61	3.94
5500	62	3.71
5600	57	3.03
5700	60	3.21
5785	59	3.21
5805	57	2.88
5850	57	3.35

2D Gain Pattern_Ant2_ZX Cut(Phi=0)




Layer	Max value	Min value	Average
2400(MHz)	1.08 dB	-13.13 dB	-4.44 dB
2450(MHz)	1.24 dB	-11.68 dB	-4.47 dB
2500(MHz)	1.41 dB	-14.36 dB	-4.52 dB
5150(MHz)	1.61 dB	-18.23 dB	-4.42 dB
5320(MHz)	1.84 dB	-12.58 dB	-4.24 dB
5500(MHz)	1.53 dB	-9.11 dB	-3.58 dB
5785(MHz)	1.08 dB	-10.71 dB	-3.91 dB
5850(MHz)	0.24 dB	-12.87 dB	-4.26 dB

2D Gain Pattern_Ant2_ZY Cut(Phi=90)



Layer	Max value	Min value	Average
2400(MHz)	3.09 dB	-14.79 dB	-1.52 dB
2450(MHz)	3.05 dB	-13.67 dB	-1.48 dB
2500(MHz)	2.23 dB	-13.05 dB	-2.05 dB
5150(MHz)	4.22 dB	-16.29 dB	-0.72 dB
5320(MHz)	3.34 dB	-21.61 dB	-1.06 dB
5500(MHz)	3.41 dB	-17.55 dB	-1.55 dB
5785(MHz)	2.27 dB	-13.76 dB	-1.98 dB
5850(MHz)	2.34 dB	-15.93 dB	-2.06 dB


2D Gain Pattern_Ant2_XY Cut(Theta=0)



Layer	Max value	Min value	Average
2400(MHz)	3.38 dB	-14.07 dB	-5.50 dB
2450(MHz)	3.18 dB	-15.00 dB	-5.51 dB
2500(MHz)	2.48 dB	-15.05 dB	-5.76 dB
5150(MHz)	3.58 dB	-22.48 dB	-5.13 dB
5320(MHz)	3.73 dB	-21.54 dB	-4.87 dB
5500(MHz)	2.99 dB	-24.21 dB	-4.54 dB
5785(MHz)	2.41 dB	-17.40 dB	-4.45 dB
5850(MHz)	2.62 dB	-18.78 dB	-4.42 dB

3D Gain Pattern_Ant2

2450MHz



5500MHz

