





FCC RADIO TEST REPORT

Applicant : ELO TOUCH SOLUTIONS, INC.
Address : 670 N. McCarthy Blvd., Suite 100 Milpitas,
CA 95035 USA
Equipment : Touch All-In-One Computer
Model No. : ESY15I1D-C
Trade Name : Elo or 
FCC ID : RBWESY15I1DC

I HEREBY CERTIFY THAT :

The sample was received on Jun. 28, 2021 and the testing was completed on Aug. 28, 2021 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:



Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment	6
2.2 Carrier Frequency of Channels	7
2.3 Test Mode and Test Software	8
2.4 Description of Test System	9
2.5 General Information of Test	10
2.6 Measurement Uncertainty	10
3. Test Equipment and Ancillaries Used for Tests	11
4. Antenna Requirements	13
4.1 Antenna Construction and Directional Gain	13
5. Test of AC Power Line Conducted Emission	14
5.1 Test Limit	14
5.2 Test Procedures	14
5.3 Typical Test Setup	15
5.4 Test Result and Data	16
5.5 Test Photographs	18
6. Test of Radiated Spurious Emission	19
6.1 Test Limit	19
6.2 Test Procedures	20
6.3 Typical Test Setup	21
6.4 Test Result and Data (9KHz ~ 30MHz)	22
6.5 Test Result and Data (30MHz ~ 1GHz)	22
6.6 Test Result and Data (1GHz ~ 25GHz)	24
6.7 Restricted Bands of Operation	48
6.8 Test Photographs (30MHz ~ 1GHz)	49
6.9 Test Photographs (1GHz ~ 25GHz)	50
7. Test of Conducted Spurious Emission	52
7.1 Test Limit	52
7.2 Test Procedure	52
7.3 Test Setup Layout	52
7.4 Test Result and Data	52
8. On Time, Duty Cycle and Measurement methods	65
8.1 Test Limit	65
8.2 Test Procedure	65
8.3 Test Setup Layout	65
8.4 Test Result and Data	65
9. 6dB Bandwidth Measurement Data	67
9.1 Test Limit	67
9.2 Test Procedures	67
9.3 Test Setup Layout	67



9.4 Test Result and Data..... 67

10. Maximum Peak and Average Output Power71

10.1 Test Limit 71

10.2 Test Procedures 71

10.3 Test Setup Layout 71

10.4 Test Result and Data..... 72

11. Power Spectral Density 73

11.1 Test Limit 73

11.2 Test Procedures 73

11.3 Test Setup Layout 73

11.4 Test Result and Data..... 73

12. Radio Frequency Exposure77

12.1 Applicable Standards 77

12.2 EUT Specification..... 77

12.3 Test Results..... 78

12.4 Calculation..... 78

12.5 Maximum Permissible Exposure..... 79



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak and Average Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
2.1091	. Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.

*This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report(21050212-TEFV01).



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment

Frequency Range	BT / BLE: 2402MHz~2480MHz 802.11b/g/n: 2412MHz~2462MHz 802.11a/n/ac: 5180MHz~5240MHz, 5260MHz~5320MHz, 5500MHz~5720MHz, 5745MHz~5825MHz
Modulation Type	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK WLAN: 2.4GHz: 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 5GHz: 802.11n/a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Modulation Technology	DSSS, OFDM, FHSS, DTS
Data Rate	BT: GFSK: 1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps WLAN: 2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	Slot Antenna
Antenna Gain	For BT / BLE: 2402-2480MHz: ANT A: 2.91dBi For WLAN: 2412MHz~2462MHz: ANT A: 2.91dBi, ANT B: 3.91dBi 5180MHz~5240MHz: ANT A: 2.52dBi, ANT B: 2.01dBi 5260MHz~5320MHz: ANT A: 2.52dBi, ANT B: 2.01dBi 5500MHz~5720MHz: ANT A: 2.68dBi, ANT B: 2.56dBi 5745MHz~5825MHz: ANT A: 1.97dBi, ANT B: 1.92dBi
Adapter	Brand: Delta Electronics Inc. Model: ADP-65JH HB
Power Cord	Brand: HONHLIN Model:HL-013+HL-052
I/O Hub	Brand: Elo Model: KIT, USBC-IO-DONGLE-POWER-BRICK
Firmware Number	SWEP_sdm660la302_01.061.02.p_01
Serial Number	KEX-DLCP07

Note:

1. EUT support TPC Function.
2. WLAN and BT can simultaneously transmission.
3. EUT support Client Mode without Radar Detection.
4. For more details, please refer to the User's manual of the EUT.



2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT20 (2412MHz~2462MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
*01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	*11	2462
*06	2437	---	---

802.11n HT40 (2422MHz~2452MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
*03	2422	*09	2452
04	2427	---	---
05	2432	---	---
*06	2437	---	---

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- b. The complete test system included Remote workstation and EUT for RF test. The Remote workstation included Notebook.
- c. An executive program, "QRCT ver.4.0.00129.0" under Windows OS system was executed to transmit and receive data via WLAN.
- d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11n HT40 (13.5Mbps)
caused "Test Mode 4" generated the worst case, it was reported as the final data.	
Radiation Emissions ((9KHz ~30MHz & 30MHz ~ 1GHz))	
Test Mode	Operating Description
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11n HT40 (13.5Mbps)
caused "Test Mode 4" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11n HT40 (13.5Mbps)
caused "Test Mode 1~4" generated the worst case, they were reported as the final data.	

The EUT incorporates a MIMO function

Modulation Type	TX CONFIGURATION
802.11b	1TX Fix ANT B
802.11g	1TX Fix ANT B
802.11n HT20	2TX
802.11n HT40	2TX



2.4 Description of Test System

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
Micro USB Cable	kolin	EX-DLCP07	1m / NS	N/A



2.5 General Information of Test

Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881	
	FCC	TW1079, TW1439
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication test C-4663 for Conducted emission test R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2021/07/26	26°C / 54%	Nick Guan
Radiated Emissions	3M02-NK	2021/07/21~2021/08/20	23~25°C / 42~46%	Nick Guan
AC Power Line Conducted Emission	CON01-NK	2021/08/28	27°C / 49%	Nick Guan

2.6 Measurement Uncertainty

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.63dB
Radiated Spurious Emission(9KHz~30MHz)	±3.4dB
Radiated Spurious Emission(30MHz~1GHz)	±5.6dB
Radiated Spurious Emission(1GHz~40GHz)	±6.6dB
6dB Bandwidth	±4.4%
26dB Bandwidth	±4.4%
Occupied Bandwidth	±4.4%
Peak Output Power(Conducted Power Meter)	±1.1dB
Power Spectral Density	±1.8dB
Duty Cycle	±1.5%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	369	2021/04/26	2022/04/25
Active Loop Antenna	EMCO	6507	40855	2021/06/10	2022/06/09
Horn Antenna	EMCO	3115	31601	2020/10/16	2021/10/15
Horn Antenna	EMCO	3116	31974	2020/09/24	2021/09/23
EMI Receiver	ROHDE & SCHWARZ	ESCI	101423	2021/06/30	2022/06/29
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2021/07/14	2022/07/13
Preamplifier	EM Electronics corp.	EM330	60658	2020/10/20	2021/10/19
Preamplifier	EM Electronics corp.	EM330	60660	2021/03/18	2022/03/17
Preamplifier	Agilent	8449B	3008A01954	2021/03/22	2022/03/21
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2020/11/06	2021/11/05
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2021/04/19	2022/04/18
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2021/04/12	2022/04/11
Cable-0.5m(1G-18G)	E MEC	EM104-SMSM-0.5M	CCE1354	2021/05/06	2022/05/05
Cable-3m(1G-18G)	E MEC	EM104-SMSM-3M	CCE1355	2021/05/06	2022/05/05
Cable-8m(1G-18G)	E MEC	EM104-SMSM-8M	CCE1356	2021/05/06	2022/05/05
Cable-0.5m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	28420/2	2021/04/03	2022/04/02
Cable-3m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	MY2608/2	2021/04/09	2022/04/08
Cable-0.5m(1G-40G)	Rapidtek	40GHZ 50CM	38MS-38MS50314	2021/04/08	2022/04/07
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130605	2020/09/18	2021/09/17
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2021/07/14	2022/07/13
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2021/04/19	2022/04/18
CAX Signal Analyzer	KEYSIGHT	N9000B	MY57100339	2020/12/25	2021/12/24
Attenuator	KEYSIGHT	8491B	MY39250703	2021/04/09	2022/04/08
Power Meter	Anritsu	ML2495A	1224005	2021/04/14	2022/04/13
Power Sensor	Anritsu	MA2411B	1207295	2021/04/14	2022/04/13



Test Item	AC Power Line Conducted Emission				
Test Site	CON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESCI	100821	2020/09/11	2021/09/10
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127-516	2020/09/26	2021/09/25
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	101933	2020/09/17	2021/09/16
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130605	2020/09/18	2021/09/17
E3	AUDIX	v8.2014-8-6	RK-000531	NA	NA



4. Antenna Requirements

4.1 Antenna Construction and Directional Gain

Antenna Type	Slot Antenna
Antenna Gain	ANT A: 2.91dBi, ANT B: 3.91dBi

2412-2462MHz:

For 11b / 11g:

For Power directional gain= $G_{ant}= 3.91$ dBi

For PSD directional gain = $G_{ant}= 3.91$ dBi

For 11n:

For Power directional gain= $G_{ant}= 3.91$ dBi

For PSD directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$
= 6.43 (dBi)



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.4-2014. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




5.3 Typical Test Setup





5.4 Test Result and Data

Power	: AC 120V / 60Hz	Pol/Phase	: LINE
Test Mode	: Mode 4		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.17	9.96	20.06	30.02	54.78	-24.76	Average	P
2	0.17	9.96	34.59	44.55	64.78	-20.23	QP	P
3	0.22	9.96	6.81	16.77	52.72	-35.95	Average	P
4	0.22	9.96	23.80	33.76	62.72	-28.96	QP	P
5	0.47	9.98	17.31	27.29	46.57	-19.28	Average	P
6	0.47	9.98	26.96	36.94	56.57	-19.63	QP	P
7	1.15	10.05	9.86	19.91	46.00	-26.09	Average	P
8	1.15	10.05	23.07	33.12	56.00	-22.88	QP	P
9	1.35	10.06	7.69	17.75	46.00	-28.25	Average	P
10	1.35	10.06	22.44	32.50	56.00	-23.50	QP	P
11	17.52	11.16	10.16	21.32	50.00	-28.68	Average	P
12	17.52	11.16	15.93	27.09	60.00	-32.91	QP	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	: AC 120V / 60Hz	Pol/Phase	: NEUTRAL
Test Mode	: Mode 4		



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV)	Limit (dBUV)	Margin (dB)	Detector	P/F
1	0.17	9.97	15.65	25.62	55.00	-29.38	Average	P
2	0.17	9.97	34.09	44.06	65.00	-20.94	QP	P
3	0.23	9.97	10.45	20.42	52.40	-31.98	Average	P
4	0.23	9.97	26.93	36.90	62.40	-25.50	QP	P
5	0.46	9.98	13.26	23.24	46.76	-23.52	Average	P
6	0.46	9.98	26.92	36.90	56.76	-19.86	QP	P
7	1.15	10.04	9.14	19.18	46.00	-26.82	Average	P
8	1.15	10.04	22.77	32.81	56.00	-23.19	QP	P
9	1.45	10.06	7.62	17.68	46.00	-28.32	Average	P
10	1.45	10.06	21.82	31.88	56.00	-24.12	QP	P
11	20.28	11.11	11.09	22.20	50.00	-27.80	Average	P
12	20.28	11.11	17.15	28.26	60.00	-31.74	QP	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Radiated Spurious Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

- 1.The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.
(Y-AXIS is the worst.)
- 2.Due to the test software function limit the operation band setting(200dBuV/m).
There's no corresponding limitation in the actual test item.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9KHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 4		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	324.98	-9.00	37.53	28.53	46.00	-17.47	Peak	400	0	P
2	350.24	-8.42	41.98	33.56	46.00	-12.44	Peak	400	0	P
3	400.66	-7.05	43.83	36.78	46.00	-9.22	Peak	400	0	P
4	450.45	-5.78	38.62	32.84	46.00	-13.16	Peak	400	0	P
5	524.88	-4.09	36.91	32.82	46.00	-13.18	Peak	400	0	P
6	625.35	-2.03	33.63	31.60	46.00	-14.40	Peak	400	0	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 4		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	324.97	-9.00	40.31	31.31	46.00	-14.69	Peak	400	360	P
2	350.26	-8.41	42.88	34.47	46.00	-11.53	Peak	400	360	P
3	400.65	-7.05	40.37	33.32	46.00	-12.68	Peak	400	360	P
4	450.92	-5.78	42.37	36.59	46.00	-9.41	Peak	400	360	P
5	524.92	-4.09	35.64	31.55	46.00	-14.45	Peak	400	360	P
6	825.25	1.02	31.12	32.14	46.00	-13.86	Peak	400	360	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	40.57	36.95	54.00	-17.05	Average	370	66	P
2	2390.00	-3.62	53.92	50.30	74.00	-23.70	Peak	370	66	P
3	2412.00	-3.60	97.15	93.55	200.00	-106.45	Average	370	66	P
4	2412.00	-3.60	99.73	96.13	200.00	-103.87	Peak	370	66	P
5	4824.00	3.73	38.88	42.61	54.00	-11.39	Average	308	55	P
6	4824.00	3.73	46.92	50.65	74.00	-23.35	Peak	308	55	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	43.01	39.39	54.00	-14.61	Average	230	55	P
2	2390.00	-3.62	54.56	50.94	74.00	-23.06	Peak	230	55	P
3	2412.00	-3.60	104.97	101.37	200.00	-98.63	Average	230	55	P
4	2412.00	-3.60	107.73	104.13	200.00	-95.87	Peak	230	55	P
5	4824.00	3.73	47.46	51.19	54.00	-2.81	Average	121	68	P
6	4824.00	3.73	50.51	54.24	74.00	-19.76	Peak	121	68	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	40.90	37.28	54.00	-16.72	Average	100	294	P
2	2390.00	-3.62	54.89	51.27	74.00	-22.73	Peak	100	294	P
3	2437.00	-3.57	95.23	91.66	200.00	-108.34	Average	100	294	P
4	2437.00	-3.57	97.77	94.20	200.00	-105.80	Peak	100	294	P
5	2483.50	-3.40	40.93	37.53	54.00	-16.47	Average	100	294	P
6	2483.50	-3.40	53.82	50.42	74.00	-23.58	Peak	100	294	P
7	4874.00	3.90	40.23	44.13	54.00	-9.87	Average	100	310	P
8	4874.00	3.90	45.91	49.81	74.00	-24.19	Peak	100	310	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	41.03	37.41	54.00	-16.59	Average	100	305	P
2	2390.00	-3.62	54.31	50.69	74.00	-23.31	Peak	100	305	P
3	2437.00	-3.57	104.86	101.29	200.00	-98.71	Average	100	305	P
4	2437.00	-3.57	107.42	103.85	200.00	-96.15	Peak	100	305	P
5	2483.50	-3.40	41.07	37.67	54.00	-16.33	Average	100	305	P
6	2483.50	-3.40	54.15	50.75	74.00	-23.25	Peak	100	305	P
7	4874.00	3.90	48.10	52.00	54.00	-2.00	Average	233	291	P
8	4874.00	3.90	51.19	55.09	74.00	-18.91	Peak	233	291	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-3.50	95.13	91.63	200.00	-108.37	Average	100	231	P
2	2462.00	-3.50	98.17	94.67	200.00	-105.33	Peak	100	231	P
3	2483.50	-3.40	39.63	36.23	54.00	-17.77	Average	100	231	P
4	2483.50	-3.40	54.72	51.32	74.00	-22.68	Peak	100	231	P
5	4924.00	4.10	37.80	41.90	54.00	-12.10	Average	100	311	P
6	4924.00	4.10	45.10	49.20	74.00	-24.80	Peak	100	311	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-3.50	104.05	100.55	200.00	-99.45	Average	143	302	P
2	2462.00	-3.50	107.10	103.60	200.00	-96.40	Peak	143	302	P
3	2483.50	-3.40	40.09	36.69	54.00	-17.31	Average	143	302	P
4	2483.50	-3.40	54.20	50.80	74.00	-23.20	Peak	143	302	P
5	4924.00	4.10	47.10	51.20	54.00	-2.80	Average	245	251	P
6	4924.00	4.10	50.22	54.32	74.00	-19.68	Peak	245	251	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	40.32	36.70	54.00	-17.30	Average	100	293	P
2	2390.00	-3.62	54.71	51.09	74.00	-22.91	Peak	100	293	P
3	2412.00	-3.60	85.89	82.29	200.00	-117.71	Average	100	293	P
4	2412.00	-3.60	96.90	93.30	200.00	-106.70	Peak	100	293	P
5	4824.00	3.73	29.48	33.21	54.00	-20.79	Average	100	85	P
6	4824.00	3.73	44.35	48.08	74.00	-25.92	Peak	100	85	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	43.38	39.76	54.00	-14.24	Average	122	304	P
2	2390.00	-3.62	57.43	53.81	74.00	-20.19	Peak	122	304	P
3	2412.00	-3.60	96.36	92.76	200.00	-107.24	Average	122	304	P
4	2412.00	-3.60	107.28	103.68	200.00	-96.32	Peak	122	304	P
5	4824.00	3.73	31.74	35.47	54.00	-18.53	Average	377	248	P
6	4824.00	3.73	46.10	49.83	74.00	-24.17	Peak	377	248	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	39.81	36.19	54.00	-17.81	Average	111	291	P
2	2390.00	-3.62	54.20	50.58	74.00	-23.42	Peak	111	291	P
3	2437.00	-3.57	86.44	82.87	200.00	-117.13	Average	111	291	P
4	2437.00	-3.57	97.46	93.89	200.00	-106.11	Peak	111	291	P
5	2483.50	-3.40	39.83	36.43	54.00	-17.57	Average	111	291	P
6	2483.50	-3.40	54.57	51.17	74.00	-22.83	Peak	111	291	P
7	4874.00	3.90	27.35	31.25	54.00	-22.75	Average	100	119	P
8	4874.00	3.90	41.63	45.53	74.00	-28.47	Peak	100	119	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	41.09	37.47	54.00	-16.53	Average	164	310	P
2	2390.00	-3.62	54.10	50.48	74.00	-23.52	Peak	164	310	P
3	2437.00	-3.57	95.40	91.83	200.00	-108.17	Average	164	310	P
4	2437.00	-3.57	106.39	102.82	200.00	-97.18	Peak	164	310	P
5	2483.50	-3.40	40.51	37.11	54.00	-16.89	Average	164	310	P
6	2483.50	-3.40	54.92	51.52	74.00	-22.48	Peak	164	310	P
7	4874.00	3.90	28.20	32.10	54.00	-21.90	Average	100	48	P
8	4874.00	3.90	43.37	47.27	74.00	-26.73	Peak	100	48	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-3.50	86.06	82.56	200.00	-117.44	Average	100	229	P
2	2462.00	-3.50	97.21	93.71	200.00	-106.29	Peak	100	229	P
3	2483.50	-3.40	40.50	37.10	54.00	-16.90	Average	100	229	P
4	2483.50	-3.40	54.88	51.48	74.00	-22.52	Peak	100	229	P
5	4924.00	4.10	27.16	31.26	54.00	-22.74	Average	100	42	P
6	4924.00	4.10	41.70	45.80	74.00	-28.20	Peak	100	42	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-3.50	94.76	91.26	200.00	-108.74	Average	114	303	P
2	2462.00	-3.50	106.09	102.59	200.00	-97.41	Peak	114	303	P
3	2483.50	-3.40	41.07	37.67	54.00	-16.33	Average	100	251	P
4	2483.50	-3.40	55.97	52.57	74.00	-21.43	Peak	100	251	P
5	4924.00	4.10	27.94	32.04	54.00	-21.96	Average	100	74	P
6	4924.00	4.10	43.27	47.37	74.00	-26.63	Peak	100	74	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 3, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	42.76	39.14	54.00	-14.86	Average	106	298	P
2	2390.00	-3.62	55.95	52.33	74.00	-21.67	Peak	106	298	P
3	2412.00	-3.60	91.29	87.69	200.00	-112.31	Average	106	298	P
4	2412.00	-3.60	102.79	99.19	200.00	-100.81	Peak	106	298	P
5	4824.00	3.73	27.42	31.15	54.00	-22.85	Average	100	99	P
6	4824.00	3.73	42.41	46.14	74.00	-27.86	Peak	100	99	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 3, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	49.00	45.38	54.00	-8.62	Average	201	310	P
2	2390.00	-3.62	64.81	61.19	74.00	-12.81	Peak	201	310	P
3	2412.00	-3.60	100.71	97.11	200.00	-102.89	Average	201	310	P
4	2412.00	-3.60	112.88	109.28	200.00	-90.72	Peak	201	310	P
5	4824.00	3.73	32.89	36.62	54.00	-17.38	Average	245	253	P
6	4824.00	3.73	46.75	50.48	74.00	-23.52	Peak	245	253	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 3, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	39.94	36.32	54.00	-17.68	Average	100	300	P
2	2390.00	-3.62	54.09	50.47	74.00	-23.53	Peak	100	300	P
3	2437.00	-3.57	90.03	86.46	200.00	-113.54	Average	100	300	P
4	2437.00	-3.57	102.33	98.76	200.00	-101.24	Peak	100	300	P
5	2483.50	-3.40	39.96	36.56	54.00	-17.44	Average	100	300	P
6	2483.50	-3.40	54.05	50.65	74.00	-23.35	Peak	100	300	P
7	4874.00	3.90	28.15	32.05	54.00	-21.95	Average	100	312	P
8	4874.00	3.90	42.85	46.75	74.00	-27.25	Peak	100	312	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 3, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	42.06	38.44	54.00	-15.56	Average	153	303	P
2	2390.00	-3.62	54.84	51.22	74.00	-22.78	Peak	153	303	P
3	2437.00	-3.57	101.13	97.56	200.00	-102.44	Average	153	303	P
4	2437.00	-3.57	112.65	109.08	200.00	-90.92	Peak	153	303	P
5	2483.50	-3.40	41.47	38.07	54.00	-15.93	Average	153	303	P
6	2483.50	-3.40	55.58	52.18	74.00	-21.82	Peak	153	303	P
7	4874.00	3.90	31.92	35.82	54.00	-18.18	Average	227	295	P
8	4874.00	3.90	47.45	51.35	74.00	-22.65	Peak	227	295	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 3, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-3.50	87.92	84.42	200.00	-115.58	Average	205	288	P
2	2462.00	-3.50	99.79	96.29	200.00	-103.71	Peak	205	288	P
3	2483.50	-3.40	39.42	36.02	54.00	-17.98	Average	205	288	P
4	2483.50	-3.40	54.28	50.88	74.00	-23.12	Peak	205	288	P
5	4924.00	4.10	27.10	31.20	54.00	-22.80	Average	100	320	P
6	4924.00	4.10	41.82	45.92	74.00	-28.08	Peak	100	320	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 3, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-3.50	99.79	96.29	200.00	-103.71	Average	246	308	P
2	2462.00	-3.50	111.10	107.60	200.00	-92.40	Peak	246	308	P
3	2483.50	-3.40	41.57	38.17	54.00	-15.83	Average	246	308	P
4	2483.50	-3.40	56.37	52.97	74.00	-21.03	Peak	246	308	P
5	4924.00	4.10	29.57	33.67	54.00	-20.33	Average	218	319	P
6	4924.00	4.10	45.88	49.98	74.00	-24.02	Peak	218	319	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 4, CH03		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	41.81	38.19	54.00	-15.81	Average	100	294	P
2	2390.00	-3.62	55.05	51.43	74.00	-22.57	Peak	100	294	P
3	2422.00	-3.59	86.64	83.05	200.00	-116.95	Average	100	294	P
4	2422.00	-3.59	99.47	95.88	200.00	-104.12	Peak	100	294	P
5	4844.00	3.80	27.25	31.05	54.00	-22.95	Average	100	220	P
6	4844.00	3.80	41.57	45.37	74.00	-28.63	Peak	100	220	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 4, CH03		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	52.91	49.29	54.00	-4.71	Average	115	304	P
2	2390.00	-3.62	66.30	62.68	74.00	-11.32	Peak	115	304	P
3	2422.00	-3.59	95.17	91.58	200.00	-108.42	Average	115	304	P
4	2422.00	-3.59	108.88	105.29	200.00	-94.71	Peak	115	304	P
5	4844.00	3.80	29.24	33.04	54.00	-20.96	Average	244	252	P
6	4844.00	3.80	44.02	47.82	74.00	-26.18	Peak	244	252	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 4, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	40.92	37.30	54.00	-16.70	Average	100	293	P
2	2390.00	-3.62	53.49	49.87	74.00	-24.13	Peak	100	293	P
3	2437.00	-3.57	86.49	82.92	200.00	-117.08	Average	100	293	P
4	2437.00	-3.57	99.22	95.65	200.00	-104.35	Peak	100	293	P
5	2483.50	-3.40	40.40	37.00	54.00	-17.00	Average	100	293	P
6	2483.50	-3.40	54.49	51.09	74.00	-22.91	Peak	100	293	P
7	4874.00	3.90	29.44	33.34	54.00	-20.66	Average	100	256	P
8	4874.00	3.90	43.10	47.00	74.00	-27.00	Peak	100	256	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 4, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.62	46.28	42.66	54.00	-11.34	Average	157	302	P
2	2390.00	-3.62	59.77	56.15	74.00	-17.85	Peak	157	302	P
3	2437.00	-3.57	96.74	93.17	200.00	-106.83	Average	157	302	P
4	2437.00	-3.57	109.59	106.02	200.00	-93.98	Peak	157	302	P
5	2483.50	-3.40	41.84	38.44	54.00	-15.56	Average	157	302	P
6	2483.50	-3.40	55.20	51.80	74.00	-22.20	Peak	157	302	P
7	4874.00	3.90	29.78	33.68	54.00	-20.32	Average	241	324	P
8	4874.00	3.90	43.46	47.36	74.00	-26.64	Peak	241	324	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 4, CH09		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2452.00	-3.55	87.14	83.59	200.00	-116.41	Average	109	291	P
2	2452.00	-3.55	100.41	96.86	200.00	-103.14	Peak	109	291	P
3	2483.50	-3.40	41.43	38.03	54.00	-15.97	Average	109	291	P
4	2483.50	-3.40	54.64	51.24	74.00	-22.76	Peak	109	291	P
5	4904.00	4.00	29.12	33.12	54.00	-20.88	Average	100	232	P
6	4904.00	4.00	42.52	46.52	74.00	-27.48	Peak	100	232	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 4, CH09		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2452.00	-3.55	97.25	93.70	200.00	-106.30	Average	116	306	P
2	2452.00	-3.55	109.75	106.20	200.00	-93.80	Peak	116	306	P
3	2483.50	-3.40	44.20	40.80	54.00	-13.20	Average	116	306	P
4	2483.50	-3.40	57.67	54.27	74.00	-19.73	Peak	116	306	P
5	4904.00	4.00	29.82	33.82	54.00	-20.18	Average	127	334	P
6	4904.00	4.00	42.96	46.96	74.00	-27.04	Peak	127	334	P

Note: Level=Reading+Factor
 Margin=Level-Limit
 Factor=Antenna Factor + cable loss - Amplifier Factor



6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



7. Test of Conducted Spurious Emission


7.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

- a. The transmitter output was connected to the spectrum analyzer via a low loss cable.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- c. Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- d. The band edges was measured and recorded.

7.3 Test Setup Layout



7.4 Test Result and Data

Note: Test plots refers to the following pages.





ANT A

Modulation Type: 802.11n HT20, CH01



Modulation Type: 802.11n HT20, CH06





ANT A

Modulation Type: 802.11n HT20, CH11





ANT A

Modulation Type: 802.11n HT40, CH03



Modulation Type: 802.11n HT40, CH06





ANT A

Modulation Type: 802.11n HT40, CH09





ANT B

Modulation Type: 802.11b, CH 01




Modulation Type: 802.11b, CH 06





ANT B

Modulation Type: 802.11b, CH 11






ANT B

Modulation Type: 802.11g, CH 01



Modulation Type: 802.11g, CH 06





ANT B

Modulation Type: 802.11g, CH 11







ANT B

Modulation Type: 802.11n HT20, CH01



Modulation Type: 802.11n HT20, CH06





ANT B

Modulation Type: 802.11n HT20, CH11





ANT B

Modulation Type: 802.11n HT40, CH03



Modulation Type: 802.11n HT40, CH06





ANT B

Modulation Type: 802.11n HT40, CH09





8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout



8.4 Test Result and Data

Modulation Type	On Time (ms)	Period Time (ms)	Duty Cycle (%)
11b,1M	12.45	12.55	99.20%
11g,6M	2.06	2.10	98.00%
11n HT20	1.93	1.96	98.32%
11n HT40	0.95	1.00	95.21%



Modulation Type: 802.11b(1Mbps)



Modulation Type: 802.11n HT40(13.5Mbps)



Modulation Type: 802.11g(6Mbps)



Modulation Type: 802.11n HT20(6.5Mbps)





9. 6dB Bandwidth Measurement Data


9.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW to 300 KHz.
- c. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- d. The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout



9.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Limit (MHz)
			ANT A	ANT B	
11b	1	2412	-	8.07	0.5
	6	2437	-	8.07	0.5
	11	2462	-	8.07	0.5
11g	1	2412	-	15.45	0.5
	6	2437	-	15.45	0.5
	11	2462	-	15.33	0.5
11n HT20	1	2412	16.05	16.11	0.5
	6	2437	16.35	16.92	0.5
	11	2462	15.15	15.96	0.5
11n HT40	3	2422	35.10	35.10	0.5
	6	2437	36.30	35.76	0.5
	9	2452	35.16	35.10	0.5



ANT A
Modulation Type: 802.11n HT20
CH01



Modulation Type: 802.11n HT40
CH03



CH06



CH06



CH11



CH09





ANT B

Modulation Type: 802.11b
CH01

Modulation Type: 802.11g
CH01



CH06

CH06



CH11

CH11





ANT B

Modulation Type: 802.11n HT20
CH01



Modulation Type: 802.11n HT40
CH03



CH06



CH06



CH11



CH09





10. Maximum Peak and Average Output Power

10.1 Test Limit


The Maximum Peak Output Power Measurement is 30dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

10.2 Test Procedures

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout





10.4 Test Result and Data

Setting	Modulation Mode	Channel	Frequency (MHz)	Conducted(peak) output power (dBm)		Total PK power (dBm)	Total PK power (mW)	Powe Limit (dBm)
				ANT A	ANT B			
16	11b	1	2412	-	18.23	18.23	66.527	30.00
16.5		6	2437	-	18.62	18.62	72.778	30.00
16		11	2462	-	18.48	18.48	70.469	30.00
12.5	11g	1	2412	-	17.01	12.61	18.239	30.00
13		6	2437	-	17.05	17.05	50.699	30.00
13		11	2462	-	17.14	17.14	51.761	30.00
13	11n HT20	1	2412	17.00	17.11	20.07	101.523	30.00
13.5		6	2437	17.08	16.79	19.95	98.803	30.00
13		11	2462	17.30	16.90	20.11	102.681	30.00
12	11n HT40	3	2422	18.50	18.46	21.49	140.940	30.00
12.5		6	2437	18.53	18.49	21.52	141.917	30.00
12.5		9	2452	19.27	18.91	22.10	162.332	30.00

Setting	Modulation Mode	Channel	Frequency (MHz)	Conducted(average) output power (dBm)		Total AV power (dBm)	Total AV power (mW)	Powe Limit (dBm)
				ANT A	ANT B			
16	11b	1	2412	-	16.06	16.06	40.365	NA
16.5		6	2437	-	16.36	16.36	43.251	NA
16		11	2462	-	16.13	16.13	41.020	NA
12.5	11g	1	2412	-	12.61	12.61	18.239	NA
13		6	2437	-	12.68	12.68	18.535	NA
13		11	2462	-	12.65	12.65	18.408	NA
13	11n HT20	1	2412	12.40	12.66	15.54	35.828	NA
13.5		6	2437	12.38	12.33	15.37	34.398	NA
13		11	2462	12.54	12.33	15.45	35.047	NA
12	11n HT40	3	2422	12.29	12.40	15.36	34.321	NA
12.5		6	2437	12.33	12.59	15.47	35.255	NA
12.5		9	2452	12.86	12.76	15.82	38.200	NA

Note: Average power is for reference only.



11. Power Spectral Density

11.1 Test Limit


The Maximum of Power Spectral Density Measurement is 8dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

11.2 Test Procedures

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 3kHz RBW and 10KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- The power spectral density was measured and recorded.

11.3 Test Setup Layout




11.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 3KHz Bandwidth(dBm)		Sum chain (dBm)	Duty Cycle CF(dB)	Total PSD (dBm)	Limit (dBm)
			ANT A	ANT B				
11b	1	2412	-	-9.22	-9.22	0.00	-9.22	8.00
	6	2437	-	-8.81	-8.81	0.00	-8.81	8.00
	11	2462	-	-9.24	-9.24	0.00	-9.24	8.00
11g	1	2412	-	-13.29	-13.29	0.00	-13.29	8.00
	6	2437	-	-14.23	-14.23	0.00	-14.23	8.00
	11	2462	-	-13.80	-13.80	0.00	-13.80	8.00
11n HT20	1	2412	-14.33	-12.36	-10.22	0.00	-10.22	7.57
	6	2437	-12.85	-13.74	-10.26	0.00	-10.26	7.57
	11	2462	-12.79	-14.28	-10.46	0.00	-10.46	7.57
11n HT40	3	2422	-16.07	-17.20	-13.59	0.00	-13.59	7.57
	6	2437	-17.19	-16.83	-14.00	0.00	-14.00	7.57
	9	2452	-15.94	-14.94	-12.40	0.00	-12.40	7.57



ANT A
Modulation Type: 802.11n HT20
CH01




Modulation Type: 802.11n HT40
CH03




CH06




CH06



CH11



CH09






ANT B

Modulation Type: 802.11b
CH01




Modulation Type: 802.11g
CH01



CH06




CH06



CH11




CH11







ANT B
Modulation Type: 802.11n HT20
CH01




Modulation Type: 802.11n HT40
CH03




CH06



CH06



CH11



CH09

