



FCC RADIO TEST REPORT

Applicant : Elo Touch Solutions, Inc.

Address : 670 N. McCarthy Blvd., Suite 100, Milpitas,
CA 95035, USA

Equipment : Touch All-in-One Computer

Model No. : ESY22I1D

Trade Name : Elo or 

FCC ID : RBWESY22I1DNFC

I HEREBY CERTIFY THAT :

The sample was received on Mar. 01, 2024 and the testing was completed on May. 15, 2024 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:



Mark Liao / Supervisor

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test.....	6
2.1 Feature of Equipment.....	6
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software.....	8
2.4 Description of Test System.....	9
2.5 General Information of Test.....	10
2.6 Measurement Uncertainty	11
3. Test Equipment and Ancillaries Used for Tests.....	12
4. Antenna Requirements.....	14
4.1 Antenna Construction and Directional Gain.....	14
5. Test of AC Power Line Conducted Emission	15
5.1 Test Limit	15
5.2 Test Procedures	15
5.3 Typical Test Setup	16
5.4 Test Result and Data.....	17
5.5 Test Photographs	23
6. Test of Radiated Spurious Emission.....	24
6.1 Test Limit	24
6.2 Test Procedures	25
6.3 Typical Test Setup	26
6.4 Test Result and Data (9KHz ~ 30MHz)	27
6.5 Test Result and Data (30MHz ~ 1GHz)	27
6.6 Test Result and Data (1GHz ~ 25GHz).....	33
6.7 Restricted Bands of Operation.....	69
6.8 Test Photographs (30MHz ~ 1GHz)	70
6.9 Test Photographs (1GHz ~ 25GHz)	71
7. Test of Conducted Spurious Emission	73
7.1 Test Limit	73
7.2 Test Procedure	73
7.3 Test Setup Layout	73
7.4 Test Result and Data.....	73
8. On Time, Duty Cycle and Measurement methods	90
8.1 Test Limit	90
8.2 Test Procedure	90
8.3 Test Setup Layout	90
8.4 Test Result and Data.....	90
9. 6dB Bandwidth Measurement Data.....	93
9.1 Test Limit	93
9.2 Test Procedures	93
9.3 Test Setup Layout	93



9.4	Test Result and Data.....	94
10.	Maximum Peak and Average Output Power	99
10.1	Test Limit	99
10.2	Test Procedures	99
10.3	Test Setup Layout	99
10.4	Test Result and Data.....	100
11.	Power Spectral Density	102
11.1	Test Limit	102
11.2	Test Procedures	102
11.3	Test Setup Layout	102
11.4	Test Result and Data.....	103
12.	Radio Frequency Exposure	108
12.1	Applicable Standards	108
12.2	EUT Specification.....	109
12.3	Result	109



History of this test report

Report No.	Issued Date	Description
24030030-TRFCC03	Jun. 07, 2024	Original



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak and Average Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
2.1091	. Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment

Operation Frequency Range	NFC: 13.553MHz~13.567MHz BT / BLE: 2400-2483.5MHz 802.11b/g/n: 2400-2483.5MHz 802.11a/n/ac: 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz
Center Frequency Range	NFC: 13.56MHz BT / BLE: 2402MHz-2480MHz 802.11b/g/n: 2412MHz-2462MHz 802.11a/n/ac: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz
Modulation Type	NFC: ASK BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK WLAN: 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 802.11a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Modulation Technology	DSSS, OFDM, FHSS, DTS
Data Rate	BT: GFSK: 1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps WLAN: 2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	NFC: Loop Antenna BT/BLE/2.4G/5G: Dipole Antenna
Antenna Gain	For NFC: 0dBi For BT / BLE: 2400-2480MHz: ANT A: 4.45dBi For WLAN: 2400-2500MHz: ANT A: 4.45dBi, ANT B: 2.5dBi 5150-5250MHz: ANT A: 3.79dBi, ANT B: 4.80dBi 5250-5350MHz: ANT A: 3.62dBi, ANT B: 4.98dBi 5471-5725MHz: ANT A: 2.12dBi, ANT B: 5.87dBi 5725-5850MHz: ANT A: 1.87dBi, ANT B: 5.97dBi
Adapter	Brand: DELTA Model: ADP-65JH HB
	Brand: BILLION Model: BA090-190474MBX
	Brand: BILLION Model: BA070-190342MBX
Panel	Brand: LG Model: LM215WF3



	Brand: AUO Model: M215HAN01.2
Firmware Number	22in-I-Series-4
Serial Number	SWEP_sdm660la50_v12.047.03.p_01

Note:

1. EUT support TPC Function.
2. EUT support Client Mode without radar detection.
3. EUT WLAN 2.4GHz 802.11b and 802.11g 1TX diversity
4. WLAN and BT can simultaneously transmission.
5. For more details, please refer to the User's manual of the EUT.
6. Panel (Brand: LG, Model: LM215WF3) is worst case, hence used at test report.

2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT20 (2412MHz~2462MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
*01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	*11	2462
*06	2437	---	---

802.11n HT40 (2422MHz~2452MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
*03	2422	*09	2452
04	2427	---	---
05	2432	---	---
*06	2437	---	---

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- b. The complete test system included Remote workstation and EUT for RF test. The Remote workstation included Notebook.
- c. An executive program, " QRCT ver.4.0.00189.0" under Windows OS system was executed to transmit and receive data via WLAN.
- d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	802.11b (1Mbps) , From Adapter , ANT A
2	802.11g (6Mbps) , From Adapter , ANT A
3	802.11b (1Mbps) , From Adapter , ANT B
4	802.11g (6Mbps) , From Adapter , ANT B
5	802.11n HT20 (6.5Mbps) From Adapter , MIMO ANT
6	802.11n HT40 (13.5Mbps) From Adapter , MIMO ANT

caused "Test Mode 2,4,5" generated the worst case, they were reported as the final data.

Radiation Emissions (Below 1GHz)

Test Mode	Operating Description
1	802.11b (1Mbps) , From Adapter , ANT A
2	802.11g (6Mbps) , From Adapter , ANT A
3	802.11b (1Mbps) , From Adapter , ANT B
4	802.11g (6Mbps) , From Adapter , ANT B
5	802.11n HT20 (6.5Mbps) From Adapter , MIMO ANT
6	802.11n HT40 (13.5Mbps) From Adapter , MIMO ANT

caused "Test Mode 2,4,5" generated the worst case, they were reported as the final data.

Radiation Emissions (1GHz ~ 25GHz)

Test Mode	Operating Description
1	802.11b (1Mbps) , From Adapter , ANT A
2	802.11g (6Mbps) , From Adapter , ANT A
3	802.11b (1Mbps) , From Adapter , ANT B
4	802.11g (6Mbps) , From Adapter , ANT B
5	802.11n HT20 (6.5Mbps) From Adapter , MIMO ANT
6	802.11n HT40 (13.5Mbps) From Adapter , MIMO ANT

caused "Test Mode 1~6" generated the worst case, they were reported as the final data.

Note:1. There are two kinds of test voltage: AC 120V / 60Hz and AC 240V / 60Hz.

For AC Power Line Conducted Emission, AC 240V / 60Hz is worst case.

For Radiated Spurious Emission(Below 1GHz),

ANT A , ANT B : AC 240V / 60Hz is worst case.

MIMO ANT : AC 120V / 60Hz is worst case.

For Radiated Spurious Emission(1GHz ~ 25GHz), AC 120V / 60Hz is worst case.

2. There are three types of Adapters with the shipment, After engineering evaluation,
Model: ADP-65JH HB are worst case, hence, are used at test report.



The EUT incorporates a MIMO function

Modulation Type	TX CONFIGURATION
802.11b	1TX diversity
802.11g	1TX diversity
802.11n HT20	2TX
802.11n HT40	2TX

2.4 Description of Test System

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	lenovo	S1GL2W	N/A	N/A
USB Cable (A to A)	BENEVO	E210567AWM	1m / NS	N/A
Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude E5470	N/A	Adapter / 1.8m / NS
USB Cable (A to A)	BENEVO	E210567AWM	1m / NS	N/A
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude E5470	N/A	Adapter / 1.8m / NS
USB Cable (A to A)	BENEVO	E210567AWM	1m / NS	N/A



2.5 General Information of Test

<input checked="" type="checkbox"/> Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
Frequency Range Investigated	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz	
Test Distance	The test distance of radiated emission from antenna to EUT is 3 M.	

ANT A

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/03/25	24.4°C / 45%	Leon Huang
Radiated Emissions	3M02-NK	2024/03/14	19.1°C / 39%	Leon Huang
Radiated Emissions	3M02-NK	2024/05/15	22.1°C / 36%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2024/03/21	21.7°C / 47%	Leon Huang

ANT B

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/03/25	24.4°C / 45%	Leon Huang
Radiated Emissions	3M02-NK	2024/03/15	22°C / 45%	Leon Huang
Radiated Emissions	3M02-NK	2024/05/15	22.1°C / 36%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2024/03/21	21.7°C / 47%	Leon Huang

MIMO ANT

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/03/23	25.3°C / 47%	Leon Huang
Radiated Emissions	3M02-NK	2024/03/13	19.6°C / 42%	Leon Huang
Radiated Emissions	3M02-NK	2024/05/15	22.1°C / 36%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2024/03/21	21.7°C / 47%	Leon Huang



2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.12dB
Radiated Spurious Emission(9KHz~30MHz)	±3.5dB
Radiated Spurious Emission(30MHz~1GHz)	±5.1dB
Radiated Spurious Emission(1GHz~25GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±5.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±7.6%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	369	2024/02/19	2025/02/18
Active Loop Antenna	Schwarzbeck	FMZB 1513	414	2024/01/16	2025/01/15
Horn Antenna	EMCO	3115	31601	2023/10/18	2024/10/17
Horn Antenna	EMCO	3116	31974	2023/10/16	2024/10/15
EMI Receiver	ROHDE & SCHWARZ	ESCI	101423	2023/07/05	2024/07/04
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2023/08/15	2024/08/14
Preamplifier	Agilent	8449B	3008A01954	2024/03/01	2025/02/28
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2023/10/13	2024/10/12
Preamplifier	EM Electronics corp.	EM330	60659	2024/02/17	2025/02/16
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2023/07/31	2024/07/30
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2024/02/23	2025/02/22
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2024/03/05	2025/03/04
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2024/03/05	2025/03/04
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2024/03/05	2025/03/04
Cable-1m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	552450	2023/06/08	2024/06/07
Cable-3m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	552451	2023/06/08	2024/06/07
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
High Pass Filter	Warison	WFIL-H3000-18000F-03	WRJ5CFWC2J 1	2023/07/03	2024/07/02
Highpass Filter	WOKEN	WFIL-H7000-18000F-01	WR468FWC2B 1	2023/08/18	2024/08/17

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2024/03/01	2025/02/28
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19
Cable-0.5m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	28420/2	2023/10/12	2024/10/11
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Switch Box	Theda	1-4	TW5451159	NA	NA



Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2023/05/08	2024/05/07
TWO-LINE V-NETWORK	ROHDE & SCHWARZ	ENV216	102185	2023/08/29	2024/08/28
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2023/07/31	2024/07/30
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA



4. Antenna Requirements

4.1 Antenna Construction and Directional Gain

Antenna Type	Dipole Antenna
Antenna Gain	2400-2500MHz: ANT A: 4.45 dBi, ANT B: 2.5 dBi

2400-2500MHz

802.11b and 802.11g

For Power directional gain= $G_{ant} = 4.45 \text{ dBi}$

For PSD directional gain = $G_{ant} = 6.54 \text{ dBi}$

802.11n HT20/40

For Power directional gain= $G_{ant} = 4.45 \text{ dBi}$

For PSD directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}] = 6.54 \text{ dBi}$

*MIMO type: Cyclic Delay Diversity (CDD) mode.



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



5.3 Typical Test Setup






5.4 Test Result and Data

ANTA

Test Mode : 1TX 11g CH11 6Mbps
Voltage : From Adapter(AC 240V/60Hz)
Phase : Line

Data: 72



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1559	9.66	18.22	19.88	55.68	-35.80	Average	P
2	0.1559	9.66	35.13	44.79	65.68	-20.89	QP	P
3	0.1873	9.64	6.88	16.52	54.16	-37.64	Average	P
4	0.1873	9.64	29.64	39.28	64.16	-24.88	QP	P
5	0.2097	9.64	19.61	29.25	53.22	-23.97	Average	P
6	0.2097	9.64	29.17	38.81	63.22	-24.41	QP	P
7	0.4614	9.66	9.27	18.93	46.67	-27.74	Average	P
8	0.4614	9.66	22.84	32.50	56.67	-24.17	QP	P
9	15.6016	9.91	25.87	35.78	50.00	-14.22	Average	P
10	15.6016	9.91	31.23	41.14	60.00	-18.86	QP	P
11	19.3478	9.94	27.80	37.74	50.00	-12.26	Average	P
12	19.3478	9.94	32.77	42.71	60.00	-17.29	QP	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Test Mode : 1TX 11g CH11 6Mbps
Voltage : From Adapter(AC 240V/60Hz)
Phase : Neutral

Data: 73



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1626	9.57	32.43	42.00	55.33	-13.33	Average	P
2	0.1626	9.57	38.21	47.78	65.33	-17.55	QP	P
3	0.2007	9.59	30.45	40.04	53.58	-13.54	Average	P
4	0.2007	9.59	35.12	44.71	63.58	-18.87	QP	P
5	0.2541	9.58	5.08	14.66	51.62	-36.96	Average	P
6	0.2541	9.58	24.81	34.39	61.62	-27.23	QP	P
7	0.4905	9.57	24.45	34.02	46.16	-12.14	Average	P
8	0.4905	9.57	30.46	40.03	56.16	-16.13	QP	P
9	15.6735	9.91	26.59	36.50	50.00	-13.50	Average	P
10	15.6735	9.91	32.28	42.19	60.00	-17.81	QP	P
11	19.7358	9.97	28.35	38.32	50.00	-11.68	Average	P
12	19.7358	9.97	33.66	43.63	60.00	-16.37	QP	P

Note: Level=Reading+Factor

Margin=Level-Limit


Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



ANT B

Test Mode : 1TX 11g CH06 6Mbps
Voltage : From Adapter(AC 240V/60Hz)
Phase : Line

Data: 74



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1610	9.66	32.41	42.07	55.41	-13.34	Average	P
2	0.1610	9.66	38.65	48.31	65.41	-17.10	QP	P
3	0.2033	9.64	30.47	40.11	53.47	-13.36	Average	P
4	0.2033	9.64	36.09	45.73	63.47	-17.74	QP	P
5	0.2483	9.64	18.84	28.48	51.82	-23.34	Average	P
6	0.2483	9.64	24.49	34.13	61.82	-27.69	QP	P
7	0.4860	9.65	30.27	39.92	46.24	-6.32	Average	P
8	0.4860	9.65	32.47	42.12	56.24	-14.12	QP	P
9	16.9608	9.92	27.73	37.65	50.00	-12.35	Average	P
10	16.9608	9.92	33.18	43.10	60.00	-16.90	QP	P
11	19.1851	9.94	33.45	43.39	50.00	-6.61	Average	P
12	19.1851	9.94	38.67	48.61	60.00	-11.39	QP	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Test Mode : 1TX 11g CH06 6Mbps
Voltage : From Adapter(AC 240V/60Hz)
Phase : Neutral

Data: 75



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1586	9.57	30.12	39.69	55.54	-15.85	Average	P
2	0.1586	9.57	35.74	45.31	65.54	-20.23	QP	P
3	0.2018	9.59	30.98	40.57	53.54	-12.97	Average	P
4	0.2018	9.59	35.76	45.35	63.54	-18.19	QP	P
5	0.2435	9.58	27.17	36.75	51.97	-15.22	Average	P
6	0.2435	9.58	31.31	40.89	61.97	-21.08	QP	P
7	0.4860	9.57	30.68	40.25	46.24	-5.99	Average	P
8	0.4860	9.57	32.71	42.28	56.24	-13.96	QP	P
9	15.7527	9.91	26.58	36.49	50.00	-13.51	Average	P
10	15.7527	9.91	32.20	42.11	60.00	-17.89	QP	P
11	19.6208	9.97	28.62	38.59	50.00	-11.41	Average	P
12	19.6208	9.97	33.82	43.79	60.00	-16.21	QP	P


Note: Level=Reading+Factor
Margin=Level-Limit
Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



MIMO ANT

Test Mode : 2TX 11n20 CH06 MCS0
Voltage : From Adapter(AC 240V/60Hz)
Phase : Line

Data: 70



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1602	9.66	9.28	18.94	55.45	-36.51	Average	P
2	0.1602	9.66	34.32	43.98	65.45	-21.47	QP	P
3	0.2123	9.64	14.55	24.19	53.12	-28.93	Average	P
4	0.2123	9.64	28.39	38.03	63.12	-25.09	QP	P
5	0.2367	9.64	16.36	26.00	52.21	-26.21	Average	P
6	0.2367	9.64	24.73	34.37	62.21	-27.84	QP	P
7	0.4495	9.66	26.52	36.18	46.88	-10.70	Average	P
8	0.4495	9.66	29.86	39.52	56.88	-17.36	QP	P
9	15.8832	9.91	25.09	35.00	50.00	-15.00	Average	P
10	15.8832	9.91	30.40	40.31	60.00	-19.69	QP	P
11	19.3455	9.94	27.70	37.64	50.00	-12.36	Average	P
12	19.3455	9.94	32.71	42.65	60.00	-17.35	QP	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Test Mode : 2TX 11n20 CH06 MCS0
Voltage : From Adapter(AC 240V/60Hz)
Phase : Neutral

Data: 71



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1589	9.57	30.31	39.88	55.52	-15.64	Average	P
2	0.1589	9.57	36.94	46.51	65.52	-19.01	QP	P
3	0.2074	9.59	24.56	34.15	53.31	-19.16	Average	P
4	0.2074	9.59	30.03	39.62	63.31	-23.69	QP	P
5	0.2510	9.58	11.69	21.27	51.72	-30.45	Average	P
6	0.2510	9.58	26.78	36.36	61.72	-25.36	QP	P
7	0.4871	9.57	29.94	39.51	46.22	-6.71	Average	P
8	0.4871	9.57	32.41	41.98	56.22	-14.24	QP	P
9	15.7688	9.91	26.52	36.43	50.00	-13.57	Average	P
10	15.7688	9.91	32.25	42.16	60.00	-17.84	QP	P
11	19.4879	9.97	28.51	38.48	50.00	-11.52	Average	P
12	19.4879	9.97	33.72	43.69	60.00	-16.31	QP	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Radiated Spurious Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.

Note:

1.The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.


2.Due to the test software function limit the operation band setting(200dBuV/m).

There's no corresponding limitation in the actual test item.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9KHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

ANT A

Test Mode : 1TX 11g CH11 6Mbps
Voltage : From Adapter(AC240V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	55.30	-9.21	46.94	37.73	40.00	-2.27	QP	100	58	P
2	168.78	-9.63	49.19	39.56	43.50	-3.94	QP	100	77	P
3	253.10	-10.04	50.74	40.70	46.00	-5.30	Peak	400	0	P
4	421.88	-5.07	44.82	39.75	46.00	-6.25	Peak	400	0	P
5	507.24	-3.18	38.26	35.08	46.00	-10.92	Peak	400	0	P
6	761.38	1.97	35.02	36.99	46.00	-9.01	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11g CH11 6Mbps
Voltage : From Adapter(AC240V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	41.64	-9.74	44.88	35.14	40.00	-4.86	Peak	400	360	P
2	88.20	-15.96	48.12	32.16	43.50	-11.34	Peak	400	360	P
3	150.28	-9.50	45.86	36.36	43.50	-7.14	Peak	400	360	P
4	253.10	-10.04	50.10	40.06	46.00	-5.94	Peak	400	360	P
5	421.88	-5.07	43.11	38.04	46.00	-7.96	Peak	400	360	P
6	763.32	2.03	36.82	38.85	46.00	-7.15	Peak	400	360	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



ANT B

Test Mode : ITX 11g CH06 6Mbps
Voltage : From Adapter(AC240V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dB _{UV})	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	55.30	-9.21	46.94	37.73	40.00	-2.27	QP	100	78	P
2	167.74	-9.55	48.69	39.14	43.50	-4.36	QP	100	88	P
3	253.10	-10.04	49.11	39.07	46.00	-6.93	Peak	400	0	P
4	423.82	-5.00	45.10	40.10	46.00	-5.90	Peak	400	0	P
5	507.24	-3.18	37.60	34.42	46.00	-11.58	Peak	400	0	P
6	759.44	1.92	34.69	36.61	46.00	-9.39	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11g CH06 6Mbps
Voltage : From Adapter(AC240V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dB _{UV})	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	59.10	-9.44	42.30	32.86	40.00	-7.14	Peak	400	360	P
2	167.74	-9.55	45.75	36.20	43.50	-7.30	Peak	400	360	P
3	253.10	-10.04	52.18	42.14	46.00	-3.86	Peak	400	360	P
4	336.52	-7.42	44.71	37.29	46.00	-8.71	Peak	400	360	P
5	423.82	-5.00	42.12	37.12	46.00	-8.88	Peak	400	360	P
6	759.44	1.92	35.27	37.19	46.00	-8.81	Peak	400	360	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



MIMO ANT

Test Mode : 2TX 11n20 CH06 NSS1 MCS0
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	55.30	-9.21	47.70	38.49	40.00	-1.51	QP	100	95	P
2	168.95	-9.65	47.71	38.06	43.50	-5.44	QP	100	98	P
3	253.10	-10.04	49.39	39.35	46.00	-6.65	Peak	400	0	P
4	423.82	-5.00	45.91	40.91	46.00	-5.09	Peak	400	0	P
5	763.32	2.03	36.19	38.22	46.00	-7.78	Peak	400	0	P
6	844.80	3.13	32.97	36.10	46.00	-9.90	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11n20 CH06 NSS1 MCS0
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	59.10	-9.44	44.70	35.26	40.00	-4.74	Peak	400	0	P
2	167.74	-9.55	45.58	36.03	43.50	-7.47	Peak	400	0	P
3	253.10	-10.04	49.73	39.69	46.00	-6.31	Peak	400	0	P
4	311.30	-8.23	45.05	36.82	46.00	-9.18	Peak	400	0	P
5	336.52	-7.42	42.12	34.78	46.00	-11.30	Peak	400	0	P
6	421.88	-5.07	43.46	38.39	46.00	-7.61	Peak	400	0	P

Note: Level=Reading+Factor

Margin=Level-Limit


Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

ANTA

Test Mode : 1Tx 1lb CH01 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	55.00	52.67	54.00	-1.33	Average	100	87	P
2	2390.00	-2.33	59.47	57.14	74.00	-16.86	Peak	100	87	P
3	2412.00	-2.29	107.69	105.40	200.00	-94.60	Average	100	87	P
4	2412.00	-2.29	110.88	108.59	200.00	-91.41	Peak	100	87	P
5	4824.00	6.08	42.25	48.33	54.00	-5.67	Average	112	47	P
6	4824.00	6.08	46.53	52.61	74.00	-21.39	Peak	112	47	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11b CH01 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	53.02	50.69	54.00	-3.31	Average	137	149	P
2	2390.00	-2.33	59.27	56.94	74.00	-17.06	Peak	137	149	P
3	2412.00	-2.29	104.87	102.58	200.00	-97.42	Average	137	149	P
4	2412.00	-2.29	107.39	105.10	200.00	-94.90	Peak	137	149	P
5	4824.00	6.08	39.29	45.37	54.00	-8.63	Average	100	160	P
6	4824.00	6.08	44.70	50.78	74.00	-23.22	Peak	100	160	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11b CH06 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth P/F (deg)
1	2390.00	-2.33	42.95	40.62	54.00	-13.38	Average	100	338 P
2	2390.00	-2.33	55.49	53.16	74.00	-20.84	Peak	100	338 P
3	2437.00	-2.17	110.70	108.53	200.00	-91.47	Average	100	338 P
4	2437.00	-2.17	112.78	110.61	200.00	-89.39	Peak	100	338 P
5	2483.50	-2.01	44.77	42.76	54.00	-11.24	Average	100	338 P
6	2483.50	-2.01	57.60	55.59	74.00	-18.41	Peak	100	338 P
7	4874.00	6.23	42.41	48.64	54.00	-5.36	Average	100	186 P
8	4874.00	6.23	46.96	53.19	74.00	-20.81	Peak	100	186 P
9	7311.00	11.33	28.34	39.67	54.00	-14.33	Average	100	235 P
10	7311.00	11.33	41.37	52.70	74.00	-21.30	Peak	100	235 P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11b CH06 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	41.55	39.22	54.00	-14.78	Average	116	154	P
2	2390.00	-2.33	54.97	52.64	74.00	-21.36	Peak	116	154	P
3	2437.00	-2.17	104.99	102.82	200.00	-97.18	Average	116	154	P
4	2437.00	-2.17	106.30	104.13	200.00	-95.87	Peak	116	154	P
5	2483.50	-2.01	41.85	39.84	54.00	-14.16	Average	116	154	P
6	2483.50	-2.01	55.07	53.06	74.00	-20.94	Peak	116	154	P
7	4874.00	6.23	43.00	49.23	54.00	-4.77	Average	100	160	P
8	4874.00	6.23	46.72	52.95	74.00	-21.05	Peak	100	160	P
9	7311.00	11.33	27.67	39.00	54.00	-15.00	Average	100	158	P
10	7311.00	11.33	41.40	52.73	74.00	-21.27	Peak	100	158	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11b CH11 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	111.77	109.73	200.00	-90.27	Average	100	93	P
2	2462.00	-2.04	112.91	110.87	200.00	-89.13	Peak	100	93	P
3	2483.50	-2.01	53.73	51.72	54.00	-2.28	Average	100	93	P
4	2483.50	-2.01	59.81	57.80	74.00	-16.20	Peak	100	93	P
5	4924.00	6.40	46.20	52.60	54.00	-1.40	Average	237	154	P
6	4924.00	6.40	49.25	55.65	74.00	-18.35	Peak	237	154	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11b CH11 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	105.55	103.51	200.00	-96.49	Average	108	153	P
2	2462.00	-2.04	106.65	104.61	200.00	-95.39	Peak	108	153	P
3	2483.50	-2.01	46.92	44.91	54.00	-9.09	Average	108	153	P
4	2483.50	-2.01	56.20	54.19	74.00	-19.81	Peak	108	153	P
5	4924.00	6.40	42.57	48.97	54.00	-5.03	Average	100	159	P
6	4924.00	6.40	47.06	53.46	74.00	-20.54	Peak	100	159	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11g CH01 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	54.87	52.54	54.00	-1.46	Average	100	339	P
2	2390.00	-2.33	67.22	64.89	74.00	-9.11	Peak	100	339	P
3	2412.00	-2.29	100.71	98.42	200.00	-101.58	Average	100	339	P
4	2412.00	-2.29	110.97	108.68	200.00	-91.32	Peak	100	339	P
5	4824.00	6.08	28.30	34.38	54.00	-19.62	Average	100	165	P
6	4824.00	6.08	41.70	47.78	74.00	-26.22	Peak	100	165	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11g CH01 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	50.16	47.83	54.00	-6.17	Average	220	152	P
2	2390.00	-2.33	63.18	60.85	74.00	-13.15	Peak	220	152	P
3	2412.00	-2.29	95.97	93.68	200.00	-106.32	Average	220	152	P
4	2412.00	-2.29	105.47	103.18	200.00	-96.82	Peak	220	152	P
5	4824.00	6.08	28.22	34.30	54.00	-19.70	Average	220	152	P
6	4824.00	6.08	41.37	47.45	74.00	-26.55	Peak	220	152	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11g CH06 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	44.79	42.46	54.00	-11.54	Average	100	339	P
2	2390.00	-2.33	58.52	56.19	74.00	-17.81	Peak	100	339	P
3	2437.00	-2.17	104.01	101.84	200.00	-98.16	Average	100	339	P
4	2437.00	-2.17	113.48	111.31	200.00	-88.69	Peak	100	339	P
5	2483.50	-2.01	43.51	41.50	54.00	-12.50	Average	100	339	P
6	2483.50	-2.01	57.58	55.57	74.00	-18.43	Peak	100	339	P
7	4874.00	6.23	26.69	32.92	54.00	-21.08	Average	100	157	P
8	4874.00	6.23	42.46	48.69	74.00	-25.31	Peak	100	157	P



Test Mode : 1TX 11g CH06 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	42.71	40.38	54.00	-13.62	Average	118	153	P
2	2390.00	-2.33	55.63	53.30	74.00	-20.70	Peak	118	153	P
3	2437.00	-2.17	97.99	95.82	200.00	-104.18	Average	118	153	P
4	2437.00	-2.17	107.38	105.21	200.00	-94.79	Peak	118	153	P
5	2483.50	-2.01	41.62	39.61	54.00	-14.39	Average	118	153	P
6	2483.50	-2.01	55.00	52.99	74.00	-21.01	Peak	118	153	P
7	4874.00	6.23	29.82	36.05	54.00	-17.95	Average	100	161	P
8	4874.00	6.23	43.32	49.55	74.00	-24.45	Peak	100	161	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11g CH11 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	101.33	99.29	200.00	-100.71	Average	100	88	P
2	2462.00	-2.04	111.07	109.03	200.00	-90.97	Peak	100	88	P
3	2483.50	-2.01	54.73	52.72	54.00	-1.28	Average	100	88	P
4	2483.50	-2.01	64.43	62.42	74.00	-11.58	Peak	100	88	P
5	4924.00	6.40	28.38	34.78	54.00	-19.22	Average	100	118	P
6	4924.00	6.40	41.67	48.07	74.00	-25.93	Peak	100	118	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11g CH11 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	96.15	94.11	200.00	-105.89	Average	133	149	P
2	2462.00	-2.04	105.82	103.78	200.00	-96.22	Peak	133	149	P
3	2483.50	-2.01	47.76	45.75	54.00	-8.25	Average	133	149	P
4	2483.50	-2.01	60.07	58.06	74.00	-15.94	Peak	133	149	P
5	4924.00	6.40	29.32	35.72	54.00	-18.28	Average	100	189	P
6	4924.00	6.40	42.12	48.52	74.00	-25.48	Peak	100	189	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



ANT B

Test Mode : 1TX 11b CH01 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth P/F (deg)	P/F
1	2390.00	-2.33	40.11	37.78	54.00	-16.22	Average	226	87	P
2	2390.00	-2.33	54.26	51.93	74.00	-22.07	Peak	226	87	P
3	2412.00	-2.29	102.23	99.94	200.00	-100.06	Average	226	87	P
4	2412.00	-2.29	104.55	102.26	200.00	-97.74	Peak	226	87	P
5	4824.00	6.08	46.67	52.75	54.00	-1.25	Average	100	112	P
6	4824.00	6.08	49.04	55.12	74.00	-18.88	Peak	100	112	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 1TX 11b CH01 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dB _{UV})	Level (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	40.26	37.93	54.00	-16.07	Average	100	243	P
2	2390.00	-2.33	51.48	49.15	74.00	-24.85	Peak	100	243	P
3	2412.00	-2.29	90.65	88.36	200.00	-111.64	Average	100	243	P
4	2412.00	-2.29	92.23	89.94	200.00	-110.06	Peak	100	243	P
5	4824.00	6.08	43.54	49.62	54.00	-4.38	Average	100	189	P
6	4824.00	6.08	47.54	53.62	74.00	-20.38	Peak	100	189	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor