

# RF EXPOSURE EVALUATION

# 1. PRODUCT INFORMATION

Product Description	Wireless 2-in-1 Adapter
Test Model	BT4810E
Series Model	BT4810A, BT4810B, BT4810C, BT4810D, BT4810F
FCC ID	RCT-BT4810E

# 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

# 3. CALCULATION

Pt=3.516dBm=2.25mW

The value of the Maximum output power Pt is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR=(2.25mW /5mm) .[ $\sqrt{2.48}$ (GHz)]= 0.71<3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR.

# 4. CONCLUSION

The SAR evaluation is not required.