

# FCC Test Report

Report No.: AGC11277220501FE03

FCC ID	:	RCT-BT4810E
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Wireless 2-in-1 Adapter
BRAND NAME	:	N/A
MODEL NAME	:	BT4810E, BT4810A, BT4810B, BT4810C, BT4810D, BT4810F
APPLICANT	:	Shenzhen I-Link Technology Co., Ltd.
DATE OF ISSUE	:	May 31, 2022
STANDARD(S)	:	FCC Part 15.247
<b>REPORT VERSION</b>	:	V1.0







#### **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 31, 2022	Valid	Initial Release



### TABLE OF CONTENTS

1.		. 5
2.	GENERAL INFORMATION	. 6
	2.1. PRODUCT DESCRIPTION	. 6
	2.2. TABLE OF CARRIER FREQUENCYS	. 6
	2.3. RECEIVER INPUT BANDWIDTH	.7
	2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE	. 7
	2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR	.7
	2.6. RELATED SUBMITTAL(S) / GRANT (S)	. 8
	2.7. TEST METHODOLOGY	. 8
	2.8. SPECIAL ACCESSORIES	. 8
	2.9. EQUIPMENT MODIFICATIONS	
	2.10. ANTENNA REQUIREMENT	. 8
3.	MEASUREMENT UNCERTAINTY	. 9
4.	DESCRIPTION OF TEST MODES	10
5.	SYSTEM TEST CONFIGURATION	11
	5.1. CONFIGURATION OF EUT SYSTEM	11
	5.2. EQUIPMENT USED IN TESTED SYSTEM	11
	5.3. SUMMARY OF TEST RESULTS	11
6.	TEST FACILITY	12
7.	PEAK OUTPUT POWER	13
	7.1. MEASUREMENT PROCEDURE	13
	7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
	7.3. LIMITS AND MEASUREMENT RESULT	14
8.	20DB BANDWIDTH	19
	8.1. MEASUREMENT PROCEDURE	19
	8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
	8.3. LIMITS AND MEASUREMENT RESULTS	20
9.	CONDUCTED SPURIOUS EMISSION	25
	9.1. MEASUREMENT PROCEDURE	25



9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
9.3. MEASUREMENT EQUIPMENT USED	
9.4. LIMITS AND MEASUREMENT RESULT	
10. RADIATED EMISSION	
10.1. MEASUREMENT PROCEDURE	
10.2. TEST SETUP	
10.3. LIMITS AND MEASUREMENT RESULT	
10.4. TEST RESULT	
11. NUMBER OF HOPPING FREQUENCY	
11.1. MEASUREMENT PROCEDURE	
11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
11.3. MEASUREMENT EQUIPMENT USED	
11.4. LIMITS AND MEASUREMENT RESULT	
12. TIME OF OCCUPANCY (DWELL TIME)	64
12.1. MEASUREMENT PROCEDURE	
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	64
12.3. MEASUREMENT EQUIPMENT USED	
12.4. LIMITS AND MEASUREMENT RESULT	
13. FREQUENCY SEPARATION	
13.1. MEASUREMENT PROCEDURE	
13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
13.3. MEASUREMENT EQUIPMENT USED	
13.4. LIMITS AND MEASUREMENT RESULT	
14. LINE CONDUCTED EMISSION TEST	69
14.1. LIMITS OF LINE CONDUCTED EMISSION TEST	
14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	
14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	
14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	
14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	71
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	
APPENDIX B: PHOTOGRAPHS OF EUT	



## **1. VERIFICATION OF CONFORMITY**

Applicant	Shenzhen I-Link Technology Co., Ltd.	
Address	Floor B2, Block 1, Yongqi Technopark, Yintian,Industrial Park, Xixiang Town, Bao'an District, Shenzhen, China	
Manufacturer	Shenzhen I-Link Technology Co., Ltd.	
Address	Floor B2, Block 1, Yongqi Technopark, Yintian,Industrial Park, Xixiang Town, Bao'an District, Shenzhen, China	
Factory	Shenzhen I-Link Technology Co., Ltd.	
Address	Floor B2, Block 1, Yongqi Technopark, Yintian,Industrial Park, Xixiang Town, Bao'an District, Shenzhen, China	
Product Designation	Wireless 2-in-1 Adapter	
Brand Name	N/A	
Test Model	BT4810E	
Series Model	BT4810A, BT4810B, BT4810C, BT4810D, BT4810F	
Declaration of Difference	All the series models are the same as the test model except for the model names.	
Date of test	May 23, 2022 to May 31, 2022	
Deviation	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result	Pass	
Report Template	AGCRT-US-BR/RF	

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC PART 15.247.

Prepared By

Cool cheny

Cool Cheng (Project Engineer)

May 31, 2022

Reviewed By

Calvin Liu

(Reviewer)

May 31, 2022

Approved By

Max Zhang (Authorized Officer)

May 31, 2022

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



# 2. GENERAL INFORMATION

#### 2.1. PRODUCT DESCRIPTION

The EUT is designed as "Wireless 2-in-1 Adapter". It is designed by way of utilizing the GFSK, Pi/4 DQPSK and 8DPSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480 GHz
RF Output Power	3.516dBm (Max)
Bluetooth Version	V5.0
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK 1Mbps □GFSK 2Mbps
Number of channels	79
Hardware Version	V1.2
Software Version	V1.0
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	0dBi
Power Supply	DC 3.7V by battery or DC 5V by adapter

#### 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402 MHz
	1	2403 MHz
	:	:
	38	2440 MHz
2402~2480MHz	39	2441 MHz
	40	2442 MHz
	•	:
	77	2479 MHz
	78	2480 MHz



#### 2.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

#### 2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a hopping sequence in data mode: 40, 21, 44, 23, 04, 15, 66, 56, 19, 78, 07, 28, 69, 55, 36, 45, 05, 13, 43, 74, 57, 35, 67, 76, 02, 34, 54, 63, 42, 11, 30, 06, 64, 25, 75, 48, 17, 33, 58, 01, 29, 14, 51, 72, 03, 31, 50, 61, 77, 18, 10, 47, 12, 68, 08, 49, 20, 00, 73, 09, 16, 60, 71, 41, 24, 53, 38, 26, 46, 37, 65, 32, 70, 52, 27, 59, 22, 62, 39

## 2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD\_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.



The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.

### 2.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: RCT-BT4810E** filing to comply with the FCC PART 15.247 requirements.

#### 2.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### 2.8. SPECIAL ACCESSORIES

Refer to section 5.2.

#### 2.9. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.10. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



# **3. MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



#### **4. DESCRIPTION OF TEST MODES**

NO.	TEST MODE DESCRIPTION	
1	Low channel GFSK	
2	Middle channel GFSK	
3	High channel GFSK	
4	Low channel π/4-DQPSK	
5	Middle channel π/4-DQPSK	
6	High channel π/4-DQPSK	
7	Low channel 8DPSK	
8	Middle channel 8DPSK	
9	High channel 8DPSK	
10	Hopping mode GFSK	
11	Hopping mode π/4-DQPSK	
12	Hopping mode 8DPSK	


Note:

1. Only the result of the worst case was recorded in the report, if no other cases.

2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

#### Software Setting





# **5. SYSTEM TEST CONFIGURATION**

#### 5.1. CONFIGURATION OF EUT SYSTEM

Radiated Emission Configure:



Conducted Emission Configure:

EUT		AE
-----	--	----

#### 5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Wireless 2-in-1 Adapter	BT4810E	RCT-BT4810E	EUT
2	Adapter	ZL-PCB0100020502000		AE

#### **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(1)	Peak Output Power	Compliant
15.247 (a)(1)	20 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.209	Radiated Emission	Compliant
15.247 (a)(1)(iii)	Number of Hopping Frequency	Compliant
15.247 (a)(1)(iii)	Time of Occupancy	Compliant
15.247 (a)(1)	Frequency Separation	Compliant
15.207	Conducted Emission	Compliant



#### 6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China		
Designation Number	CN1259		
FCC Test Firm Registration Number	975832		
A2LA Cert. No.	5054.02		
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA		

#### TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
LISN	R&S	ESH2-Z5	100086	Jun. 09, 2021	Jun. 08, 2022
Test software	R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A

#### TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
Power sensor	Aglient	U2021XA	MY54110007	Mar. 04, 2022	Mar. 03, 2023
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Mar. 22, 2022	Mar. 21, 2024
Attenuator	ZHINAN	E-002	N/A	Sep. 03, 2020	Sep. 02, 2022
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 21, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 03, 2020	Sep. 02, 2022
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2020	Jan. 07, 2023
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A



# 7. PEAK OUTPUT POWER

### 7.1. MEASUREMENT PROCEDURE


For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW  $\geq$ RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

## 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

## PEAK POWER TEST SETUP







#### 7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power				
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2402	1.352	⊴21	Pass
GFSK	2441	2.172	≪21	Pass
	2480	3.432	⊴21	Pass
π /4-DQPSK	2402	1.363	⊴21	Pass
	2441	2.207	⊴21	Pass
	2480	3.433	⊴21	Pass
8DPSK	2402	1.396	⊴21	Pass
	2441	2.310	≪21	Pass
	2480	3.516	⊴21	Pass


#### **Test Graphs of Conducted Output Power**
























#### 8. 20DB BANDWIDTH

#### **8.1. MEASUREMENT PROCEDURE**

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

#### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






Test Data of Occupied Bandwidth and -20dB Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail
	2402	0.856	0.937	N/A	Pass
GFSK	2441	0.856	0.937	N/A	Pass
	2480	0.903	0.944	N/A	Pass
π /4-DQPSK	2402	1.162	1.262	N/A	Pass
	2441	1.161	1.258	N/A	Pass
	2480	1.169	1.255	N/A	Pass
8DPSK	2402	1.154	1.243	N/A	Pass
	2441	1.151	1.243	N/A	Pass
	2480	1.153	1.243	N/A	Pass

#### 8.3. LIMITS AND MEASUREMENT RESULTS

#### Test Graphs of Occupied Bandwidth and -20 Bandwidth





















# 9. CONDUCTED SPURIOUS EMISSION

# 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
- Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
   RBW = 100 kHz; VBW= 300 kHz; Sweep = auto; Detector function = peak.
- 4. Set SPA Trace 1 Max hold, then View.

#### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 8.2

#### 9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

#### 9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT			
Applieghte Limite	Measurement Result		
Applicable Limits	Test Data	Criteria	
In any 100 kHz Bandwidth Outside the	At least -20dBc than the limit		
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS	
intentional radiator is operating, the radio frequency	Channel		
power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the TOP Channel	PASS	









#### Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands






























































req 13.75000		SENSE:	Avg Typ	ALIGNAUTO e: Log-Pwr I:>10/10		Frequency
Ref 20.00 di	IFGain:Low	#Atten: 30 dE		Mkr	1 24.995 5 GHz	Auto Tune
						Center Fred 13.750000000 GH;
						<b>Start Fred</b> 2.500000000 GH:
						<b>Stop Free</b> 25.000000000 GH:
					1,	CF Step 2.250000000 GH: Auto Mar
						Freq Offse 0 H:
GHz 100 kHz	#V	BW 300 kHz		Sweep 2	2.152 s (30000 pts	
	Ref 20.00 df	IFGain:Low         Ref 20.00 dBm         Image: Imag	PNO: Fast	Ref 20.00 dBm       Trig: Free Run       AvgHoid         Image: State of the state of	PNO: Fast       Trig: Free Run       Avg Hold>10/10         Mkr         Ref 20.00 dBm       Image: Second sec	Normalized       Trig: Free Run #Atten: 30 dB       AvgHold>10/10       Trig: Free Run Der Mikr1 24.995 5 GHz -49.112 dBm         Ref 20.00 dBm       Image: Stop 25.00 GHz 100 kHz       Image: Stop 25.00 GHz 100 kHz       Image: Stop 25.00 GHz 100 kHz






#### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands


























# **10. RADIATED EMISSION**

## **10.1. MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting		
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP		
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP		
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average		

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




#### **10.2. TEST SETUP**


Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



## RADIATED EMISSION TEST SETUP ABOVE 1000MHz





#### **10.3. LIMITS AND MEASUREMENT RESULT**

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

## 10.4. TEST RESULT

#### Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.




EUT	Wireless 2-in-1 Adapter		Model Name	BT4810E
Temperature	25°C		Relative Humidit	<b>y</b> 55.4%
Pressure	960hPa		Test Voltage	Normal Voltage
Test Mode	Mode 7		Antenna	Horizontal
72.0 dBuV/m				Linit —
				Margin:
		ſ		
		ſ		5
32		2	- 4 5	
	1	Ă.	* Montegranderstorph	ang to see the condition of the second second
manyakana	Allow service to the way on the second of th	When the many many many the series	and the state of t	
· · · ·				
-8 30.000 40 5	50 60 70 90	(MHz)	300 400	500 600 700 1000.000
	Reading	Correct M	easure-	
No. Mk.	Freq. Level	,	nent Limit	Over
	MHz dBuV	dB dl	BuV/m dBuV/m	dB Detector
1 67	7.2022 6.25	16.93 2	3.18 40.00	-16.82 peak
2 128	8.1130 9.99	17.84 2	7.83 43.50	-15.67 peak
3 256	6.5211 9.56	16.37 2	5.93 46.00	-20.07 peak
4 319	9.9370 7.93	20.49 2	8.42 46.00	-17.58 peak
5 383	3.9318 8.86	20.64 2	9.50 46.00	-16.50 peak
6 * 922	2.5157 5.93	27.89 3	3.82 46.00	-12.18 peak

## Radiated emission from 30MHz to 1000MHz

## **RESULT: PASS**



EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E	
Temperature	25°C	Relative Humidity	55.4%	
Pressure	960hPa	Test Voltage	Normal Voltage	
Test Mode	Mode 7	Antenna	Vertical	




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		30.8535	14.41	12.20	26.61	40.00	-13.39	peak
2		43.2017	12.43	14.54	26.97	40.00	-13.03	peak
3		54.2610	8.57	14.86	23.43	40.00	-16.57	peak
4	*	128.1130	17.03	18.08	35.11	43.50	-8.39	peak
5		256.5211	7.64	18.37	26.01	46.00	-19.99	peak
6		383.9318	7.09	19.06	26.15	46.00	-19.85	peak



EUT	Wireless 2-in-1 Adapter		Model Name	BT4810E	
Temperature	25°C		Relative Humidit	ty 55.4%	
Pressure	960hPa		Test Voltage	Normal Voltage	
Test Mode	Mode 8		Antenna	Horizontal	
72.0 dBuV/m				Limit —	
				Margin:	
		ſ			
		ſ		6	
32		2	3 <b>4</b> 5 X X X	and the first of the stand of the	
		Monte and manufacture and	a made the man we are with the server	with the design of the second s	
and the second states and	were the forthe destroy	. udenetherdary	00 100 P		
-8					
30.000 40 5	50 60 70 80	(MHz)	300 400	500 600 700 1000.000	
No. Mk.	Reading Freq. Level		easure- ment Limit	Over	
	MHz dBuV	dB d	BuV/m dBuV/m	dB Detector	
1 6	8.3908 5.39	17.01 2	22.40 40.00	-17.60 peak	
2 12	8.1130 8.71	17.84 2	26.55 43.50	-16.95 peak	
3 25	6.5211 10.72	16.37 2	27.09 46.00	-18.91 peak	
4 31	9.9370 7.58	20.49 2	28.07 46.00	-17.93 peak	
5 38	3.9318 7.04	20.64	27.68 46.00	-18.32 peak	
6 * 90	3.3094 5.83	27.87 3	33.70 46.00	-12.30 peak	




EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 8	Antenna	Vertical



No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		30.7455	16.16	12.19	28.35	40.00	-11.65	peak
2		42.6000	12.59	14.64	27.23	40.00	-12.77	peak
3	*	128.1130	17.50	18.08	35.58	43.50	-7.92	peak
4		256.5211	6.65	18.37	25.02	46.00	-20.98	peak
5		383.9318	8.47	19.06	27.53	46.00	-18.47	peak
6		857.0247	7.51	27.54	35.05	46.00	-10.95	peak




EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E	
Temperature	25°C	Relative Humidity	55.4%	
Pressure	960hPa	Test Voltage	Normal Voltage	
Test Mode	Mode 9	Antenna	Horizontal	



No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		67.9129	5.25	16.98	22.23	40.00	-17.77	peak
2		128.1130	10.25	17.84	28.09	43.50	-15.41	peak
3		256.5211	11.83	16.37	28.20	46.00	-17.80	peak
4		319.9370	8.08	20.49	28.57	46.00	-17.43	peak
5		383.9318	8.02	20.64	28.66	46.00	-17.34	peak
6	*	925.7563	5.77	27.89	33.66	46.00	-12.34	peak



EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		30.8535	14.65	12.20	26.85	40.00	-13.15	peak
2		41.4215	10.75	14.85	25.60	40.00	-14.40	peak
3		54.8348	14.40	15.06	29.46	40.00	-10.54	peak
4	*	128.1130	18.41	18.08	36.49	43.50	-7.01	peak
5		256.5211	8.08	18.37	26.45	46.00	-19.55	peak
6		699.3046	5.94	25.15	31.09	46.00	-14.91	peak

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The 8DPSK is the worst case and recorded in the report.



#### Radiated emission above 1GHz

EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	46.53	0.08	46.61	74	-27.39	peak
4804.000	37.54	0.08	37.62	54	-16.38	AVG
7206.000	41.05	2.21	43.26	74	-30.74	peak
7206.000	32.49	2.21	34.7	54	-19.3	AVG
Remark:						
Factor = Anten	ina Factor + Cabl	e Loss – Pre-a	amplifier.			

EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C Relative Humi		55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	45.16	0.08	45.24	74	-28.76	peak
4804.000	36.89	0.08	36.97	54	-17.03	AVG
7206.000	41.05	2.21	43.26	74	-30.74	peak
7206.000	32.49	2.21	34.7	54	-19.3	AVG
Remark:					1	1
Factor = Anter	na Factor + Cabl	e Loss – Pre-a	mplifier.			



EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 8	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4882.000	45.29	0.14	45.43	74	-28.57	peak
4882.000	38.54	0.14	38.68	54	-15.32	AVG
7323.000	40.15	2.36	42.51	74	-31.49	peak
7323.000	32.48	2.36	34.84	54	-19.16	AVG
Remark:	· · · · · ·				1	•
Factor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			

EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 8	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4882.000	46.29	0.14	46.43	74	-27.57	peak
4882.000	37.54	0.14	37.68	54	-16.32	AVG
7323.000	40.25	2.36	42.61	74	-31.39	peak
7323.000	30.59	2.36	32.95	54	-21.05	AVG
Remark:						
actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			



EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	46.29	0.22	46.51	74	-27.49	peak
4960.000	38.57	0.22	38.79	54	-15.21	AVG
7440.000	41.06	2.64	43.7	74	-30.3	peak
7440.000	32.49	2.64	35.13	54	-18.87	AVG
Remark:						
Factor = Anter	na Factor + Cabl	e Loss – Pre-a	mplifier.			

EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	47.51	0.22	47.73	74	-26.27	peak
4960.000	38.52	0.22	38.74	54	-15.26	AVG
7440.000	40.16	2.64	42.8	74	-31.2	peak
7440.000	32.49	2.64	35.13	54	-18.87	AVG
Remark:			-		1	
Factor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.


The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been tested. The 8DPSK modulation is the worst case and recorded in the report.




	<b>U</b>		
EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Horizontal

#### Test Graph for Peak Measurement



Test Graph for Average Measurement




## **RESULT: PASS**




#### Report No.: AGC11277220501FE03 Page 60 of 77

EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




## **RESULT: PASS**




#### Report No.: AGC11277220501FE03 Page 61 of 77

EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




## **RESULT: PASS**




#### Report No.: AGC11277220501FE03 Page 62 of 77

EUT	Wireless 2-in-1 Adapter	Model Name	BT4810E
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



# **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer. The 8DPSKK modulation is the worst case and recorded in the report.



# **11. NUMBER OF HOPPING FREQUENCY**

## **11.1. MEASUREMENT PROCEDURE**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.

2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

3. VBW  $\geq$  RBW. Sweep: Auto. Detector function: Peak. Trace: Max hold.

4. Allow the trace to stabilize.

## 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

## **11.3. MEASUREMENT EQUIPMENT USED**

The same as described in section 6

## **11.4. LIMITS AND MEASUREMENT RESULT**

Test Data of Number of Hopping Frequency				
Test Mode Number of Hopping Frequency Limits Pass or Fa				
GFSK Hopping	79	>=15	Pass	

#### **Test Graphs of Number of Hopping Frequency**



#### Note: The GFSK modulation is the worst case and recorded in the report.

# 12. TIME OF OCCUPANCY (DWELL TIME)

# 12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Zero span, centered on a hopping channel.

2. RBW shall be  $\leq$  channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.

3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

4. Detector function: Peak. Trace: Max hold.

5. Use the marker-delta function to determine the transmit time per hop.

6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer)  $\times$  (period specified in the requirements / analyzer sweep time)

7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

# 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

# **12.3. MEASUREMENT EQUIPMENT USED**


The same as described in section 6

## **12.4. LIMITS AND MEASUREMENT RESULT**

Test Data of Dwell Time						
Channel	Time of Pulse for DH5 (ms)	Number of hops in the period specified in the requirements	Sweep Time (ms)	Limit (ms)	Pass or Fail	
2402	2.866	27.0*4	309.528	400	Pass	
2441	2.866	27.0*4	309.528	400	Pass	
2480	2.866	27.0*4	309.528	400	Pass	


Note: The GFSK modulation is the worst case and recorded in the report.






## **Test Graphs of Dwell Time**











# **13. FREQUENCY SEPARATION**

## **13.1. MEASUREMENT PROCEDURE**

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Wide enough to capture the peaks of two adjacent channels.

2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

3. Video (or average) bandwidth (VBW)  $\geq$  RBW.

4. Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

## 13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)


Same as described in section 6.2

#### **13.3. MEASUREMENT EQUIPMENT USED**

The same as described in section 6.3

#### **13.4. LIMITS AND MEASUREMENT RESULT**

Test Data of Frequency Separation				
Test Mode	Channel Separation (MHz)	Limits	Pass or Fail	
GFSK Hopping	0.989	>= 2/3 -20dB BW	Pass	



## **Test Graphs of Number of Hopping Frequency**

Note: The GFSK modulation is the worst case and recorded in the report.



# **14. LINE CONDUCTED EMISSION TEST**

## 14.1. LIMITS OF LINE CONDUCTED EMISSION TEST


Frequency	Maximum RF Line Voltage			
Frequency	Q.P. (dBµV)	Average (dBµV)		
150kHz~500kHz	66-56	56-46		
500kHz~5MHz	56	46		
5MHz~30MHz	60	50		

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





## 14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


## 14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



#### 14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST





MEASUREMENT RESULT: "agc fin"

2022/5/25 16:10						
Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.526000 0.562000 0.654000 0.822000 0.970000 1.594000	26.30 34.00 27.00 29.60	5.4 5.4 5.4 5.4 5.4 6.1	56 56 56 56 56 56	26.3 29.7 22.0 29.0 26.4 31.5	QP QP QP QP	L1 L1 L1 L1 L1 L1

## MEASUREMENT RESULT: "agc\_fin2"

2022/5/25 16:	:10					
Frequency	Level	Transd	Limit	Margin	Detector	Line
MHz	dBµV	dB	dBµV	dB		
0.562000	14.80	5.4	46	31.2	27	L1
0.650000	21.40	5.4	46	24.6		L1
0.966000	18.00	5.4	46	28.0	AV	L1
1.570000	13.60	6.1	46	32.4	AV	ь1
1.594000	13.10	6.1	46	32.9	AV	L1
1.638000	12.30	6.2	46	33.7	AV	ь1


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com
 Web: http://www.agccert.com/







2022/5/25 16:07

Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.374000 0.566000 0.654000	25.30 27.00 30.60	5.8 5.4 5.4	58 56 56		QP	N N N
0.822000 1.154000 1.310000	25.20 25.40 24.30	5.4 5.6 5.8	56 56 56	30.8 30.6 31.7	QP QP	N N N

#### MEASUREMENT RESULT: "agc fin2"

16:06					
-	Transd dB	Limit dBµV	Margin dB	Detector	Line
0 9.30	5.7	48	38.9	AV	N
0 8.90	5.4	46	37.1	AV	Ν
0 12.20	5.4	46	33.8	AV	Ν
0 7.60	5.4	46	38.4	AV	N
0 7.80	5.4	46	38.2	AV	Ν
0 10.80	8.5	50	39.2	AV	Ν
	z dBμV 0 9.30 0 8.90 0 12.20 0 7.60 0 7.80	y Level Transd z dBµV dB 0 9.30 5.7 0 8.90 5.4 0 12.20 5.4 0 7.60 5.4 0 7.80 5.4	y Level Transd Limit z dBµV dB dBµV 0 9.30 5.7 48 0 8.90 5.4 46 0 12.20 5.4 46 0 7.60 5.4 46 0 7.80 5.4 46	y Level Transd Limit Margin z dBµV dB dBµV dB 0 9.30 5.7 48 38.9 0 8.90 5.4 46 37.1 0 12.20 5.4 46 33.8 0 7.60 5.4 46 38.4 0 7.80 5.4 46 38.2	y Level Transd Limit Margin Detector z dBµV dB dBµV dB 0 9.30 5.7 48 38.9 AV 0 8.90 5.4 46 37.1 AV 0 12.20 5.4 46 33.8 AV 0 7.60 5.4 46 38.4 AV 0 7.80 5.4 46 38.2 AV

#### **RESULT: PASS**


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



2

Mode 8 Line Conducted Emission Test Line 1-L



#### MEASUREMENT RESULT: "agc\_fin"

2022/5/25 16:	16					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.390000 0.566000 0.654000 0.826000 0.962000 1.690000	30.20 33.60 33.90 28.90 30.50 27.60	5.7 5.4 5.4 5.4 5.4 6.2	58 56 56 56 56	27.9 22.4 22.1 27.1 25.5 28.4	QP QP QP	L1 L1 L1 L1 L1 L1

#### MEASUREMENT RESULT: "agc\_fin2"


2022/5/25 16	:15					
Frequency	Level	Transd	Limit	Margin	Detector	Line
MHz	dBµV	dB	dBµV	dB		
0.358000	17.70	5.8	49	31.1	AV	ь1
0.386000	18.80	5.7	48	29.3	AV	L1
0.534000	22.40	5.4	46	23.6	AV	L1
0.654000	21.00	5.4	46	25.0	AV	ь1
0.794000	15.60	5.4	46	30.4	AV	ь1
0.962000	17.20	5.4	46	28.8	AV	ь1


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/







2022/5/25 16:19

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.586000	24.20 29.50	5.4		31.8 26.5	QP	N N
0.806000	20.90	5.4	56	35.1	QP	N
0.926000	23.50	5.4	56	32.5		N
1.722000	22.30	6.3	56	33.7	-	N
13.578000	25.50	8.0	60	34.5		N

#### MEASUREMENT RESULT: "agc\_fin2"

2022/5/25	16:18					
Frequen M	cy Lev Hz dB			Margin dB	Detector	Line
0.6500	00 11.	30 5.4	46	34.7	AV	N
0.8180	00 7.	00 5.4	46	39.0	AV	Ν
0.9380	00 7.	30 5.4	46	38.7	AV	Ν
16.2940	00 8.	10 8.5	50	41.9	AV	Ν
28.7780	00 6.	70 9.5	50	43.3	AV	Ν
29.3220	00 5.	30 9.5	50	44.2	AV	N


#### **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd



Mode 9 Line Conducted Emission Test Line 1-L



2022/5/31 8:35 Transd Limit Margin Line Frequency Level Detector dB dBµV dBµV dB MHz 0.482000 32.40 5.4 56 23.9 QP ь1 56 0.650000 35.10 5.4 20.9 QP ь1 56 1.002000 29.50 5.4 26.5 QP ь1 1.298000 29.60 5.8 56 26.4 ь1 QP 1.434000 30.50 6.0 56 25.5 QP ь1 1.714000 28.90 6.2 56 27.1 QP ъ1

#### MEASUREMENT

2022/5/31 8:36 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.494000 0.614000 0.654000 0.922000 1.002000 1.710000	18.80 22.70 20.90 10.90 12.90 15.10	5.4 5.4 5.4 5.4 5.4 6.2	46 46 46 46 46	27.3 23.3 25.1 35.1 33.1 30.9	AV AV AV	L1 L1 L1 L1 L1 L1


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com
 Web: http://www.agccert.com/







2022/5/31 8:40

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.618000	37.50	5.4	56	18.5	QP	N
0.754000	29.20	5.4	56	26.8	QP	N
1.118000	32.00	5.6	56	24.0	QP	N
1.158000	33.60	5.7	56	22.4	QP	N
2.078000	29.80	6.5	56	26.2	QP	Ν
2.670000	29.70	6.5	56	26.3	QP	N

#### MEASUREMENT RESULT: "agc\_fin2"

2022/5/31 Frequen M			Limit dBµV	Margin dB	Detector	Line
0.6300 0.7980			46 46			N N
1.1460	00 23.70	5.6	46		AV	Ν
1.2260			46			N
1.6140			46			N
2.0780	00 19.60	6.5	46	26.4	AV	N

#### **RESULT: PASS**

Note: All test modes had been pre-tested. The 8DPSK is the worst case and recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd



# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC11277220501AP02

# APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC11277220501AP03

# ----END OF REPORT----



# Conditions of Issuance of Test Reports

 All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
 Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.