



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V05  
Report Template Revision Date: 2021-11-03

# RF Exposure Evaluation Report

**Report No.:** CQASZ20220300356E-02  
**Applicant:** Shenzhen I-Link Technology CO., LTD .  
**Address of Applicant:** Floor B2, Block 1, Yongqi Technopark, Yintian Industrial park, Xixiang Town, Baoan district, Shenzhen, P.R.China  
**Equipment Under Test (EUT):**  
**EUT Name:** Bluetooth Headset  
**Test Model No.:** LK01, LKDG01, LK02, LK03, LK04  
**Model No.:** LK01  
**Brand Name:** N/A  
**FCC ID:** RCT-LK01  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2022-03-11  
**Date of Test:** 2022-03-11 to 2022-03-25  
**Date of Issue:** 2022-03-30  
**Test Result:** **PASS\***

**\*In the configuration tested, the EUT complied with the standards specified above**

**Tested By:** Lewis Zhou  
( Lewis Zhou )

**Reviewed By:** Rock Huang  
( Rock Huang )

**Approved By:** Jack Ai  
( Jack Ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220300356E-02	Rev.01	Initial report	2022-03-30

## 2 Contents

	Page
<b>1 VERSION</b> .....	2
<b>2 CONTENTS</b> .....	3
<b>3 GENERAL INFORMATION</b> .....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
3.3 GENERAL DESCRIPTION OF BT.....	4
<b>4 SAR EVALUATION</b> .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i> .....	5
4.1.2 <i>Limits</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen I-Link Technology CO., LTD .
Address of Applicant:	Floor B2, Block 1, Yongqi Technopark, Yintian Industrial park, Xixiang Town, Baoan district, Shenzhen, P.R.China
Manufacturer:	Shenzhen I-Link Technology CO., LTD .
Address of Manufacturer:	Floor B2, Block 1, Yongqi Technopark, Yintian Industrial park, Xixiang Town, Baoan district, Shenzhen, P.R.China
Factory:	Shenzhen I-Link Technology CO., LTD .
Address of Factory:	Floor B2, Block 1, Yongqi Technopark, Yintian Industrial park, Xixiang Town, Baoan district, Shenzhen, P.R.China

#### 3.2 General Description of EUT

Product Name:	Bluetooth Headset
Model No.:	LK01, LKDG01, LK02, LK03, LK04
Test Model No	LK01
Trade Mark:	N/A
EUT Supports Radios application:	Bluetooth mode 2402-2480MHz
Software Version:	Link_LK01_SDK1.52_20220221_V1.9.0
Hardware Version:	Link-LK01-V1.2 2021-04-30
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
EUT Power Supply:	Li-ion battery: DC 3.7V 220mAh, Charge by DC 5V for adapter

#### 3.3 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Test Software of EUT:	BT FCC Tool V2.24
Antenna Type:	PCB antenna
Antenna Gain:	2dBi

Note:

Model No.: LK01, LKDG01, LK02, LK03, LK04

Only the model LK01 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 4.1.3 EUT RF Exposure

#### Measurement Data

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-2.48	-2.5±1	-1.5	0.708	0.219	3.0
Middle (2441MHz)	-0.72	-0.5±1	0.5	1.122	0.351	
Highest (2480MHz)	0.54	0.5±1	1.5	1.413	0.445	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20220300356E-01.

\*\*\* END OF REPORT \*\*\*