



EX3DV4- SN:3847

April 26, 2018

|           |   |   |      |       |       |      |       |         |
|-----------|---|---|------|-------|-------|------|-------|---------|
| 10575-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)  | X | 4.50 | 66.17 | 16.08 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.63 | 66.56 | 16.40 |      | 130.0 |         |
|           |   | Z | 4.35 | 66.16 | 15.93 |      | 130.0 |         |
| 10576-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)  | X | 4.52 | 66.33 | 16.14 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.66 | 66.72 | 16.46 |      | 130.0 |         |
|           |   | Z | 4.37 | 66.35 | 16.02 |      | 130.0 |         |
| 10577-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle) | X | 4.71 | 66.61 | 16.32 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.86 | 67.01 | 16.63 |      | 130.0 |         |
|           |   | Z | 4.54 | 66.60 | 16.17 |      | 130.0 |         |
| 10578-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle) | X | 4.60 | 66.74 | 16.40 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.76 | 67.17 | 16.73 |      | 130.0 |         |
|           |   | Z | 4.44 | 66.73 | 16.27 |      | 130.0 |         |
| 10579-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle) | X | 4.37 | 65.99 | 15.69 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.52 | 66.47 | 16.05 |      | 130.0 |         |
|           |   | Z | 4.19 | 65.88 | 15.49 |      | 130.0 |         |
| 10580-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle) | X | 4.42 | 66.07 | 15.73 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.57 | 66.51 | 16.08 |      | 130.0 |         |
|           |   | Z | 4.23 | 65.94 | 15.51 |      | 130.0 |         |
| 10581-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle) | X | 4.50 | 66.76 | 16.33 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.65 | 67.21 | 16.67 |      | 130.0 |         |
|           |   | Z | 4.34 | 66.76 | 16.22 |      | 130.0 |         |
| 10582-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle) | X | 4.31 | 65.77 | 15.48 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.47 | 66.23 | 15.84 |      | 130.0 |         |
|           |   | Z | 4.12 | 65.65 | 15.26 |      | 130.0 |         |
| 10583-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)       | X | 4.50 | 66.17 | 16.08 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.63 | 66.56 | 16.40 |      | 130.0 |         |
|           |   | Z | 4.35 | 66.16 | 15.93 |      | 130.0 |         |
| 10584-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)       | X | 4.52 | 66.33 | 16.14 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.66 | 66.72 | 16.46 |      | 130.0 |         |
|           |   | Z | 4.37 | 66.35 | 16.02 |      | 130.0 |         |
| 10585-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)      | X | 4.71 | 66.61 | 16.32 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.86 | 67.01 | 16.63 |      | 130.0 |         |
|           |   | Z | 4.54 | 66.60 | 16.17 |      | 130.0 |         |
| 10586-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)      | X | 4.60 | 66.74 | 16.40 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.76 | 67.17 | 16.73 |      | 130.0 |         |
|           |   | Z | 4.44 | 66.73 | 16.27 |      | 130.0 |         |
| 10587-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)      | X | 4.37 | 65.99 | 15.69 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.52 | 66.47 | 16.05 |      | 130.0 |         |
|           |   | Z | 4.19 | 65.88 | 15.49 |      | 130.0 |         |
| 10588-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)      | X | 4.42 | 66.07 | 15.73 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.57 | 66.51 | 16.08 |      | 130.0 |         |
|           |   | Z | 4.23 | 65.94 | 15.51 |      | 130.0 |         |
| 10589-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)      | X | 4.50 | 66.76 | 16.33 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.65 | 67.21 | 16.67 |      | 130.0 |         |
|           |   | Z | 4.34 | 66.76 | 16.22 |      | 130.0 |         |
| 10590-AAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)      | X | 4.31 | 65.77 | 15.48 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.47 | 66.23 | 15.84 |      | 130.0 |         |
|           |   | Z | 4.12 | 65.65 | 15.26 |      | 130.0 |         |

Certificate No: EX3-3847\_Apr18

Page 34 of 39



EX3DV4- SN:3847

April 26, 2018

|           |   |   |      |       |       |      |       |         |
|-----------|---|---|------|-------|-------|------|-------|---------|
| 10591-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle) | X | 4.65 | 66.26 | 16.20 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.78 | 66.62 | 16.49 |      | 130.0 |         |
|           |   | Z | 4.51 | 66.28 | 16.08 |      | 130.0 |         |
| 10592-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle) | X | 4.79 | 66.57 | 16.33 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.94 | 66.96 | 16.63 |      | 130.0 |         |
|           |   | Z | 4.63 | 66.56 | 16.20 |      | 130.0 |         |
| 10593-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle) | X | 4.71 | 66.46 | 16.20 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.86 | 66.87 | 16.51 |      | 130.0 |         |
|           |   | Z | 4.54 | 66.42 | 16.05 |      | 130.0 |         |
| 10594-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle) | X | 4.76 | 66.63 | 16.36 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.91 | 67.03 | 16.66 |      | 130.0 |         |
|           |   | Z | 4.60 | 66.61 | 16.22 |      | 130.0 |         |
| 10595-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle) | X | 4.73 | 66.58 | 16.25 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.88 | 66.98 | 16.56 |      | 130.0 |         |
|           |   | Z | 4.56 | 66.57 | 16.12 |      | 130.0 |         |
| 10596-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle) | X | 4.66 | 66.56 | 16.25 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.82 | 66.98 | 16.56 |      | 130.0 |         |
|           |   | Z | 4.49 | 66.52 | 16.10 |      | 130.0 |         |
| 10597-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle) | X | 4.61 | 66.45 | 16.11 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.77 | 66.89 | 16.45 |      | 130.0 |         |
|           |   | Z | 4.44 | 66.39 | 15.95 |      | 130.0 |         |
| 10598-AAB | IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle) | X | 4.59 | 66.66 | 16.37 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.75 | 67.11 | 16.70 |      | 130.0 |         |
|           |   | Z | 4.43 | 66.62 | 16.23 |      | 130.0 |         |
| 10599-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle) | X | 5.34 | 66.83 | 16.48 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.45 | 67.17 | 16.70 |      | 130.0 |         |
|           |   | Z | 5.20 | 66.82 | 16.39 |      | 130.0 |         |
| 10600-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle) | X | 5.48 | 67.28 | 16.68 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.58 | 67.55 | 16.86 |      | 130.0 |         |
|           |   | Z | 5.31 | 67.19 | 16.55 |      | 130.0 |         |
| 10601-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle) | X | 5.36 | 67.01 | 16.55 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.47 | 67.32 | 16.77 |      | 130.0 |         |
|           |   | Z | 5.21 | 66.95 | 16.45 |      | 130.0 |         |
| 10602-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle) | X | 5.48 | 67.14 | 16.54 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.56 | 67.34 | 16.70 |      | 130.0 |         |
|           |   | Z | 5.32 | 67.06 | 16.42 |      | 130.0 |         |
| 10603-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle) | X | 5.54 | 67.39 | 16.80 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.65 | 67.65 | 16.98 |      | 130.0 |         |
|           |   | Z | 5.37 | 67.31 | 16.69 |      | 130.0 |         |
| 10604-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle) | X | 5.41 | 67.02 | 16.60 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.46 | 67.14 | 16.71 |      | 130.0 |         |
|           |   | Z | 5.27 | 66.97 | 16.49 |      | 130.0 |         |
| 10605-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle) | X | 5.47 | 67.20 | 16.69 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.56 | 67.45 | 16.87 |      | 130.0 |         |
|           |   | Z | 5.29 | 67.05 | 16.52 |      | 130.0 |         |
| 10606-AAB | IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle) | X | 5.19 | 66.44 | 16.16 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.32 | 66.83 | 16.42 |      | 130.0 |         |
|           |   | Z | 5.08 | 66.47 | 16.09 |      | 130.0 |         |

Certificate No: EX3-3847\_Apr18

Page 35 of 39



EX3DV4- SN:3847

April 26, 2018

|           |   |   |      |       |       |      |       |         |
|-----------|---|---|------|-------|-------|------|-------|---------|
| 10607-AAB | IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle) | X | 4.49 | 65.54 | 15.80 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.62 | 65.94 | 16.12 |      | 130.0 |         |
|           |   | Z | 4.35 | 65.57 | 15.69 |      | 130.0 |         |
| 10608-AAB | IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle) | X | 4.65 | 65.91 | 15.96 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.81 | 66.35 | 16.29 |      | 130.0 |         |
|           |   | Z | 4.48 | 65.89 | 15.84 |      | 130.0 |         |
| 10609-AAB | IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle) | X | 4.54 | 65.74 | 15.79 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.70 | 66.20 | 16.13 |      | 130.0 |         |
|           |   | Z | 4.38 | 65.70 | 15.64 |      | 130.0 |         |
| 10610-AAB | IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle) | X | 4.59 | 65.90 | 15.95 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.75 | 66.36 | 16.29 |      | 130.0 |         |
|           |   | Z | 4.43 | 65.88 | 15.82 |      | 130.0 |         |
| 10611-AAB | IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle) | X | 4.51 | 65.70 | 15.80 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.66 | 66.16 | 16.14 |      | 130.0 |         |
|           |   | Z | 4.34 | 65.67 | 15.66 |      | 130.0 |         |
| 10612-AAB | IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle) | X | 4.51 | 65.84 | 15.83 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.67 | 66.32 | 16.18 |      | 130.0 |         |
|           |   | Z | 4.33 | 65.77 | 15.68 |      | 130.0 |         |
| 10613-AAB | IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle) | X | 4.51 | 65.70 | 15.71 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.68 | 66.20 | 16.07 |      | 130.0 |         |
|           |   | Z | 4.32 | 65.60 | 15.53 |      | 130.0 |         |
| 10614-AAB | IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle) | X | 4.46 | 65.88 | 15.93 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.62 | 66.38 | 16.29 |      | 130.0 |         |
|           |   | Z | 4.29 | 65.83 | 15.79 |      | 130.0 |         |
| 10615-AAB | IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle) | X | 4.51 | 65.55 | 15.58 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 4.67 | 66.00 | 15.92 |      | 130.0 |         |
|           |   | Z | 4.33 | 65.49 | 15.41 |      | 130.0 |         |
| 10616-AAB | IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle) | X | 5.15 | 66.03 | 16.05 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.27 | 66.43 | 16.32 |      | 130.0 |         |
|           |   | Z | 5.00 | 65.97 | 15.95 |      | 130.0 |         |
| 10617-AAB | IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle) | X | 5.22 | 66.24 | 16.14 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.34 | 66.59 | 16.37 |      | 130.0 |         |
|           |   | Z | 5.04 | 66.10 | 15.99 |      | 130.0 |         |
| 10618-AAB | IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle) | X | 5.10 | 66.23 | 16.14 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.22 | 66.60 | 16.39 |      | 130.0 |         |
|           |   | Z | 4.95 | 66.15 | 16.02 |      | 130.0 |         |
| 10619-AAB | IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle) | X | 5.11 | 66.02 | 15.97 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.24 | 66.42 | 16.23 |      | 130.0 |         |
|           |   | Z | 4.97 | 65.97 | 15.87 |      | 130.0 |         |
| 10620-AAB | IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle) | X | 5.20 | 66.06 | 16.05 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.33 | 66.46 | 16.31 |      | 130.0 |         |
|           |   | Z | 5.04 | 65.98 | 15.93 |      | 130.0 |         |
| 10621-AAB | IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle) | X | 5.21 | 66.21 | 16.24 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.33 | 66.58 | 16.48 |      | 130.0 |         |
|           |   | Z | 5.05 | 66.10 | 16.11 |      | 130.0 |         |
| 10622-AAB | IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle) | X | 5.22 | 66.37 | 16.31 | 0.46 | 130.0 | ± 9.6 % |
|           |   | Y | 5.34 | 66.74 | 16.55 |      | 130.0 |         |
|           |   | Z | 5.04 | 66.18 | 16.15 |      | 130.0 |         |

Certificate No: EX3-3847\_Apr18

Page 36 of 39





EX3DV4- SN:3847

April 26, 2018

|           |  |   |      |       |       |      |       |         |
|-----------|--|---|------|-------|-------|------|-------|---------|
| 10623-AAB | IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)  | X | 5.10 | 65.88 | 15.93 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.22 | 66.28 | 16.20 |      | 130.0 |         |
|           |  | Z | 4.93 | 65.72 | 15.77 |      | 130.0 |         |
| 10624-AAB | IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)  | X | 5.29 | 66.10 | 16.11 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.41 | 66.47 | 16.36 |      | 130.0 |         |
|           |  | Z | 5.13 | 66.01 | 15.99 |      | 130.0 |         |
| 10625-AAB | IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)  | X | 5.57 | 66.83 | 16.54 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.77 | 67.42 | 16.88 |      | 130.0 |         |
|           |  | Z | 5.22 | 66.17 | 16.14 |      | 130.0 |         |
| 10626-AAB | IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)  | X | 5.46 | 66.12 | 16.04 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.57 | 66.49 | 16.27 |      | 130.0 |         |
|           |  | Z | 5.33 | 66.02 | 15.93 |      | 130.0 |         |
| 10627-AAB | IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)  | X | 5.71 | 66.74 | 16.32 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.80 | 67.03 | 16.50 |      | 130.0 |         |
|           |  | Z | 5.57 | 66.65 | 16.21 |      | 130.0 |         |
| 10628-AAB | IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)  | X | 5.48 | 66.16 | 15.96 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.60 | 66.59 | 16.22 |      | 130.0 |         |
|           |  | Z | 5.33 | 66.00 | 15.81 |      | 130.0 |         |
| 10629-AAB | IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)  | X | 5.56 | 66.26 | 16.00 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.68 | 66.64 | 16.24 |      | 130.0 |         |
|           |  | Z | 5.43 | 66.19 | 15.91 |      | 130.0 |         |
| 10630-AAB | IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)  | X | 5.96 | 67.65 | 16.70 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 6.09 | 68.07 | 16.95 |      | 130.0 |         |
|           |  | Z | 5.68 | 67.14 | 16.38 |      | 130.0 |         |
| 10631-AAB | IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)  | X | 5.85 | 67.41 | 16.77 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 6.00 | 67.90 | 17.05 |      | 130.0 |         |
|           |  | Z | 5.64 | 67.15 | 16.59 |      | 130.0 |         |
| 10632-AAB | IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)  | X | 5.68 | 66.81 | 16.49 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.77 | 67.09 | 16.67 |      | 130.0 |         |
|           |  | Z | 5.57 | 66.83 | 16.45 |      | 130.0 |         |
| 10633-AAB | IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)  | X | 5.54 | 66.34 | 16.08 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.66 | 66.75 | 16.33 |      | 130.0 |         |
|           |  | Z | 5.36 | 66.11 | 15.91 |      | 130.0 |         |
| 10634-AAB | IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)  | X | 5.52 | 66.35 | 16.14 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.65 | 66.78 | 16.40 |      | 130.0 |         |
|           |  | Z | 5.38 | 66.27 | 16.04 |      | 130.0 |         |
| 10635-AAB | IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)  | X | 5.40 | 65.69 | 15.55 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.53 | 66.13 | 15.82 |      | 130.0 |         |
|           |  | Z | 5.24 | 65.52 | 15.38 |      | 130.0 |         |
| 10636-AAC | IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle) | X | 5.89 | 66.51 | 16.15 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 5.98 | 66.86 | 16.36 |      | 130.0 |         |
|           |  | Z | 5.77 | 66.40 | 16.04 |      | 130.0 |         |
| 10637-AAC | IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle) | X | 6.05 | 66.90 | 16.33 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 6.13 | 67.23 | 16.53 |      | 130.0 |         |
|           |  | Z | 5.89 | 66.72 | 16.18 |      | 130.0 |         |
| 10638-AAC | IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle) | X | 6.04 | 66.86 | 16.29 | 0.46 | 130.0 | ± 9.6 % |
|           |  | Y | 6.13 | 67.21 | 16.49 |      | 130.0 |         |
|           |  | Z | 5.91 | 66.76 | 16.18 |      | 130.0 |         |



EX3DV4- SN:3847

April 26, 2018

|           |  |   |        |        |       |       |       |         |
|-----------|--|---|--------|--------|-------|-------|-------|---------|
| 10639-AAC | IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)     | X | 6.01   | 66.78  | 16.29 | 0.46  | 130.0 | ± 9.6 % |
|           |  | Y | 6.11   | 67.16  | 16.52 |       | 130.0 |         |
|           |  | Z | 5.87   | 66.64  | 16.16 |       | 130.0 |         |
| 10640-AAC | IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)     | X | 6.01   | 66.78  | 16.23 | 0.46  | 130.0 | ± 9.6 % |
|           |  | Y | 6.12   | 67.18  | 16.47 |       | 130.0 |         |
|           |  | Z | 5.83   | 66.54  | 16.05 |       | 130.0 |         |
| 10641-AAC | IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)     | X | 6.08   | 66.77  | 16.25 | 0.46  | 130.0 | ± 9.6 % |
|           |  | Y | 6.16   | 67.08  | 16.43 |       | 130.0 |         |
|           |  | Z | 5.93   | 66.63  | 16.12 |       | 130.0 |         |
| 10642-AAC | IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)     | X | 6.10   | 66.96  | 16.51 | 0.46  | 130.0 | ± 9.6 % |
|           |  | Y | 6.20   | 67.33  | 16.72 |       | 130.0 |         |
|           |  | Z | 5.95   | 66.83  | 16.39 |       | 130.0 |         |
| 10643-AAC | IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)     | X | 5.95   | 66.67  | 16.26 | 0.46  | 130.0 | ± 9.6 % |
|           |  | Y | 6.04   | 67.02  | 16.47 |       | 130.0 |         |
|           |  | Z | 5.80   | 66.51  | 16.11 |       | 130.0 |         |
| 10644-AAC | IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)     | X | 6.06   | 67.02  | 16.46 | 0.46  | 130.0 | ± 9.6 % |
|           |  | Y | 6.20   | 67.51  | 16.74 |       | 130.0 |         |
|           |  | Z | 5.86   | 66.69  | 16.23 |       | 130.0 |         |
| 10645-AAC | IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)     | X | 6.22   | 67.15  | 16.49 | 0.46  | 130.0 | ± 9.6 % |
|           |  | Y | 6.53   | 68.09  | 16.99 |       | 130.0 |         |
|           |  | Z | 6.01   | 66.82  | 16.26 |       | 130.0 |         |
| 10646-AAD | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)  | X | 12.46  | 102.82 | 35.86 | 9.30  | 60.0  | ± 9.6 % |
|           |  | Y | 25.38  | 119.99 | 41.31 |       | 60.0  |         |
|           |  | Z | 6.60   | 88.90  | 30.62 |       | 60.0  |         |
| 10647-AAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7) | X | 10.85  | 100.16 | 35.12 | 9.30  | 60.0  | ± 9.6 % |
|           |  | Y | 20.81  | 115.94 | 40.28 |       | 60.0  |         |
|           |  | Z | 5.89   | 86.80  | 29.96 |       | 60.0  |         |
| 10648-AAA | CDMA2000 (1x Advanced)                                 | X | 0.51   | 60.75  | 7.97  | 0.00  | 150.0 | ± 9.6 % |
|           |  | Y | 0.66   | 63.18  | 10.50 |       | 150.0 |         |
|           |  | Z | 0.41   | 60.00  | 6.58  |       | 150.0 |         |
| 10652-AAB | LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)         | X | 3.30   | 65.73  | 15.83 | 2.23  | 80.0  | ± 9.6 % |
|           |  | Y | 3.62   | 67.09  | 16.80 |       | 80.0  |         |
|           |  | Z | 3.01   | 65.04  | 15.12 |       | 80.0  |         |
| 10653-AAB | LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)        | X | 3.88   | 65.34  | 16.17 | 2.23  | 80.0  | ± 9.6 % |
|           |  | Y | 4.12   | 66.32  | 16.85 |       | 80.0  |         |
|           |  | Z | 3.63   | 64.83  | 15.69 |       | 80.0  |         |
| 10654-AAB | LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)        | X | 3.88   | 65.02  | 16.21 | 2.23  | 80.0  | ± 9.6 % |
|           |  | Y | 4.09   | 65.94  | 16.83 |       | 80.0  |         |
|           |  | Z | 3.66   | 64.54  | 15.77 |       | 80.0  |         |
| 10655-AAB | LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)        | X | 3.95   | 65.00  | 16.26 | 2.23  | 80.0  | ± 9.6 % |
|           |  | Y | 4.15   | 65.93  | 16.86 |       | 80.0  |         |
|           |  | Z | 3.74   | 64.49  | 15.83 |       | 80.0  |         |
| 10658-AAA | Pulse Waveform (200Hz, 10%)                            | X | 100.00 | 110.04 | 25.52 | 10.00 | 50.0  | ± 9.6 % |
|           |  | Y | 100.00 | 112.50 | 26.65 |       | 50.0  |         |
|           |  | Z | 4.52   | 71.85  | 13.49 |       | 50.0  |         |
| 10659-AAA | Pulse Waveform (200Hz, 20%)                            | X | 100.00 | 108.16 | 23.56 | 6.99  | 60.0  | ± 9.6 % |
|           |  | Y | 100.00 | 112.26 | 25.56 |       | 60.0  |         |
|           |  | Z | 3.99   | 73.17  | 12.80 |       | 60.0  |         |

Certificate No: EX3-3847\_Apr18

Page 38 of 39



EX3DV4- SN:3847

April 26, 2018

|           |                             |   |        |        |       |      |       |         |
|-----------|-----------------------------|---|--------|--------|-------|------|-------|---------|
| 10660-AAA | Pulse Waveform (200Hz, 40%) | X | 100.00 | 105.70 | 21.19 | 3.98 | 80.0  | ± 9.6 % |
|           |                             | Y | 100.00 | 114.35 | 25.21 |      | 80.0  |         |
|           |                             | Z | 1.97   | 69.76  | 10.09 |      | 80.0  |         |
| 10661-AAA | Pulse Waveform (200Hz, 60%) | X | 100.00 | 100.43 | 17.89 | 2.22 | 100.0 | ± 9.6 % |
|           |                             | Y | 100.00 | 117.83 | 25.42 |      | 100.0 |         |
|           |                             | Z | 0.29   | 60.00  | 4.69  |      | 100.0 |         |
| 10662-AAA | Pulse Waveform (200Hz, 80%) | X | 0.17   | 60.00  | 3.90  | 0.97 | 120.0 | ± 9.6 % |
|           |                             | Y | 100.00 | 119.81 | 24.45 |      | 120.0 |         |
|           |                             | Z | 12.34  | 60.39  | 1.42  |      | 120.0 |         |

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



MR-008\_18-124



In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY



中国认可  
国际互认  
校准  
CALIBRATION  
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

Client : **ATL**

Certificate No: **Z18-60043**

## CALIBRATION CERTIFICATE

Object: **DAE4 - SN: 541**

Calibration Procedure(s): **FF-Z11-002-01**  
Calibration Procedure for the Data Acquisition Electronics (DAEx)

Calibration date: **March 22, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards      | ID #    | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
|------------------------|---------|--|-----------------------|
| Process Calibrator 753 | 1971018 | 27-Jun-17 (CTTL, No.J17X05859)           | June-18               |

|                | Name        | Function           | Signature |
|----------------|-------------|--------------------|-----------|
| Calibrated by: | Yu Zongying | SAR Test Engineer  |           |
| Reviewed by:   | Lin Hao     | SAR Test Engineer  |           |
| Approved by:   | Qi Dianyuan | SAR Project Leader |           |

Issued: March 23, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z18-60043

Page 1 of 3





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com Http://www.chinattl.cn

#### **Glossary:**

DAE data acquisition electronics  
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

#### **Methods Applied and Interpretation of Parameters:**

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: cttl@chinattl.com Http://www.chinattl.cn

**DC Voltage Measurement**

A/D - Converter Resolution nominal  
 High Range: 1LSB = 6.1μV , full range = -100...+300 mV  
 Low Range: 1LSB = 61nV , full range = -1.....+3mV  
 DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X                     | Y                     | Z                     |
|---------------------|-----------------------|-----------------------|-----------------------|
| High Range          | 404.524 ± 0.15% (k=2) | 404.384 ± 0.15% (k=2) | 404.149 ± 0.15% (k=2) |
| Low Range           | 3.96849 ± 0.7% (k=2)  | 3.93466 ± 0.7% (k=2)  | 3.97493 ± 0.7% (k=2)  |

**Connector Angle**

|   |            |
|---|------------|
| Connector Angle to be used in DASY system | 289° ± 1 ° |
|---|------------|