

# TEST REPORT

**Product Name** : Bluetooth headset  
**Brand Mark** : N/A  
**Model No.** : BH22DT10A  
**FCC ID** : RDR-BH22DT10AL  
**Report Number** : BLA-EMC-202206-A13103  
**Date of Sample Receipt** : 2022/7/4  
**Date of Test** : 2022/7/4 to 2022/7/16  
**Date of Issue** : 2022/7/16  
**Test Standard** : 47 CFR Part 15, Part1.1307  
47 CFR Part 15, Part2.1093  
KDB447498D04 General RF Exposure  
Guidance v01  
**Test Result** : Pass

Prepared for:

**Dongguan Hele Electronics Co.,Ltd**  
**No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province**  
**China**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,**  
**Shenzhen, Guangdong Province, China**  
**TEL: +86-755-23059481**

Compiled by: *Charlie*

Review by: *Sueels*

Approved by: *Blue Zhong*

Date: 2022/7/16



**REPORT REVISE RECORD**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
00	2022/7/16	Original

BlueAsia

## TABLE OF CONTENTS

<b>1 TEST SUMMARY</b> .....	<b>4</b>
<b>2 GENERAL INFORMATION</b> .....	<b>5</b>
<b>3 GENERAL DESCRIPTION OF E.U.T.</b> .....	<b>5</b>
<b>4 LABORATORY LOCATION</b> .....	<b>6</b>
<b>5 RF EXPOSURE COMPLIANCE REQUIREMENT</b> .....	<b>7</b>
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	7
<i>Standard Requirement</i> .....	7
<i>Limits</i> .....	7

BlueAsia

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	PASS

BlueAsia

## 2 GENERAL INFORMATION

<b>Applicant</b>	Dongguan Hele Electronics Co.,Ltd
<b>Address</b>	No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province China
<b>Manufacturer</b>	Dongguan Hele Electronics Co.,Ltd
<b>Address</b>	No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province China
<b>Factory</b>	Dongguan Hele Electronics Co.,Ltd
<b>Address</b>	No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province China
<b>Product Name</b>	Bluetooth headset
<b>Test Model No.</b>	BH22DT10A

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	V5.3
<b>Software Version</b>	V5.3
<b>Operation Frequency:</b>	2402MHz-2480MHz
<b>Modulation Type:</b>	GFSK, pi/4DQPSK,
<b>Channel Spacing:</b>	1MHz
<b>Number of Channels:</b>	79
<b>Antenna Type:</b>	Internal Antenna
<b>Antenna Gain:</b>	1.22dBi

#### 4 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

BlueAsia

## 5 RF EXPOSURE COMPLIANCE REQUIREMENT

### 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT

## Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

## Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
300	39	65	88	110	129	148	166	184	201	217	
450	22	44	67	89	112	135	158	180	203	226	
835	9	25	44	66	90	116	145	175	207	240	
1900	3	12	26	44	66	92	122	157	195	236	
2450	3	10	22	38	59	83	111	143	179	219	
3600	2	8	18	32	49	71	96	125	158	195	
5800	1	6	14	25	40	58	80	106	136	169	

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$EIRP = p_t \times g_t = (EXd)^2/30$$

where:

$p_t$  = transmitter output power in watts,

$g_t$  = numeric gain of the transmitting antenna (unitless),

$E$  = electric field strength in V/m, ---  $10((dBuV/m)/20)/10^6$

$d$  = measurement distance in meters (m)---3m

$$S_{opt} = (EXd)^2/30 \times g_t$$

$$\text{Ant gain} = 1.22 \text{ dBi}$$

$$\text{Max Output power} = -3.174 \text{ dBm @ } 2441 \text{ MHz}$$

$$\text{ERP} = -3.174 \text{ dBm} + 1.22 \text{ dBi} - 2.15 = -4.104 \text{ dBm}$$

So

ERP is worse case

$$10^{-0.4104} = 0.388 \text{ mW} < 3 \text{ mW}$$

Then SAR evaluation is not required

**----END OF REPORT----**

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.



**----END OF REPORT----**

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia