


Radiated Emission Measurement




Site	Polarization: Horizontal	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: TWS Bluetooth earphones	Distance: 3m	
M/N: In2024		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2310.000	53.79	-14.01	39.78	74.00	-34.22	peak		
2	*	2390.000	54.26	-13.62	40.64	74.00	-33.36	peak		



Highest channel

Radiated Emission Measurement




Site	Polarization: <i>Horizontal</i>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: TWS Bluetooth earphones	Distance: 3m	
M/N: In2024		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		2483.500	52.73	-13.11	39.62	74.00	-34.38	peak	
2	*	2500.000	53.08	-13.02	40.06	74.00	-33.94	peak	



Radiated Emission Measurement



Site	Polarization: Vertical	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: TWS Bluetooth earphones	Distance: 3m	
M/N: In2024		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2483.500	54.98	-13.50	41.48	74.00	-32.52	peak		
2		2500.000	54.44	-13.42	41.02	74.00	-32.98	peak		




CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25°C
Humidity	60%

LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


BlueAsia

DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX_non-Hop mode
Test Mode (Final Test)	TX_non-Hop mode
Tester	Eason
Temperature	25°C
Humidity	60%

LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

BLOCK DIAGRAM OF TEST SETUP


TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX_non-Hop mode
Test Mode (Final Test)	TX_non-Hop mode
Tester	Eason
Temperature	25°C
Humidity	60%

LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX_non-Hop mode
Test Mode (Final Test)	TX_non-Hop mode
Tester	Eason
Temperature	25°C
Humidity	60%

LIMITS

Limit:	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W
---------------	--

BLOCK DIAGRAM OF TEST SETUP




TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25°C
Humidity	60%

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25°C
Humidity	60%

LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

10 APPENDIX

Appendix1




10.1 APPENDIX: 20DBEMISSION BANDWIDTH

Test Result


TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	1.107	2401.475	2402.582	---	PASS
		2441	1.101	2440.478	2441.579	---	PASS
		2480	1.104	2479.475	2480.579	---	PASS
2DH1	Ant1	2402	1.365	2401.340	2402.705	---	PASS
		2441	1.362	2440.340	2441.702	---	PASS
		2480	1.362	2479.340	2480.702	---	PASS
3DH1	Ant1	2402	1.335	2401.367	2402.702	---	PASS
		2441	1.332	2440.370	2441.702	---	PASS
		2480	1.329	2479.370	2480.699	---	PASS

Test Graphs







3DH1_Ant1_2402



3DH1_Ant1_2441



3DH1_Ant1_2480







10.2 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER
Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	6.03	<=20.97	PASS
		2441	5.32	<=20.97	PASS
		2480	4.71	<=20.97	PASS
2DH1	Ant1	2402	7.98	<=20.97	PASS
		2441	7.43	<=20.97	PASS
		2480	6.76	<=20.97	PASS
3DH1	Ant1	2402	8.55	<=20.97	PASS
		2441	7.98	<=20.97	PASS
		2480	7.48	<=20.97	PASS


Test Graphs









3DH1_Ant1_2402



3DH1_Ant1_2441



3DH1_Ant1_2480



10.3 APPENDIX: CARRIER FREQUENCY SEPARATION

Test Result

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	0.998	≥ 0.738	PASS
2DH1	Ant1	Hop	1.334	≥ 0.910	PASS
3DH1	Ant1	Hop	1.332	≥ 0.890	PASS

Test Graphs





10.4 APPENDIX: TIME OF OCCUPANCY

Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.39	330	0.129	<=0.4	PASS
DH3	Ant1	Hop	1.65	160	0.264	<=0.4	PASS
DH5	Ant1	Hop	2.89	120	0.347	<=0.4	PASS

Test Graphs





10.5 APPENDIXF: NUMBER OF HOPPING CHANNELS**Test Result**

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	≥ 15	PASS
2DH1	Ant1	Hop	79	≥ 15	PASS
3DH1	Ant1	Hop	79	≥ 15	PASS

BlueAsia

Test Graphs




10.6 APPENDIX: BAND EDGE MEASUREMENTS

Test Result


TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH1	Ant1	Low	2402	5.91	-55.18	<=-14.09	PASS
		High	2480	4.73	-55.11	<=-15.27	PASS
		Low	Hop_2402	5.65	-54.88	-14.35	PASS
		High	Hop_2480	4.65	-55.57	-15.35	PASS
2DH1	Ant1	Low	2402	6.78	-53.8	<=-13.22	PASS
		High	2480	5.66	-54.6	<=-14.35	PASS
		Low	Hop_2402	5.77	-54.86	-14.23	PASS
		High	Hop_2480	5.73	-54.94	-14.27	PASS
3DH1	Ant1	Low	2402	6.82	-54.69	<=-13.18	PASS
		High	2480	5.71	-55.36	<=-14.29	PASS
		Low	Hop_2402	6.02	-54.21	-13.98	PASS
		High	Hop_2480	5.75	-55.09	-14.25	PASS

Test Graphs









2DH1_Ant1_Low_2402






2DH1_Ant1_High_2402



2DH1_Ant1_Low_Hop_2402





10.7 APPENDIX: CONDUCTED SPURIOUS EMISSION
Test Result

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH1	Ant1	2402	Reference	5.90	5.90	---	PASS
			30~1000	30~1000	-67.648	<=-14.103	PASS
			1000~26500	1000~26500	-35.105	<=-14.103	PASS
		2441	Reference	5.21	5.21	---	PASS
			30~1000	30~1000	-67.795	<=-14.789	PASS
			1000~26500	1000~26500	-37.668	<=-14.789	PASS
		2480	Reference	4.71	4.71	---	PASS
			30~1000	30~1000	-68.536	<=-15.286	PASS
			1000~26500	1000~26500	-38.182	<=-15.286	PASS
2DH1	Ant1	2402	Reference	6.76	6.76	---	PASS
			30~1000	30~1000	-68.049	<=-13.239	PASS
			1000~26500	1000~26500	-33.349	<=-13.239	PASS
		2441	Reference	6.16	6.16	---	PASS
			30~1000	30~1000	-67.892	<=-13.845	PASS
			1000~26500	1000~26500	-38.046	<=-13.845	PASS
		2480	Reference	5.65	5.65	---	PASS
			30~1000	30~1000	-67.48	<=-14.346	PASS
			1000~26500	1000~26500	-38.236	<=-14.346	PASS
3DH1	Ant1	2402	Reference	6.73	6.73	---	PASS
			30~1000	30~1000	-67.914	<=-13.266	PASS
			1000~26500	1000~26500	-37.439	<=-13.266	PASS
		2441	Reference	6.22	6.22	---	PASS
			30~1000	30~1000	-68.198	<=-13.784	PASS
			1000~26500	1000~26500	-35.351	<=-13.784	PASS
		2480	Reference	5.73	5.73	---	PASS
			30~1000	30~1000	-68.42	<=-14.269	PASS
			1000~26500	1000~26500	-39.009	<=-14.269	PASS

Test Graphs

