

# TEST REPORT

**Product Name** : Bluetooth Headset  
**Brand Mark** : QCY  
**Model No.** : In2026, In2026R  
**Report Number** : BLA-EMC-202009-A1501  
**FCC ID** : RDR-IN2026R  
**Date of Sample Receipt** : 2020/9/2  
**Date of Test** : 2020/9/2 to 2020/9/11  
**Date of Issue** : 2020/9/15  
**Test Standard** : 47 CFR Part 15, Subpart C 15.247  
**Test Result** : Pass

Prepared for:

**Dongguan Hele Electronics Co.,Ltd**  
Dalingya Industrial Zone, Daojiao Town, Dongguan City, Guangdong, China

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
**IOT Test Centre of BlueAsia**  
**No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China**  
**TEL: +86-755-23059481**

Compiled by:

*Jozu.*

Review by:

*Sweet. Liang*

Approved by:

*Jimen Li*

Date:

2020/9/15



**REPORT REVISE RECORD**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
00	2020/9/15	Original

BlueAsia

## TABLE OF CONTENTS

<b>1</b>	<b>TEST SUMMARY .....</b>	<b>6</b>
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>7</b>
<b>3</b>	<b>GENERAL DESCRIPTION OF E.U.T. ....</b>	<b>7</b>
<b>4</b>	<b>TEST ENVIRONMENT .....</b>	<b>8</b>
<b>5</b>	<b>TEST MODE .....</b>	<b>8</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>7</b>	<b>DESCRIPTION OF SUPPORT UNIT.....</b>	<b>9</b>
<b>8</b>	<b>LABORATORY LOCATION.....</b>	<b>9</b>
<b>9</b>	<b>TEST INSTRUMENTS LIST .....</b>	<b>10</b>
	<b>ANTENNA REQUIREMENT.....</b>	<b>14</b>
	CONCLUSION.....	14
	<b>RADIATED SPURIOUS EMISSIONS .....</b>	<b>15</b>
	LIMITS.....	15
	BLOCK DIAGRAM OF TEST SETUP.....	16
	PROCEDURE .....	16
	TEST DATA .....	18
	<b>RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....</b>	<b>26</b>
	LIMITS.....	26
	BLOCK DIAGRAM OF TEST SETUP.....	27
	PROCEDURE .....	27
	TEST DATA .....	29
	<b>CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>33</b>
	LIMITS.....	33
	BLOCK DIAGRAM OF TEST SETUP.....	33
	TEST DATA .....	34
	<b>CONDUCTED BAND EDGES MEASUREMENT .....</b>	<b>35</b>
	LIMITS.....	35
	BLOCK DIAGRAM OF TEST SETUP.....	35
	TEST DATA .....	36

<b>DWELL TIME.....</b>	<b>37</b>
LIMITS.....	37
BLOCK DIAGRAM OF TEST SETUP.....	37
TEST DATA.....	38
<b>HOPPING CHANNEL NUMBER.....</b>	<b>39</b>
LIMITS.....	39
BLOCK DIAGRAM OF TEST SETUP.....	39
TEST DATA.....	39
<b>CARRIER FREQUENCIES SEPARATION.....</b>	<b>40</b>
LIMITS.....	40
BLOCK DIAGRAM OF TEST SETUP.....	40
TEST DATA.....	40
<b>20DB BANDWIDTH.....</b>	<b>41</b>
BLOCK DIAGRAM OF TEST SETUP.....	41
TEST DATA.....	41
<b>CONDUCTED PEAK OUTPUT POWER.....</b>	<b>42</b>
LIMITS.....	42
BLOCK DIAGRAM OF TEST SETUP.....	42
TEST DATA.....	43
<b>CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....</b>	<b>44</b>
LIMITS.....	44
BLOCK DIAGRAM OF TEST SETUP.....	44
PROCEDURE.....	44
TEST DATA.....	46
<b>10 APPENDIX.....</b>	<b>48</b>
10.1 APPENDIX: 20DBEMISSION BANDWIDTH.....	48
<i>Test Result</i> .....	48
<i>Test Graphs</i> .....	49
10.2 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER.....	51
<i>Test Result</i> .....	51
<i>Test Graphs</i> .....	52
10.3 APPENDIX: CARRIER FREQUENCY SEPARATION.....	55
<i>Test Result</i> .....	55

<i>Test Graphs</i> .....	56
10.4    APPENDIX: TIME OF OCCUPANCY.....	57
<i>Test Result</i> .....	57
<i>Test Graphs</i> .....	58
10.5    APPENDIX: NUMBER OF HOPPING CHANNELS.....	60
<i>Test Result</i> .....	60
<i>Test Graphs</i> .....	61
10.6    APPENDIX: BAND EDGE MEASUREMENTS.....	62
<i>Test Result</i> .....	62
<i>Test Graphs</i> .....	63
10.7    APPENDIX: CONDUCTED SPURIOUS EMISSION.....	66
<i>Test Result</i> .....	66
<i>Test Graphs</i> .....	67
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....</b>	<b>73</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT.....</b>	<b>75</b>

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	Dongguan Hele Electronics Co.,Ltd
<b>Address</b>	Dalingya Industrial Zone,Daojiao Town,Dongguan City,Guangdong,China
<b>Manufacturer</b>	Dongguan Hele Electronics Co.,Ltd
<b>Address</b>	Dalingya Industrial Zone,Daojiao Town,Dongguan City,Guangdong,China
<b>Factory</b>	Dongguan Hele Electronics Co.,Ltd
<b>Address</b>	Dalingya Industrial Zone,Daojiao Town,Dongguan City,Guangdong,China
<b>Product Name</b>	Bluetooth Headset
<b>Test Model No.</b>	In2026

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	V5.0
<b>Software Version</b>	V5.0
<b>Operation Frequency:</b>	2402MHz-2480MHz
<b>Modulation Type:</b>	GFSK, $\pi/4$ DQPSK
<b>Channel Spacing:</b>	1MHz
<b>Number of Channels:</b>	79
<b>Antenna Type:</b>	Internal Antenna
<b>Antenna Gain:</b>	1.6dBi(Provided by the customer)

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.7V

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE )
Remark: Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned only worse case is reported.	

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission	±4.34dB
Radiated Emission	±4.24dB
Radiated Emission	±4.68dB
AC Power Line Conducted Emission	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Radiated Emission (1GHz ~ 18GHz)	±4.44 dB



## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	HASEE	K610D	N/A	N/A
AC Adapter	UGREEN	CD112	N/A	N/A

## 8 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co., Ltd.  
IOT Test Centre of BlueAsia  
No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen,China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673  
Tests were sub-contracted:  
Radiation test is conducted by Global United Technology Services Co., Ltd.  
No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, sBaoan District, Shenzhen, Guangdong, China 518102  
FCC —Registration No.: 381383  
Job No.: GTS202009000027

## 9 TEST INSTRUMENTS LIST

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

Test Equipment Of Conducted Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

**Test Equipment Of Conducted Band Edges Measurement**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

**Test Equipment Of Dwell Time**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

**Test Equipment Of Hopping Channel Number**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

**Test Equipment Of Carrier Frequencies Separation**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021

Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

**Test Equipment Of 20dB Bandwidth**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

**Test Equipment Of Conducted Peak Output Power**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

**Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	6/10/2018	6/9/2021
Receiver	R&S	ESPI3	101082	4/20/2020	4/19/2021
LISN	R&S	ENV216	3560.6550.15	7/1/2020	6/30/2021
LISN	AT	AT166-2	AKK1806000003	12/17/2019	12/16/2020

EMI software	EZ	EZ-EMC	N/A	N/A	N/A
--------------	----	--------	-----	-----	-----

BlueAsia

### ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

### CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.6dBi.



### RADIATED SPURIOUS EMISSIONS

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX mode (SE) above 1G;TX mode (SE) below 1G
<b>Test Mode (Final Test)</b>	TX mode (SE) above 1G;TX mode (SE) below 1G
<b>Tester</b>	Jozu
<b>Temperature</b>	25℃
<b>Humidity</b>	60%


### LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



### BLOCK DIAGRAM OF TEST SETUP



### PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.



- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

**TEST DATA**

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]

Power:AC120V/60Hz




Condition : FCC PART15 CLASS B 3m HORIZONTAL  
Job.No : GTS202009000027  
Test Mode : TX 2402MHz  
Test Engineer: Hans  
Remark :

	Freq	ReadLevel	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	34.760	37.67	11.30	35.34	0.61	14.24	40.00	-25.76	QP
2	41.277	38.03	12.21	35.74	0.68	15.18	40.00	-24.82	QP
3	54.835	36.77	11.80	36.25	0.82	13.14	40.00	-26.86	QP
4	96.099	34.97	11.65	36.69	1.16	11.09	43.50	-32.41	QP
5	167.824	37.07	8.46	37.18	1.67	10.02	43.50	-33.48	QP
6	365.539	33.43	14.78	37.49	2.69	13.41	46.00	-32.59	QP

**Test Result: Pass**

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]

Power:AC120V/60Hz



Condition : FCC PART15 CLASS B 3m VERTICAL  
Job.No : GTS202009000027  
Test Mode : TX 2402MHz  
Test Engineer: Hans  
Remark :


	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	36.381	36.30	11.58	35.45	0.62	13.05	40.00	-26.95	QP
2	45.058	36.34	12.25	35.94	0.72	13.37	40.00	-26.63	QP
3	52.025	36.08	12.07	36.21	0.79	12.73	40.00	-27.27	QP
4	100.934	33.28	12.10	36.73	1.20	9.85	43.50	-33.65	QP
5	283.979	33.00	13.16	37.41	2.29	11.04	46.00	-34.96	QP
6	787.851	32.80	21.21	37.62	4.41	20.80	46.00	-25.20	QP

**Test Result: Pass**

[TestMode: Pi/4QPSK]


Remark: During the test, pre-scan the GFSK, Pi/4QPSK modulation, and found the Pi/4QPSK modulation which it is worse case.

Test channel:lowest



Condition : FCC PART 15 (PK) 3m HORIZONTAL  
Job No. : GTS202009000027  
Test Mode : TX 2402MHz  
Test Engineer: Hans  
Remark :

	Read	Antenna	Preamp	Cable	Limit	Over		
Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4804.000	25.29	31.35	37.73	4.61	23.52	54.00	-30.48 Average
2	4804.000	34.57	31.35	37.73	4.61	32.80	74.00	-41.20 Peak
3	7206.000	23.00	35.89	35.63	6.48	29.74	54.00	-24.26 Average
4	7206.000	29.18	35.89	35.63	6.48	35.92	74.00	-38.08 Peak
5	9608.000	21.72	37.74	34.94	7.97	32.49	54.00	-21.51 Average
6	9608.000	28.72	37.74	34.94	7.97	39.49	74.00	-34.51 Peak




Condition : FCC PART 15 (PK) 3m VERTICAL  
 Job No. : GTS202009000027  
 Test Mode : TX 2402MHz  
 Test Engineer: Hans  
 Remark :

	Freq	ReadAntenna	Preamp	Cable	Limit	Over	
	MHz	Level	Factor	Loss	Level	Line	Limit Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	4804.000	28.11	31.35	37.73	4.61	26.34	54.00 -27.66 Average
2	4804.000	34.11	31.35	37.73	4.61	32.34	74.00 -41.66 Peak
3	7206.000	21.71	35.89	35.63	6.48	28.45	54.00 -25.55 Average
4	7206.000	28.71	35.89	35.63	6.48	35.45	74.00 -38.55 Peak
5	9608.000	28.86	37.74	34.94	7.97	39.63	54.00 -14.37 Average
6	9608.000	22.86	37.74	34.94	7.97	33.63	74.00 -40.37 Peak





Test channel: Middle



Condition : FCC PART 15 (PK) 3m VERTICAL  
 Job No. : GTS202009000027  
 Test Mode : TX 2441MHz  
 Test Engineer: Hans  
 Remark :

	Read	Antenna	Preamp	Cable	Limit	Over	
Freq	Level	Factor	Factor	Loss	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	4882.000	26.03	31.49	37.76	4.69	24.45	54.00 -29.55 Average
2	4882.000	33.03	31.49	37.76	4.69	31.45	74.00 -42.55 Peak
3	7323.000	22.71	36.18	35.60	6.63	29.92	54.00 -24.08 Average
4	7323.000	29.71	36.18	35.60	6.63	36.92	74.00 -37.08 Peak
5	9764.000	21.36	38.08	35.03	8.03	32.44	54.00 -21.56 Average
6	9764.000	29.36	38.08	35.03	8.03	40.44	74.00 -33.56 Peak







Condition : FCC PART 15 (PK) 3m HORIZONTAL  
 Job No. : GTS202009000027  
 Test Mode : TX 2441MHz  
 Test Engineer: Hans  
 Remark :

	Read Freq	Antenna Level	Preamp Factor	Cable Loss	Cable Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	4882.000	25.26	31.49	37.76	4.69	23.68	54.00	-30.32 Average
2	4882.000	32.26	31.49	37.76	4.69	30.68	74.00	-43.32 Peak
3	7323.000	23.65	36.18	35.60	6.63	30.86	54.00	-23.14 Average
4	7323.000	29.65	36.18	35.60	6.63	36.86	74.00	-37.14 Peak
5	9764.000	22.46	38.08	35.03	8.03	33.54	54.00	-20.46 Average
6	9764.000	29.46	38.08	35.03	8.03	40.54	74.00	-33.46 Peak









Condition : FCC PART 15 (PK) 3m VERTICAL  
 Job No. : GTS202009000027  
 Test Mode : TX 2480MHz  
 Test Engineer: Hans  
 Remark :

	Read	Antenna	Preamp	Cable	Limit	Over		
Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4960.000	25.20	31.63	37.78	4.79	23.84	54.00	-30.16 Average
2	4960.000	32.20	31.63	37.78	4.79	30.84	74.00	-43.16 Peak
3	7440.000	23.86	36.46	35.56	6.77	31.53	54.00	-22.47 Average
4	7440.000	30.86	36.46	35.56	6.77	38.53	74.00	-35.47 Peak
5	9920.000	21.17	38.42	35.14	8.09	32.54	54.00	-21.46 Average
6	9920.000	29.17	38.42	35.14	8.09	40.54	74.00	-33.46 Peak

**Test Result: Pass**

**RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS**


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

**LIMITS**

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## BLOCK DIAGRAM OF TEST SETUP



## PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1:  $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamp\ Factor$


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

**TEST DATA**

Remark: During the test, pre-scan the GFSK, Pi/4QPSK, modulation, and found the Pi/4QPSK modulation which it is worse case.


**Lowest channel**



Condition : FCC PART 15 (PK) 3m VERTICAL  
Job No. : GTS202009000027  
Test Mode : TX 2402MHz  
Test Engineer: Hans  
Remark :

	Read	Antenna	Preamp	Cable	Limit	Over		
Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2310.000	37.61	27.14	30.43	2.81	37.13	54.00	-16.87 Average
2	2310.000	44.61	27.14	30.43	2.81	44.13	74.00	-29.87 Peak
3	2390.000	36.52	27.37	30.24	2.91	36.56	54.00	-17.44 Average
4	2390.000	43.52	27.37	30.24	2.91	43.56	74.00	-30.44 Peak
5	2400.000	36.16	27.41	30.26	2.91	36.22	54.00	-17.78 Average
6	2400.000	43.16	27.41	30.26	2.91	43.22	74.00	-30.78 Peak






Condition : FCC PART 15 (PK) 3m HORIZONTAL  
 Job No. : GTS202009000027  
 Test Mode : TX 2402MHz  
 Test Engineer: Hans  
 Remark :

	Read	Antenna	Preamp	Cable	Limit	Over		
Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2310.000	35.03	27.14	30.43	2.81	34.55	54.00	-19.45 Average
2	2310.000	44.03	27.14	30.43	2.81	43.55	74.00	-30.45 Peak
3	2390.000	35.42	27.37	30.24	2.91	35.46	54.00	-18.54 Average
4	2390.000	44.42	27.37	30.24	2.91	44.46	74.00	-29.54 Peak
5	2400.000	36.06	27.41	30.26	2.91	36.12	54.00	-17.88 Average
6	2400.000	44.06	27.41	30.26	2.91	44.12	74.00	-29.88 Peak

BLA


### Highest channel



Condition : FCC PART 15 (PK) 3m HORIZONTAL  
Job No. : GTS202009000027  
Test Mode : TX 2480MHz  
Test Engineer: Hans  
Remark :

	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	37.38	27.66	30.12	2.99	37.91	54.00	-16.09	Average
2	2483.500	44.38	27.66	30.12	2.99	44.91	74.00	-29.09	Peak
3	2500.000	36.51	27.70	30.13	3.01	37.09	54.00	-16.91	Average
4	2500.000	43.51	27.70	30.13	3.01	44.09	74.00	-29.91	Peak





Condition : FCC PART 15 (PK) 3m VERTICAL  
 Job No. : GTS202009000027  
 Test Mode : TX 2480MHz  
 Test Engineer: Hans  
 Remark :

	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	36.51	27.66	30.12	2.99	37.04	54.00	-16.96	Average
2	2483.500	43.51	27.66	30.12	2.99	44.04	74.00	-29.96	Peak
3	2500.000	36.65	27.70	30.13	3.01	37.23	54.00	-16.77	Average
4	2500.000	43.65	27.70	30.13	3.01	44.23	74.00	-29.77	Peak

BLUE




### CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

### BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


## CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

### BLOCK DIAGRAM OF TEST SETUP



TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia


### DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

### BLOCK DIAGRAM OF TEST SETUP



TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia


### HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

### BLOCK DIAGRAM OF TEST SETUP



### TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


### CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### LIMITS

<b>Limit:</b>	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W
---------------	--

### BLOCK DIAGRAM OF TEST SETUP



### TEST DATA


**Pass: Please Refer To Appendix: Appendix1 For Details**



## 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### BLOCK DIAGRAM OF TEST SETUP



### TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


### CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

### LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

### BLOCK DIAGRAM OF TEST SETUP



TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia

### CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

#### LIMITS

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### BLOCK DIAGRAM OF TEST SETUP



Remark  
 E.U.T: Equipment Under Test  
 LISN: Line Impedance Stabilization Network  
 Test table height=0.8m

#### PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 $\mu$ H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

**TEST DATA**

[TestMode: TX]; [Line: Nutral]

**Conducted Emission Measurement**



File :CE      Data :#3      Date: 2020/9/10      Time: 16:55:51

Site      Phase: **N**      Temperature: 26

Limit: FCC Class B Conduction(QP)      Power:      Humidity: 60 %

EUT: Bluetooth Headset

M/N: In2026

Mode: BT mode

Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1740	21.35	9.87	31.22	64.77	-33.55	QP	
2		0.1740	15.72	9.87	25.59	54.77	-29.18	AVG	
3		1.1860	17.95	9.83	27.78	56.00	-28.22	QP	
4		1.1860	12.61	9.83	22.44	46.00	-23.56	AVG	
5		2.0820	12.57	9.86	22.43	56.00	-33.57	QP	
6		2.0820	6.74	9.86	16.60	46.00	-29.40	AVG	
7		4.3620	21.98	9.86	31.84	56.00	-24.16	QP	
8	*	4.3620	13.65	9.86	23.51	46.00	-22.49	AVG	
9		7.6380	26.23	9.86	36.09	60.00	-23.91	QP	
10		7.6380	13.43	9.86	23.29	50.00	-26.71	AVG	
11		14.4020	17.67	10.01	27.68	60.00	-32.32	QP	
12		14.4020	7.85	10.01	17.86	50.00	-32.14	AVG	

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX]; [Line: Line]

**Conducted Emission Measurement**


Site:      Phase: **L1**      Temperature: 26  
 Limit: FCC Class B Conduction(QP)      Power:      Humidity: 60 %  
 EUT: Bluetooth Headset  
 M/N: In2026  
 Mode: BT mode  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.5820	20.10	9.74	29.84	56.00	-26.16	QP	
2	*	0.5820	15.97	9.74	25.71	46.00	-20.29	AVG	
3		1.1100	17.34	9.84	27.18	56.00	-28.82	QP	
4		1.1100	12.08	9.84	21.92	46.00	-24.08	AVG	
5		2.1940	20.78	9.82	30.60	56.00	-25.40	QP	
6		2.1940	11.11	9.82	20.93	46.00	-25.07	AVG	
7		4.2740	23.01	9.84	32.85	56.00	-23.15	QP	
8		4.2740	14.94	9.84	24.78	46.00	-21.22	AVG	
9		7.9620	29.26	9.87	39.13	60.00	-20.87	QP	
10		7.9620	16.42	9.87	26.29	50.00	-23.71	AVG	
11		14.5620	20.80	9.97	30.77	60.00	-29.23	QP	
12		14.5620	10.61	9.97	20.58	50.00	-29.42	AVG	

\*:Maximum data    x:Over limit    !:over margin      <Reference Only

**Test Result: Pass**

## 10 APPENDIX

### Appendix1

#### 10.1 APPENDIX: 20DBEMISSION BANDWIDTH


##### Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	1.083	2401.469	2402.552	---	PASS
		2441	1.086	2440.469	2441.555	---	PASS
		2480	1.083	2479.469	2480.552	---	PASS
2DH1	Ant1	2402	1.371	2401.325	2402.696	---	PASS
		2441	1.374	2440.322	2441.696	---	PASS
		2480	1.371	2479.322	2480.693	---	PASS




### Test Graphs






2DH1\_Ant1\_2441



2DH1\_Ant1\_2480




## 10.2 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER




### Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	-3.25	<=20.97	PASS
		2441	-3.25	<=20.97	PASS
		2480	-3.59	<=20.97	PASS
2DH1	Ant1	2402	-3.05	<=20.97	PASS
		2441	-3.03	<=20.97	PASS
		2480	-3.37	<=20.97	PASS


BlueAsia

### Test Graphs





**2DH1\_Ant1\_2480**



BlueAsia

### 10.3 APPENDIX: CARRIER FREQUENCY SEPARATION

#### Test Result

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	1	$\geq 0.724$	PASS
2DH1	Ant1	Hop	1.006	$\geq 0.916$	PASS

BlueAsia

### Test Graphs






#### 10.4 APPENDIX: TIME OF OCCUPANCY




##### Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.38	320	0.12	<=0.4	PASS
DH3	Ant1	Hop	1.64	180	0.295	<=0.4	PASS
DH5	Ant1	Hop	2.88	100	0.288	<=0.4	PASS

BlueAsia

### Test Graphs





**10.5 APPENDIX: NUMBER OF HOPPING CHANNELS****Test Result**

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	$\geq 15$	PASS
2DH1	Ant1	Hop	79	$\geq 15$	PASS

BlueAsia

### Test Graphs



## 10.6 APPENDIX: BAND EDGE MEASUREMENTS


### Test Result

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH1	Ant1	Low	2402	-3.63	-54.29	<=-23.63	PASS
		High	2480	-3.90	-54.97	<=-23.9	PASS
		Low	Hop_2402	-3.61	-54.18	-23.61	PASS
		High	Hop_2480	-3.73	-54.48	-23.73	PASS
2DH1	Ant1	Low	2402	-3.81	-54.3	<=-23.81	PASS
		High	2480	-4.00	-55.35	<=-24	PASS
		Low	Hop_2402	-3.64	-55.07	-23.64	PASS
		High	Hop_2480	-3.79	-54.72	-23.79	PASS


BlueAsia

### Test Graphs






2DH1\_Ant1\_Low\_2402




2DH1\_Ant1\_High\_2402




2DH1\_Ant1\_Low\_Hop\_2402





2DH1\_Ant1\_High\_Hop\_2480




**10.7 APPENDIX: CONDUCTED SPURIOUS EMISSION**
**Test Result**


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH1	Ant1	2402	Reference	-3.62	-3.62	---	PASS
			30~1000	30~1000	-68.284	<=-23.615	PASS
			1000~26500	1000~26500	-52.156	<=-23.615	PASS
		2441	Reference	-3.68	-3.68	---	PASS
			30~1000	30~1000	-68.052	<=-23.681	PASS
			1000~26500	1000~26500	-51.696	<=-23.681	PASS
		2480	Reference	-3.92	-3.92	---	PASS
			30~1000	30~1000	-68.04	<=-23.919	PASS
			1000~26500	1000~26500	-53.334	<=-23.919	PASS
2DH1	Ant1	2402	Reference	-3.95	-3.95	---	PASS
			30~1000	30~1000	-68.393	<=-23.946	PASS
			1000~26500	1000~26500	-53.64	<=-23.946	PASS
		2441	Reference	-3.93	-3.93	---	PASS
			30~1000	30~1000	-44.136	<=-23.927	PASS
			1000~26500	1000~26500	-52.364	<=-23.927	PASS
		2480	Reference	-4.00	-4.00	---	PASS
			30~1000	30~1000	-68.229	<=-23.998	PASS
			1000~26500	1000~26500	-53.275	<=-23.998	PASS

### Test Graphs







DH1\_Ant1\_2441\_30~1000




DH1\_Ant1\_2441\_1000~26500




DH1\_Ant1\_2480\_0~Reference




DH1\_Ant1\_2480\_30~1000




DH1\_Ant1\_2480\_1000~26500




2DH1\_Ant1\_2402\_0~Reference



2DH1\_Ant1\_2402\_30~1000



2DH1\_Ant1\_2402\_1000~26500



2DH1\_Ant1\_2441\_0~Reference