11 - RF EXPOSURE

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

(A) Limits for General Population/Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time		
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm^2)	(minute)		
Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	$*(180/f^2)$	30		
30-300	27.5	0.073	0.2	30		
300-1500	/	/	f/1500	30		
1500-100,000	/	/	1.0	30		

(B) Limits for Occupational/Controlled Exposures

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)		
Limits for Occupational/Controlled Exposure						
0.3-3.0	614	1.63	*(100)	6		
3.0-30	1842/f	4.89/f	*(900/f ²)	6		
30-300	61.4	0.163	1.0	6		
300-1500	/	/	f/300	6		
1500-100,000	/	/	5	6		

f = frequency in MHz

MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S = PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Indoor Antenna:

^{* =} Plane-wave equivalent power density

Meru Networks FCC ID: RE7-AP100

Maximum peak output power at antenna input terminal: 23.73 (dBm)

Maximum peak output power at antenna input terminal: 236 (mW)

Prediction distance: 20 (cm)
Predication frequency: 2437 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm^2)

Antenna Gain (typical): 3 (dBi)

Maximum antenna gain: 2.0 (numeric)

Power density at predication frequency at 100 cm: 0.09mW/cm²)

Outdoor Antenna:

Maximum peak output power at antenna input terminal: 23.73 (dBm)

Maximum peak output power at antenna input terminal: 236 (mW)

Prediction distance: 120 (cm)

Predication frequency: 2437 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm^2)

Antenna Gain (typical): 15 (dBi)

Maximum antenna gain: 31.6 (numeric)

Power density at predication frequency at 120 cm: 0.05mW/cm²)

Test Result

The EUT is defined to be a mobile device. Predicted power density level at 20cm is 0.09mW/cm² which is below the limit of 1 mW/cm². Predicted power density level at 120cm is 0.05mW/cm² which is below the limit of 1 mW/cm².