



APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	Single Radio Access Point AP110
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	IEEE 802.11b mode: 20.79 dBm (119.94 mW) IEEE 802.11g mode: 23.64 dBm (231.20 mW) IEEE 802.11n HT 20 MHz mode: 22.85 dBm (192.75 mW) IEEE 802.11n HT 40 MHz mode: 24.82 dBm (303.38 mW)
Antenna gain (Max)	3.12 dBi (Numeric gain: 2.05) MIMO: $10 * \text{LOG}(((10^{(3.12/20)} + 10^{(0.59/20)})^2)/2) = 4.96\text{dBi}$ (Numeric gain: 3.13)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

Remark:

The maximum output power is 24.82 dBm (303.38mW) at 2422MHz (with 3.13 numeric antenna gain.)

TEST RESULTS

No non-compliance noted.

MPE EVALUATION

No non-compliance noted.



Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where $E =$ Field strength in Volts / meter

$P =$ Power in Watts

$G =$ Numeric antenna gain

$d =$ Distance in meters

$S =$ Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where $d =$ Distance in cm

$P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where $P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²



IEEE 802.11b mode:

EUT output power = 119.94 mW

Numeric Antenna gain = 2.05

→ Power density = 0.0489 mW / cm²

IEEE 802.11g mode:

EUT output power = 231.20 mW

Numeric Antenna gain = 2.05

→ Power density = 0.0943 mW / cm²

IEEE 802.11n HT 20 MHz mode:

EUT output power = 192.75 mW

Numeric Antenna gain = 3.13

→ Power density = 0.1200 mW / cm²

IEEE 802.11n HT 40 MHz mode:

EUT output power = 303.38 mW

Numeric Antenna gain = 3.13

→ Power density = 0.1889 mW / cm²

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)