NOTES: UNLESS OTHERWISE SPECIFIED)	REV	DATE	DESCRIPTION
1. MUST CONFORM TO UL969 MARKING & LABELING SYSTEM PGDQ2; VAL-THERM-D OR EQUIVALENT.	1	9/19/12	Initial Release
 ALL TEXT AND GRAPHICS ARE BLACK. CE, GITEKI & KOREAN MARK HAVE MINIMUM HEIGHT OF 5mm. 	2	11/13/12	Remove incomplete certification information
4. The diameter of the C-Tick mark has a minimum requirement of 3mm and the suppliers identification characters have a minimum height requirement of 1mm5. For UAE mark, "TRA" min height 3mm, all other characters min height 2mm	3	2/25/13	Add certs, update product desc, Release to MVT

6. For So. Africa mark, the ICASA logo min requirement is 3 x 3 mm

7. Factory Code: Shanghai = "S", Shenzhen = "SZ"

102 mm x 15.5 mm

Meru Networks₀
Dual Radio Access Point
Model No. AP832i
Powered by PoE: -48 V...750 mA
Powered by AC Adapter: 12 V...2.0A

C Usus LISTED

ITE. ACCESSORY
E239453 52

IC. 6749A-AP8321

SCALE 1:1

	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES			TITLE							
#1.5°	2 PLCS ±.05	3 PLCS ±.010	Label, Regulatory 1, AP832i								
	DO NOT SCALETHIS DRAWING			E PROJECTION	MERU NETWORKS PROPRIETARY USE PURSUANT TO COMPANY INSTRUCTIONS						
PROE FILE NAME	1:1 PROEFILE NAME		ENG DATE	HS 2/25/13	DRAWING NUMBER 845-00704	SHEET	REV/REL	DWG SIZE C2/A1R			