

FCC Part 15C Measurement and Test Report

For

Shenzhen Wanscam Technology Co., Ltd

5th Floor, A24 Building, 2nd Industrial zone of Fuwei, Fuyong,

Baoan, Shenzhen, China

FCC ID: REH-HW0024

FCC Rule(s):	<u>FCC Part 15C</u>
Product Description:	<u>IP Camera</u>
Tested Model:	<u>HW0024</u>
Report No.:	<u>STR16088279I-1</u>
Tested Date:	<u>2016-08-27 to 2016-09-05</u>
Issued Date:	<u>2016-09-06</u>
Tested By:	<u>Terry Su / Engineer</u> <i>Terry Su</i>
Reviewed By:	<u>Silin Chen / EMC Manager</u> <i>Silin Chen</i>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u> <i>Jandy So</i>
Prepared By:	

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
1.2 TEST STANDARDS	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 EUT SETUP AND TEST MODE	5
1.6 MEASUREMENT UNCERTAINTY	5
1.7 TEST EQUIPMENT LIST AND DETAILS	6
2. SUMMARY OF TEST RESULTS	7
3. RF EXPOSURE	8
3.1 STANDARD APPLICABLE	8
3.2 TEST RESULT	8
4. ANTENNA REQUIREMENT	9
4.1 STANDARD APPLICABLE	9
4.2 EVALUATION INFORMATION	9
5. POWER SPECTRAL DENSITY	10
5.1 STANDARD APPLICABLE	10
5.2 TEST PROCEDURE	10
5.3 ENVIRONMENTAL CONDITIONS	10
5.4 SUMMARY OF TEST RESULTS/PLOTS	11
6. 6DB BANDWIDTH	18
6.1 STANDARD APPLICABLE	18
6.2 TEST PROCEDURE	18
6.3 ENVIRONMENTAL CONDITIONS	18
6.4 SUMMARY OF TEST RESULTS/PLOTS	18
7. RF OUTPUT POWER	25
7.1 STANDARD APPLICABLE	25
7.2 TEST PROCEDURE	25
7.3 ENVIRONMENTAL CONDITIONS	25
7.4 SUMMARY OF TEST RESULTS/PLOTS	26
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	33
8.1 STANDARD APPLICABLE	33
8.2 TEST PROCEDURE	33
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	34
8.4 ENVIRONMENTAL CONDITIONS	34
8.5 SUMMARY OF TEST RESULTS/PLOTS	35
9. OUT OF BAND EMISSIONS	63
9.1 STANDARD APPLICABLE	63
9.2 TEST PROCEDURE	63
9.3 ENVIRONMENTAL CONDITIONS	64
9.4 SUMMARY OF TEST RESULTS/PLOTS	64
10. CONDUCTED EMISSIONS	78
10.1 TEST PROCEDURE	78
10.2 BASIC TEST SETUP BLOCK DIAGRAM	78
10.3 ENVIRONMENTAL CONDITIONS	78
10.4 TEST RECEIVER SETUP	79
10.5 SUMMARY OF TEST RESULTS/PLOTS	79
10.6 CONDUCTED EMISSIONS TEST DATA	79

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Wanscam Technology Co., Ltd
 Address of applicant: 5th Floor, A24 Building, 2nd Industrial zone of Fuwei, Fuyong, Baoan, Shenzhen, China

Manufacturer: Shenzhen Wanscam Technology Co., Ltd
 Address of manufacturer: 5th Floor, A24 Building, 2nd Industrial zone of Fuwei, Fuyong, Baoan, Shenzhen, China

General Description of EUT	
Product Name:	IP Camera
Trade Name:	Wanscam
Model No.:	HW0024
Adding Model(s):	HW0021
Rated Voltage:	Adapter DC 5V
Power Adapter Model:	MIC 12-0502000CE I/P: AC 100-240V; O/P: DC 5V/2A
Software Version:	B18HX_V7.1.4.1.13-20160204
Hardware Version:	HW2440-MAIN-3A
<p><i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model HW0024, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	15.71dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Type of Antenna:	Integral
Antenna Gain:	2dBi
Lowest internal frequency of EUT:	32.768kHz

1.2 Test Standards

The following report is prepared on behalf of the Shenzhen Wanscam Technology Co., Ltd in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v03r05 for digital transmission systems shall be performed also.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
/	/	/	/
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	ETS	3116B	00088203	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v03r05, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-6.806	8
	2437	-10.64	8
	2462	-12.58	8
802.11g	2412	-10.04	8
	2437	-13.65	8
	2462	-15.29	8
802.11n HT20	2412	-10.08	8
	2437	-11.21	8
	2462	-15.72	8
802.11n HT40	2422	-9.968	8
	2437	-13.2	8
	2452	-12.49	8

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit kHz
802.11b	2412	12.3193	10.090	≥ 500
	2437	12.2460	9.828	≥ 500
	2462	12.2643	9.966	≥ 500
802.11g	2412	16.4960	16.432	≥ 500
	2437	16.4227	16.432	≥ 500
	2462	16.4181	16.487	≥ 500
802.11n-HT20	2412	17.6043	16.681	≥ 500
	2437	17.4970	17.489	≥ 500
	2462	17.4950	16.889	≥ 500
802.11n-HT40	2422	35.9424	35.529	≥ 500
	2437	35.7968	35.435	≥ 500
	2452	35.7696	35.408	≥ 500

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to the KDB-558074 D01 v03r05, 9.2.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle $< 98 \%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98 \%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	15.71	37.24	1000
	2437	11.64	14.59	1000
	2462	9.13	8.18	1000
802.11g_54Mbps	2412	14.23	26.49	1000
	2437	10.20	10.47	1000
	2462	7.93	6.21	1000
802.11n HT20_MCS7	2412	15.33	34.12	1000
	2437	12.11	16.26	1000
	2462	10.32	10.76	1000
802.11n HT40_MCS7	2422	9.40	8.71	1000
	2437	7.04	5.06	1000
	2452	6.60	4.57	1000

Please refer to the following test plots:


802.11b-11Mbps-Low Channel




802.11b -11Mbps-Middle Channel




802.11b -11Mbps-High Channel




802.11g-54Mbps-Low Channel




802.11g-54Mbps-Middle Channel




802.11g-54Mbps-High Channel




802.11n-HT20-MCS7-Low Channel




802.11n-HT20-MCS7-Middle Channel




802.11n-HT20-MCS7-High Channel




802.11n-HT40-MCS7-Low Channel



802.11n-HT40-MCS7-Middle Channel



802.11n-HT40-MCS7-High Channel



8. Field Strength of Spurious Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar


8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: IP Camera
 Tested Model: HW0024
 Operating Condition: 802.11b Transmitting Low Channel-2412MHz
 Comment: AC 120V/60Hz; Adapter DC 5V
 Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	312.1794	26.64	9.24	35.88	46.00	-10.12	0	100	peak
2	455.9058	26.56	10.45	37.01	46.00	-8.99	0	100	peak
3	842.1296	23.57	15.63	39.20	46.00	-6.80	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	263.8190	18.47	7.29	25.76	46.00	-20.24	0	100	peak
2	504.7062	22.79	10.98	33.77	46.00	-12.23	0	100	peak
3	903.3094	16.65	16.79	33.44	46.00	-12.56	0	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	312.1794	26.12	9.24	35.36	46.00	-10.64	0	100	peak
2	455.9058	26.07	10.45	36.52	46.00	-9.48	0	100	peak
3	842.1296	23.08	15.63	38.71	46.00	-7.29	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	455.9058	20.47	10.45	30.92	46.00	-15.08	0	100	peak
2	504.7062	22.78	10.98	33.76	46.00	-12.24	0	100	peak
3	696.8567	20.06	13.70	33.76	46.00	-12.24	0	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	312.1794	26.49	9.24	35.73	46.00	-10.27	0	100	peak
2	455.9058	26.23	10.45	36.68	46.00	-9.32	0	100	peak
3	842.1296	22.89	15.63	38.52	46.00	-7.48	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	239.9874	17.49	6.33	23.82	46.00	-22.18	0	100	peak
2	455.9058	20.41	10.45	30.86	46.00	-15.14	0	100	peak
3	504.7062	23.00	10.98	33.98	46.00	-12.02	0	100	peak

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: *IP Camera*
 Tested Model: *HW0024*
 Operating Condition: *802.11g Transmitting Low Channel-2412MHz*
 Comment: *AC 120V/60Hz; Adapter DC 5V*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	263.8190	28.16	7.29	35.45	46.00	-10.55	0	100	peak
2	455.9058	28.32	10.45	38.77	46.00	-7.23	0	100	peak
3	793.3960	26.00	14.04	40.04	46.00	-5.96	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	216.0240	18.65	4.81	23.46	46.00	-22.54	0	100	peak
2	455.9058	19.77	10.45	30.22	46.00	-15.78	0	100	peak
3	504.7062	22.58	10.98	33.56	46.00	-12.44	0	100	peak

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	263.8190	27.50	7.29	34.79	46.00	-11.21	0	100	peak
2	455.9058	28.45	10.45	38.90	46.00	-7.10	0	100	peak
3	793.3960	25.49	14.04	39.53	46.00	-6.47	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	455.9058	20.91	10.45	31.36	46.00	-14.64	0	100	peak
2	504.7062	24.25	10.98	35.23	46.00	-10.77	0	100	peak
3	696.8567	19.14	13.70	32.84	46.00	-13.16	0	100	peak

Operating Condition: 802.11g Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	312.1794	26.55	9.24	35.79	46.00	-10.21	0	100	peak
2	455.9058	28.56	10.45	39.01	46.00	-6.99	0	100	peak
3	793.3960	24.91	14.04	38.95	46.00	-7.05	0	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	455.9058	20.60	10.45	31.05	46.00	-14.95	0	100	peak
2	504.7062	23.23	10.98	34.21	46.00	-11.79	0	100	peak
3	696.8567	18.10	13.70	31.80	46.00	-14.20	0	100	peak


Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: IP Camera
 Tested Model: HW0024
 Operating Condition: 802.11n-HT20 Transmitting Low Channel-2412MHz
 Comment: AC 120V/60Hz; Adapter DC 5V
 Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	312.1794	26.85	9.24	36.09	46.00	-9.91	0	100	peak
2	455.9058	28.76	10.45	39.21	46.00	-6.79	0	100	peak
3	793.3960	24.66	14.04	38.70	46.00	-7.30	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	263.8190	18.09	7.29	25.38	46.00	-20.62	0	100	peak
2	455.9058	20.18	10.45	30.63	46.00	-15.37	0	100	peak
3	504.7062	23.00	10.98	33.98	46.00	-12.02	0	100	peak

Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	263.8190	25.55	7.29	32.84	46.00	-13.16	0	100	peak
2	312.1794	27.53	9.24	36.77	46.00	-9.23	0	100	peak
3	455.9058	27.14	10.45	37.59	46.00	-8.41	0	100	peak
4	842.1296	22.92	15.63	38.55	46.00	-7.45	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	455.9058	19.57	10.45	30.02	46.00	-15.98	0	100	peak
2	504.7062	22.37	10.98	33.35	46.00	-12.65	0	100	peak
3	696.8567	18.46	13.70	32.16	46.00	-13.84	0	100	peak

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	312.1794	26.02	9.24	35.26	46.00	-10.74	0	100	peak
2	455.9058	26.74	10.45	37.19	46.00	-8.81	0	100	peak
3	842.1296	22.62	15.63	38.25	46.00	-7.75	0	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	146.8877	17.80	2.46	20.26	43.50	-23.24	0	100	peak
2	455.9058	20.58	10.45	31.03	46.00	-14.97	0	100	peak
3	504.7062	20.86	10.98	31.84	46.00	-14.16	0	100	peak


EUT: IP Camera
 Tested Model: HW0024
 Operating Condition: 802.11n-HT40 Transmitting Low Channel-2422MHz
 Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Detector
1	49.7068	23.33	-7.44	15.89	40.00	-24.11	0	100	peak
2	100.5806	22.04	-9.57	12.47	43.50	-31.03	0	100	peak
3*	595.1329	25.13	-1.81	23.32	46.00	-22.68	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Detector
1	36.3814	24.24	-9.52	14.72	40.00	-25.28	0	100	peak
2*	51.1209	24.69	-7.56	17.13	40.00	-22.87	0	100	peak
3	506.4791	23.25	-1.17	22.08	46.00	-23.92	0	100	peak

Operating Condition: 802.11n-HT40 Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Detector
1	46.1780	22.25	-7.46	14.79	40.00	-25.21	0	100	peak
2*	55.8047	24.02	-8.04	15.98	40.00	-24.02	0	100	peak
3	434.0651	23.14	-2.32	20.82	46.00	-25.18	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Detector
1	33.3279	25.07	-10.48	14.59	40.00	-25.41	0	100	peak
2*	36.6375	24.94	-9.39	15.55	40.00	-24.45	0	100	peak
3	99.5281	22.72	-9.61	13.11	43.50	-30.39	0	100	peak

Operating Condition: 802.11n-HT40 Transmitting High Channel-2452MHz


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Detector
1	53.8818	22.60	-7.83	14.77	40.00	-25.23	0	100	peak
2	552.8833	22.91	-1.38	21.53	46.00	-24.47	0	100	peak
3*	798.9797	23.17	2.60	25.77	46.00	-20.23	0	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Detector
1	36.6375	23.98	-9.39	14.59	40.00	-25.41	0	100	peak
2	55.4147	23.65	-7.99	15.66	40.00	-24.34	0	100	peak
3*	912.8620	21.34	5.43	26.77	46.00	-19.23	0	100	peak

Spurious Emissions Above 1GHz

Test Mode: 802.11b

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	58.18	-3.86	54.32	74	-19.68	H	PK
4824.000	40.00	-3.86	36.14	54	-17.86	H	AV
7236.000	59.09	1.1	60.19	74	-13.81	H	PK
7236.000	50.00	1.1	51.10	54	-2.90	H	AV
4824.000	57.27	-3.86	53.41	74	-20.59	V	PK
4824.000	40.91	-3.86	37.05	54	-16.95	V	AV
7236.000	56.36	1.1	57.46	74	-16.54	V	PK
7236.000	43.64	1.1	44.74	54	-9.26	V	AV
Middle Channel-2437MHz							
4874.000	59.09	-3.74	55.35	74	-18.65	H	PK
4874.000	44.55	-3.74	40.81	54	-13.19	H	AV
7311.000	55.45	1.47	56.92	74	-17.08	H	PK
7311.000	40.00	1.47	41.47	54	-12.53	H	AV
4874.000	54.55	-3.74	50.81	74	-23.19	V	PK
4874.000	44.55	-3.74	40.81	54	-13.19	V	AV
7311.000	60.00	1.47	61.47	74	-12.53	V	PK
7311.000	43.64	1.47	45.11	54	-8.89	V	AV
High Channel-2462MHz							
4924.000	56.36	-3.63	52.73	74	-21.27	H	PK
4924.000	45.45	-3.63	41.82	54	-12.18	H	AV
7386.000	57.27	1.62	58.89	74	-15.11	H	PK
7386.000	50.00	1.62	51.62	54	-2.38	H	AV
4924.000	55.45	-3.63	51.82	74	-22.18	V	PK
4924.000	44.55	-3.63	40.92	54	-13.08	V	AV
7386.000	55.45	1.62	57.07	74	-16.93	V	PK
7386.000	46.36	1.62	47.98	54	-6.02	V	AV

Test Mode: 802.11g

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	55.50	-3.86	51.64	74.00	-22.36	H	PK
4824.000	42.23	-3.86	38.37	54.00	-15.63	H	AV
7236.000	48.42	1.10	49.52	74.00	-24.48	H	PK
7236.000	34.40	1.10	35.50	54.00	-18.50	H	AV
4824.000	55.99	-3.86	52.13	74.00	-21.87	V	PK
4824.000	42.65	-3.86	38.79	54.00	-15.21	V	AV
7236.000	49.22	1.10	50.32	74.00	-23.68	V	PK
7236.000	35.54	1.10	36.64	54.00	-17.36	V	AV
Middle Channel-2437MHz							
4874.000	55.10	-3.74	51.36	74.00	-22.64	H	PK
4874.000	43.28	-3.74	39.54	54.00	-14.46	H	AV
7311.000	47.38	1.47	48.85	74.00	-25.15	H	PK
7311.000	35.27	1.47	36.74	54.00	-17.26	H	AV
4874.000	57.07	-3.74	53.33	74.00	-20.67	V	PK
4874.000	43.86	-3.74	40.12	54.00	-13.88	V	AV
7311.000	48.40	1.47	49.87	74.00	-24.13	V	PK
7311.000	35.33	1.47	36.80	54.00	-17.20	V	AV
High Channel-2462MHz							
4924.000	54.00	-3.59	50.41	74.00	-23.59	H	PK
4924.000	40.75	-3.59	37.16	54.00	-16.84	H	AV
7386.000	47.18	1.79	48.97	74.00	-25.03	H	PK
7386.000	34.73	1.79	36.52	54.00	-17.48	H	AV
4924.000	56.11	-3.59	52.52	74.00	-21.48	V	PK
4924.000	42.69	-3.59	39.10	54.00	-14.90	V	AV
7386.000	48.58	1.79	50.37	74.00	-23.63	V	PK
7386.000	35.95	1.79	37.74	54.00	-16.26	V	AV

Test Mode: 802.11n-HT20

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	55.60	-3.86	51.74	74.00	-22.26	H	PK
4824.000	40.54	-3.86	36.68	54.00	-17.32	H	AV
7236.000	47.26	1.10	48.36	74.00	-25.64	H	PK
7236.000	34.44	1.10	35.54	54.00	-18.46	H	AV
4824.000	56.71	-3.86	52.85	74.00	-21.15	V	PK
4824.000	43.18	-3.86	39.32	54.00	-14.68	V	AV
7236.000	49.21	1.10	50.31	74.00	-23.69	V	PK
7236.000	35.77	1.10	36.87	54.00	-17.13	V	AV
Middle Channel-2437MHz							
4874.000	54.16	-3.74	50.42	74.00	-23.58	H	PK
4874.000	42.48	-3.74	38.74	54.00	-15.26	H	AV
7311.000	48.74	1.47	50.21	74.00	-23.79	H	PK
7311.000	33.10	1.47	34.57	54.00	-19.43	H	AV
4874.000	54.92	-3.74	51.18	74.00	-22.82	V	PK
4874.000	42.62	-3.74	38.88	54.00	-15.12	V	AV
7311.000	48.49	1.47	49.96	74.00	-24.04	V	PK
7311.000	35.20	1.47	36.67	54.00	-17.33	V	AV
High Channel-2462MHz							
4924.000	53.90	-3.59	50.31	74.00	-23.69	H	PK
4924.000	43.23	-3.59	39.64	54.00	-14.36	H	AV
7386.000	48.31	1.79	50.10	74.00	-23.90	H	PK
7386.000	36.10	1.79	37.89	54.00	-16.11	H	AV
4924.000	55.70	-3.59	52.11	74.00	-21.89	V	PK
4924.000	41.48	-3.59	37.89	54.00	-16.11	V	AV
7386.000	48.55	1.79	50.34	74.00	-23.66	V	PK
7386.000	35.36	1.79	37.15	54.00	-16.85	V	AV

Test Mode: 802.11n-HT40

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2422MHz							
4844.000	53.25	-3.90	49.35	74.00	-24.65	H	PK
4824.000	38.25	-3.90	34.35	54.00	-19.65	H	AV
7266.000	46.48	1.06	47.54	74.00	-26.46	H	PK
7266.000	32.56	1.06	33.62	54.00	-20.38	H	AV
4844.000	54.22	-3.90	50.32	74.00	-23.68	V	PK
4824.000	39.42	-3.90	35.52	54.00	-18.48	V	AV
7266.000	48.81	1.06	49.87	74.00	-24.13	V	PK
7266.000	34.78	1.06	35.84	54.00	-18.16	V	AV
Middle Channel-2437MHz							
4874.000	52.53	-3.74	48.79	74.00	-25.21	H	PK
4874.000	37.88	-3.74	34.14	54.00	-19.86	H	AV
7311.000	44.88	1.47	46.35	74.00	-27.65	H	PK
7311.000	32.03	1.47	33.50	54.00	-20.50	H	AV
4874.000	53.74	-3.74	50.00	74.00	-24.00	V	PK
4874.000	39.95	-3.74	36.21	54.00	-17.79	V	AV
7311.000	45.78	1.47	47.25	74.00	-26.75	V	PK
7311.000	34.00	1.47	35.47	54.00	-18.53	V	AV
High Channel-2452MHz							
4904.000	52.65	-3.63	49.02	74.00	-24.98	H	PK
4904.000	39.37	-3.63	35.74	54.00	-18.26	H	AV
7356.000	45.63	1.62	47.25	74.00	-26.75	H	PK
7356.000	30.73	1.62	32.35	54.00	-21.65	H	AV
4904.000	54.84	-3.63	51.21	74.00	-22.79	V	PK
4904.000	40.83	-3.63	37.20	54.00	-16.80	V	AV
7356.000	48.18	1.62	49.80	74.00	-24.20	V	PK
7356.000	35.12	1.62	36.74	54.00	-17.26	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v03r05, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v03r05, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW \geq 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.


9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

802.11b-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	31.45	-3.71	27.74	54.00	-26.26	Average Detector
		43.80	-3.71	40.09	74.00	-33.91	Peak Detector
2	2390.000	32.75	-3.54	29.21	54.00	-24.79	Average Detector
		45.87	-3.54	42.33	74.00	-31.67	Peak Detector
3	2400.000	52.57	-3.51	49.06	Delta=36.15dBc		Average Detector
4	2411.280	88.69	-3.48	85.21			Average Detector

802.11b-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.750	91.48	-3.37	88.11	54.00	34.11	Average Detector
	2461.650	100.42	-3.37	97.05	74.00	23.05	Peak Detector
2	2483.500	Delta =57.61dBc		30.54	54.00	-23.46	Average Detector
	2483.500			42.43	74.00	-31.57	Peak Detector
3	2500.000	34.06	-3.28	30.78	54.00	-23.22	Average Detector
	2500.000	46.91	-3.28	43.63	74.00	-30.37	Peak Detector

802.11g-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	31.01	-3.71	27.30	54.00	-26.70	Average Detector
		44.58	-3.71	40.87	74.00	-33.13	Peak Detector
2	2390.000	32.07	-3.54	28.53	54.00	-25.47	Average Detector
		43.99	-3.54	40.45	74.00	-33.55	Peak Detector
3	2400.000	41.54	-3.51	38.03	Delta=41.95dBc		Average Detector
4	2418.480	83.44	-3.46	79.98			Average Detector

802.11g-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2465.450	85.47	-3.36	82.11	54.00	28.11	Average Detector
	2465.150	97.39	-3.36	94.03	74.00	20.03	Peak Detector
2	2483.500	Delta =51.1dBc		31.04	54.00	-22.96	Average Detector
	2483.500			45.32	74.00	-28.68	Peak Detector
3	2500.000	32.83	-3.28	29.55	54.00	-24.45	Average Detector
	2500.000	44.35	-3.28	41.07	74.00	-32.93	Peak Detector

802.11n-HT20-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	30.96	-3.71	27.25	54.00	-26.75	Average Detector
		43.32	-3.71	39.61			74.00
2	2390.000	32.22	-3.54	28.68	54.00	-25.32	Average Detector
		43.73	-3.54	40.19			74.00
3	2400.000	42.10	-3.51	38.59	Delta=41.13dBc		Average Detector
4	2418.240	83.18	-3.46	79.72			Average Detector

802.11n-HT20-Highest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2467.900	84.77	-3.35	81.42	54.00	27.42	Average Detector
	2466.250	95.88	-3.35	92.53	74.00	18.53	Peak Detector
2	2483.500	Delta =49.62dBc		31.82	54.00	-22.18	Average Detector
	2483.500	Delta =49.62dBc		47.12	74.00	-26.88	Peak Detector
3	2500.000	32.77	-3.28	29.49	54.00	-24.51	Average Detector
	2500.000	45.03	-3.28	41.75	74.00	-32.25	Peak Detector

802.11n-HT40-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	31.02	-3.71	27.31	54.00	-26.69	Average Detector
	2310.000	43.24	-3.71	39.53	74.00	-34.47	Peak Detector
2	2390.000	34.18	-3.54	30.64	54.00	-23.36	Average Detector
	2390.000	51.06	-3.54	47.52	74.00	-26.48	Peak Detector
3	2400.000	45.60	-3.51	42.09	Delta=36.83dBc		Average Detector
4	2431.520	82.36	-3.44	78.92			Average Detector


802.11n-HT40-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2471.440	82.97	-3.35	79.62	54.00	25.62	Average Detector
	2469.410	94.45	-3.35	91.10	74.00	17.10	Peak Detector
2	2483.500	Delta =31.36dBc		48.28	54.00	-5.72	Average Detector
	2483.500	Delta =31.36dBc		63.03	74.00	-10.97	Peak Detector
3	2500.000	36.69	-3.28	33.41	54.00	-20.59	Average Detector
	2500.000	51.58	-3.28	48.30	74.00	-25.70	Peak Detector


Spurious (Conducted)
 802.11b-Lowest
 Lowest



Middle




Highest




Spurious (Conducted)

802.11g-Lowest


Lowest




Middle




Highest




Spurious (Conducted)
 802.11n-HT20-Lowest
 Lowest




Middle




Highest




Spurious (Conducted)
802.11n-HT40-Lowest
Lowest



Middle



Highest




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

10.5 Summary of Test Results/Plots

According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


-5.43 dB at 0.4180 MHz in the **Line** mode, **Average** detector, **0.15-30MHz**

10.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: IP Camera
 Tested Model: HW0024
 Operating Condition: Transmitting(Wi-Fi)
 Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.4220	38.54	9.51	48.05	57.41	-9.36	peak
2	0.4220	24.93	9.51	34.44	47.41	-12.97	AVG
3	0.6980	34.19	9.61	43.80	56.00	-12.20	peak
4	0.7100	17.05	9.61	26.66	46.00	-19.34	AVG
5	1.0540	32.90	9.69	42.59	56.00	-13.41	peak
6	1.2100	15.49	9.71	25.20	46.00	-20.80	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.4180	32.55	9.51	42.06	47.49	-5.43	AVG
2	0.4220	40.40	9.51	49.91	57.41	-7.50	peak
3	1.0100	34.27	9.68	43.95	56.00	-12.05	peak
4	1.0100	23.99	9.68	33.67	46.00	-12.33	AVG
5	2.7220	32.17	9.92	42.09	56.00	-13.91	peak
6	2.8660	20.32	9.94	30.26	46.00	-15.74	AVG

***** END OF REPORT *****