
Guangzhou Changjia Electronic Co., Ltd.

Tablet PC

Model Number: TPC7102

Additional Model: SC-75JB

FCC ID: REOSC-75JB

Prepared for : Guangzhou Changjia Electronic Co., Ltd.
Bo-ying Industrial Garden, Taishi Industrial Zone, Yuwotou,
Dongchong Town, Panyu district, Guangzhou

Prepared By : EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town,
DongGuan City, GuangDong, China.
Tel: 86-769-83081888-808

Report Number: ESTE-R1301023
Date of Test : Jan.17~30,2013
Date of Report : Jan.31,2013

RF EXPOSURE EVALUATION METHOD SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Maximum measured transmitter power.

Mode	CH	Peak output Power (dBm)	Peak output Power (mW)
11b	CH1	8.85	7.674
	CH6	8.67	7.362
	CH11	8.68	7.379
11g	CH1	4.15	2.600
	CH6	4.47	2.799
	CH11	5.24	3.342
11n HT20	CH1	2.92	1.959
	CH6	1.45	1.396
	CH11	2.34	1.714
11n HT0	CH1	1.18	1.312
	CH4	1.79	1.510
	CH7	1.38	1.374

Refer to 447498 25 D01 General RF Exposure Guidance v05 Appendix A,
You see that for Maximum Conducted Output Power 7.674 mW(<10mW),
so no SAR is required.