

902 - 928 MHz Omni-Directional Antenna

-MA-WO91-8X

MARS ISM Omni - Directional Antenna is a ruggedized model suitable for outdoor installations on end of tower / spike poles. UV protected radome allowing for harsh environment installations. Antenna features stable and efficient performance with 8 dBi of gain.



Specifications:

Electrical

Frequency range	902 - 928 MHz
Gain, min.	8 dBi
VSWR, max.	2:1
3 dB Beam-Width, H-Plane, typ.	360 °
3 dB Beam-Width, E-Plane, typ.	14 °
Polarization	Linear Vertical
Input power, max	10 Watt
Input Impedance	50 Ohm

Mechanical

Dimensions (HxDiameter)	1350 x 64 mm (53"x2.5")
Weight	900 gr.
Connector	N-Type, Female
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected, Plastic
Mount	2.5" Pole Mount Attachment

Environmental

Operating Temperature Range	-40° C to +65° C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex. A.1.1)
Ice and Snow	25 mm radial (survival)
Salt Fog	According to IEC 68-2-11
Service Life	> 10 years

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product and are available in the "Policies" section.