

§ 15.247(i) Maximum Permissible Exposure

RF Exposure Requirements: §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

RF Radiation Exposure Limit: §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

EUT with 2.4GHz 5 dBi Omni Antenna

MPE Limit Calculation: EUT's operating frequencies @ 2412-2462 MHz; highest conducted power = *28.58dBm* (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT antenna gain = *3.16 dBi*.

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (1 mW/cm²)

P = Power Input to antenna (721.11 mW)

G = Antenna Gain (3.16 numeric)

R = Minimum Distance between User and Antenna (20 cm)

$$S = (721.11 * 3.16) / (4 * 3.14 * 20^2) = 2280.342 / 5024 = 0.454 \text{ mW/cm}^2$$

Since $S < 1 \text{ mW/cm}^2$, the minimum distance (R) is 20cm

EUT with 2.4GHz 8 dBi Omni Antenna

MPE Limit Calculation: EUT's operating frequencies @ 2412-2462 MHz; highest conducted power = *26.38dBm* (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT antenna gain = *6.31 dBi*.

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (1 mW/cm²)

P = Power Input to antenna (434.51 mW)

G = Antenna Gain (6.31 numeric)

R = Minimum Distance between User and Antenna (20 cm)

$$S = (434.51 * 6.31) / (4 * 3.14 * 20^2) = 2741.574 / 5024 = 0.546 \text{ mW/cm}^2$$

Since $S < 1 \text{ mW/cm}^2$, the minimum distance (R) is 20cm

EUT with 5.8GHz 9 dBi Omni Antenna

MPE Limit Calculation: EUT's operating frequencies @ 5745-5825 MHz; highest conducted power = *26.773 dBm* (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT antenna gain = *7.94 dBi*.

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (1 mW/cm²)

P = Power Input to antenna (475.66 mW)

G = Antenna Gain (7.94 numeric)

R = Minimum Distance between User and Antenna (20 cm)

$$S = (475.66 * 7.94) / (4 * 3.14 * 20^2) = 3776.74 / 5024 = 0.752 \text{ mW/cm}^2$$

Since $S < 1 \text{ mW/cm}^2$, the minimum distance (R) is 20cm

EUT with 5.8GHz 15 dBi Sector Antenna

MPE Limit Calculation: EUT's operating frequencies @ 5745-5825 MHz; highest conducted power = 20.938 dBm (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT antenna gain = 31.62 dBi.

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG} / 4\pi S$$

where, S = Power Density (1 mW/cm²)

P = Power Input to antenna (124.11 mW)

G = Antenna Gain (31.62 numeric)

R = Minimum Distance between User and Antenna (20 cm)

$$S = (124.11 * 31.62) / (4 * 3.14 * 20^2) = 3924.642 / 5024 = 0.781 \text{ mW/cm}^2$$

Since $S < 1 \text{ mW/cm}^2$, the minimum distance (R) is 20cm

EUT with 5.8GHz 16 dBi Panel Antenna

MPE Limit Calculation: EUT's operating frequencies @ 5745-5825 MHz; highest conducted power = 19.985 dBm (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT antenna gain = 39.81 dBi.

$$S = G / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG} / 4\pi S$$

where, S = Power Density (1 mW/cm²)

P = Power Input to antenna (99.65 mW)

G = Antenna Gain (39.81 numeric)

R = Minimum Distance between User and Antenna (20 cm)

$$S = (99.65 * 39.81) / (4 * 3.14 * 20^2) = 3967.345 / 5024 = 0.790 \text{ mW/cm}^2$$

Since $S < 1 \text{ mW/cm}^2$, the minimum distance (R) is 20cm