

## **Electromagnetic Compatibility Criteria for Intentional Radiators**

## **§ 15.407(f) RF Exposure**

RF Exposure Requirements: §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section

shall be operated in a manner that ensures that the public is not exposed to radio frequency

energy levels in excess of the Commission's guidelines.

RF Radiation Exposure Limit: §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit

shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which

shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ <u>5745-5805MHz</u>; highest conducted power = 22.78dBm (peak) therefore, Limit for Uncontrolled exposure: 1 mW/cm<sup>2</sup> or 10 W/m<sup>2</sup>

EUT maximum antenna gain = 9dBi Omni.

Equation from page 18 of OET 65, Edition 97-01

 $S = PG / 4\pi R^2$  or  $R = \int PG / 4\pi S$ 

where,  $S = Power Density (1 mW/cm^2)$ 

P = Power Input to antenna (189.6mW)

G = Antenna Gain (7.94 numeric)

 $S = (189.67*7.94 / 4*3.14*20.0^2) = (1506.607 / 5024) = 2.99 \text{ mW/cm}^2$ @ 20cm separation

EUT maximum antenna gain =  $\underline{16dBi \ Sector.}$ 

Equation from page 18 of OET 65, Edition 97-01

 $S = PG / 4\pi R^2$  or  $R = \int PG / 4\pi S$ 

where,  $S = Power Density (1 mW/cm^2)$ 

P = Power Input to antenna (189.6mW)

G = Antenna Gain (39.81 numeric)

 $R = (189.6*39.81 / 4*3.14*1.0)^{1/2} = (7550.922 / 12.56)^{1/2} = 24.51cm$ 

EUT maximum antenna gain = 19dBi Panel.

Equation from page 18 of OET 65, Edition 97-01

 $S = PG / 4\pi R^2$  or  $R = \int PG / 4\pi S$ 

where,  $S = Power Density (1 mW/cm^2)$ 

P = Power Input to antenna (189.6mW)

G = Antenna Gain (79.432 numeric)

 $R = (189.6*79.432 / 4*3.14*1.0)^{1/2} = (15066.07 / 12.56)^{1/2} = 34.63$ cm