

TEST REPORT

Reference No. : WTS18S08122666W
FCC ID..... : REY-FDW010
Applicant..... : SKYRC Technology Co., Ltd.
Address : 4,5,8/F, Building No. 4, MeiTai Industry Park, GuanGuang South Road, Guihua, Guanlan, longhua District, Shenzhen,guangdong China
Manufacturer : SKYRC Technology Co., Ltd.
Address : 4,5,8/F, Building No. 4, MeiTai Industry Park, GuanGuang South Road, Guihua, Guanlan, longhua District, Shenzhen,guangdong China
Product..... : Nutri
Model(s)..... : FDW010
Standards : FCC CFR47 Part 15 C Section 15.247: 2018
Date of Receipt sample..... : 2018-08-31
Date of Test..... : 2018-09-03 to 2018-09-11
Date of Issue : 2018-09-19
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.
The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Tested by:

Frank Yin

Frank Yin / Test Engineer

Approved by:



Phil Zhong

Phil Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation, the certification number is 4243.01) of USA, CNAS (China National Accreditation Service for Conformity Assessment, the registration number is L3110) of China. Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), ISED Canada (Innovation, Science and Economic Development Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

2.1 Test Facility

A. Accreditations for Conformity Assessment (International)

Country/Region	Scope Covered By	Scope	Note
USA	ISO/IEC 17025	FCC ID \ SDoC(VOC/DOC)	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		WPC	-
Thailand		NTC	-
Singapore		IDA	-
Note: 1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476. 2. ISED Canada Registration No.: 7760A			

B.TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd.	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

3 Contents

	Page
1 COVER PAGE	1
2 LABORATORIES INTRODUCTION	2
2.1 TEST FACILITY.....	3
3 CONTENTS	4
2. REVISION HISTORY	5
4 GENERAL INFORMATION	6
4.1 GENERAL DESCRIPTION OF E.U.T.....	6
4.2 DETAILS OF E.U.T.....	6
4.3 CHANNEL LIST.....	6
4.4 TEST MODE.....	7
5 EQUIPMENT USED DURING TEST	8
5.1 EQUIPMENTS LIST.....	8
5.2 MEASUREMENT UNCERTAINTY.....	9
5.3 TEST EQUIPMENT CALIBRATION.....	9
6 TEST SUMMARY	10
7 CONDUCTED EMISSION	11
7.1 E.U.T. OPERATION.....	11
7.2 EUT SETUP.....	11
7.3 MEASUREMENT DESCRIPTION.....	11
7.4 CONDUCTED EMISSION TEST RESULT.....	12
8 RADIATED EMISSIONS	14
8.1 EUT OPERATION.....	14
8.2 TEST SETUP.....	15
8.3 SPECTRUM ANALYZER SETUP.....	16
8.4 TEST PROCEDURE.....	17
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
8.6 SUMMARY OF TEST RESULTS.....	18
9 BAND EDGE MEASUREMENT	30
9.1 TEST PRODUCE.....	30
9.2 TEST RESULT.....	31
10 BANDWIDTH MEASUREMENT	35
10.1 TEST PROCEDURE:.....	35
10.2 TEST RESULT:.....	35
11 MAXIMUM CONDUCTED (AVERAGE) OUTPUT POWER	42
11.1 TEST PROCEDURE:.....	42
11.2 TEST RESULT:.....	42
12 POWER SPECTRAL DENSITY	43
12.1 TEST PROCEDURE:.....	43
12.2 TEST RESULT:.....	43
13 ANTENNA REQUIREMENT	50
14 FCC ID: REY-FDW010 RF EXPOSURE REPORT	51
15 PHOTOGRAPHS - MODEL FDW010 TEST SETUP PHOTOS	51
16 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS	51
16.1 MODEL FDW010 - EXTERNAL PHOTOS.....	51
16.2 MODEL FDW010 - INTERNAL PHOTOS.....	51

2. Revision History

Test report #	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS18S08122666W	2018-08-31	2018-09-03 to 2018-09-11	2018-09-19	Original	-	Valid

4 General Information

4.1 General Description of E.U.T

Product:	Nutri
Model(s):	FDW010
Operation Frequency:	802.11b/g/n HT20: 2412MHz~2462MHz 802.11n HT40: 2422MHz~2452MHz
RF output power	Wifi: 8.76dBm
Antenna installation:	Integrated Antenna
Antenna Gain:	0dBi
Type of modulation:	IEEE 802.11b (CCK/QPSK/BPSK, 11Mbps max.) IEEE 802.11g (BPSK/QPSK/16QAM/64QAM, 54Mbps max.) IEEE 802.11n (BPSK/QPSK/16QAM/64QAM, HT20: 72Mbps max., HT40: 150Mbps max.)

4.2 Details of E.U.T

Ratings

Input: AC 100-240V~, 50/60Hz
Output: DC 5V, 1A

4.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

4.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Power Spectral Density	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Frequency Range	802.11b	11 Mbps	1/11	TX
	802.11g	54 Mbps	1/11	TX
	802.11n HT20	108 Mbps	1/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Transmitter Spurious Emissions	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product.

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2017-09-12	2018-09-11
2.	LISN	R&S	ENV216	100115	2017-09-12	2018-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2017-09-12	2018-09-11
3m Semi-anechoic Chamber for Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2018-04-29	2019-04-28
2	Broad-band Horn Antenna(1-18GHz)	SCHWARZBECK	BBHA 9120 D	667	2018-04-29	2019-04-28
3	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2018-04-29	2019-04-28
4	Coaxial Cable (above 1GHz)	Top	1GHz-18GHz	EW02014-7	2018-04-29	2019-04-28
5	Spectrum Analyzer	R&S	FSP40	100501	2017-10-20	2018-10-19
6	Broad-band Horn Antenna(18-40GHz)	SCHWARZBECK	BBHA 9170	BBHA917065 1	2017-10-25	2018-10-24
7	Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	100472	2017-10-25	2018-10-24
8	Cable	Top	18-40GHz	-	2017-10-25	2018-10-24
3m Semi-anechoic Chamber for Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2018-04-29	2019-04-28
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2018-04-29	2019-04-28
3	Active Loop Antenna	Com-power	AL-130R	10160007	2018-04-17	2019-04-16
4	Amplifier	ANRITSU	MH648A	M43381	2018-04-29	2019-04-28
5	Cable	HUBER+SUHNER	CBL2	525178	2018-04-29	2019-04-28
6	Coaxial Cable (below 1GHz)	Top	TYPE16 (13M)	-	2017-09-12	2018-09-11
RF Conducted Testing						

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	R&S	FSL6	100959	2017-09-12	2018-09-11
2	Coaxial Cable	Top	10Hz-30GHz	-	2017-09-12	2018-09-11
3	Antenna Connector*	Realacc	45RSm	-	2017-09-12	2018-09-11
4	DC Block	Gwave	GDCB-3G-N-SMA	140307001	2017-09-12	2018-09-11

“*”: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by GUANG ZHOU GRG METROLOGY & TEST CO., LTD. address is No.163, Pingyun Rd. West of Huangpu Ave, Tianhe District, Guangzhou, Guangdong, China.

6 Test Summary

Test Items	Test Requirement	Result
Spurious Radiated Emissions	15.247 15.205(a) 15.209(a)	C
Conducted Emissions	15.207(a)	C
Conducted Spurious Emissions	15.247	C
Bandwidth	15.247(a)(2)	C
Maximum Peak Output Power	15.247(b)(3),(4)	C
Power Spectral Density	15.247(e)	C
Band Edge	15.247(d)	C
Antenna Requirement	15.203	C
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	C
Note: C=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.		

7 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)

7.1 E.U.T. Operation

Operating Environment :

Temperature: 21.5 °C
Humidity: 51.9 % RH


Atmospheric Pressure: 101.2kPa

EUT Operation : Transmitting mode

The test was performed in Transmitting mode, Only the worst case 802.11b mode were record in the report.

7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.




7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

7.4 Conducted Emission Test Result


An initial pre-scan was performed on the live and neutral lines.

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.4940	25.37	10.42	35.79	56.10	-20.31	QP	
2	0.4940	16.58	10.42	27.00	46.10	-19.10	AVG	
3	0.6300	18.69	10.47	29.16	56.00	-26.84	QP	
4	0.6300	9.84	10.47	20.31	46.00	-25.69	AVG	
5	1.2460	14.84	10.45	25.29	56.00	-30.71	QP	
6	1.2460	6.77	10.45	17.22	46.00	-28.78	AVG	
7	2.6820	14.21	10.67	24.88	56.00	-31.12	QP	
8	2.6820	5.42	10.67	16.09	46.00	-29.91	AVG	
9	4.1620	16.08	10.78	26.86	56.00	-29.14	QP	
10	4.1620	6.24	10.78	17.02	46.00	-28.98	AVG	
11	4.9340	15.12	10.81	25.93	56.00	-30.07	QP	
12	4.9340	4.65	10.81	15.46	46.00	-30.54	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Remark
1	0.4940	34.23	10.42	44.65	56.10	-11.45	QP	
2	0.4940	29.38	10.42	39.80	46.10	-6.30	AVG	
3	0.5899	23.67	10.48	34.15	56.00	-21.85	QP	
4	0.5899	18.37	10.48	28.85	46.00	-17.15	AVG	
5	0.8780	22.36	10.44	32.80	56.00	-23.20	QP	
6	0.8780	17.57	10.44	28.01	46.00	-17.99	AVG	
7	1.3300	23.58	10.46	34.04	56.00	-21.96	QP	
8	1.3300	18.73	10.46	29.19	46.00	-16.81	AVG	
9	2.0780	26.38	10.58	36.96	56.00	-19.04	QP	
10	2.0780	21.03	10.58	31.61	46.00	-14.39	AVG	
11	2.4420	25.86	10.65	36.51	56.00	-19.49	QP	
12	2.4420	20.43	10.65	31.08	46.00	-14.92	AVG	

8 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane;
For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high -pass filter is used during radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

8.6 Summary of Test Results

Test Frequency: 9kHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Low Channel 2412MHz									
36.90	48.63	QP	1	2.0	H	-17.50	31.13	40.00	-8.87
36.90	31.64	QP	206	1.0	V	-17.50	14.14	40.00	-25.86
4824.00	54.45	PK	351	1.8	V	-1.06	53.39	74.00	-20.61
4824.00	38.89	Ave	351	1.8	V	-1.06	37.83	54.00	-16.17
7236.00	49.08	PK	134	1.6	H	1.33	50.41	74.00	-23.59
7236.00	40.29	Ave	134	1.6	H	1.33	41.62	54.00	-12.38
2345.83	45.08	PK	230	1.1	V	-13.19	31.89	74.00	-42.11
2345.83	37.90	Ave	230	1.1	V	-13.19	24.71	54.00	-29.29
2366.28	42.85	PK	0	1.2	H	-13.14	29.71	74.00	-44.29
2366.28	37.85	Ave	0	1.2	H	-13.14	24.71	54.00	-29.29
2488.51	43.96	PK	121	1.7	V	-13.08	30.88	74.00	-43.12
2488.51	37.14	Ave	121	1.7	V	-13.08	24.06	54.00	-29.94

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Middle Channel 2437MHz									
36.90	50.12	QP	134	1.2	H	-17.50	32.62	40.00	-7.38
36.90	31.03	QP	51	1.2	V	-17.50	13.53	40.00	-26.47
4874.00	52.75	PK	338	1.1	V	-0.62	52.13	74.00	-21.87
4874.00	44.76	Ave	338	1.1	V	-0.62	44.14	54.00	-9.86
7311.00	45.25	PK	173	1.3	H	2.21	47.46	74.00	-26.54
7311.00	42.52	Ave	173	1.3	H	2.21	44.73	54.00	-9.27
2318.10	45.33	PK	182	1.5	V	-13.19	32.14	74.00	-41.86
2318.10	38.47	Ave	182	1.5	V	-13.19	25.28	54.00	-28.72
2370.41	42.32	PK	189	1.1	H	-13.14	29.18	74.00	-44.82
2370.41	38.85	Ave	189	1.1	H	-13.14	25.71	54.00	-28.29
2494.12	44.38	PK	220	1.5	V	-13.08	31.30	74.00	-42.70
2494.12	36.66	Ave	220	1.5	V	-13.08	23.58	54.00	-30.42

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: High Channel 2462MHz									
36.90	49.59	QP	227	1.6	H	-17.50	32.09	40.00	-7.91
36.90	32.37	QP	216	1.2	V	-17.50	14.87	40.00	-25.13
4924.00	48.98	PK	135	1.1	V	-0.24	48.74	74.00	-25.26
4924.00	44.72	Ave	135	1.1	V	-0.24	44.48	54.00	-9.52
7386.00	46.51	PK	201	2.0	H	2.84	49.35	74.00	-24.65
7386.00	42.25	Ave	201	2.0	H	2.84	45.09	54.00	-8.91
2344.67	45.74	PK	147	1.2	V	-13.19	32.55	74.00	-41.45
2344.67	38.85	Ave	147	1.2	V	-13.19	25.66	54.00	-28.34
2382.75	42.37	PK	37	1.5	H	-13.14	29.23	74.00	-44.77
2382.75	36.25	Ave	37	1.5	H	-13.14	23.11	54.00	-30.89
2489.08	44.04	PK	22	1.5	V	-13.08	30.96	74.00	-43.04
2489.08	37.12	Ave	22	1.5	V	-13.08	24.04	54.00	-29.96

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: Low Channel 2412MHz									
36.90	48.49	QP	229	1.7	H	-17.50	30.99	40.00	-9.01
36.90	30.18	QP	249	1.8	V	-17.50	12.68	40.00	-27.32
4824.00	47.49	PK	164	1.5	V	-1.06	46.43	74.00	-27.57
4824.00	48.70	Ave	164	1.5	V	-1.06	47.64	54.00	-6.36
7236.00	49.45	PK	38	1.1	H	1.33	50.78	74.00	-23.22
7236.00	45.10	Ave	38	1.1	H	1.33	46.43	54.00	-7.57
2313.97	45.31	PK	38	1.3	V	-13.19	32.12	74.00	-41.88
2313.97	38.28	Ave	38	1.3	V	-13.19	25.09	54.00	-28.91
2384.61	44.85	PK	24	2.0	H	-13.14	31.71	74.00	-42.29
2384.61	38.38	Ave	24	2.0	H	-13.14	25.24	54.00	-28.76
2488.65	43.69	PK	41	1.6	V	-13.08	30.61	74.00	-43.39
2488.65	36.48	Ave	41	1.6	V	-13.08	23.40	54.00	-30.60

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: Middle Channel 2437MHz									
36.90	48.29	QP	268	1.2	H	-17.50	30.79	40.00	-9.21
36.90	32.15	QP	40	2.0	V	-17.50	14.65	40.00	-25.35
4874.00	50.61	PK	257	1.1	V	-0.62	49.99	74.00	-24.01
4874.00	45.28	Ave	257	1.1	V	-0.62	44.66	54.00	-9.34
7311.00	48.34	PK	313	1.1	H	2.21	50.55	74.00	-23.45
7311.00	46.27	Ave	313	1.1	H	2.21	48.48	54.00	-5.52
2338.61	45.62	PK	306	1.9	V	-13.19	32.43	74.00	-41.57
2338.61	37.91	Ave	306	1.9	V	-13.19	24.72	54.00	-29.28
2386.00	42.02	PK	131	1.3	H	-13.14	28.88	74.00	-45.12
2386.00	36.44	Ave	131	1.3	H	-13.14	23.30	54.00	-30.70
2490.51	44.73	PK	295	1.8	V	-13.08	31.65	74.00	-42.35
2490.51	38.59	Ave	295	1.8	V	-13.08	25.51	54.00	-28.49

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: High Channel 2462MHz									
36.90	50.03	QP	348	1.8	H	-17.50	32.53	40.00	-7.47
36.90	32.09	QP	249	1.8	V	-17.50	14.59	40.00	-25.41
4924.00	51.70	PK	1	1.3	V	-0.24	51.46	74.00	-22.54
4924.00	43.61	Ave	1	1.3	V	-0.24	43.37	54.00	-10.63
7386.00	44.63	PK	119	1.5	H	2.84	47.47	74.00	-26.53
7386.00	42.31	Ave	119	1.5	H	2.84	45.15	54.00	-8.85
2324.85	45.15	PK	208	1.1	V	-13.19	31.96	74.00	-42.04
2324.85	39.73	Ave	208	1.1	V	-13.19	26.54	54.00	-27.46
2356.07	44.80	PK	56	1.7	H	-13.14	31.66	74.00	-42.34
2356.07	36.75	Ave	56	1.7	H	-13.14	23.61	54.00	-30.39
2489.93	44.12	PK	154	1.4	V	-13.08	31.04	74.00	-42.96
2489.93	37.32	Ave	154	1.4	V	-13.08	24.24	54.00	-29.76

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
n20: Low Channel 2412MHz									
36.90	49.63	QP	294	1.5	H	-17.50	32.13	40.00	-7.87
36.90	31.04	QP	30	1.5	V	-17.50	13.54	40.00	-26.46
4824.00	45.71	PK	350	1.2	V	-1.06	44.65	74.00	-29.35
4824.00	40.87	Ave	350	1.2	V	-1.06	39.81	54.00	-14.19
7236.00	47.47	PK	323	1.4	H	1.33	48.80	74.00	-25.20
7236.00	42.99	Ave	323	1.4	H	1.33	44.32	54.00	-9.68
2342.81	45.11	PK	72	1.3	V	-13.19	31.92	74.00	-42.08
2342.81	37.56	Ave	72	1.3	V	-13.19	24.37	54.00	-29.63
2357.40	43.03	PK	293	1.8	H	-13.14	29.89	74.00	-44.11
2357.40	37.98	Ave	293	1.8	H	-13.14	24.84	54.00	-29.16
2487.56	42.11	PK	151	1.8	V	-13.08	29.03	74.00	-44.97
2487.56	38.05	Ave	151	1.8	V	-13.08	24.97	54.00	-29.03

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
n20: Middle Channel 2437MHz									
36.90	47.85	QP	238	1.3	H	-17.50	30.35	40.00	-9.65
36.90	30.45	QP	9	1.3	V	-17.50	12.95	40.00	-27.05
4874.00	50.95	PK	290	1.9	V	-0.62	50.33	74.00	-23.67
4874.00	43.12	Ave	290	1.9	V	-0.62	42.50	54.00	-11.50
7311.00	47.17	PK	184	1.7	H	2.21	49.38	74.00	-24.62
7311.00	38.45	Ave	184	1.7	H	2.21	40.66	54.00	-13.34
2332.33	46.04	PK	72	1.1	V	-13.19	32.85	74.00	-41.15
2332.33	38.46	Ave	72	1.1	V	-13.19	25.27	54.00	-28.73
2389.45	43.16	PK	10	1.5	H	-13.14	30.02	74.00	-43.98
2389.45	38.61	Ave	10	1.5	H	-13.14	25.47	54.00	-28.53
2496.69	43.90	PK	29	1.3	V	-13.08	30.82	74.00	-43.18
2496.69	38.42	Ave	29	1.3	V	-13.08	25.34	54.00	-28.66

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
n20: High Channel 2462MHz									
36.90	48.03	QP	65	1.1	H	-17.50	30.53	40.00	-9.47
36.90	31.58	QP	73	1.9	V	-17.50	14.08	40.00	-25.92
4924.00	50.57	PK	49	1.8	V	-0.24	50.33	74.00	-23.67
4924.00	40.95	Ave	49	1.8	V	-0.24	40.71	54.00	-13.29
7386.00	50.66	PK	204	1.2	H	2.84	53.50	74.00	-20.50
7386.00	45.47	Ave	204	1.2	H	2.84	48.31	54.00	-5.69
2346.18	45.14	PK	263	1.5	V	-13.19	31.95	74.00	-42.05
2346.18	37.56	Ave	263	1.5	V	-13.19	24.37	54.00	-29.63
2350.80	44.99	PK	278	1.6	H	-13.14	31.85	74.00	-42.15
2350.80	36.21	Ave	278	1.6	H	-13.14	23.07	54.00	-30.93
2494.27	44.02	PK	184	1.5	V	-13.08	30.94	74.00	-43.06
2494.27	37.63	Ave	184	1.5	V	-13.08	24.55	54.00	-29.45

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
n40: Low Channel 2422MHz									
36.90	47.77	QP	209	1.1	H	-17.50	30.27	40.00	-9.73
36.90	30.75	QP	115	1.7	V	-17.50	13.25	40.00	-26.75
4844.00	44.02	PK	42	1.0	V	-1.06	42.96	74.00	-31.04
4844.00	35.26	Ave	42	1.0	V	-1.06	34.20	54.00	-19.80
7266.00	42.22	PK	40	1.7	H	1.33	43.55	74.00	-30.45
7266.00	39.20	Ave	40	1.7	H	1.33	40.53	54.00	-13.47
2318.23	45.63	PK	247	1.2	V	-13.19	32.44	74.00	-41.56
2318.23	39.40	Ave	247	1.2	V	-13.19	26.21	54.00	-27.79
2362.28	44.58	PK	161	1.5	H	-13.14	31.44	74.00	-42.56
2362.28	38.17	Ave	161	1.5	H	-13.14	25.03	54.00	-28.97
2498.48	44.93	PK	243	1.7	V	-13.08	31.85	74.00	-42.15
2498.48	37.76	Ave	243	1.7	V	-13.08	24.68	54.00	-29.32

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
n40: Middle Channel 2437MHz									
36.90	48.40	QP	60	2.0	H	-17.50	30.90	40.00	-9.10
36.90	31.46	QP	193	1.4	V	-17.50	13.96	40.00	-26.04
4874.00	46.81	PK	85	1.5	V	-0.62	46.19	74.00	-27.81
4874.00	41.73	Ave	85	1.5	V	-0.62	41.11	54.00	-12.89
7311.00	37.93	PK	130	2.0	H	2.21	40.14	74.00	-33.86
7311.00	36.80	Ave	130	2.0	H	2.21	39.01	54.00	-14.99
2344.04	46.04	PK	255	1.7	V	-13.19	32.85	74.00	-41.15
2344.04	37.38	Ave	255	1.7	V	-13.19	24.19	54.00	-29.81
2381.89	42.16	PK	170	1.8	H	-13.14	29.02	74.00	-44.98
2381.89	38.19	Ave	170	1.8	H	-13.14	25.05	54.00	-28.95
2496.29	43.49	PK	107	1.7	V	-13.08	30.41	74.00	-43.59
2496.29	37.93	Ave	107	1.7	V	-13.08	24.85	54.00	-29.15

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
n40: High Channel 2452MHz									
36.90	47.65	QP	256	1.1	H	-17.50	30.15	40.00	-9.85
36.90	32.36	QP	167	1.9	V	-17.50	14.86	40.00	-25.14
4904.00	49.31	PK	66	1.7	V	-0.24	49.07	74.00	-24.93
4904.00	41.62	Ave	66	1.7	V	-0.24	41.38	54.00	-12.62
7356.00	37.12	PK	266	1.3	H	2.84	39.96	74.00	-34.04
7356.00	38.88	Ave	266	1.3	H	2.84	41.72	54.00	-12.28
2345.00	46.96	PK	301	1.3	V	-13.19	33.77	74.00	-40.23
2345.00	38.74	Ave	301	1.3	V	-13.19	25.55	54.00	-28.45
2389.00	44.76	PK	185	1.1	H	-13.14	31.62	74.00	-42.38
2389.00	38.00	Ave	185	1.1	H	-13.14	24.86	54.00	-29.14
2498.51	42.21	PK	95	1.3	V	-13.08	29.13	74.00	-44.87
2498.51	37.50	Ave	95	1.3	V	-13.08	24.42	54.00	-29.58

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not recorded.

9 Band Edge Measurement


Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	558074 D01 15.247 Meas Guidance v05
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

9.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


9.2 Test Result

Test result plots shown as follows:




Date: 5.SEP.2018 03:58:51

TX 11b: Band edge-right side




Date: 5.SEP.2018 04:12:05

TX 11g: Band edge-left side




Date: 5.SEP.2018 04:14:50

TX 11g: Band edge-right side




Date: 5.SEP.2018 04:13:23

TX 11n HT20: Band edge-left side




Date: 5.SEP.2018 04:18:18

TX 11n HT20: Band edge-right side




Date: 5.SEP.2018 04:19:51

TX 11n HT40: Band edge-left side



Date: 5.SEP.2018 04:23:16

TX 11n HT40: Band edge-right side



Date: 5.SEP.2018 04:21:52

10 Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247


Test Method: 558074 D01 15.247 Meas Guidance v05

10.1 Test Procedure:


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

10.2 Test Result:

Operation mode	6dB Bandwidth (MHz)			99% Bandwidth (MHz)		
	Channel 1	Channel 6	Channel 11	Channel 1	Channel 6	Channel 11
TX 11b	10.080	10.112	10.112	14.240	14.240	14.240
TX 11g	16.600	16.600	16.600	16.500	16.450	16.450
TX 11n HT20	17.820	17.820	17.766	17.658	17.712	17.658
TX 11n HT40	36.380	36.450	36.410	35.970	35.970	35.970




Mode: TX 11b channel 6




Date: 5.SEP.2018 02:41:21

Mode: TX 11b channel 11




Date: 5.SEP.2018 02:43:46

Mode: TX 11g channel 1




Date: 5.SEP.2018 02:53:19

Mode: TX 11g channel 6




Date: 5.SEP.2018 02:51:16

Mode: TX 11g channel 11




Date: 5.SEP.2018 02:49:30

Mode: TX 11n HT20 channel 1




Date: 5.SEP.2018 02:56:17

Mode: TX 11n HT20 channel 6




Date: 5.SEP.2018 02:58:23

Mode: TX 11n HT20 channel 11




Date: 5.SEP.2018 03:01:52

Mode: TX 11n HT40 channel 3




Date: 5.SEP.2018 03:03:55

Mode: TX 11n HT40 channel 6



Date: 5.SEP.2018 03:06:04

Mode: TX 11n HT40 channel 9



Date: 5.SEP.2018 03:08:41

11 Maximum Conducted (average) Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: 558074 D01 15.247 Meas Guidance v05

11.1 Test Procedure:

558074 D01 15.247 Meas Guidance v05

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak, Set the span to fully encompass the DTS bandwidth.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

11.2 Test Result:

Test mode :TX 11b		
Maximum Conducted (average) Output Power (dBm)		
2412MHz	2437MHz	2462MHz
8.69	8.74	8.76
Limit: 1W/30dBm		
Test mode :TX 11g		
Maximum Conducted (average) Output Power (dBm)		
2412MHz	2437MHz	2462MHz
8.24	8.32	8.19
Limit: 1W/30dBm		
Test mode :TX 11n HT20		
Maximum Conducted (average) Output Power (dBm)		
2412MHz	2437MHz	2462MHz
8.17	8.10	8.20
Limit: 1W/30dBm		
Test mode :TX 11n HT40		
Maximum Conducted (average) Output Power (dBm)		
2422MHz	2437MHz	2452MHz
8.07	8.11	8.04
Limit: 1W/30dBm		

12 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: 558074 D01 15.247 Meas Guidance v05


12.1 Test Procedure:

558074 D01 15.247 Meas Guidance v05


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section
Submit this plot.

12.2 Test Result:


Test mode :TX 11b		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-9.36	-10.02	-9.93
Limit: 8dBm per 3kHz		
Test mode :TX 11g		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-8.88	-9.62	-9.23
Limit: 8dBm per 3kHz		
Test mode :TX 11n HT20		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-8.52	-9.15	-7.67
Limit: 8dBm per 3kHz		
Test mode :TX 11n HT40		
Power Spectral (dBm per 3kHz)		
2422MHz	2437MHz	2452MHz
-14.43	-13.23	-15.59
Limit: 8dBm per 3kHz		




Date: 5.SEP.2018 03:50:53




Date: 5.SEP.2018 03:52:44




Date: 5.SEP.2018 03:53:32




Date: 5.SEP.2018 03:49:56




Date: 5.SEP.2018 03:49:19




Date: 5.SEP.2018 03:48:00




Date: 5.SEP.2018 03:43:24




Date: 5.SEP.2018 03:45:18




Date: 5.SEP.2018 03:46:33



Date: 5.SEP.2018 03:41:57



Date: 5.SEP.2018 03:40:39



Date: 5.SEP.2018 03:39:21


13 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT have one Integrated Antenna, meets the requirements of FCC 15.203.



14 FCC ID: REY-FDW010 RF Exposure Report

Note: Please refer to RF Exposure Report: WTS18S08122666-2W.

15 Photographs - Model FDW010 Test Setup Photos

Note: Please refer to Photos: WTS18S08122666-3W.

16 Photographs - Constructional Details

16.1 Model FDW010 - External Photos

Note: Please refer to Photos: WTS18S08122666-3W.

16.2 Model FDW010 - Internal Photos

Note: Please refer to Photos: WTS18S08122666-3W.

=====**End of Report**=====