

SKYRC Technology Co.,Ltd.

4/F, Building No.6, Meitai Industry Park,
Guanguang South Road, Guihua, Guanlan,
518110, Baoan District, Shenzhen, CHINA

FCC Modular Approval Request

Number: **CF305**

Version: **V03**

Date: 01-08-2011

To the FCC or FCC TCB handling this application

Hereby we,

Company name (grantee) SKYRC Technology Co.,Ltd.

Address 4/F, Building No.6, Meitai Industry Park, Guanguang South Road, Guihua, Guanlan

City / ZIP / State / Country 518110, Baoan District, Shenzhen, CHINA

request **modular approval** for the certification of our equipment within this application, identified by:

FCC ID: REY-WIFIMODULE

The table below contains the justification for modular approval of this equipment:

Requirement	Explanation from grantee (do not write yes / no, but explain why it complies / how it is achieved)
1. The modular transmitter must have its own RF shielding.	Metal shield soldered to transceiver board.
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	The transceiver is permanently attached to on-board drivers which limits performance to within the FCC limits. These settings cannot be overwritten by any host.
3. The modular transmitter must have its own power supply regulation.	Power supply attached to modular transceiver.
4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable)..	The antenna is soldered on the transceiver (fixed antenna)
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed.	The test house tested the unit in stand alone configuration.
6. The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	Label will be provided on module and in equipment module is installed
7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.	The transceiver module will be sold for installation in host equipment. According to the document of FCC KDB, the product makes use of internal software to prevent the others to changing the firmware. The firmware is already burned into wifi module in advance. In addition, the wifi module does not have the interface that can be used to upgrade driver firmware.
8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.	The device will withstand exposure to external interference including any that may cause undesired operation. Module certification supports 20cm MPE situation.

Attestation (by grantee)

City and Country:	Date:	Name: (this must be a person)	Function:	Signature: (or official company stamp)
Enschede, The Netherlands	06-20-2014	M. Koop (authorized)	Manager	