



SGS-CSTC Standards  
Technical Services Ltd.

1/F., Building No. 1 Building, Agriculture Machinery Materials Co. Wushan  
Road, Shipai, Tianhe District, Guangzhou, China  
Telephone: +86 (0) 20 3848 1001 Fax: +86 (0) 20 3848 1006  
kent\_hsu@sgs.com



FEDERAL COMMUNICATIONS COMMISSION  
Registration number: 282399

Report No.: 03.10.1909EF-1  
Page: 1 of 16  
FCC ID: RF7SI654TX

## ***FCC TEST REPORT***

**Application No.** : 03.10.1909EF-1  
**Applicant** : STL INTERNATIONAL LTD  
**FCC ID** : RF7SI654TX  
**Fundamental Frequency** : 2.414GHz  
**Equipment under Test (EUT):**  
Name : TV Anywhere  
Model : SI654

**Standards** : FCC PART 15, SUBPART C : 2002  
**Date of Receipt** : 10 October 2003  
**Date of Test** : 12 to 15 October 2003  
**Date of Issue** : 25 October 2003

<b>Test Result :</b>	<b>PASS *</b>
----------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Kent Hsu  
Laboratory Manager  
SGS-CSTC Co., Ltd.

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf  
This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the SGS PRODUCT CERTIFICATION MARK.. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.  
This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



## 2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS .....	2
3 GENERAL INFORMATION.....	3
3.1 CLIENT INFORMATION .....	3
3.2 DETAILS OF E.U.T. ....	3
3.3 DESCRIPTION OF SUPPORT UNITS.....	3
3.4 TEST LOCATION .....	3
3.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	3
3.6 TEST FACILITY .....	4
4 TEST RESULTS.....	5
4.1 TEST INSTRUMENTS .....	5
4.2 E.U.T. OPERATION .....	5
4.3 TEST PROCEDURE & MEASUREMENT DATA.....	6
4.3.1 Radiated Emissions .....	6
4.3.2 Conducted Emissions Mains Terminals, 150kHz to 30MHz .....	10
4.3.3 Measurement Data .....	10
4.3.4 Occupied Bandwidth .....	11
5 PHOTOGRAPHS - RADIATED EMISSION TEST SETUP.....	12
6 PHOTOGRAPHS – CONDUCTED EMISSION TEST SETUP .....	13
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	14-16

### **3 General Information**

#### **3.1 Client Information**

Applicant: STL INTERNATIONAL LTD

Address of Applicant: TUNG KONG INDUSTRIAL ZONE.LIU MEI  
VILLAGE,YUEN ZHOU,BOLOU,PRC

#### **3.2 Details of E.U.T.**

Product Name: TV Anywhere

Model: SI654

Power Supply: 120Vac / 60Hz (for AC/DC Adapter supplied)  
AC/DC Adapter: Input: 120Vac/60Hz;  
Output: 9.0Vdc, 600mA.

Power Cord: 2.0 m , 2 wires unshielding DC cable

#### **3.3 Description of Support Units**

The EUT was tested as an independent unit: a 2.4GHz radio transmitter.

- 1.Test with a Playsation II as the AV input signal.
- 2.Test with a TV input system as the TV input signal.

#### **3.4 Test Location**

All tests were performed at:-

SGS-CSTC Standards Technical Services Ltd., Guangzhou Safety & EMC Laboratory, 1/F,  
Building No. 1, Agriculture Machinery Materials Company Warehouse Ltd., Wushan Road  
Shipai, Tianhe District, Guangzhou, China. P.C. 510630.

Tel: +86 20 3848 1001

Fax: +86 20 3848 1006

#### **3.5 Other Information Requested by the Customer**

None.

### **3.6 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP – Lab Code: 200611-0**  
SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 2000611-0. Effective through February 2, 2003.
- **ACA**  
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.
- **VCCI**  
The 3m Semi-anechoic chamber and Shielded Room (11.5m x 4m x 4m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1599 and C-1706 respectively.  
Date of Registration: February 28, 2003. Valid until May 30, 2005
- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FINKO**  
Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.
- **CNAL – LAB Code: L0141**  
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.
- **FCC – Registration No.: 282399**  
SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP, SGS-CSTC is an authorized test laboratory for the DoC process.

## 4 Test Results

### 4.1 Test Instruments

Test Equipment	Manufacturer	Model	Asset No.	Cal. Due Date
Temperature, Humidity & Barometer	Oregon Scientific	BA-888	EMC0003	25-07-2003
3m Semi- Anechoic Chamber	Frankonia	N/A	EMC0501	04-11-2003
EMI Test Receiver	ROHDE & SCHWARZ	ESCS30	EMC0506	17-11-2003
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 30	EMC0521	01-04-2004
Bilog Type Antenna	Schaffner Chase	CBL6143	EMC0519	01-12-2003
Horn Antenna	ROHDE & SCHWARZ	HF906	EMC0517	01-04-2004
Peramplifier	Agilent	8449B	EMC0520	30-06-2003
Coaxial cable	SGS	N/A	EMC0514	04-11-2003
Shielding Room	Frankonia	12 x 4 x 4 m <sup>3</sup>	EMC0103	N/A
LISN	Schaffner Chase	MNZ050D11	1421	05-11-2003
EMI Test Receiver	Rohde & Schwarz	ESCS30	100086	17-11-2003
Coaxial Cable	SGS	2m	EMC0107	01-06-2004

### 4.2 E.U.T. Operation

Input voltage: 120Vac / 60Hz (for AC/DC Adapter supplied)

Operating Environment:

Temperature: 24.0 °C

Humidity: 50 % RH

Atmospheric Pressure: 1006 mbar

EUT Operation:

Pre-test in transmitting mode with AV signal & transmitting mode with TV signal.  
Compliance test in transmitting mode AV signal since no worse case be found. (Two mode are almost same)

### 4.3 Test Procedure & Measurement Data

#### 4.3.1 Radiated Emissions

##### 4.3.1.1 Test in transmitting mode

Test Requirement: FCC Part15 C  
Test Method: Based on FCC Part15 C Section 15.249  
Test Date: 12 October 2003  
Measurement Distance: 3m (Semi-Anechoic Chamber)  
Frequency range 30 MHz – 25GHz for transmitting mode.  
Test instrumentation resolution bandwidth 120 kHz (30 MHz - 1000 MHz)  
1 MHz (1000 MHz – 25GHz)  
Receive antenna scan height 1 m - 4 m, polarization Vertical/Horizontal

Requirements:

Fundamental Frequency MHz	Field Strength of Fundamental (dBuV/m @ 3m)	Field Strength of Harmonics and Spurious Emissions (dBuV/m @ 3m)
902 to 928	94.0	54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0
24000 to 24250	108.0	68.0

The fundamental frequency of the EUT is 2414MHz

The limit for average field strength dBuV/m for the fundamental frequency= 94.0 dBuV/m.

No fundamental is allowed in the restricted bands.

The limit for average field strength dBuV/m for the harmonics and spurious frequencies = 54.0 dBuV/m. Spurious in the restricted bands must be less than 54.0 dBuV/m or 15.209.

**Test Procedure:** The procedure used was ANSI Standard C63.4-2000. The receive was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

The field strength is calculated by adding the Antenna Factor, Cable Factor & Peramplifier .  
The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Peramlifer Factor

The following test results were performed on the EUT on 12 October 2003:

1. Fundamental emission

Test Frequency (GHz)	Peak (dBuV/m)		Limits (dBuV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
2.414	108.8	106.5	114.0	5.2	7.5
Test Frequency (GHz)	Average (dBuV/m)		Limits (dBuV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
2.414	89.6	84.2	94.0	4.4	9.8

2. Harmonics & Spurious Emissions

Test Frequency (GHz)	Peak (dBuV/m)		Limits (dBuV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
4.828	66.4	63.8	74.0	7.6	10.2
7.242	61.5	64.2	74.0	12.5	9.8
9.656	55.6	42.3	74.0	18.4	31.7
12.070	38.2	37.6	74.0	35.8	36.4
14.484	37.2	36.8	74.0	36.8	37.2
16.898	36.8	35.6	74.0	37.2	38.4
Test Frequency (GHz)	Average (dBuV/m)		Limits (dBuV/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
4.828	47.6	44.9	54.0	6.4	9.1
7.242	43.8	43.0	54.0	10.2	11.0
9.656	40.5	41.2	54.0	13.5	12.8
12.070	36.2	37.0	54.0	17.8	17.0
14.484	36.8	36.6	54.0	17.2	17.4
16.898	36.5	35.0	54.0	17.5	19.0

**Remark:**

- 1). For this intentional radiator operates below 10 GHz, the spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the fifth harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 7<sup>th</sup> harmonic.
- 2). According to 15.249 (d) As shown in Section 15.35(b), for frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

**TEST RESULTS:** The unit does meet the FCC requirements.



### 3. Other Spurious Emissions. ( 30MHz-1000MHz)

Test Requirement: FCC Part15 Section 15.209  
 Test Method: Based on FCC Part15 B  
 Measurement Distance: 3m  
 Limit:  
     40.0 dB $\mu$ V/m between 30MHz & 88MHz  
     43.5 dB $\mu$ V/m between 88MHz & 216MHz  
     46.0 dB $\mu$ V/m between 216MHz & 960MHz  
     54.0 dB $\mu$ V/m above 960MHz  
 Detector: Peak for pre-scan (120kHz resolution bandwidth)  
             Quasi-Peak if maximised peak within 6dB of limit

The following quasi-peak measurements were performed on the EUT:

Frequency (MHz)	Antenna Polarization	Emission Level (dB $\mu$ V/m)	Limit dB $\mu$ V/m)	Margin (dB)
36.865	Vertical	29.0	40.0	11.0
64.875	Vertical	27.8	40.0	12.2
98.820	Vertical	27.9	43.5	15.6
232.640	Vertical	21.3	46.0	24.7
299.110	Vertical	23.4	46.0	22.6
768.063	Vertical	28.8	46.0	17.2
99.375	Horizontal	26.0	43.5	17.5
232.980	Horizontal	27.5	46.0	18.5
250.023	Horizontal	32.6	46.0	13.4
298.875	Horizontal	23.9	46.0	22.1
397.250	Horizontal	29.7	46.0	16.3
430.625	Horizontal	26.8	46.0	19.2

The field strength is calculated by adding the Antenna Factor, Cable Factor & Peramplifier .

The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Peramplifier Factor

TEST RESULTS: The unit does meet the FCC requirements.

#### 4.3.2 Conducted Emissions Mains Terminals, 150kHz to 30MHz

Test Requirement: FCC Part15 Section 15.207  
 Test Method: ANSI C63.4  
 Test Date: 13 October 2003  
 Frequency Range: 150KHz to 30MHz  
 Class / Severity: Class B  
 Detector: Peak for pre-scan (9kHz Resolution Bandwidth)  
 Operating Environment:  
     Temperature: 24.0 °C      Humidity: 52% RH      Atmospheric Pressure: 1012 Mbar  
 EUT Operation: Pre-test in transmitting mode with AV signal & transmitting mode with TV signal. Compliance test in transmitting mode AV signal since no worse case be found. (Two mode are almost same)  
     As appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

#### 4.3.3 Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

The following Quasi-Peak and Average measurements were performed on the EUT.:

Freq. MHz	Line	QP Level dBuV	Limit dBuV	Margin dB	AV Level dBuV	Limit dBuV	Margin dB
0.177	Live	36.8	64.6	27.8	33.9	54.6	20.7
0.235	Live	29.5	62.3	32.8	28.4	52.3	23.9
0.354	Live	26.0	58.9	32.9	25.2	48.9	23.7
0.945	Live	22.8	60.0	37.2	22.0	50.0	28.0
2.780	Live	25.2	60.0	34.8	22.3	50.0	27.7
16.015	Live	24.0	60.0	36.0	16.3	50.0	33.7
0.150	Neutral	34.7	66.0	31.3	9.6	56.0	46.4
0.177	Neutral	37.1	64.6	27.5	34.2	54.6	20.4
0.240	Neutral	27.1	62.3	35.2	25.9	52.3	26.4
0.357	Neutral	25.4	58.9	33.5	24.8	48.9	24.1
2.725	Neutral	26.5	60.0	33.5	24.6	50.0	25.4
15.698	Neutral	28.2	60.0	31.8	23.6	50.0	26.4

TEST RESULTS: The unit does meet the FCC requirements.

## 4.3.4 Occupied Bandwidth

Test Requirement: FCC Part15 C  
Test Method: Based on FCC Part15 C Section 15.249:  
Test Date: 15 October 2003

Requirements: 15.249 (c) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Method of measurement: A small sample of the transmitter output was fed into the Spectrum Analyzer and the attached plot was taken. The vertical is set to 10dB per division. The horizontal scale is set to 100KHz per division.

The graph as below, represents the emissions take for this device.



The results: The unit does meet the FCC requirements.