

Test report No:  
NIE: 69743RAN.005

## Assessment report

### RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091; FCC 47 CFR Part 1.1307 FCC 47 CFR Part 1.1310

(*) Identification of item under evaluation	CR50 Communications Controller
(*) Trademark	Leica
(*) Model and /or type reference	CR50
(*) Other identification of the product	HW version: 2A SW version: 0.1.1707 Contains FCC ID: N7NEM75 Contains IC: 2417C-EM75
(*) Features	Bluetooth, 802.11 @2.4GHz, E, 400/900 Mhz Radio
(*) Manufacturer	LEICA GEOSYSTEMS AG Heinrich-Wild-Strasse, 9435 Heerbrugg, Switzerland
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. FCC 47 CFR Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared. FCC 47 CFR Part 1.1310: Radiofrequency radiation exposure limits.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2022-09-30
Report template No	FAN36_02 (*) "Data provided by the client"

# Index

Competences and guarantees .....	3
General conditions .....	3
Data provided by the client.....	3
Identification of the client.....	3
Document history .....	3
Appendix A: FCC RF Exposure assessment result .....	4
General description of the device under evaluation .....	5
Evaluation Results.....	6
Appendix B: FCC RF Exposure information .....	7
RF Exposure determination of exemption.....	8
RF Exposure evaluation .....	10

## Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

## General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

## Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "General description of the device", "Other identification of the product").
2. Maximum output power for 3G, LTE and SRD technologies, maximum antenna gain and use distance information.
3. The device under evaluation consists of an On-machine communication unit.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Identification of the client

LEICA GEOSYSTEMS AG  
Heinrich-Wild-Strasse, 9435 Heerbrugg, Switzerland

## Document history

Report number	Date	Description
69743RAN.005	2022-09-30	First release

## Appendix A: FCC RF Exposure assessment result

## General description of the device under evaluation

The device under evaluation consists of an On-machine communication unit.

According to the manufacturer, during its normal use, the separation distance between the radiating structures of the device and nearby users will be greater than 30 cm.

The equipment specifications for each supported technology are shown in Table 1. Values corresponding to UMTS, LTE and SRD technologies and antenna gain have been declared by the manufacturer. Values corresponding to 802.11b/g/n and Bluetooth output power have been measured and stated into DEKRA Testing and Certification, S.A.U. test report num. 69743RRF.011.

Technology / Mode	Band	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Antenna peak gain (dBi)	Maximum E.R.P. (dBm)	Maximum E.R.P. (mW)
UMTS	II	1850 - 1910	24.00	2.50	24.35	272.27
UMTS	IV	1710 - 1755	24.00	2.50	24.35	272.27
UMTS	V	824 - 849	24.00	2.50	24.35	272.27
LTE	2	1850 - 1910	24.00	2.50	24.35	272.27
LTE	4	1710 - 1755	24.00	2.50	24.35	272.27
LTE	5	824 - 849	24.00	2.50	24.35	272.27
LTE	7	2500 - 2570	23.00	2.50	23.35	216.27
LTE	12	699 - 716	24.00	2.50	24.35	272.27
LTE	13	777 - 787	24.00	2.50	24.35	272.27
LTE	26	814 - 849	24.00	2.50	24.35	272.27
LTE	41	2496 - 2690	23.00	2.50	23.35	216.27
LTE	42	3400 - 3600	23.00	2.50	23.35	216.27
LTE	43	3600 - 3800	23.00	2.50	23.35	216.27
LTE	48	3550 - 3700	23.00	2.50	23.35	216.27
LTE	66	1710 - 1780	24.00	2.50	24.35	272.27
802.11b/g/n	2.4 GHz	2412 - 2484	13.42	5.20	16.47	44.36
Bluetooth	2.4 GHz	2400 - 2483.5	2.23	5.20	5.28	3.37
SRD	400	403 - 473	29.35	0.00	27.20	524.81
SRD	900	902 - 928	29.35	0.00	27.20	524.81

**Table 1:** Equipment specifications

## Evaluation Results

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Power density (mW/cm <sup>2</sup> )	FCC General Population Limit (mW/cm <sup>2</sup> )	Verdict
UMTS	II	1850 - 1910	30.00	0.04	1.00	Pass
UMTS	IV	1710 - 1755	30.00	0.04	1.00	Pass
UMTS	V	824 - 849	30.00	0.04	0.55	Pass
LTE	2	1850 - 1910	30.00	0.04	1.00	Pass
LTE	4	1710 - 1755	30.00	0.04	1.00	Pass
LTE	5	824 - 849	30.00	0.04	0.55	Pass
LTE	7	2500 - 2570	30.00	0.03	1.00	Pass
LTE	12	699 - 716	30.00	0.04	0.47	Pass
LTE	13	777 - 787	30.00	0.04	0.52	Pass
LTE	26	814 - 849	30.00	0.04	0.54	Pass
LTE	41	2496 - 2690	30.00	0.03	1.00	Pass
LTE	42	3400 - 3600	30.00	0.03	1.00	Pass
LTE	43	3600 - 3800	30.00	0.03	1.00	Pass
LTE	48	3550 - 3700	30.00	0.03	1.00	Pass
LTE	66	1710 - 1780	30.00	0.04	1.00	Pass
802.11b/g/n	2.4 GHz	2412 - 2484	30.00	0.00643	1.00	Pass
Bluetooth	2.4 GHz	2400 - 2483.5	30.00	0.00049	1.00	Pass
SRD	400	403 - 473	30.00	0.08	0.27	Pass
SRD	900	902 - 928	30.00	0.08	0.60	Pass

**Table 2:** FCC Evaluation Results

The computed value(s) are below the limit(s), so these modes meet the requirements stated in FCC 47 CFR Part 1.1307.

### Simultaneous transmission assessment:

Simultaneous technologies and modes	Result ( $\sum$ of Pout/Pmax ratios)	Verdict ( $\sum \leq 1$ )
LTE 12 + 802.11b/g/n 2.4 GHz + SRD 400	0.37	Pass
LTE 12 + 802.11b/g/n 2.4 GHz + SRD 900	0.22	Pass
LTE 12 + Bluetooth 2.4 GHz + SRD 400	0.37	Pass
LTE 12 + Bluetooth 2.4 GHz + SRD 900	0.21	Pass

**Table 3:** Simultaneous Transmission assessment

## Appendix B: FCC RF Exposure information

## RF Exposure determination of exemption

According to FCC 47 CFR §1.1307 (b)(3) Determination of exemption:

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2)), a single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2 R^2$ .



(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated,k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit,k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

## RF Exposure evaluation

Limits for Maximum Permissible Exposure (MPE) for RF sources are defined in FCC 47 CFR “§1.1310 Radiation Exposure limits, paragraph (e)”:

TABLE 1 TO §1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. \* = Plane-wave equivalent power density.

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst-case" or conservative prediction:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

Where:

S = power density

$P_{E.I.R.P.}$  = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

P<sub>T</sub> = transmitter output power (including tune-up tolerance)

G<sub>T</sub> = gain of the transmitting antenna

L<sub>C</sub> = signal attenuation in the connecting cable between the transmitter and the antenna if applicable