



<b>FCC TEST REPORT</b> <b>FCC 47 CFR Part 22H</b> <b>Industry Canada RSS-132, Issue 3</b> <b>Cellular Telephones Operating in the Bands 824-849MHz and 869-894MHz</b> <b>FCC 47 CFR Part 24E</b> <b>Industry Canada RSS-133, Issue 6</b> <b>2GHz Personal Communication Services</b>	
<b>Report Reference No.</b> .....	G0M-1406-3915-TFC224GS-V01
<b>Testing Laboratory</b> .....	Eurofins Product Service GmbH
Address.....	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation .....	<div style="display: flex; justify-content: center; align-items: center;">   </div> <p style="text-align: center; font-size: small;">A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A</p>
<b>Applicant's name</b> .....	Leica Geosystems AG
Address.....	Heinrich Wild Strasse 9435 Heerbrugg SWITZERLAND
<b>Test specification:</b>	
Standard .....	47 CFR Part 22H, 47 CFR Part 24E RSS-132, Issue 3 : 2013-01, RSS-133, Issue 6 : 2013-01 SRSP-503 Issue 7 : 2008-09, SRSP-510 Issue 5 : 2009-02 RSS-Gen, Issue 4, 2014-11, ANSI/TIA-603-C-2004
<b>Equipment under test (EUT):</b>	
Product description	Field Controller Win EC7
Model No.	CS20 CDMA Disto
Additional Model(s)	None
Brand Name(s)	Leica Geosystems
Hardware version	V5.0
Firmware / Software version	None
	FCC-ID: RFD-CSNGC                      IC: 3177A-CSNGC
<b>Test result</b>	<b>Passed</b>

**Possible test case verdicts:**

- neither assessed nor tested .....: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object .....: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

**Testing:**

Test Lab Temperature.....: 20 – 23 °C

Test Lab Humidity .....: 32 – 38 %

Date of receipt of test item .....: 2014-09-22

Date (s) of performance of tests .....: 2014-12-03 - 2014-12-04

Compiled by .....: Christian Weber

Tested by (+ signature).....: Burkhard Pudell *B. Pudell*  
 (Responsible for Test) .....

Approved by (+ signature) .....: Christian Weber *C. Weber*  
 .....

Date of issue .....: 2015-04-20

Total number of pages .....: 122

**General remarks:**

**The test results presented in this report relate only to the object tested.**  
**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**Additional comments:**

Test case selection is based on full modular approval of licensed transmitter module used by the EUT. The EUT uses a GSM/GPRS module with full modular approval according to FCC and IC rules. For details about the radio module see EUT description in section 1.

---

## Version History

Version	Issue Date	Remarks	Revised by
01	2015-04-20	Initial Release	

---

## REPORT INDEX

<b>1</b>	<b>EQUIPMENT (TEST ITEM) DESCRIPTION</b>	<b>5</b>
1.1	Photos – Equipment External	7
1.2	Photos – Equipment internal	8
1.3	Photos – Test setup	10
1.4	Supporting Equipment Used During Testing	11
1.5	Test Modes	12
1.6	Test Equipment Used During Testing	13
1.7	Sample emission level calculation	14
<b>2</b>	<b>RESULT SUMMARY</b>	<b>15</b>
<b>3</b>	<b>TEST CONDITIONS AND RESULTS</b>	<b>16</b>
3.1	Test Conditions and Results – Occupied Bandwidth	16
3.2	Test Conditions and Results – Effective radiated power / Equivalent isotropic radiated power	30
3.3	Test Conditions and Results – Transmitter radiated emissions	32
3.4	Test Conditions and Results – Receiver radiated emissions	35
ANNEX A	Transmitter radiated spurious emissions	37
ANNEX B	Receiver radiated spurious emissions	109

## 1 Equipment (Test item) Description

<b>Description</b>	Field Controller Win EC7		
<b>Model</b>	CS20 CDMA Disto		
<b>Additional Model(s)</b>	None		
<b>Brand Name(s)</b>	Leica Geosystems		
<b>Serial number</b>	None		
<b>Hardware version</b>	V5.0		
<b>Software / Firmware version</b>	None		
<b>FCC-ID</b>	RFD-CSNGC		
<b>IC</b>	3177A-CSNGC		
<b>Equipment type</b>	End product		
<b>Equipment classification</b>	Portable Device (Human Body distance < 20 cm)		
<b>Radio type</b>	Transceiver		
<b>Radio technology</b>	GSM850 / GSM1900		
<b>Operating frequency range</b>	GSM850 : TX = 824 - 849 MHz, RX = 869 - 894 MHz GSM1900 : TX = 1850 - 1910 MHz, RX = 1930 - 1990 MHz		
<b>Assigned frequency band</b>	Cell. Service Block A & B : 824 - 849 MHz & 869 - 894 MHz Broadband PCS : 1850 - 1910 MHz & 1930 - 1990 MHz		
<b>Main test frequencies GSM850</b>	F <sub>LOW</sub>	CH : 128 UL: 824.2 MHz	CH : 128 DL: 869.2 MHz
	F <sub>MID</sub>	CH : 188 UL: 836.2 MHz	CH : 188 DL: 881.2 MHz
	F <sub>HIGH</sub>	CH : 251 UL: 848.8 MHz	CH : 251 DL: 893.8 MHz
<b>Main test frequencies GSM1900</b>	F <sub>LOW</sub>	CH : 512 UL: 1850.2 MHz	CH : 512 DL: 1930.2 MHz
	F <sub>MID</sub>	CH : 661 UL: 1880.0 MHz	CH : 661 DL: 1960.0 MHz
	F <sub>HIGH</sub>	CH : 810 UL: 1909.8 MHz	CH : 810 DL: 1989.8 MHz
<b>Supported transmission modes</b>	GSM, GPRS, EGPRS		
<b>Modulations</b>	GSM, GPRS : GMSK, EGPRS : 8PSK		
<b>Multislot class</b>	12		
<b>Number of antennas</b>	1		
<b>Radio module</b>	Type	GSM/GPRS/EGPRS module	
	Model	PXS8	
	Manufacturer	Gemalto	
	HW Version	B2	
	SW Version	3.001	
	FCC-ID	QIPPXS8	
	IC	7830A-PXS8	
<b>Antenna</b>	Type	integrated	
	Model	P522303	
	Manufacturer	Ethertronics	
	Gain	2.8 dBi	

---

Test Report No.: G0M-1406-3915-TFC224GS-V01

---

<b>Manufacturer</b>	Leica Geosystems AG Heinrich Wild Strasse 9435 Heerbrugg SWITZERLAND	
<b>Power supply</b>	V <sub>NOM</sub>	11.1 VDC (Lithium Battery)
	V <sub>MIN</sub>	N/A
	V <sub>MIN</sub>	N/A
<b>AC/DC-Adaptor</b>	Model	N/A
	Vendor	N/A
	Input	N/A
	Output	N/A

#### 1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
SIM	Communication Tester	R&S	CMW500	
<p><b>*Note:</b> Use the following abbreviations:</p> <p>AE : Auxiliary/Associated Equipment, or</p> <p>SIM : Simulator (Not Subjected to Test)</p> <p>CABL : Connecting cables</p>				

**1.5 Test Modes**

<b>Mode #</b>	<b>Description</b>	
GPRS850	General conditions:	EUT powered by battery. Active call to communication tester.
	Radio conditions:	Mode = transmit Connection = packet switched Modulation = GMSK Slot configuration = 1 up / 1 down Power level = Maximum (GAMMA 3)
EGPRS850	General conditions:	EUT powered by battery. Active call to communication tester.
	Radio conditions:	Mode = transmit Connection = packet switched Modulation = 8-PSK Slot configuration = 1 up / 1 down Power level = Maximum (GAMMA 5)
GPRS1900	General conditions:	EUT powered by battery. Active call to communication tester.
	Radio conditions:	Mode = transmit Connection = packet switched Modulation = GMSK Slot configuration = 1 up / 1 down Power level = Maximum (GAMMA 3)
EGPR1900	General conditions:	EUT powered by battery. Active call to communication tester.
	Radio conditions:	Mode = transmit Connection = packet switched Modulation = 8-PSK Slot configuration = 1 up / 1 down Power level = Maximum (GAMMA 5)
IDLE850	General conditions:	EUT powered by battery.
	Radio conditions:	Mode = idle
IDLE1900	General conditions:	EUT powered by battery
	Radio conditions:	Mode = idle



**1.6 Test Equipment Used During Testing**

<b>Measurement Software</b>			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2014.1.15

<b>Occupied Bandwidth</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSEK 30	EF00168	2014-01	2015-01

<b>Radiated power</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 1	EF00062	-	-
Spectrum Analyzer	R&S	FSEK 30	EF00168	2014-01	2015-01
Biconical Antenna	R&S	HK 116	EF00012	2013-02	2016-02
LPD Antenna	R&S	HL 223	EF00187	2014-03	2017-03
Horn antenna	Schwarzbeck	BBHA 9120D	EF00019	2014-03	2016-03

<b>Radiated spurious emissions</b>					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 1	EF00062	-	-
Spectrum Analyzer	R&S	FSEK 30	EF00168	2014-01	2015-01
Biconical Antenna	R&S	HK 116	EF00012	2013-02	2016-02
LPD Antenna	R&S	HL 223	EF00212	2013-02	2016-02
Horn antenna	Schwarzbeck	BBHA 9120D	EF00019	2014-03	2016-03

## 1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB $\mu$ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB $\mu$ V/m). The FCC limits are given in units of  $\mu$ V/m. The following formula is used to convert the units of  $\mu$ V/m to dB $\mu$ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 \cdot \log(\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:


$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading} - \text{FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

## 2 Result Summary

FCC 47 CFR Part 22H, 24E, IC RSS-132, 133				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
FCC § 2.1049 RSS-Gen 6.6	Occupied Bandwidth	RSS-Gen 6.6		Informational only
FCC § 24.235 FCC § 22.355 IC RSS-132 § 4.3 IC RSS-133 § 6.3	Frequency stability	FCC § 24.235 FCC § 22.355 IC RSS-132 § 4.3 IC RSS-133 § 6.3	N/R	Conducted results of licensed radio unaffected. See module radio report.
FCC § 22.913(a)	Effective radiated power	ANSI/TIA-603-C	PASS	
FCC § 24.232(c) IC RSS-132 § 4.4 IC RSS-133 § 6.4	Equivalent isotropic radiated power	ANSI/TIA-603-C	PASS	
FCC § 24.232(d) IC RSS-133 § 6.4	Peak to average ratio	FCC § 24.232(d) IC RSS-133 § 6.4	N/R	Conducted results of licensed radio unaffected. See module radio report
FCC § 22.917(b) FCC § 24.238(b) IC RSS-132 § 4.5 IC RSS-133 § 6.5	Band-edge compliance	FCC § 22.917(b) FCC § 24.238(b) IC RSS-132 § 4.5 IC RSS-133 § 6.5	N/R	Conducted results of licensed radio unaffected. See module radio report
FCC § 22.917(a) FCC § 24.238(a) IC RSS-132 § 4.5 IC RSS-133 § 6.5	Conducted out-of-band emissions	FCC § 22.917(a) FCC § 24.238(a) IC RSS-132 § 4.5 IC RSS-133 § 6.5	N/R	Conducted results of licensed radio unaffected. See module radio report
FCC § 22.917(a) FCC § 24.238(a) IC RSS-132 § 4.5 IC RSS-133 § 6.5	Radiated out-of-band emissions	ANSI/TIA-603-C	PASS	
IC RSS-132 § 4.6 IC RSS-133 § 6.6 IC RSS-Gen 7.1	Receiver radiated spurious emissions	IC RSS-132 § 4.6 IC RSS-133 § 6.6 IC RSS-Gen 7.1	PASS	
<b>Remarks:</b>				

### 3 Test Conditions and Results

#### 3.1 Test Conditions and Results – Occupied Bandwidth

Occupied Bandwidth acc. to FCC Part 2 / IC RSS-Gen			
Test according to measurement reference	Reference Method		
	RSS-Gen 6.6		
Test frequency range	Tested frequencies		
	$F_{LOW} / F_{MID} / F_{HIGH}$		
<b>Limits</b>			
None (Informational only)			
<b>Test setup</b>			
 <pre> graph LR     SA[Spectrum Analyzer] --- EUT[EUT]             </pre>			
<b>Test procedure</b>			
<ol style="list-style-type: none"> <li>1. EUT set to test mode (Communication tester is used if needed)</li> <li>2. Span set to at least twice the emission spectrum</li> <li>3. Resolution bandwidth set to 1 % of span</li> <li>4. Occupied Bandwidth (99 %) measurement with spectrum analyzer built in measurement function</li> </ol>			
<b>Test results – GSM850</b>			
Channel	Frequency [MHz]	Mode	Occupied Bandwidth [kHz]
$F_{LOW}$	824.2	GPRS850	244.489
$F_{MID}$	836.2	GPRS850	244.489
$F_{HIGH}$	848.8	GPRS850	242.485
$F_{LOW}$	824.2	EGPRS850	242.485
$F_{MID}$	836.2	EGPRS850	240.481
$F_{HIGH}$	848.8	EGPRS850	242.485


<b>Test results – GSM1900</b>			
<b>Channel</b>	<b>Frequency [MHz]</b>	<b>Mode</b>	<b>Occupied Bandwidth [kHz]</b>
F <sub>LOW</sub>	1850.2	GPRS1900	244.489
F <sub>MID</sub>	1880	GPRS1900	244.489
F <sub>HIGH</sub>	1909.8	GPRS1900	244.489
F <sub>LOW</sub>	1850.2	EGPRS1900	244.489
F <sub>MID</sub>	1880	EGPRS1900	244.489
F <sub>HIGH</sub>	1909.8	EGPRS1900	244.489
Comments:			

Occupied Bandwidth – GSM850 F<sub>Low</sub>

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: GPRS 850 / CH: 128 / Gamma:3 ( 33 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.489 kHz




Occupied Bandwidth – GSM850 F<sub>MID</sub>

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: GPRS 850 / CH: 188 / Gamma:3 ( 33 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.489 kHz




Occupied Bandwidth – GSM850 F<sub>HIGH</sub>

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: GPRS 850 / CH: 251 / Gamma:3 ( 33 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 242.485 kHz






**Occupied Bandwidth – EGPRS850 F<sub>Low</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915


Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: EDGE 850 / CH: 128 / Gamma:6 ( 27 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 242.485 kHz



**Occupied Bandwidth – EGPRS850 F<sub>MID</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915


Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: EDGE 850 / CH: 188 / Gamma:6 ( 27 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 240.481 kHz



**Occupied Bandwidth – EGPRS850 F<sub>HIGH</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915


Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: EDGE 850 / CH: 251 / Gamma:6 ( 27 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 242.485 kHz



**Occupied Bandwidth – GSM1900 F<sub>Low</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: GPRS 1900 / CH: 512 / Gamma:3 ( 30 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.489 kHz




Occupied Bandwidth – GSM1900 F<sub>MID</sub>

Occupied Bandwidth acc. to RSS-Gen

Project Number: G0M-1406-3915


Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: GPRS 1900 / CH: 661 / Gamma:3 ( 30 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.489 kHz



**Occupied Bandwidth – GSM1900 F<sub>HIGH</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915


Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: GPRS 1900 / CH: 810 / Gamma:3 ( 30 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.489 kHz



**Occupied Bandwidth – EGPRS1900 F<sub>Low</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915


Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: EDGE 1900 / CH: 512 / Gamma:5 ( 26 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.489 kHz



**Occupied Bandwidth – EGPRS1900 F<sub>MID</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: EDGE 1900 / CH: 661 / Gamma:5 ( 26 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.89 kHz







**Occupied Bandwidth – EGPRS1900 F<sub>HIGH</sub>**
**Occupied Bandwidth acc. to RSS-Gen**

Project Number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Burkhard Pudell  
 Test Conditions: Tnom / Vnom  
 Mode: EDGE 1900 / CH: 810 / Gamma:5 ( 26 dBm ) / Main Slot 2  
 Test Date: 2014-12-04  
 Verdict: NONE (INFORMATION ONLY)  
 Note 1: A spectrum analyzer with an integrated 99% power bandwidth function is used  
 Note 2: OBW = 244.489 kHz




**3.2 Test Conditions and Results – Effective radiated power / Equivalent isotropic radiated power**

Radiated power acc. to FCC 22H / FCC 24E / IC RSS-132 / IC RSS-133		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC § 22.913(a) / FCC § 24.232(c) IC RSS-132 § 4.4 /IC RSS-133 § 6.4	
Test according to measurement reference	Reference Method	
	FCC § 22.913(a) / FCC § 24.232(c) / ANSI/TIA-603-C IC RSS-132 § 4.4 /IC RSS-133 § 6.4	
Test frequency range	Tested frequencies	
	$F_{LOW} / F_{MID} / F_{HIGH}$	
Limits		
Frequency range	Equipment type	Power limit
824-849 MHz	Mobile transmitter	FCC : 7 Watts (38.45 dBm) e.i.r.p. IC : 11.5 Watts (40.6 dBm) e.i.r.p.
1850-1910 MHz	Mobile transmitter	FCC : 2 Watts (33 dBm) e.i.r.p. IC : 2 Watts (33 dBm) e.i.r.p.
Test setup		
 <p>The diagram illustrates the test setup within a semi-anechoic chamber. An Amplifier Matrix (blue box) is connected to a Measurement Receiver (yellow box). The Measurement Receiver is connected to a measurement antenna (represented by a vertical line with a horizontal bar) inside the chamber. The EUT (yellow box) is placed on a Turn table (vertical line) inside the chamber. The chamber has a Ground Plane (hatched area) at the bottom. The measurement antenna is positioned vertically, and the EUT is rotated on the turn table.</p>		
Test procedure		
<ol style="list-style-type: none"> <li>1. EUT set to test mode</li> <li>2. The radiated power is measured with a measurement antenna in vertical polarization</li> <li>3. To obtain maximum level the EUT is rotated</li> <li>4. The EUT is replaced with a half-wave dipole and the power to the dipole is adjusted to obtain same radiated power measurement value</li> </ol>		

<b>Test results – GSM850 E.R.P.</b>							
Channel	Frequency [MHz]	Mode	Pol.	Power [dBm e.r.p]	Limit [dBm e.r.p]	Margin [dB]	Result
F <sub>LOW</sub>	824.2	GPRS850	hor	28.2	38.45	-10.25	PASS
F <sub>MID</sub>	836.2	GPRS850	hor	28.4	38.45	-10.05	PASS
F <sub>HIGH</sub>	848.8	GPRS850	hor	28.6	38.45	-09.85	PASS
F <sub>LOW</sub>	824.2	EGPRS850	hor	22.6	38.45	-15.85	PASS
F <sub>MID</sub>	836.2	EGPRS850	hor	22.8	38.45	-15.65	PASS
F <sub>HIGH</sub>	848.8	EGPRS850	hor	22.6	38.45	-15.85	PASS
<b>Test results – GSM850 E.I.R.P.</b>							
Channel	Frequency [MHz]	Mode	Pol.	Power [dBm e.i.r.p]	Limit [dBm e.i.r.p]	Margin [dB]	Result
F <sub>LOW</sub>	824.2	GPRS850	hor	30.35	40.6	-10.25	PASS
F <sub>MID</sub>	836.2	GPRS850	hor	30.55	40.6	-10.05	PASS
F <sub>HIGH</sub>	848.8	GPRS850	hor	30.75	40.6	-09.85	PASS
F <sub>LOW</sub>	824.2	EGPRS850	hor	24.75	40.6	-15.85	PASS
F <sub>MID</sub>	836.2	EGPRS850	hor	24.95	40.6	-15.65	PASS
F <sub>HIGH</sub>	848.8	EGPRS850	hor	24.75	40.6	-15.85	PASS
<b>Test results – GSM1900 E.I.R.P.</b>							
Channel	Frequency [MHz]	Mode	Pol.	Power [dBm e.i.r.p]	Limit [dBm e.i.r.p]	Margin [dB]	Result
F <sub>LOW</sub>	1850.2	GPRS1900	hor	32.7	33	-00.30	PASS
F <sub>MID</sub>	1880	GPRS1900	hor	31.9	33	-01.10	PASS
F <sub>HIGH</sub>	1909.8	GPRS1900	hor	31.1	33	-01.90	PASS
F <sub>LOW</sub>	1850.2	EGPRS1900	hor	28.9	33	-04.10	PASS
F <sub>MID</sub>	1880	EGPRS1900	hor	28.0	33	-05.00	PASS
F <sub>HIGH</sub>	1909.8	EGPRS1900	hor	26.8	33	-06.20	PASS
Comments:							


**3.3 Test Conditions and Results – Transmitter radiated emissions**

Transmitter radiated power acc. to FCC 22H / FCC 24E / IC RSS-132 / IC RSS-133		Verdict: PASS
Test according referenced standards	Reference Method	
	FCC § 22.917(a) / FCC § 24.238(a) IC RSS-132 § 4.5 / IC RSS-133 § 6.5	
Test according to measurement reference	Reference Method	
	ANSI/TIA-603-C	
Test frequency range	Tested frequencies	
	30 MHz – 10 <sup>th</sup> Harmonic	
Limits		
Frequency range	Limit	
824-849 MHz	Attenuation below transmitter power $\geq 43 + 10 \cdot \log_{10}(P)$ [dB] = -13 dBm	
1850-1910 MHz	Attenuation below transmitter power $\geq 43 + 10 \cdot \log_{10}(P)$ [dB] = -13 dBm	
Test setup		
		
Test procedure		
<ol style="list-style-type: none"> <li>1. EUT set to test mode</li> <li>2. Maximum emission level is measured by rotating the EUT and adjusting the antenna height for vertical polarization</li> <li>3. The EUT is replaced by a substitution antenna and generator</li> <li>4. The power level is set to obtain the same power reading</li> <li>5. Measurement is repeated for horizontal polarization</li> </ol>		

Test results – GSM850							
Channel	Frequency [MHz]	Mode	Emission [MHz]	Level [dbm]	Pol.	Limit [dBm]	Margin [dB]
128	824.2	GPRS850	823.984	-18.40	hor	-13.00	-05.40
128	824.2	GPRS850	823.992	-20.50	ver	-13.00	-07.53
128	824.2	GPRS850	1648	-25.50	ver	-13.00	-12.47
128	824.2	GPRS850	1648	-19.20	hor	-13.00	-06.24
188	836.2	GPRS850	1666	-20.10	hor	-13.00	-07.05
188	836.2	GPRS850	1672	-29.90	ver	-13.00	-16.92
251	848.8	GPRS850	849.016	-17.50	hor	-13.00	-04.51
251	848.8	GPRS850	849.028	-22.40	ver	-13.00	-09.41
251	848.8	GPRS850	1696	-28.40	ver	-13.00	-15.42
251	848.8	GPRS850	1696	-24.70	hor	-13.00	-11.67
251	848.8	GPRS850	2543	-27.50	hor	-13.00	-14.46
128	824.2	EGPRS850	823.972	-28.50	ver	-13.00	-15.55
128	824.2	EGPRS850	823.996	-23.20	hor	-13.00	-10.18
251	848.8	EGPRS850	849.04	-26.50	ver	-13.00	-13.55
251	848.8	EGPRS850	849.04	-23.60	hor	-13.00	-10.60
Comments:							

Test results – GSM1900							
Channel	Frequency [MHz]	Mode	Emission [MHz]	Level [dbm]	Pol.	Limit [dBm]	Margin [dB]
512	1850.2	GPRS1900	374.4	-23.90	ver	-13.00	-10.93
512	1850.2	GPRS1900	819.319	-24.80	hor	-13.00	-11.83
512	1850.2	GPRS1900	1850	-22.70	ver	-13.00	-09.75
512	1850.2	GPRS1900	1850	-15.90	hor	-13.00	-02.90
810	1909.8	GPRS1900	1910	-21.70	ver	-13.00	-08.75
810	1909.8	GPRS1900	1910	-16.00	hor	-13.00	-03.04
512	1850.2	EGPRS1900	1850	-27.00	ver	-13.00	-13.97
512	1850.2	EGPRS1900	1850	-20.80	hor	-13.00	-07.79
810	1909.8	EGPRS1900	1910	-25.50	ver	-13.00	-12.49
810	1909.8	EGPRS1900	1910	-23.10	hor	-13.00	-10.15
Comments:							

3.4 Test Conditions and Results – Receiver radiated emissions

Receiver radiated emissions acc. to IC RSS-132 / IC RSS-133				Verdict: PASS
Test according to measurement reference	Reference Method			
	ANSI C63.4			
Test frequency range	Tested frequencies			
	30 MHz – 3 <sup>th</sup> Harmonic			
EUT test mode	Receive			
Limits				
Frequency range [MHz]	Detector	Limit [ $\mu$ V/m]	Limit [dB $\mu$ V/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Test setup				
				

**Test procedure**

1. EUT set to receive mode (Communication tester is used if needed)
2. Span it set according to measurement range
3. Resolution bandwidth below 1GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1MHz with peak/average detector is used above 1GHz
4. Markers are set to peak emission levels

**Test results – GSM850**

Channel	Frequency [MHz]	Emission [MHz]	Emission Level [dB $\mu$ V/m]	Pol.	Det.	Limit [dB $\mu$ V/m]	Margin dB[dB]
188	IDLE850	374.4	36.44	ver	pk	46.00	-09.56
188	IDLE850	750.4	37.38	hor	pk	46.00	-08.62

**Test results – GSM1900**

Channel	Frequency [MHz]	Emission [MHz]	Emission Level [dB $\mu$ V/m]	Pol.	Det.	Limit [dB $\mu$ V/m]	Margin [dB]
661	IDLE1900	374.4	36.56	ver	pk	46.00	-09.44
661	IDLE1900	750.4	37.54	hor	pk	46.00	-08.46
661	IDLE1900	7864	52.46	hor	pk	53.98	-01.52
661	IDLE1900	7984	51.57	ver	pk	53.98	-02.41

**Comments:**

\* Physical distance between EUT and measurement antenna.

\*\* Emission level corresponds to ambient noise floor




## ANNEX A Transmitter radiated spurious emissions

### Spurious emissions according to FCC part 22 Subpart H, IC RSS-132

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 70




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 69




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 53




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 51




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 54




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
823.992 MHz	-20.5 dBm	-13 dBm	-7.53 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 52




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
823.984 MHz	-18.4 dBm	-13 dBm	-5.4 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 55




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 57






**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical

Index 56




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical

Index 58




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 61




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 59




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 62




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
849.028 MHz	-22.4 dBm	-13 dBm	-9.41 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 60




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
849.016 MHz	-17.5 dBm	-13 dBm	-4.51 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: TX; EDGE 850, CH: 128, 1 uplink slot, Gamma 6  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 65




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
823.972 MHz	-28.5 dBm	-13 dBm	-15.55 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; EDGE 850, CH: 128, 1 uplink slot, Gamma 6  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 66



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
823.996 MHz	-23.2 dBm	-13 dBm	-10.18 dB	Pass




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 188, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 64




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 188, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 67




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: TX; EDGE 850, CH: 251, 1 uplink slot, Gamma 6  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 63




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
849.04 MHz	-26.5 dBm	-13 dBm	-13.55 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; EDGE 850, CH: 251, 1 uplink slot, Gamma 6  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 68




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
849.04 MHz	-23.6 dBm	-13 dBm	-10.6 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 71




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.648 GHz	-25.5 dBm	-13 dBm	-12.47 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 86




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.648 GHz	-19.2 dBm	-13 dBm	-6.24 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 74




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.672 GHz	-29.9 dBm	-13 dBm	-16.92 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 89



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.666 GHz	-20.1 dBm	-13 dBm	-7.05 dB	Pass




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 77




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.696 GHz	-28.4 dBm	-13 dBm	-15.42 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 92




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.696 GHz	-24.7 dBm	-13 dBm	-11.67 dB	Pass
2.543 GHz	-27.5 dBm	-13 dBm	-14.46 dB	Pass

**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 128, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 80




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 128, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 85




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 188, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 81




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 188, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 84




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 251, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 82




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; EDGE 850, CH: 251, 1 uplink slot, Gamma 6
Test Date:	2014-12-03
Note:	EUT vertical

Index 83






**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 72




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 87




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 75




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 90




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 78




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 93




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 73




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 128, 1 uplink slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 88






**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 76




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 188, 1 uplink slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 91




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 79




**Spurious emissions according to FCC part 22 Subpart H, IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 850, CH: 251, 1 uplink slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 94




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 45




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-03
Note:	EUT vertical; worst case

Index 46




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical; worst case

Index 44




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
374.4 MHz	-23.9 dBm	-13 dBm	-10.93 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3  
 Test Date: 2014-12-03  
 Note: EUT vertical; worst case

Index 43



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
819.319 MHz	-24.8 dBm	-13 dBm	-11.83 dB	Pass




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 60




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 70




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 61




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.85 GHz	-22.7 dBm	-13 dBm	-9.75 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 71




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.85 GHz	-15.9 dBm	-13 dBm	-2.9 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: TX; EDGE 1900, CH. 512, UL 1x Slot, Gamma 5  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 78




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.85 GHz	-27 dBm	-13 dBm	-13.97 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; EDGE 1900, CH. 512, UL 1x Slot, Gamma 5  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 83




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.85 GHz	-20.8 dBm	-13 dBm	-7.79 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 661, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 62




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 661, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 68






**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 661, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical

Index 63




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 661, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical

Index 69




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; EDGE 1900, CH. 661, UL 1x Slot, Gamma 5
Test Date:	2014-12-04
Note:	EUT vertical

Index 79




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; EDGE 1900, CH. 661, UL 1x Slot, Gamma 5
Test Date:	2014-12-04
Note:	EUT vertical

Index 82




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 810, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 64




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 810, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 66




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: TX; GPRS 1900, CH. 810, UL 1x Slot, Gamma 3  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 65




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.91 GHz	-21.7 dBm	-13 dBm	-8.75 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; GPRS 1900, CH. 810, UL 1x Slot, Gamma 3  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 67



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.91 GHz	-16 dBm	-13 dBm	-3.04 dB	Pass




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: TX; EDGE 1900, CH. 810, UL 1x Slot, Gamma 5  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 80




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.91 GHz	-25.5 dBm	-13 dBm	-12.49 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: TX; EDGE 1900, CH. 810, UL 1x Slot, Gamma 5  
 Test Date: 2014-12-04  
 Note: EUT vertical

Index 81




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
1.91 GHz	-23.1 dBm	-13 dBm	-10.15 dB	Pass

**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 75




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 72



**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 76




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 73




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 77




**Spurious emissions according to FCC part 24 Subpart E, IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	TX; GPRS 1900, CH. 512, UL 1x Slot, Gamma 3
Test Date:	2014-12-04
Note:	EUT vertical; worst case

Index 74






## ANNEX B Receiver radiated spurious emissions

### Spurious emissions according to IC RSS-132

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	RX; GSM 850, CH. 188, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 61




**Spurious emissions according to IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	RX; GSM 850, CH. 188, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 64




**Spurious emissions according to IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: RX; GSM 850, CH. 188, RX-Idle Mode  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 57




Frequency	Peak	Peak Limit	Peak Difference	Status
374.4 MHz	36.44 dBµV/m	46 dBµV/m	-9.56 dB	Pass

**Spurious emissions according to IC RSS-132**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; GSM 850, CH. 188, RX-Idle Mode  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 60




Frequency	Peak	Peak Limit	Peak Difference	Status
750.4 MHz	37.38 dBµV/m	46 dBµV/m	-8.62 dB	Pass

**Spurious emissions according to IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	RX; GSM 850, CH. 188, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 65




**Spurious emissions according to IC RSS-132**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	RX; GSM 850, CH. 188, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 70




**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	RX; GSM 1900, CH. 661, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 62




**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	RX; GSM 1900, CH. 661, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 63






**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Vertical  
 Measurement distance: 3 m  
 Mode: RX; GSM 1900, CH. 661, RX-Idle Mode  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 58




Frequency	Peak	Peak Limit	Peak Difference	Status
374.4 MHz	36.56 dBµV/m	46 dBµV/m	-9.44 dB	Pass

**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 223, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; GSM 1900, CH. 661, RX-Idle Mode  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 59




Frequency	Peak	Peak Limit	Peak Difference	Status
750.4 MHz	37.54 dBµV/m	46 dBµV/m	-8.46 dB	Pass

**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	3 m
Mode:	RX; GSM 1900, CH. 661, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 66




**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant:	Leica Geosystems AG
EUT Name:	Field Controller Win EC7
Model:	CS20
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pudell
Test Conditions:	Tnom: 24°C, Vnom: 11.1 VDC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	3 m
Mode:	RX; GSM 1900, CH. 661, RX-Idle Mode
Test Date:	2014-12-03
Note:	EUT vertical

Index 69




**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Vertical  
 Measurement distance: 3 m  
 Mode: RX; GSM 1900, CH. 661, RX-Idle Mode  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 67




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
7.984 GHz	51.57 dBµV/m	53.98 dBµV/m	-2.41 dB	Pass

**Spurious emissions according to IC RSS-133**

Project number: G0M-1406-3915

Applicant: Leica Geosystems AG  
 EUT Name: Field Controller Win EC7  
 Model: CS20  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pudell  
 Test Conditions: Tnom: 24°C, Vnom: 11.1 VDC  
 Antenna: Rohde & Schwarz HL 025, Horizontal  
 Measurement distance: 3 m  
 Mode: RX; GSM 1900, CH. 661, RX-Idle Mode  
 Test Date: 2014-12-03  
 Note: EUT vertical

Index 68



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
7.864 GHz	52.46 dBµV/m	53.98 dBµV/m	-1.52 dB	Pass