





<b>RF-EXPOSURE ASSESSMENT REPORT</b> <b>FCC 47 CFR Part 2.1091</b> <b>Industry Canada RSS-102</b> <b>RF-Exposure evaluation of mobile equipment</b>	
<b>Report Reference No.</b> .....	G0M-1702-6292-TFC091ME-V01
<b>Testing Laboratory</b> .....	Eurofins Product Service GmbH
Address.....	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation .....	<div style="display: flex; justify-content: center; gap: 20px;">     </div> <p style="text-align: center;">           DAkkS - Registration number : D-PL-12092-01-03 (ISED)            ISED Testing Laboratory site: 3470A-2            DAkkS - Registration number : D-PL-12092-01-04 (FCC)            FCC Filed Test Laboratory, Reg.-No.: 96970         </p>
<b>Applicant's name</b> .....	Leica Geosystems AG
Address.....	Heinrich Wild Strasse 9435 Heerbrugg SWITZERLAND
<b>Test specification:</b>	
Standard .....	47 CFR 2.1091 KDB 447498 D01 v06:2015-10-23 RSS-102, Issue 5:2015-03
<b>Equipment under test (EUT):</b>	
Product description	Radio Module 300m
Model No.	CT301
Additional Model(s)	None
Brand Name(s)	Leica
Hardware version	P2-B
Firmware / Software version	0x6CB
	FCC-ID: RFD-CT301                      IC: 3177A-CT301
<b>Test result</b>	<b>Passed</b>

**Possible test case verdicts:**

- neither assessed nor tested.....: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object.....: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

**Testing:**

Test Lab Temperature.....: 20 – 23 °C

Test Lab Humidity.....: 32 – 38 %

Date of receipt of test item .....: 2019-01-31

Date (s) of assessment .....: 2019-04-30

Compiled by .....: Toralf Jahn

Assessed by (+ signature) .....: Toralf Jahn  
(Responsible for Assessment)

Approved by (+ signature).....: Christian Weber  
(Head of Lab)

Date of issue .....: 2019-05-03

Total number of pages .....: 13



**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**Additional comments:**

---

---

## Version History

Version	Issue Date	Remarks	Revised by
01	2019-05-03	Initial Release	

---

**REPORT INDEX**

<b>1</b>	<b>EQUIPMENT (TEST ITEM) DESCRIPTION</b>	<b>5</b>
1.1	Reference Documents	6
1.2	Standalone Radiation Sources	7
1.3	Concurrent-Transmitter Modes	7
<b>2</b>	<b>RESULT SUMMARY</b>	<b>8</b>
<b>3</b>	<b>RF-EXPOSURE CLASSIFICATIONS</b>	<b>9</b>
<b>4</b>	<b>ASSESSMENT</b>	<b>10</b>
4.1	MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102	10
4.2	Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102	13

**1 Equipment (Test item) Description**

<b>Description</b>	Radio Module 300m
<b>Model</b>	CT301
<b>Additional Model(s)</b>	None
<b>Brand Name(s)</b>	Leica
<b>Serial number</b>	Conducted: 1218520032 Radiated: 1218520034
<b>Hardware version</b>	P2-B
<b>Software / Firmware version</b>	0x6CB
<b>PMN</b>	CT301
<b>HVIN</b>	CT301
<b>FVIN</b>	None
<b>HMN</b>	None
<b>FCC-ID</b>	RFD-CT301
<b>IC</b>	3177A-CT301
<b>Equipment type</b>	End product

**1.1 Reference Documents**

Document type	Document No.	Issued by	Date
FCC 15.247 Test Report	G0M-1702-6292-TFC247ZB-V01	Eurofins Product Service GmbH	2019-04-30

## 1.2 Standalone Radiation Sources

Mode #	Description	
IEEE 802.15.4	Frequency range [MHz]	2405 - 2480
	Transmission modes	O-QPSK
	Maximum conducted power [dBm]	18.079
	Maximum radiated power [dBm]	18.779
	Maximum transmission duty cycle [%]	8.3
	Antenna gain [dBi]	0.7
	Antenna diameter [cm]	2
	Assessment Frequency [MHz]	2440

## 1.3 Concurrent-Transmitter Modes

None

## 2 Result Summary

FCC 47 CFR Part 2.1091, IC RSS-102			
Product Specific Standard Section	Requirement	Result	Remarks
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS	
RSS-102 2.5.2	Maximum permissible exposure @ 20cm below limit	PASS	
<b>Remarks:</b>			



### 3 RF-Exposure Classifications

<b>Device Types</b>	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)
<b>Exposure Categories</b>	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

#### 4 Assessment

##### 4.1 MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102

MPE ASSESSMENT ACC. TO 47 CFR 2.1091 / ISED RSS-102				VERDICT: PASS
Assessment according to reference		Reference Method		
		FCC OET Bulletin 65 / RSS-102 & Safety Code 6		
Device type		mobile		
Exposure category		General public		
IC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.003-10*	170	180	-	Instantaneous*
0.1-10	-	1.6 / $f$	-	6**
1.29-10	193 / $f^{0.5}$	-	-	6**
10-20	61.4	0.163	-10	6
20-48	129.8 / $f^{0.25}$	0.3444 / $f^{0.25}$	44.72 / $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000 / $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	9.40 x 10 <sup>-4</sup> $f^{0.5}$	3.33 x 10 <sup>-4</sup> $f$	616000 / $f^{1.2}$
IC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.003-10*	83	90	-	Instantaneous*
0.1-10	-	0.73 / $f$	-	6**
1.1-10	87 / $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07 / $f^{0.25}$	0.1540 / $f^{0.25}$	8.944 / $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000 / $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 <sup>-4</sup> $f^{0.5}$	6.67 x 10 <sup>-5</sup> $f$	616000 / $f^{1.2}$
* = Based on nerve stimulation				
** = Bases on specific absorption rate				

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm <sup>2</sup> ]	Averaging time [min]
0.3 – 3.0	614	1.63	(100)*	6
3.0 - 30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	N/A	N/A	f / 300	6
1500 - 100000	N/A	N/A	5.0	6
FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm <sup>2</sup> ]	Averaging time [min]
0.3 – 1.34	614	1.63	(100)*	30
1.34 - 30	842 / f	2.19 / f	(180 / f <sup>2</sup> )*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	N/A	N/A	f / 1500	30
1500 - 100000	N/A	N/A	1.0	30

\* = Plane wave equivalent power density; f in MHz

Assessment Relations
$\lambda[m] = \frac{c \left[ \frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$
$S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2} ; R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$
$P_R[mW] = P_C[mW] \cdot G ; P_R[dBm] = P_C[dBm] + G[dBi]$
$DCC [dB] = 10 \cdot \text{Log}_{10} \left( \frac{DC[\%]}{100} \right)$
$\sum_{i=1}^N \frac{S_i \left[ \frac{W}{m^2} \right]}{S_{Li} \left[ \frac{W}{m^2} \right]} + \sum_{j=1}^M \left( \frac{E_j \left[ \frac{V}{m} \right]}{E_{Lj} \left[ \frac{V}{m} \right]} \right)^2 + \sum_{k=1}^O \left( \frac{H_k \left[ \frac{A}{m} \right]}{H_{Lk} \left[ \frac{A}{m} \right]} \right)^2 < 1$

**Assessment procedure**Standalone operation assessment:

For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.

Concurrent operation assessment:

First the evaluation distance is set to 20 cm. The ratios of the power densities and/or field strength values and the corresponding limits are calculated and summed and the sum is compared to the maximum of 1.

**4.2 Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102**

<b>Assessment result - IEEE 802.15.4</b>		
<b>Transmission mode</b>		
Operating mode frequency range [MHz]	2405 - 2480	
Assessment frequency (f) [MHz]	2440	
Transmission duty cycle (DC) [%]	8.3	
Peak conducted power (P <sub>C</sub> ) [dBm]	18.079	
Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]	18.779	
Peak Antenna gain (G) [dBi]	0.7	
Maximum Antenna Diameter D [cm]	2	
<b>Antenna far-field distance</b>		
Transmission frequency wavelength (λ)	0.123 m	12.30 cm
Antenna far-field distance (R <sub>FF</sub> )	0.007 m	0.65 cm
<b>Power evaluation</b>		
Peak conducted power (P <sub>C</sub> )	64.25 mW	18.08 dBm
Peak Antenna Gain (G)	1.17	0.70 dBi
Calculated peak radiated power (P <sub>R-Calc</sub> )	75.49 mW	18.78 dBm
Measured peak radiated power (P <sub>R</sub> )	75.49 mW	18.78 dBm
<b>Source average Power</b>		
Maximum transmission duty cycle (DC)	8.3 %	
Duty cycle correction (DCC)	0.08	-10.81 dB
Measured peak radiated power (P <sub>R</sub> )	75.49 mW	18.78 dBm
Averaged peak radiated power (P <sub>RAVG</sub> )	6.27 mW	7.97 dBm
<b>Power density</b>		
Compliance power density limit FCC (S <sub>FCCLimit</sub> )	1.000 mW/cm <sup>2</sup>	10.00 W/m <sup>2</sup>
Compliance power density limit IC (S <sub>ICLimit</sub> )	0.541 mW/cm <sup>2</sup>	5.41 W/m <sup>2</sup>
Power density @ Antenna far-field distance	1.178 mW/cm <sup>2</sup>	11.777 W/m <sup>2</sup>
Power density @ 20cm	0.001 mW/cm <sup>2</sup>	0.012 W/m <sup>2</sup>
Distance for compliance power density FCC	0.007 m	0.71 cm
Distance for compliance power density IC	0.010 m	0.96 cm
<b>Verdict</b>		
The power density of the EUT at 20cm is below the FCC MPE limit!		
The power density of the EUT at 20cm is below the IC MPE limit!		
<b>Comments:</b>		