




Appendix B

Peak Output Power




Marker 1 [T1] RBW 1 MHz RF Att 30 dB
Ref Lvl -3.98 dBm VBW 1 MHz
10 dBm 2.40216132 GHz SWT 5 ms Unit dBm



Title: Peak Output Power conducted Ch.: 0
Comment A: PANMOD 1i
Date: 30.SEP.2005 10:53:53




Marker 1 [T1] RBW 1 MHz RF Att 30 dB
Ref Lvl -5.34 dBm VBW 1 MHz
10 dBm 2.44117535 GHz SWT 5 ms Unit dBm



Title: Peak Output Power conducted Ch.: 39
Comment A: PANMOD 1i
Date: 30.SEP.2005 10:58:17



Marker 1 [T1] RBW 1 MHz RF Att 30 dB
Ref Lvl -6.96 dBm VBW 1 MHz
10 dBm 2.48016132 GHz SWT 5 ms Unit dBm




Title: Peak Output Power conducted Ch.: 78
Comment A: PANMOD 1i
Date: 30.SEP.2005 10:59:30

Carrier power (dBm)

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.402GHz, Pmax: -6.19dBm, RBW: 3MHz



Carrier power (dBm)

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.402GHz, Pmax: 1.85dBm, RBW: 3MHz



Carrier power (dBm)

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.441GHz, Pmax: -11.46dBm, RBW: 3MHz



Carrier power (dBm)

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 11 / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.441GHz, Pmax: -3.33dBm, RBW: 3MHz



Carrier power (dBm)

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.480GHz, Pmax: -10.72dBm, RBW: 3MHz



Carrier power (dBm)

FCC RULES PART 15, SUBPART C

Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.480GHz, Pmax: -7.52dBm, RBW: 3MHz






Appendix C

Spurious Emissions radiated - Transmitter operating

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq: 2.402GHz, Emax: 93.26dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 198.637MHz, Emax: 33.05dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 188.076MHz, Emax: 33.92dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 983.968MHz, Emax: 24.35dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 11 / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 985.571MHz, Emax: 23.31dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.397GHz, Emax: 57.08dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.397GHz, Emax: 57.08dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.397GHz, Emax: 61.02dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, average detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 3.869GHz, Emax: 30.72dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 6.004GHz, Emax: 42.51dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 6.004GHz, Emax: 38.88dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.551GHz, Emax: 41.02dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.150GHz, Emax: 40.70dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.365GHz, Emax: 43.29dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.224GHz, Emax: 43.32dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 17.038GHz, Emax: 43.91dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2402 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 17.133GHz, Emax: 44.20dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 11 / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 195.230MHz, Emax: 32.37dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 187.735MHz, Emax: 32.88dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 985.571MHz, Emax: 24.22dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 985.571MHz, Emax: 23.28dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 3.830GHz, Emax: 43.79dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.397GHz, Emax: 45.50dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.439GHz, Emax: 40.59dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.303GHz, Emax: 41.43dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.124GHz, Emax: 44.02dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.886GHz, Emax: 43.40dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 23.911GHz, Emax: 43.39dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 17.038GHz, Emax: 44.99dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 172.745MHz, Emax: 32.67dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: li / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 200.000MHz, Emax: 33.16dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 985.571MHz, Emax: 24.49dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Comment 2: Freq: 985.571MHz, Emax: 23.95dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.487GHz, Emax: 46.05dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.
Comment 2: Freq: 2.487GHz, Emax: 48.46dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 7.447GHz, Emax: 48.48dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 11 / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 7.447GHz, Emax: 49.61dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 7.327GHz, Emax: 42.13dB μ V/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2441 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 7.327GHz, Emax: 45.62dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 11 / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.399GHz, Emax: 41.22dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 11.046GHz, Emax: 41.56dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.335GHz, Emax: 43.65dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.
Comment 2: Freq: 14.545GHz, Emax: 43.39dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 17.057GHz, Emax: 43.73dBuV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

Approval Holder: Leica Geosystems AG
EUT: PANMOD
Model: 1i / 2480 MHz
Test Site / Operator: ETS / Mr. Handrik
Temperature/ Voltage: 25°C / Unom: 3.30 V DC
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 17.019GHz, Emax: 44.13dBµV/m, RBW: 1MHz





Appendix D


Spurious Emissions conducted - Transmitter operating

Appendix E

Carrier Frequency Separation



Delta 1 [T1] RBW 100 kHz RF Att 30 dB
Ref Lvl -0.16 dB VBW 100 kHz
5 dBm 1.00080160 MHz SWT 5 ms Unit dBm



Title: Carrier Frequency Separation
Comment A: PANMOD 1i
Date: 30.SEP.2005 14:12:54




Appendix F

Number of Hopping Frequencies



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm




Title: Number of Hopping Frequencies Ch.: 0-13
Comment A: PANMOD 11
Date: 30.SEP.2005 14:34:46



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm




Title: Number of Hopping Frequencies Ch.: 14-38
Comment A: PANMOD 1i
Date: 30.SEP.2005 14:41:59



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm




Title: Number of Hopping Frequencies Ch.: 39-63
Comment A: PANMOD 11
Date: 30.SEP.2005 14:48:08



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm




Title: Number of Hopping Frequencies Ch.: 64-78
Comment A: PANMOD 1i
Date: 30.SEP.2005 14:53:41



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm




Title: Number of Hopping Frequencies (Master Inquiry Mode)
Comment A: PANMOD 1i
Date: 30.SEP.2005 15:06:53



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm




Title: Number of Hopping Frequencies (Master Inquiry Mode)
Comment A: PANMOD 1i
Date: 30.SEP.2005 15:12:51



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm




Title: Number of Hopping Frequencies (Master Inquiry Mode)
Comment A: PANMOD 1i
Date: 30.SEP.2005 15:17:02



Ref Lvl
10 dBm

RBW 300 kHz RF Att 30 dB
VBW 300 kHz
SWT 5 ms Unit dBm



Title: Number of Hopping Frequencies (Master Inquiry Mode)
Comment A: PANMOD 1i
Date: 30.SEP.2005 15:21:05




Appendix G

Time of Occupancy (Dwell Time)




Delta 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl -0.13 dB VBW 1 MHz
10 dBm 2.905812 ms SWT 5 ms Unit dBm



Title: Time of Occupancy (Hopping DHS) 93 events*2.9058ms=270.239ms
Comment A: PANMOD 1i
Date: 05.OCT.2005 10:50:54



Delta 1 [T1] RBW 1 MHz RF Att 30 dB
Ref Lvl 0.16 dB VBW 1 MHz
10 dBm 106.525651 μ s SWT 300 μ s Unit dBm



Title: Time of Occupancy (Inquiry mode) 429 events*0.107ms=45.903ms
Comment A: PANMOD 11
Date: 05.OCT.2005 11:08:28



Delta 2 [T1]

RBW 1 MHz RF Att 40 dB


Ref Lvl -0.11 dB

VBW 1 MHz

20 dBm 3.768186 ms

SWT 11 ms

Unit dBm



Title: Duty Cycle
Comment A: PANMOD 1i
Date: 05.OCT.2005 10:56:09




Appendix H

20dB Bandwidth




Delta 1 [T1] RBW 10 kHz RF Att 20 dB
Ref Lvl 0.05 dB VBW 10 kHz
0 dBm 1.00080160 MHz SWT 56 ms Unit dBm



Title: -20 dB Bandwidth Ch.: 0
Comment A: PANMOD 1i
Date: 30.SEP.2005 11:44:07




Delta 1 [T1] RBW 10 kHz RF Att 20 dB
Ref Lvl 0.22 dB VBW 10 kHz
0 dBm 1.00080160 MHz SWT 56 ms Unit dBm



Title: -20 dB Bandwidth Ch.: 39
Comment A: PANMOD 1i
Date: 30.SEP.2005 11:42:37



Delta 1 [T1] RBW 10 kHz RF Att 20 dB
Ref Lvl -0.28 dB VBW 10 kHz
0 dBm 1.00080160 MHz SWT 56 ms Unit dBm



Title: -20 dB Bandwidth Ch.: 78
Comment A: PANMOD 1i
Date: 30.SEP.2005 11:40:54




Appendix I

Band-edge Compliance of RF Emissions




Delta 1 [T1] RBW 50 kHz RF Att 40 dB
Ref Lvl 28.48 dB VBW 50 kHz
20 dBm 2.66873747 MHz SWT 5 ms Unit dBm



Title: Band-edge Compliance (conducted, single frequency)
Comment A: PANMOD 1i
Date: 30.SEP.2005 12:58:38




Delta 1 [T1] RBW 50 kHz RF Att 40 dB
Ref Lvl 36.39 dB VBW 50 kHz
20 dBm -3.32713427 MHz SWT 5 ms Unit dBm



Title: Band-edge Compliance (conducted, single frequency)
Comment A: PANMOD 1i
Date: 30.SEP.2005 13:01:43




Delta 1 [T1] RBW 50 kHz RF Att 40 dB
Ref Lvl 28.69 dB VBW 50 kHz
20 dBm 2.67875752 MHz SWT 5 ms Unit dBm



Title: Band-edge Compliance (conducted, hopping mode)
Comment A: PANMOD 11
Date: 30.SEP.2005 13:27:58



Delta 1 [T1] RBW 50 kHz RF Att 40 dB
 Ref Lvl 37.10 dB VBW 50 kHz
 20 dBm -3.32713427 MHz SWT 5 ms Unit dBm



Title: Band-edge Compliance (conducted, hopping mode)
 Comment A: PANMOD 1i
 Date: 30.SEP.2005 13:41:18




Appendix J

Conducted Measurement at (AC) Power Line

EMI voltage test in the ac-mains according to FCC part 15

EUT: PANMOD
Manufacturer: LEICA GEOSYSTEMS AG
Operating Condition: Unom: 120 V AC (AC/DC-ADAPTOR) , Thom: 23°C
Test Site: ETS
Operator: Mr. Marquardt
Test Specification: V-Network: ESH2-Z5 (N)
Comment: model: 1i



EMI voltage test in the ac-mains according to FCC part 15

EUT: PANMOD
Manufacturer: LEICA GEOSYSTEMS AG
Operating Condition: Unom: 120 V AC (AC/DC-ADAPTOR) , Tnom: 23°C
Test Site: ETS
Operator: Mr. Marquardt
Test Specification: V-Network: ESH2-Z5 (L1)
Comment: model: 1i

