

MicroPLBTM

**406 Personal
Locator
Beacon**

Warning:

USE ONLY DURING
SITUATIONS OF GRAVE
AND IMMINENT DANGER



**COSPAS/SARSAT
EMERGENCY LOCATOR BEACON**

Operating Temp: -20°C to 55°C (Class 2)

THIS SATELLITE PLB WILL NOT FLOAT

OPERATING INSTRUCTIONS:

- 1) Remove cover
- 2) Activate and connect GPS receiver
- 3) Pull pin completely out
Blinking green = transmission
Single Blink = GPS NOT Acquired
Double Blink = GPS Acquired

SELF TEST INSTRUCTIONS:

- 1) Remove cover
- 2) Pull pin completely out
GREEN = PASS
RED = NOT PASS
- 3) Replace pin within 30 seconds
to avoid false alarms

Battery Type US DOT Approved Li/MnO₂
MBT 040600 SN: 253

Frequency 406.025 MHz 121.5MHz

Battery Expiration Date: 03/2008

ID: 2DDE2001BF81FE0

**MICROWAVE MONOLITHICS INCORPORATED
SIMI VALLEY, CA 93065 USA**

CAUTION: Antenna Deploys

*Hold away from face
when removing cap*

No user serviceable parts inside

Warranty void if seal is broken

Registration Required - see owners manual

MicroPLB™

**406 Personal
Locator
Beacon**

Warning:

USE ONLY DURING
SITUATIONS OF GRAVE
AND IMMINENT DANGER



**COSPAS/SARSAT
EMERGENCY LOCATOR BEACON**

Operating Temp: -20°C to 55°C (Class 2)

THIS SATELLITE PLB WILL NOT FLOAT

OPERATING INSTRUCTIONS:

- 1) Remove cover
- 2) Activate and connect GPS receiver
- 3) Pull pin completely out
Blinking green = transmission
Single Blink = GPS NOT Acquired
Double Blink = GPS Acquired

SELF TEST INSTRUCTIONS:

- 1) Remove cover
- 2) Push pin down into hole
GREEN = PASS
RED = NOT PASS
- 3) Release pin within 30 seconds
to avoid false alarms

Battery Type US DOT Approved Li/MnO₂
MBT 040600 SN: 256

Frequency 406 025 MHz 121.5MHz

Battery Expiration Date 03/2008

ID 2DDE20033F81FE0

MICROWAVE MONOLITHICS INCORPORATED
SIMI VALLEY, CA 93065 USA



CAUTION: Antenna Deploys

*Hold away from face
when removing cap*

No user serviceable parts inside

Warranty void if seal is broken

Registration Required - see owners manual