



# FCC Radio Test Report

## FCC ID: RI7ATD551

This report concerns: Original Grant

**Project No.** : 2404C168  
**Equipment** : LTE Cat-M1 Tracker  
**Brand Name** : 1. Telit Cinterion  
2. DeWALT  
**Test Model** : ATD551  
**Series Model** : N/A  
**Applicant** : Telit Communications S.p.A.  
**Address** : Via Stazione di Prosecco 5/b, 34010 Sgonico, Trieste, Italy  
**Manufacturer** : Telit Communications S.p.A.  
**Address** : Via Stazione di Prosecco 5/b, 34010 Sgonico, Trieste, Italy  
**Factory** : Fushan Technology (Vietnam)Limited Liability Company  
**Address** : No. 8, Road 6, VSIP Bac Ninh, Phu Chan, Tu Son, Bac Ninh, Vietnam  
**Date of Receipt** : May 07, 2024  
**Date of Test** : May 08, 2024 ~ Sep. 09, 2024  
**Issued Date** : Oct. 31, 2024  
**Report Version** : R02  
**Test Sample** : Engineering Sample No.: DG20240507140, DG20240507139  
**Standard(s)** : 47 CFR FCC Part 90 Subpart S  
47 CFR FCC Part 2

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

**Prepared by** : Edward Li  
Edward Li

**Approved by** : Treay Chen  
Treay Chen

Room 108-116, 309-310, Building 2, No.1, Yile Road, Songshan Lake Zone,  
Dongguan City, Guangdong, People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl\_qa@newbtl.com

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by **BTL**.

The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the ISO/IEC 17025: 2017 requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

<b>Table of Contents</b>	<b>Page</b>
<b>REPORT ISSUED HISTORY</b>	<b>4</b>
<b>1 . APPLICABLE STANDARDS</b>	<b>5</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>5</b>
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
2.3 TEST ENVIRONMENT CONDITIONS	7
<b>3 . GENERAL INFORMATION</b>	<b>8</b>
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATIONOFSYSTEMTESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS	10
<b>4 . TEST RESULT</b>	<b>11</b>
4.1 RADIATED SPURIOUS EMISSIONS MEASUREMENT	11
4.1.1 LIMIT	11
4.1.2 TEST PROCEDURES	11
4.1.3 TEST SETUP LAYOUT	12
4.1.4 TESTDEVIATION	13
4.1.5 TEST RESULTS (9KHZ TO 30MHZ)	13
4.1.6 TEST RESULTS (30MHZ TO 1000MHZ)	13
4.1.7 TEST RESULTS (ABOVE 1000MHZ)	13
<b>4. LIST OF MEASUREMENT EQUIPMENTS</b>	<b>14</b>
<b>5. EUT TEST PHOTO</b>	<b>16</b>
<b>APPENDIX A - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)</b>	<b>19</b>
<b>APPENDIX B - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)</b>	<b>21</b>
<b>APPENDIX C - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)</b>	<b>25</b>

**REPORT ISSUED HISTORY**

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-4-2404C168	R00	Original Report.	Sep. 26, 2024	Invalid
BTL-FCCP-4-2404C168	R01	Added the RF Module FCC ID in section 2.	Oct. 18, 2024	Invalid
BTL-FCCP-4-2404C168	R02	Updated the Laboratory address.	Oct. 31, 2024	Valid

## 1. APPLICABLE STANDARDS

The following reference test guidance is not within the scope of accreditation of A2LA:  
 ANSI C63.26-2015  
 FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part 90 Subpart S & Part 2			
Standard(s) Section	Test Item	Judgment	Remark
2.1046 & 90.635 (b)	Effective Radiated Power	PASS	<b>Note(1)</b>
2.1049 & 90.209	Occupied Bandwidth	PASS	<b>Note(1)</b>
2.1053 & 90.669	Conducted Spurious Emissions	PASS	<b>Note(1)</b>
2.1053 & 90.669	Radiated Spurious Emissions	PASS	-----
2.1053 & 90.691	Mask Measurements	PASS	<b>Note(1)</b>
-	Peak To Average Ratio	PASS	<b>Note(1)</b>
2.1055 & 90.213	Frequency Stability	PASS	<b>Note(1)</b>


Note:

- The RF module of this LTE Cat-M1 Tracker has been tested and certified. Please refer to the module report as listed in the below table for the test results of the RF module.

RF Module	Module Function	Report Number	Standard	
Model: ME310G1-WW  FCC ID: RI7ME310G1WW	GSM	60356613 003	47 CFR FCC Part 22	RSS-132 Issue 3
			47 CFR FCC Part 24	RSS-133 Issue 6
	LTE	60356613 002	47 CFR FCC Part 2	RSS-Gen Issue 5
			47 CFR FCC Part 22	RSS-132 Issue 3
			47 CFR FCC Part 24	RSS-133 Issue 6
			47 CFR FCC Part 27	RSS-130 Issue 2
60356613 001	60356613 001	47 CFR FCC Part 90	RSS-139 Issue 3	
		47 CFR FCC Part 2	RSS-Gen Issue 5	
		47 CFR FCC Part 22	RSS-132 Issue 3	
		47 CFR FCC Part 24	RSS-133 Issue 6	
			47 CFR FCC Part 27	RSS-130 Issue 2
			47 CFR FCC Part 90	RSS-139 Issue 3
			47 CFR FCC Part 2	RSS-Gen Issue 5

- The band 26 antenna gain of LTE Cat-M1 Tracker was smaller than that of module, so output power and ERP refer to module test report. Thus, only the radiated spurious emissions was evaluated and recorded in this report. For the test results of all other test items please refer to above module test report.

## 2. Table for Filed Antenna:

Brand	P/N	Antenna Type	Connector	Gain (dBi)	Note
 ethertronics <sup>®</sup> <small>AN AVIX GROUP COMPANY</small>	1004795/1004796	PCB	N/A	1.6	LTE Band 26

- 1) The antenna gain is provided by the manufacturer.

## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of 1-2/F, 4/F, Building A, 1-2/F, Building B, 3/F, Building C, No.3, Jinshagang 1st Road, Dalang Town, Dongguan City, Guangdong People's Republic of China.

BTL's Registration Number for FCC: 747969

BTL's Designation Number for FCC: CN1377

## 2.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ( $k=2$ ))

The BTL measurement uncertainty as below table:

### A. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	$U_i$ (dB)
DG-CB01	CISPR	9kHz ~ 30MHz	2.36

Test Site	Method	Measurement Frequency Range	Ant. H / V	$U_i$ (dB)
DG-CB03 (3m)	CISPR	30MHz ~ 200MHz	V	4.40
		30MHz ~ 200MHz	H	3.62
		200MHz ~ 1,000MHz	V	4.58
		200MHz ~ 1,000MHz	H	3.98

Test Site	Method	Measurement Frequency Range	$U_i$ (dB)
DG-CB03 (3m)	CISPR	1GHz ~ 6GHz	4.08
		6GHz ~ 18GHz	4.62


Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

## 2.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By	Test Date
Radiated Spurious Emissions (9 kHz to 30 MHz)	21°C	50%	AC 120V/60Hz	Hayden Chen	Jun. 29, 2024
Radiated Spurious Emissions (30 MHz to 1000 MHz)	22-24°C	56-58%	AC 120V/60Hz	Jensen Zhou	Jun. 10, 2024- Jun. 22, 2024
Radiated Spurious Emissions (Above 1000 MHz)	22-24°C	56-58%	AC 120V/60Hz	Jensen Zhou	Jun. 10, 2024- Jun. 22, 2024

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	LTE Cat-M1 Tracker	
Brand Name	1. Telit Cinterion 2. DeWALT	
Test Model	ATD551	
PMN	LTE Cat-M1 Tracker(C1) will use Brand:DeWALT LTE Cat-M1 Tracker(S0) will use Brand:Telit Cinterion LTE Cat-M1 Tracker(S1) will use Brand:Telit Cinterion LTE Cat-M1 Tracker(C2)	
Model Difference(s)	Logo, some mechanical parts color, label, accessories are different.	
Hardware Version	V0.6	
Software Version	V03.05	
Power Source	1# DC Voltage supplied from AC adapter. Model: ADS-10LA-06 05010EPCU 2# Supplied from battery.	
Power Rating	1# I/P: 100-240V ~ 50/60Hz MAX 0.3A O/P: 5V  2.0A 2# DC 3.7V / 3000mAh	
IMEI No.	Radiated	350903782706437, 350903782706486
Modulation Type	LTE(eMTC)	UL: QPSK,16QAM
	LTE(NB-IoT)	UL: BPSK, QPSK

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

LTE Band 26(eMTC)					
Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink (MHz)	N <sub>DL</sub>	Frequency of Downlink (MHz)
Low Range	1.4	26697	814.7	8697	859.7
	3	26705	815.5	8705	860.5
	5	26715	816.5	8715	861.5
Mid Range	1.4/3/5/10	26740	819	8740	864
High Range	1.4	26783	823.3	8783	868.3
	3	26775	822.5	8775	867.5
	5	26765	821.5	8765	866.5

LTE Band 26(NB-IoT)					
Test Frequency ID	Bandwidth (kHz)	N <sub>UL</sub>	Frequency of Uplink (MHz)	N <sub>DL</sub>	Frequency of Downlink (MHz)
Low Range	200	26691	814.1	8691	859.1
Mid Range	200	26740	819.0	8740	864.0
High Range	200	26789	823.9	8789	868.9




### 3.2 DESCRIPTION OF TEST MODES

Following mode(s) is (were) found to be the worst case(s) and selected for the final test.

LTE BAND 26 MODE					
Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Radiated Spurious Emissions	26697 to 26783	26740	1.4MHz	QPSK	1RB
	26715 to 26765	26740	5MHz	QPSK	1RB
	26740	26740	10MHz	QPSK	1RB
Test Item	Available Channel	Tested Channel	Sub-carrier Spacing(kHz)	Modulation	Mode
Radiated Spurious Emissions	26691 to 26789	26740	3.75	QPSK	1RB
	26691 to 26789	26740	15	QPSK	1RB

### 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



### 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
-	-	-	-	-

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	USB Cable	YES	NO	1m

## 4. TEST RESULT

### 4.1 RADIATED SPURIOUS EMISSIONS MEASUREMENT

#### 4.1.1 LIMIT



The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to -13dBm.


$E$  (dB $\mu$ V/m) = EIRP (dBm) -  $20 \log D$  + 104.8; where D is the measurement distance in meters. The emission limit equal to 82.26dB $\mu$ V/m.

#### 4.1.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.2 or ANSI C63.26-2015 Section 5.5.

1. The EUT was placed on the top of a thickness 0.1 meter above the ground at a 3 meter semi-anechoic chamber.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
4. Start the test, rotate the table 360° to find the worst Angle, maintain the worst Angle, raise the antenna to 1-4m to find the worst height, maintain the worst height, then rotate the table to determine the final worst Angle, grab the spectrum diagram.
5. EUT shall be placed in accordance with X,Y,Z as required by Figure 5 in ANSI C63.26. Repeat Step 5 above to find the worst placement. Test all bands according to the worst placement.
6. Then EIRP is then converted to field strength as follows in Equation
7.  $E$  (dB $\mu$ V/m) = EIRP (dBm) -  $20 \log(D)$  + 104.8; where D is the measurement distance (in the far field region) in m. The emission limit equal to 82.26dB $\mu$ V/m or 70.26dB $\mu$ V/m or 55.26dB $\mu$ V/m.

**4.1.3 TEST SETUP LAYOUT****Below 30MHz****30MHz to 1000MHz**



**4.1.4 TESTDEVIATION**

No deviation.

**4.1.5 TEST RESULTS (9KHZ TO 30MHZ)**

Please refer to the APPENDIX A.

**4.1.6 TEST RESULTS (30MHZ TO 1000MHZ)**

Please refer to the APPENDIX B.

**4.1.7 TEST RESULTS (ABOVE 1000MHZ)**

Please refer to the APPENDIX C.



#### 4. LIST OF MEASUREMENT EQUIPMENTS

Radiated Emissions - 9 kHz to 30 MHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Active Loop Antenna	Schwarzbeck	FMZB 1513-60B	1513-60 B-034	Mar. 30, 2025
2	MXE EMI Receiver	Keysight	N9038A	MY56400091	Dec. 22, 2024
3	Cable	N/A	RW2350-3.8A-N MBM-1.5M	N/A	Jun. 09, 2025
4	Cable	N/A	RG 213/U	N/A	Jun. 09, 2025
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
6	966 Chamber room	ETS	9*6*6	N/A	Jul. 11, 2024 May 16, 2025
7	WPT coil	N/A	100KHz-300KHz	N/A	N/A



Radiated Emissions - 30 MHz to 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	1462	Dec. 13, 2024
2	Attenuator	EMC INSTRUMENT	EMCI-N-6-06	AT-06009	Dec. 13, 2024
3	Preamplifier	EMC INSTRUMENT	EMC001330	980863	Apr. 07, 2025
4	Cable	RegalWay	LMR400-NMNM -12.5m	N/A	Jul. 04, 2024 Jun. 06, 2025
5	Cable	RegalWay	LMR400-NMNM -3m	N/A	Jul. 04, 2024 Jun. 06, 2025
6	Cable	RegalWay	LMR400-NMNM -0.5m	N/A	Jul. 04, 2024 Jun. 06, 2025
7	Receiver	Agilent	N9038A	MY52130039	Dec. 22, 2024
8	Positioning Controller	MF	MF-7802	N/A	N/A
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
10	966 Chamber room	CM	9*6*6	N/A	May 16, 2025
11	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Dec. 22, 2024
12	wideband radio communication tester	R&S	CMW500	152372	Dec. 22, 2024



Radiated Emissions - Above 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	MXA Signal Analyzer	KEYSIGHT	N9020B	MY63380204	Nov. 17, 2024
2	Receiver	Agilent	N9038A	MY52130039	Dec. 22, 2024
3	Preamplifier	EMC INSTRUMENT	EMC118A45SE	980888	Nov. 17, 2024
4	EXA Spectrum Analyzer	Keysight	N9010A	MY55150209	May 31, 2025
5	Double Ridged Guide Antenna	ETS	3115	75846	Mar. 20, 2025
6	Cable	RegalWay	RWLP50-4.0A-SMS M-12.5M	N/A	Feb. 19, 2025
7	Cable	RegalWay	RWLP50-4.0A-NM RASM-2.5M	N/A	Aug. 08, 2024 Jul. 03, 2025
8	Cable	RegalWay	RWLP50-4.0A-NM RASMRA-0.8M	N/A	Aug. 08, 2024 Jul. 03, 2025
9	966 Chamber room	CM	9*6*6	N/A	May 19, 2025
10	Filter	COM-MW	ZHPF-M1-13G-W1 02	N/A	May 31, 2025
11	Positioning Controller	MF	MF-7802	N/A	N/A
12	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
13	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Dec. 22, 2024
14	wideband radio communication tester	R&S	CMW500	152372	Dec. 22, 2024

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
All calibration period of equipment list is one year.

**5. EUT TEST PHOTO****Radiated Emissions Test Photos****9 kHz to 30 MHz**



**Radiated Emissions Test Photos****30 MHz to 1 GHz**


**Radiated Emissions Test Photos****Above 1 GHz**

## **APPENDIX A - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)**

Test Mode : TX Mode


Test Mode : TX Mode

Ant 0°



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	0.866	30.98	21.18	52.16	68.85	-16.69	OP	
2	2.210	26.61	21.11	47.72	69.54	-21.82	OP	
3	6.747	23.86	21.19	45.05	69.54	-24.49	OP	

Ant 0°




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	0.011	58.26	20.52	78.78	126.94	-48.16	AVG	
2 *	0.034	49.36	21.12	70.48	117.05	-46.57	AVG	
3	0.046	45.21	21.18	66.39	114.39	-48.00	AVG	

Test Mode : TX Mode


Test Mode : TX Mode

Ant 90°



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	0.027	50.61	21.00	71.61	119.11	-47.50	AVG	
2	0.045	47.63	21.18	68.81	114.52	-45.71	AVG	
3 *	0.053	46.25	21.21	67.46	113.17	-45.71	AVG	

Ant 90°



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	1.046	27.97	21.18	49.15	67.22	-18.07	OP	
2	1.762	25.70	21.12	46.82	69.54	-22.72	OP	
3	2.329	21.75	21.12	42.87	69.54	-26.67	OP	


## **APPENDIX B - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)**

**For eMTC:**

Test Mode : LTE Band 26\_TX CH26740\_1.4MHz


Test Mode : LTE Band 26\_TX CH26740\_1.4MHz

**Vertical**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	166.285	36.35	-11.02	25.33	82.30	-56.97	peak	
2	339.915	36.89	-9.39	27.50	82.30	-54.80	peak	
3	516.940	37.78	-5.49	32.29	82.30	-50.01	peak	
4	593.570	37.12	-3.61	33.51	82.30	-48.79	peak	
5	704.835	38.30	-2.05	36.25	82.30	-46.05	peak	
6 *	922.865	38.57	0.48	39.05	82.30	-43.25	peak	

**Horizontal**




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	292.395	35.95	-10.59	25.36	82.30	-56.94	peak	
2	371.925	37.47	-8.77	28.70	82.30	-53.60	peak	
3	487.355	37.86	-8.03	31.83	82.30	-50.47	peak	
4	649.345	36.78	-2.69	34.09	82.30	-48.21	peak	
5	704.150	40.01	-2.07	37.94	82.30	-44.36	peak	
6 *	961.685	38.60	0.71	39.31	82.30	-42.99	peak	

Test Mode : LTE Band 26\_TX CH26740\_5MHz


Test Mode : LTE Band 26\_TX CH26740\_5MHz

**Vertical**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	154.645	36.17	-10.95	25.22	82.30	-57.08	peak	
2	321.000	37.13	-9.82	27.31	82.30	-54.99	peak	
3	403.450	36.38	-7.79	28.59	82.30	-53.71	peak	
4	496.085	37.50	-5.89	31.67	82.30	-50.63	peak	
5	640.815	37.61	-2.82	34.79	82.30	-47.51	peak	
6 *	966.050	39.03	0.75	39.78	82.30	-42.52	peak	


**Horizontal**




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	259.890	37.91	-11.96	25.95	82.30	-56.35	peak	
2	334.095	35.80	-9.47	26.33	82.30	-55.97	peak	
3	432.065	37.03	-7.06	29.97	82.30	-52.33	peak	
4	588.235	37.90	-3.77	34.13	82.30	-48.17	peak	
5	676.990	37.13	-2.41	34.72	82.30	-47.58	peak	
6 *	970.900	38.84	0.79	39.63	82.30	-42.67	peak	

Test Mode : LTE Band 26\_TX CH26740\_10MHz

Test Mode : LTE Band 26\_TX CH26740\_10MHz

**Vertical**


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		153.190	36.02	-10.99	25.03	82.30	-57.27	peak	
2		378.230	36.25	-8.55	27.70	82.30	-54.60	peak	
3		474.260	37.49	-6.23	31.26	82.30	-51.04	peak	
4		577.565	35.88	-4.06	31.82	82.30	-50.48	peak	
5		686.320	37.33	-2.51	34.82	82.30	-47.48	peak	
6 *		957.905	38.26	0.67	38.93	82.30	-43.37	peak	

**Horizontal**


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		291.900	36.04	-10.60	25.44	82.30	-56.86	peak	
2		391.810	36.64	-8.04	28.60	82.30	-53.70	peak	
3		517.425	37.54	-5.47	32.07	82.30	-50.23	peak	
4		636.735	42.87	-2.88	39.99	82.30	-42.31	peak	
5		707.545	40.64	-1.98	38.66	82.30	-43.64	peak	
6 *		954.410	40.24	0.65	40.89	82.30	-41.41	peak	




For NB-IoT:

Test Mode : LTE Band 26\_TX CH26740\_3.75kHz

Test Mode : LTE Band 26\_TX CH26740\_3.75kHz

Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	35.335	40.78	-12.27	28.51	82.30	-53.79	peak	
2	168.710	35.72	-11.13	24.59	82.30	-57.71	peak	
3	261.830	36.76	-11.85	24.91	82.30	-57.39	peak	
4	414.120	36.32	-7.52	28.80	82.30	-53.50	peak	
5	574.170	36.25	-4.14	32.11	82.30	-50.19	peak	
6 *	692.510	36.82	-2.24	34.58	82.30	-47.62	peak	

Horizontal




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	44.550	35.40	-11.39	24.01	82.30	-58.29	peak	
2	162.405	36.78	-10.87	24.91	82.30	-57.39	peak	
3	343.795	36.74	-9.35	27.39	82.30	-54.91	peak	
4	458.255	36.29	-6.47	29.82	82.30	-52.48	peak	
5	576.110	36.26	-4.10	32.16	82.30	-50.14	peak	
6 *	738.100	38.38	-1.23	37.13	82.30	-45.17	peak	

Test Mode : LTE Band 26\_TX CH26740\_15kHz


Test Mode : LTE Band 26\_TX CH26740\_15kHz

Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	32.910	40.46	-12.57	27.89	82.30	-54.41	peak	
2	150.280	36.08	-11.09	24.99	82.30	-57.31	peak	
3	288.505	35.84	-10.65	25.19	82.30	-57.11	peak	
4	414.120	36.80	-7.52	29.28	82.30	-53.02	peak	
5	563.985	36.43	-4.44	31.99	82.30	-50.31	peak	
6 *	692.995	36.77	-2.23	34.54	82.30	-47.76	peak	

Horizontal



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	57.645	35.72	-11.70	24.02	82.30	-58.28	peak	
2	154.160	36.17	-10.97	25.20	82.30	-57.10	peak	
3	287.590	36.75	-8.93	27.82	82.30	-54.48	peak	
4	501.420	38.32	-5.60	32.72	82.30	-49.58	peak	
5	632.370	36.97	-2.95	34.02	82.30	-48.28	peak	
6 *	749.740	37.95	-0.94	37.01	82.30	-45.29	peak	



## **APPENDIX C - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)**

For eMTC:

Test Mode : LTE Band 26\_TX CH26740\_1.4MHz

Test Mode : LTE Band 26\_TX CH26740\_1.4MHz

Vertical



Horizontal



Test Mode : LTE Band 26\_TX CH26740\_5M

Test Mode : LTE Band 26\_TX CH26740\_5M

Vertical




Horizontal




Test Mode : LTE Band 26\_TX CH26740\_10MHz

Test Mode : LTE Band 26\_TX CH26740\_10MHz

**Vertical**


No. Mk.	Freq. MHz	Reading Level dBµV	Correct Factor dB	Measurement dBµV/m	Limit dBµV/m	Margin dB	Detector	Comment
1 *	17473.000	40.78	9.17	49.95	82.30	-32.35	peak	

**Horizontal**



No. Mk.	Freq. MHz	Reading Level dBµV	Correct Factor dB	Measurement dBµV/m	Limit dBµV/m	Margin dB	Detector	Comment
1 *	14668.000	39.76	8.79	48.55	82.30	-33.75	peak	

**For NB-IoT:**

Test Mode : LTE Band 26\_TX CH26740\_3.75kHz


Test Mode : LTE Band 26\_TX CH26740\_3.75kHz

**Vertical**



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	14498.000	39.59	9.16	48.75	82.30	-33.55	peak	

**Horizontal**




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	13809.500	39.41	9.51	48.92	82.30	-33.38	peak	

Test Mode : LTE Band 26\_TX CH26740\_15kHz


Test Mode : LTE Band 26\_TX CH26740\_15kHz

**Vertical**



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	13792.500	39.11	9.50	48.61	82.30	-33.69	peak	

**Horizon**



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	10690.000	38.00	7.92	45.92	82.30	-36.38	peak	

**End of Test Report**