





FCC RADIO TEST REPORT

FCC ID : RI7FN990A40
Equipment : 5G NR Module
Brand Name : 
Model Name : FN990A40
Marketing Name : FN990A40
Applicant : Telit Communications S.p.A.
Viale Stazione di Prosecco 5/b, Trieste 34010, Italy
Manufacturer : Telit Communications S.p.A.
Viale Stazione di Prosecco 5/b, Trieste 34010, Italy
Standard : FCC 47 CFR Part 2, 90(R)

The product was received on Jul. 19, 2022 and testing was performed from Jul. 29, 2022 to Nov. 23, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

| | |
|--|-----------|
| History of this test report | 3 |
| Summary of Test Result | 4 |
| 1 General Description | 5 |
| 1.1 Product Feature of Equipment Under Test..... | 5 |
| 1.2 Modification of EUT | 5 |
| 1.3 Testing Site..... | 5 |
| 1.4 Applied Standards | 6 |
| 2 Test Configuration of Equipment Under Test | 7 |
| 2.1 Test Mode..... | 7 |
| 2.2 Connection Diagram of Test System..... | 8 |
| 2.3 Support Unit used in test configuration and system | 8 |
| 2.4 Measurement Results Explanation Example..... | 8 |
| 2.5 Frequency List of Low/Middle/High Channels | 9 |
| 3 Conducted Test Items | 10 |
| 3.1 Measuring Instruments | 10 |
| 3.2 Conducted Output Power Measurement and ERP..... | 11 |
| 3.3 Peak-to-Average Ratio | 12 |
| 3.4 Occupied Bandwidth..... | 13 |
| 3.5 Conducted Band Edge | 14 |
| 3.6 Emission Mask..... | 15 |
| 3.7 Conducted Spurious Emission | 16 |
| 3.8 Frequency Stability | 17 |
| 4 Radiated Test Items | 18 |
| 4.1 Measuring Instruments | 18 |
| 4.2 Radiated Spurious Emission | 20 |
| 5 List of Measuring Equipment | 21 |
| 6 Uncertainty of Evaluation | 21 |
| Appendix A. Test Results of Conducted Test | |
| Appendix B. Test Results of Radiated Test | |
| Appendix C. Test Setup Photographs | |



History of this test report

| Report No. | Version | Description | Issue Date |
|------------|---------|-------------------------|---------------|
| FG270608D | 01 | Initial issue of report | Dec. 01, 2022 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |



Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items | Result (PASS/FAIL) | Remark |
|---------------|--|--|--------------------|--|
| 3.2 | §2.1046 | Conducted Output Power | Reporting only | - |
| | §90.542 (a)(7) | Effective Radiated Power | Pass | - |
| 3.3 | - | Peak-to-Average Ratio | Reporting only | - |
| 3.4 | §2.1049 | Occupied Bandwidth | Reporting only | - |
| 3.5 | §2.1053 §90.543 (e)(2) | Conducted Band Edge Measurement | Pass | - |
| 3.6 | §2.1051 §90.210 (n) | Emission Mask | Pass | - |
| 3.7 | §2.1053 §90.543 (e)(3) | Conducted Spurious Emission | Pass | - |
| 3.8 | §2.1055 §90.539 (e) | Frequency Stability Temperature & Voltage | Pass | - |
| 4.2 | §2.1053 §90.543 (e)(3) §90.543 (f) | Radiated Spurious Emission | Pass | 17.89 dB under the limit at 1586.000 MHz |

Declaration of Conformity:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
- The measurement uncertainty please refer to report "Uncertainty of Evaluation".

Comments and Explanations:

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Avis Chuang

Report Producer: Michelle Chen



1 General Description

1.1 Product Feature of Equipment Under Test

WCDMA/LTE/5G NR, and GNSS

| Product Feature | |
|-----------------|--|
| Antenna Type | WWAN: Monopole Antenna GPS/Glonass/BDS/Galileo/SBAS: Monopole Antenna |
| Antenna Gain | 3.90 dBi |

Remark: The EUT's information above is declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Site

| | |
|-----------------------|---|
| Test Site | Sporton International Inc. EMC & Wireless Communications Laboratory |
| Test Site Location | No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978 |
| Test Site No. | Sporton Site No. TH03-HY |
| Test Engineer | George Chen |
| Temperature (°C) | 22.8~24.5 |
| Relative Humidity (%) | 51~58 |

| | |
|-----------------------|--|
| Test Site | Sporton International Inc. Wensan Laboratory |
| Test Site Location | No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855 |
| Test Site No. | Sporton Site No. 03CH13-HY (TAF Code: 3786) |
| Test Engineer | Rain Lee, Jacky Hong and Mancy Chou |
| Temperature (°C) | 20~25 |
| Relative Humidity (%) | 50~60 |
| Remark | The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory |

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786



1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ FCC 47 CFR Part 2, Part 90(R)
- ♦ ANSI / TIA-603-E
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in two antenna polarization (Horizontal and Vertical), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and only the worst case emissions were reported in this report.

| Conducted Test Cases | Band | Bandwidth (MHz) | | | | | | Modulation | | | | RB # | | | Test Channel | | |
|-----------------------------|--|-----------------|---|---|----|----|----|------------|-------|-------|--------|------------|------|------|--------------|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16QAM | 64QAM | 256QAM | 1 | Half | Full | L | M | H |
| Max. Output Power | 14 | - | - | v | v | - | - | v | v | v | v | v | v | v | v | v | v |
| Peak-to-Average Ratio | 14 | - | - | | v | - | - | v | v | v | v | | | v | | v | |
| 26dB and 99% Bandwidth | 14 | - | - | v | v | - | - | v | v | v | v | | | v | | v | |
| Conducted Band Edge | 14 | - | - | v | v | - | - | v | v | v | v | v | | v | v | | v |
| Emission Mask | 14 | - | - | v | v | - | - | v | v | v | v | v | | v | v | v | v |
| Conducted Spurious Emission | 14 | - | - | v | v | - | - | v | | | | v | | | v | v | v |
| Frequency Stability | 14 | - | - | | v | - | - | v | | | | | | v | | v | |
| E.R.P | 14 | - | - | v | v | - | - | v | v | v | v | Max. Power | | | | | |
| Radiated Spurious Emission | 14 | Worst Case | | | | | | | | | | | | v | v | v | |
| Remark | <ol style="list-style-type: none"> The mark "v " means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. One representative bandwidth is selected to perform PAR and frequency stability. | | | | | | | | | | | | | | | | |

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

| Item | Equipment | Brand Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1. | System Simulator | Anritsu | MT8820C | N/A | N/A | Unshielded, 1.8 m |
| 2. | System Simulator | Anritsu | MT8821C | N/A | N/A | Unshielded, 1.8 m |

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.5 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

| LTE Band 14 Channel and Frequency List | | | | |
|--|------------------------|--------|--------|---------|
| BW [MHz] | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 10 | Channel | - | 23330 | - |
| | Frequency | - | 793 | - |
| 5 | Channel | 23305 | 23330 | 23355 |
| | Frequency | 790.5 | 793 | 795.5 |

3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power Measurement and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.



3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

90.543(e)

- (1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations.
- (2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.
- (3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW $\geq 1\%$ EBW in the 100kHz band immediately outside and adjacent to the band edge.
4. Beyond the 100kHz band from the band edge, RBW=100kHz was used.
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.6 Emission Mask

3.6.1 Description of Emissions Mask Measurement

Transmitters designed must meet the emission mask comply with the emission mask provisions of FCC Part 90.210(n).

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The power of the modulated signal was measured on a spectrum analyzer using an RMS and 10 second sweep time in order to maximize the level.
3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



3.7 Conducted Spurious Emission

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.8 Frequency Stability

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.8.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at 20±5° C and connected with the base station.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.1.1 Test Setup


For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.1.2 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.2 Radiated Spurious Emission

4.2.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

| Instrument | Brand Name | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|-------------------|-----------------|---------------------------------|-----------------------|----------------------------------|------------------|---------------------------------|---------------|--------------------------|
| Loop Antenna | Rohde & Schwarz | HFH2-Z2 | 100488 | 9 kHz~30 MHz | May 13, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | May 12, 2023 | Radiation (03CH13-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 102 | 505134/2 | 30MHz~40GHz | Feb. 21, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Feb. 20, 2023 | Radiation (03CH13-HY) |
| Amplifier | SONOMA | 310N | 187282 | 9kHz~1GHz | Dec. 15, 2021 | Jul. 29, 2022~ Aug. 02, 2022 | Dec. 14, 2022 | Radiation (03CH13-HY) |
| Bilog Antenna | TESEQ | CBL 6111D & 00800N1D01N-06 | 40103 & 07 | 30MHz~1GHz | Apr. 24, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Apr. 23, 2023 | Radiation (03CH13-HY) |
| Bilog Antenna | TESEQ | CBL 6111D & 00800N1D01N-06 | 41912 & 05 | 30MHz~1GHz | Feb. 06, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Feb. 05, 2023 | Radiation (03CH13-HY) |
| Hygrometer | TECPEL | DTM-303B | TP200889 | N/A | Sep. 30, 2021 | Jul. 29, 2022~ Aug. 02, 2022 | Sep. 29, 2022 | Radiation (03CH13-HY) |
| Preamplifier | MITEQ | AMF-7D-0010180 0-30-10P | 1590074 | 1GHz~18GHz | May 17, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | May 16, 2023 | Radiation (03CH13-HY) |
| Preamplifier | Keysight | 83017A | MY53270147 | 1GHz~26.5GHz | Oct. 26, 2021 | Jul. 29, 2022~ Aug. 02, 2022 | Oct. 25, 2022 | Radiation (03CH13-HY) |
| Spectrum Analyzer | Keysight | N9010A | MY55370526 | 10Hz~44GHz | Mar. 18, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Mar. 17, 2023 | Radiation (03CH13-HY) |
| Filter | Wainwright | WLK4-1000-1530- 8000-40SS | SN12 | 1.53GHz Low Pass Filter | Sep. 14, 2021 | Jul. 29, 2022~ Aug. 02, 2022 | Sep. 13, 2022 | Radiation (03CH13-HY) |
| Filter | Wainwright | WHKX12-1080-12 00-15000-60SS | SN3 | 1.2GHz High Pass Filter | Jun. 30, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Jun. 29, 2023 | Radiation (03CH13-HY) |
| Filter | Wainwright | WHKX12-2700-30 00-18000-60SS | SN2 | 3GHz High Pass Filter | Jul. 12, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Jul. 11, 2023 | Radiation (03CH13-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 126E | 0030/126E | 30MHz~18GHz | Feb. 09, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Feb. 08, 2023 | Radiation (03CH13-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 104 | 804793/4 | 30MHz~18GHz | Feb. 09, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Feb. 08, 2023 | Radiation (03CH13-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 102 | 804011/2,8040 12/2 | 18GHz~40GHz | Jan. 04, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Jan. 03, 2023 | Radiation (03CH13-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 104 | MY24961/4 | 30MHz~18GHz | Feb. 09, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Feb. 08, 2023 | Radiation (03CH13-HY) |
| Controller | EMEC | EM1000 | N/A | Control Turn table & Ant Mast | N/A | Jul. 29, 2022~ Aug. 02, 2022 | N/A | Radiation (03CH13-HY) |
| Antenna Mast | EMEC | AM-BS-4500-B | N/A | 1m~4m | N/A | Jul. 29, 2022~ Aug. 02, 2022 | N/A | Radiation (03CH13-HY) |
| Turn Table | EMEC | TT2000 | N/A | 0~360 Degree | N/A | Jul. 29, 2022~ Aug. 02, 2022 | N/A | Radiation (03CH13-HY) |
| Horn Antenna | SCHWARZBE CK | BBHA 9120 D | 9120D-02114 | 1-18GHz | Aug. 04, 2021 | Jul. 29, 2022~ Aug. 02, 2022 | Aug. 03, 2022 | Radiation (03CH13-HY) |
| Horn Antenna | SCHWARZBE CK | BBHA 9120 D | 9120D-1212 | 1GHz~18GHz | Mar. 10, 2022 | Jul. 29, 2022~ Aug. 02, 2022 | Mar. 09, 2023 | Radiation (03CH13-HY) |



| Instrument | Brand Name | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|------------------------------|-----------------|--|------------|-------------------------------------|------------------|---------------------------------|---------------|------------------------|
| Radio Communication Analyzer | Anritsu | MT8821C | 6262025280 | LTE FDD/TDD LTE-2CC DLCA/ULCA | Oct. 29, 2021 | Aug. 13, 2022~ Oct. 27, 2022 | Oct. 28, 2022 | Conducted (TH03-HY) |
| Radio Communication Analyzer | Anritsu | MT8821C | 6262025353 | LTE FDD/TDD LTE-2CC DLCA/ULCA | Oct. 13, 2022 | Oct. 28, 2022~ Nov. 23, 2022 | Oct. 12, 2023 | Conducted (TH03-HY) |
| Spectrum Analyzer | Rohde & Schwarz | FSV40 | 101908 | 10Hz~40GHz | Oct. 01, 2022 | Aug. 13, 2022~ Sep. 26, 2022 | Sep. 30, 2022 | Conducted (TH03-HY) |
| Spectrum Analyzer | Rohde & Schwarz | FSV40 | 101908 | 10Hz~40GHz | Sep. 27, 2022 | Sep. 27, 2022~ Nov. 23, 2022 | Sep. 26, 2023 | Conducted (TH03-HY) |
| Thermal Chamber | ESPEC | SH-641 | 92013720 | -40°C ~90°C | Sep. 09, 2021 | Aug. 13, 2022~ Sep. 07, 2022 | Sep. 08, 2022 | Conducted (TH03-HY) |
| Thermal Chamber | ESPEC | SH-641 | 92013720 | -40°C ~90°C | Sep. 07, 2022 | Sep. 08, 2022~ Nov. 23, 2022 | Sep. 06, 2023 | Conducted (TH03-HY) |
| DC Power Supply | GW Instek | GPP-2323 | GES906037 | 0V~64V : 0A~6A | Jan. 06, 2022 | Aug. 13, 2022~ Nov. 23, 2022 | Jan. 05, 2023 | Conducted (TH03-HY) |
| Coupler | Warison | 20dB 25W SMA Directional Coupler | #B | 1-18GHz | Jan. 07, 2022 | Aug. 13, 2022~ Nov. 23, 2022 | Jan. 06, 2023 | Conducted (TH03-HY) |



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|---------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 3.40 dB |
|---|---------|

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

| | |
|---|---------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 3.81 dB |
|---|---------|



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power & ERP/EIRP)

| LTE Band 14 Maximum Average Power [dBm] (GT - LC = 3.9 dB) | | | | | | | | |
|--|----------|-----------|---------|--------|--------|---------|-----------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest | ERP (dBm) | ERP (W) |
| 10 | 1 | 0 | QPSK | | 23.00 | | 24.75 | 0.2985 |
| 10 | 1 | 25 | | | 22.89 | | | |
| 10 | 1 | 49 | | | 22.84 | | | |
| 10 | 25 | 0 | | | 21.92 | | | |
| 10 | 25 | 12 | | | 21.88 | | | |
| 10 | 25 | 25 | | | 21.91 | | | |
| 10 | 50 | 0 | | | 21.85 | | | |
| 10 | 1 | 0 | 16-QAM | | 22.32 | | 24.07 | 0.2553 |
| 10 | 1 | 25 | | | 22.30 | | | |
| 10 | 1 | 49 | | | 22.26 | | | |
| 10 | 25 | 0 | | | 20.89 | | | |
| 10 | 25 | 12 | | | 20.90 | | | |
| 10 | 25 | 25 | | | 20.95 | | | |
| 10 | 50 | 0 | | | 20.87 | | | |
| 10 | 1 | 0 | 64-QAM | | 21.13 | | 22.89 | 0.1945 |
| 10 | 1 | 25 | | | 21.14 | | | |
| 10 | 1 | 49 | | | 21.06 | | | |
| 10 | 25 | 0 | | | 19.90 | | | |
| 10 | 25 | 12 | | | 19.90 | | | |
| 10 | 25 | 25 | | | 19.94 | | | |
| 10 | 50 | 0 | | | 19.84 | | | |
| 10 | 1 | 0 | 256-QAM | | 18.08 | | 19.86 | 0.0968 |
| 10 | 1 | 25 | | | 18.11 | | | |
| 10 | 1 | 49 | | | 18.06 | | | |
| 10 | 25 | 0 | | | 17.95 | | | |
| 10 | 25 | 12 | | | 17.98 | | | |
| 10 | 25 | 25 | | | 17.98 | | | |
| 10 | 50 | 0 | | | 17.92 | | | |
| Limit | ERP < 3W | | | Result | | | Pass | |




| LTE Band 14 Maximum Average Power [dBm] (GT - LC = 3.9 dB) | | | | | | | | |
|--|----------|-----------|---------|--------|--------|---------|-----------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest | ERP (dBm) | ERP (W) |
| 5 | 1 | 0 | QPSK | 22.90 | 22.88 | 22.89 | 24.73 | 0.2972 |
| 5 | 1 | 12 | | 22.95 | 22.96 | 22.98 | | |
| 5 | 1 | 24 | | 22.89 | 22.88 | 22.87 | | |
| 5 | 12 | 0 | | 21.87 | 21.89 | 21.86 | | |
| 5 | 12 | 7 | | 21.96 | 21.97 | 21.87 | | |
| 5 | 12 | 13 | | 21.92 | 21.93 | 21.91 | | |
| 5 | 25 | 0 | | 21.93 | 21.86 | 21.85 | | |
| 5 | 1 | 0 | 16-QAM | 22.25 | 22.26 | 22.27 | 24.16 | 0.2606 |
| 5 | 1 | 12 | | 22.32 | 22.41 | 22.36 | | |
| 5 | 1 | 24 | | 22.28 | 22.22 | 22.20 | | |
| 5 | 12 | 0 | | 20.90 | 20.94 | 20.93 | | |
| 5 | 12 | 7 | | 21.04 | 21.03 | 20.93 | | |
| 5 | 12 | 13 | | 21.01 | 20.97 | 20.97 | | |
| 5 | 25 | 0 | | 20.94 | 20.89 | 20.88 | | |
| 5 | 1 | 0 | 64-QAM | 21.18 | 21.16 | 21.09 | 22.94 | 0.1968 |
| 5 | 1 | 12 | | 21.17 | 21.19 | 21.14 | | |
| 5 | 1 | 24 | | 21.10 | 21.15 | 21.10 | | |
| 5 | 12 | 0 | | 19.91 | 19.94 | 19.89 | | |
| 5 | 12 | 7 | | 19.96 | 20.04 | 19.92 | | |
| 5 | 12 | 13 | | 19.98 | 19.96 | 19.94 | | |
| 5 | 25 | 0 | | 19.97 | 19.88 | 19.88 | | |
| 5 | 1 | 0 | 256-QAM | 18.06 | 18.04 | 18.05 | 19.88 | 0.0973 |
| 5 | 1 | 12 | | 18.13 | 18.11 | 18.12 | | |
| 5 | 1 | 24 | | 18.06 | 18.04 | 18.05 | | |
| 5 | 12 | 0 | | 17.81 | 17.79 | 17.80 | | |
| 5 | 12 | 7 | | 17.89 | 17.87 | 17.88 | | |
| 5 | 12 | 13 | | 17.91 | 17.89 | 17.90 | | |
| 5 | 25 | 0 | | 17.93 | 17.91 | 17.92 | | |
| Limit | ERP < 3W | | | Result | | | Pass | |



LTE Band 14

Peak-to-Average Ratio

| Mode | LTE Band 14 / 10MHz | | | | |
|-----------|---------------------|---------|---------|---------|-------------|
| Mod. | QPSK | 16QAM | 64QAM | 256QAM | Limit: 13dB |
| RB Size | Full RB | Full RB | Full RB | Full RB | Result |
| Middle CH | 4.52 | 5.65 | 6.29 | 6.55 | PASS |






26dB Bandwidth

| Mode | LTE Band 14 : 26dB BW(MHz) | | | | | | | | | | | |
|-----------|----------------------------|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Middle CH | - | - | - | - | 4.95 | 5.02 | 10.07 | 9.81 | - | - | - | - |
| Mode | LTE Band 14 : 26dB BW(MHz) | | | | | | | | | | | |
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM |
| Middle CH | - | - | - | - | 4.99 | 4.83 | 9.87 | 10.01 | - | - | - | - |




LTE Band 14

Middle Channel / 5MHz / QPSK




Date: 16.AUG.2022 16:47:05

Middle Channel / 5MHz / 16QAM




Date: 16.AUG.2022 16:47:34

Middle Channel / 10MHz / QPSK




Date: 16.AUG.2022 16:59:56

Middle Channel / 10MHz / 16QAM




Date: 16.AUG.2022 16:59:27

Middle Channel / 5MHz / 64QAM



Date: 16.AUG.2022 16:55:55

Middle Channel / 10MHz / 64QAM




Date: 16.AUG.2022 17:07:26




LTE Band 14

Middle Channel / 5MHz / 256QAM

Middle Channel / 10MHz / 256QAM



Date: 17_AUG.2022 04:32:53



Date: 17_AUG.2022 04:38:39




Occupied Bandwidth

| Mode | LTE Band 14 : 99%OBW(MHz) | | | | | | | | | | | |
|-----------|---------------------------|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Middle CH | - | - | - | - | 4.50 | 4.51 | 8.97 | 9.07 | - | - | - | - |
| Mode | LTE Band 14 : 99%OBW(MHz) | | | | | | | | | | | |
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM | 64QAM | 256QAM |
| Middle CH | - | - | - | - | 4.51 | 4.49 | 9.05 | 9.01 | - | - | - | - |




LTE Band 14

Middle Channel / 5MHz / QPSK




Date: 16.AUG.2022 16:48:18

Middle Channel / 5MHz / 16QAM




Date: 16.AUG.2022 16:47:48

Middle Channel / 10MHz / QPSK




Date: 16.AUG.2022 16:58:43

Middle Channel / 10MHz / 16QAM




Date: 16.AUG.2022 16:59:13

Middle Channel / 5MHz / 64QAM



Date: 16.AUG.2022 16:56:09

Middle Channel / 10MHz / 64QAM




Date: 16.AUG.2022 17:07:12




LTE Band 14

Middle Channel / 5MHz / 256QAM



Date: 17.AUG.2022 04:33:17

Middle Channel / 10MHz / 256QAM



Date: 17.AUG.2022 04:38:09





Conducted Band Edge

LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB





Date: 16.AUG.2022 16:44:33

Date: 16.AUG.2022 16:52:15

Lowest Band Edge / Full RB

Highest Band Edge / Full RB




Date: 16.AUG.2022 16:41:34

Date: 16.AUG.2022 16:49:16




LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 16.AUG.2022 16:43:34

Highest Band Edge / 1 RB




Date: 16.AUG.2022 16:51:16

Lowest Band Edge / Full RB



Date: 16.AUG.2022 16:42:34

Highest Band Edge / Full RB




Date: 16.AUG.2022 16:50:17




LTE Band 14 / 5MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 16.AUG.2022 16:55:23

Highest Band Edge / 1 RB




Date: 16.AUG.2022 16:58:07

Lowest Band Edge / Full RB



Date: 16.AUG.2022 16:54:24

Highest Band Edge / Full RB




Date: 16.AUG.2022 16:57:07




LTE Band 14 / 5MHz / 256QAM


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB




Date: 16.AUG.2022 17:03:35

Highest Band Edge / 1 RB



Date: 16.AUG.2022 17:04:33

Band Edge / Full RB




Date: 16.AUG.2022 17:00:39




LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 16.AUG.2022 17:02:36

Highest Band Edge / 1 RB



Date: 16.AUG.2022 17:05:31

Band Edge / Full RB




Date: 16.AUG.2022 17:01:37




LTE Band 14 / 10MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 16.AUG.2022 17:09:08

Highest Band Edge / 1 RB



Date: 16.AUG.2022 17:10:07

Band Edge / Full RB





Date: 16.AUG.2022 17:08:09



LTE Band 14 / 10MHz / 256QAM

Lowest Band Edge / 1 RB


Highest Band Edge / 1 RB



Date: 17.AUG.2022 04:36:10

Date: 17.AUG.2022 04:36:40

Band Edge / Full RB



Date: 17.AUG.2022 04:37:38





Conducted Spurious Emission


LTE Band 14 / 5MHz

Lowest Channel / QPSK

Middle Channel / QPSK




Highest Channel / QPSK





LTE Band 14 / 10MHz

Middle Channel / QPSK




Date: 16.AUG.2022 17:06:41




Mask

LTE Band 14 / 5MHz / QPSK

Lowest Channel / 1RB




Date: 16.AUG.2022 17:16:56



Date: 16.AUG.2022 17:18:03

Lowest Channel / Full RB




Date: 16.AUG.2022 17:11:21




LTE Band 14 / 5MHz / 16QAM

Lowest Channel / 1RB




Date: 16.AUG.2022 17:15:50



Date: 16.AUG.2022 17:19:09

Lowest Channel / Full RB




Date: 16.AUG.2022 17:12:29




LTE Band 14 / 5MHz / 64QAM

Lowest Channel / 1RB




Date: 16.AUG.2022 17:14:42



Date: 16.AUG.2022 17:12:11.6

Lowest Channel / Full RB




Date: 16.AUG.2022 17:13:36




LTE Band 14 / 5MHz / 256QAM

Lowest Channel / 1RB




Date: 17.AUG.2022 04:49:05



Date: 17.AUG.2022 04:49:55

Lowest Channel / Full RB




Date: 17.AUG.2022 04:50:46




LTE Band 14 / 5MHz / QPSK

Middle Channel / 1RB




Date: 16.AUG.2022 17:24:38



Date: 16.AUG.2022 17:23:32

Middle Channel / Full RB




Date: 16.AUG.2022 17:50:57




LTE Band 14 / 5MHz / 16QAM

Middle Channel / 1RB




Date: 16.AUG.2022 17:46:33



Date: 16.AUG.2022 17:22:27

Middle Channel / Full RB




Date: 16.AUG.2022 17:49:50




LTE Band 14 / 5MHz / 64QAM

Middle Channel / 1RB




Date: 16.AUG.2022 17:47:39



Date: 16.AUG.2022 17:12:11

Middle Channel / Full RB




Date: 16.AUG.2022 17:48:45




LTE Band 14 / 5MHz / 256QAM

Middle Channel / 1RB




Date: 17.AUG.2022 04:53:06



Date: 17.AUG.2022 04:54:17

Middle Channel / Full RB




Date: 17.AUG.2022 04:51:42




LTE Band 14 / 5MHz / QPSK

Highest Channel / 1RB




Date: 16.AUG.2022 17:57:16



Date: 16.AUG.2022 17:58:143

Highest Channel / Full RB




Date: 16.AUG.2022 17:52:04




LTE Band 14 / 5MHz / 16QAM

Highest Channel / 1RB




Date: 16.AUG.2022 17:56:29



Date: 16.AUG.2022 17:59:51

Highest Channel / Full RB




Date: 16.AUG.2022 17:53:10




LTE Band 14 / 5MHz / 64QAM

Highest Channel / 1RB




Date: 16.AUG.2022 17:55:23



Date: 16.AUG.2022 18:00:58

Highest Channel / Full RB




Date: 16.AUG.2022 17:54:17




LTE Band 14 / 5MHz / 256QAM

Highest Channel / 1RB




Date: 17.AUG.2022 04:55:10



Date: 17.AUG.2022 04:56:09

Highest Channel / Full RB




Date: 17.AUG.2022 04:56:54




LTE Band 14 / 10MHz / QPSK

Middle Channel / 1RB




Date: 16.AUG.2022 18:05:28



Date: 16.AUG.2022 18:04:21

Middle Channel / Full RB




Date: 16.AUG.2022 18:10:57




LTE Band 14 / 10MHz / 16QAM

Middle Channel / 1RB




Date: 16.AUG.2022 18:06:33



Date: 16.AUG.2022 18:03:15

Middle Channel / Full RB




Date: 16.AUG.2022 18:09:51




LTE Band 14 / 10MHz / 64QAM

Middle Channel / 1RB




Date: 16.AUG.2022 18:07:40



Date: 16.AUG.2022 18:02:09

Middle Channel / Full RB




Date: 16.AUG.2022 18:08:46




LTE Band 14 / 10MHz / 256QAM

Middle Channel / 1RB




Date: 17.AUG.2022 04:44:04



Date: 17.AUG.2022 04:44:54

Middle Channel / Full RB



Date: 17.AUG.2022 04:46:19



Frequency Stability

| Test Conditions | | LTE Band 14 (QPSK) / Middle Channel | Limit |
|------------------|-------------------|-------------------------------------|---------|
| Temperature (°C) | Voltage (Volt) | BW 10MHz | Note 2. |
| | | Deviation (ppm) | Result |
| 50 | Normal Voltage | 0.0111 | PASS |
| 40 | Normal Voltage | 0.0040 | |
| 30 | Normal Voltage | 0.0066 | |
| 20(Ref.) | Normal Voltage | 0.0000 | |
| 10 | Normal Voltage | 0.0035 | |
| 0 | Normal Voltage | 0.0042 | |
| -10 | Normal Voltage | 0.0072 | |
| -20 | Normal Voltage | 0.0132 | |
| -30 | Normal Voltage | 0.0025 | |
| 20 | Maximum Voltage | 0.0048 | |
| 20 | Normal Voltage | 0.0000 | |
| 20 | Battery End Point | 0.0039 | |

Note:

1. Normal Voltage = 3.3 V. ; Battery End Point (BEP) = 3.135 V. ; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.



Appendix B. Test Results of Radiated Test

<Ant. 0>

LTE Band 14

| LTE Band 14 / 5MHz / QPSK | | | | | | | | | |
|---------------------------|-------------------|-------------|---------------|---------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Channel | Frequency (MHz) | ERP (dBm) | Limit (dBm) | Margin (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 1576 | -60.25 | -42.15 | -18.10 | -75.53 | -60.77 | 6.27 | 8.94 | H |
| | 2365 | -57.71 | -13 | -44.71 | -75.51 | -57.80 | 7.59 | 9.83 | H |
| | 3153 | -56.99 | -13 | -43.99 | -76.67 | -57.38 | 8.87 | 11.41 | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | 1576 | -60.06 | -42.15 | -17.91 | -75.32 | -60.58 | 6.27 | 8.94 | V |
| | 2365 | -58.44 | -13 | -45.44 | -76.16 | -58.53 | 7.59 | 9.83 | V |
| | 3153 | -57.03 | -13 | -44.03 | -76.74 | -57.42 | 8.87 | 11.41 | V |
| | | | | | | | | | V |
| | | | | | | | | | V |
| | | | | | | | | | V |
| | | | | | | | | | V |
| Middle | 1581 | -60.13 | -42.15 | -17.98 | -75.42 | -60.70 | 6.27 | 8.99 | H |
| | 2372 | -58.66 | -13 | -45.66 | -76.44 | -58.77 | 7.60 | 9.86 | H |
| | 3163 | -56.45 | -13 | -43.45 | -76.15 | -56.84 | 8.89 | 11.43 | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | 1581 | -60.05 | -42.15 | -17.90 | -75.33 | -60.62 | 6.27 | 8.99 | V |
| | 2372 | -58.57 | -13 | -45.57 | -76.26 | -58.68 | 7.60 | 9.86 | V |
| | 3163 | -56.69 | -13 | -43.69 | -76.45 | -57.08 | 8.89 | 11.43 | V |
| | | | | | | | | | V |
| | | | | | | | | | V |
| | | | | | | | | | V |
| | | | | | | | | | V |



| | | | | | | | | | |
|---------|------|--------|--------|--------|--------|--------|------|-------|---|
| Highest | 1586 | -60.04 | -42.15 | -17.89 | -75.35 | -60.67 | 6.27 | 9.05 | H |
| | 2380 | -58.37 | -13 | -45.37 | -76.11 | -58.51 | 7.61 | 9.90 | H |
| | 3173 | -56.36 | -13 | -43.36 | -76.1 | -56.76 | 8.90 | 11.45 | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | | | | | | | | | H |
| | 1586 | -60.08 | -42.15 | -17.93 | -75.4 | -60.71 | 6.27 | 9.05 | V |
| | 2380 | -58.92 | -13 | -45.92 | -76.56 | -59.06 | 7.61 | 9.90 | V |
| | 3173 | -56.46 | -13 | -43.46 | -76.29 | -56.86 | 8.90 | 11.45 | V |
| | | | | | | | | | V |
| | | | | | | | | | V |
| | | | | | | | | | V |
| | | | | | | | | | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.