

Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

2.5 Antenna Description

No antenna is provided (or supplied to the market) together with the product.

Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

2.6 Conducted RF Power Output (FCC Section 2.1046)

§ 2.1046 Measurements required: RF power output.

- (a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tuneup procedure to give the values of current and voltage on the circuit elements specified in § 2.1033(c)(8). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.
- (b) For single sideband, independent sideband, and single channel, controlled carrier radiotelephone transmitters the procedure specified in paragraph (a) of this section shall be employed and, in addition, the transmitter shall be modulated during the test as follows. In all tests, the input level of the modulating signal shall be such as to develop rated peak envelope power or carrier power, as appropriate, for the transmitter.
- (c) For measurements conducted pursuant to paragraphs (a) and (b) of this section, all calculations and methods used by the applicant for determining carrier power or peak envelope power, as appropriate, on the basis of measured power in the radio frequency load attached to the transmitter output terminals shall be shown. Under the test conditions specified, no components of the emission spectrum shall exceed the limits specified in the applicable rule parts as necessary for meeting occupied bandwidth or emission limitations.

Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

TABLE 3a
CONDUCTED RF POWER OUTPUT

824 MHz to 848 MHz Range

Frequency of Fundamental (MHz)	Measurement (dBm)	Measurement (Watt)
824.09	31.12	1.294
835.92	30.29	1.069
848.70	29.99	0.997

2.85dB added for cable and Attenuator loss

Calculation:

$\text{Antilog}(31.12/10) = 1.294 \text{ w}$

Test Date: April 5, 2006

Tester

Signature:



Name: Austin Thompson


Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

Figure 3a.
Conducted RF Power Output




Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

Figure 3b.
Conducted RF Power Output




Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

Figure 3c.
Conducted RF Power Output



Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

TABLE 3b
CONDUCTED RF POWER OUTPUT

1850 MHz to 1909 MHz Range

Frequency of Fundamental (MHz)	Measurement (dBm)	Measurement (Watt)
1.85013	28.54	0.714
1.87990	26.37	0.433
1.90980	27.68	0.586

1.17dB added for cable and Attenuator loss

Calculation:

 $\text{Antilog}(28.54/10) = 0.714 \text{ w}$ **Test Date: April 5, 2006**

Tester

Signature: Name: Austin Thompson


Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

Figure 3d.
Conducted RF Power Output




Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

Figure 3e.
Conducted RF Power Output




Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

Figure 3f.
Conducted RF Power Output



Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

2.7 Field Strength of Spurious Radiation (FCC Section 2.1053)

Spurious emissions were evaluated from 30 MHz to 19.1 GHz at an EUT to antenna distance of 1 or 3 meters. The EUT was tested with an external power source and modulated by its own internal sources. A low, middle and high channel were tested. The EUT was placed on an open area test site and the spurious emissions tested as stipulated by EIT/TIA-603: 1992 section 2.2.12. Measurements for 30 to 1000 MHz were made with the analyzer's bandwidth set to 120 kHz. Measurements above 1 GHz were made with the analyzer's bandwidth set to 1 MHz. The worse case results are shown in Table 4a.

Initial measurements were calculated to determine margin in dB from the Limit. Any margin less than 20dB was repeated using the substitution Method of EIA/TIA-603:1992 section 2.2.1.2.

Substitution Method results are shown in table 4b.

FCC Minimum Standard (FCC Section 24.238)

On any frequency outside a licensee's frequency block, the power of any transmission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.

Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

**TABLE 4a
RADIATED RF POWER OUTPUT**

Radiated Emissions (Theoretical)								
Test By:	Test:	Substitution for GM863 Quad			Client:	Sicom		
	Project:	06-0008		Class:	B	Model:		
Frequency Range		Sicom	Model		S/N		Valid	Calibrated:
		2HN3mH	Model : SAS-571		S/N 605		Yes	01 APR 05
Frequency	Test Data	AF	Test Data	AF+CA-AMP	Results	Limits	Distance /	Margin
(MHz)	(dBm)	Table	(dBuV)	(dB)	(uV/m)	(uV/m)	Polarity	(dB)
5550.40	-64.7	2HN3mH	42.3	8.1	331.0	16552.0	3m./HORZ	34.0
7400.95	-55.7	2HN3mH	51.3	11.0	1300.4	16552.0	3m./HORZ	22.1
9251.2	-61.2	2HN3mH	45.8	12.9	866.6	16552.0	3m./HORZ	25.6
11099.2	-59.2	2HN3mH	47.8	17.1	1745.1	16552.0	3m./HORZ	19.5
5729.1	-65.7	2HN3mH	41.3	8.5	308.5	16552.0	3m./HORZ	34.6
7639.1	-52.0	2HN3mH	55.0	11.2	2055.3	16552.0	3m./HORZ	18.1
9548.9	-60.4	2HN3mH	46.6	13.2	979.2	16552.0	3m./HORZ	24.6
11456.8	-59.9	2HN3mH	47.1	17.9	1768.4	16552.0	3m./HORZ	19.4

Test Date: February 27, 2006

Tester

Signature: _____


Name: Austin Thompson

Report Number: 06-0008

Issue Date: April 18, 2006

Customer: Sicom test s.r.l.

Model: GE863-QUAD / GE863-PY Modular Transmitter

TABLE 4b RADIATED RF POWER OUTPUT (Substitution)

Frequency	Maximum RX Reading (Units A)	Recreated Reading During Substitution (Using Same Units A) - Ideally 0	Difference Column A - B	TX Gain (dBi)	TX Gain Relative to Dipole (dB)	RF Power into TX antenna (Corrected for any CL and Pads to antenna Feed Point) (dBm) (SG Value-CL)	RF Power into substitution TX antenna corrected by TX Gain Relative to Dipole (dBm)	Limit (dBm)	Margin Below Limit (dB)	Theoretical Margin Below Limit
The following applies information from test as performed on Model GM863 Quad										
7639.1	-52	-51.67	-0.33	11.4	9.26	-46.03	-37.1	-13	24.1	18.1

Test Date: February 27, 2006

Tester Signature: 

Name: Austin Thompson