

DEKRA Testing and Certification S.A.U.TCB

Parque Tecnológico de Andalucía
Severo Ochoa, 2 & 6
29590 Málaga
Spain

Date: November 13th, 2017

Reference: 55631EMF.001

RF exposure analysis for the equipment – Maximum Antenna Gain

Model: LE920A4-NA

FCC ID: R17LE920A4NA

IC: 5131A-LE920A4NA

The device Telit LE920A4-NA is a module designed to be installed in other devices. This device is to be used only for fixed and mobile applications. If the final product after integration is intended for portable use, new applications and FCC and IC are required.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all the persons and must not be co-located or operating in conjunction with any other antenna or transmitter except as under the conditions described KDB 447498 D01 General RF Exposure Guidance.

MPE exposure limits

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure:

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	f (MHz) /1500	30
1500 – 100.000	1,0	30

The table below is excerpted from RSS-102, Issue 5, 4, titled “Table 4: RF Field Strength Limits for Devices Used by the General Public”:

Frequency Range (MHz)	Power density (W/m ²)	Averaging time (minutes)
300 – 6000	$0.02619 \cdot f^{0.6834}$	6

EIRP limits

Band	Frequency (MHz) (Lowest Frequency)	FCC MPE limit (mW/cm ²)	IC MPE limit (mW/cm ²)	FCC/IC MPE limit (mW/cm ²)	FCC EIRP limit (W)	IC EIRP limit (W)
GSM 850	824,0	0,549	0,258	0,25756	11,48	11,50
EGPRS850	824,0	0,549	0,258	0,25756	11,48	11,50
WCDMA Band V	820,0	0,547	0,257	0,25671	11,48	11,50
FDD 5	820,0	0,547	0,257	0,25671	11,48	11,50
FDD 4	1710,0	1,000	0,424	0,42419	1,00	1,00
WCDMA Band IV	1710,0	1,000	0,424	0,42419	1,00	1,00
DCS 1900	1850,0	1,000	0,448	0,44763	2,00	2,00
EGPRS1900	1850,0	1,000	0,448	0,44763	2,00	2,00
WCDMA Band II	1850,0	1,000	0,448	0,44763	2,00	2,00
FDD 2	1850,0	1,000	0,448	0,44763	2,00	2,00
FDD 7	2500,0	1,000	0,550	0,54991	2,00	2,00
FDD 12	699,0	0,466	0,230	0,23017	4,92	5,00

Using the equation $S = \frac{PG}{4\pi R^2}$ to calculate the exposure to electromagnetic fields

where: S = power density (in appropriate units, e.g. mW/cm²)
P = power input to the antenna (in appropriate units, e.g., mW)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

The maximum antenna gain that can be used in the LE920A4-NA is shown in the following table:

Band	Frequency (MHz) (Lowest Frequency)	Maximum conducted output power (per tune-up) (dBm)	Duty cycle (%)	FCC MPE limit (mW/cm ²)	IC MPE limit (mW/cm ²)	FCC/IC MPE limit (mW/cm ²)	FCC ERP limit (W)	IC ERP limit (W)	Evaluation distance for compliance with MPE limits (cm)	Antenna gain to meet FCC/IC MPE limit (dBi)	Antenna gain to meet FCC ERP limit (dBi)	Antenna gain to meet IC ERP limit (dBi)	Maximun antenna gain to meet all the limits (dBi)	Maximun antenna gain to meet all the limits per frequency band (dBi)
GSM 850	824,0	33,50	25,0%	0,549	0,258	0,25756	11,48	11,50	20	3,64	7,09	7,10	3,64	3,64
EGPRS850	824,0	33,50	25,0%	0,549	0,258	0,25756	11,48	11,50	20	3,64	7,09	7,10	3,64	
WCDMA Band V	820,0	25,00	100,0%	0,547	0,257	0,25671	11,48	11,50	20	6,10	15,59	15,60	6,10	
FDD 5	820,0	25,00	100,0%	0,547	0,257	0,25671	11,48	11,50	20	6,10	15,59	15,60	6,10	5,00
FDD 4	1710,0	25,00	100,0%	1,000	0,424	0,42419	1,00	1,00	20	8,28	5,00	5,00	5,00	
WCDMA Band IV	1710,0	25,00	100,0%	1,000	0,424	0,42419	1,00	1,00	20	8,28	5,00	5,00	5,00	
DCS 1900	1850,0	30,50	25,0%	1,000	0,448	0,44763	2,00	2,00	20	9,04	2,51	2,51	2,51	2,51
EGPRS1900	1850,0	30,50	25,0%	1,000	0,448	0,44763	2,00	2,00	20	9,04	2,51	2,51	2,51	
WCDMA Band II	1850,0	25,00	100,0%	1,000	0,448	0,44763	2,00	2,00	20	8,52	8,01	8,01	8,01	
FDD 2	1850,0	25,00	100,0%	1,000	0,448	0,44763	2,00	2,00	20	8,52	8,01	8,01	8,01	8,01
FDD 7	2500,0	25,00	100,0%	1,000	0,550	0,54991	2,00	2,00	20	9,41	8,01	8,01	8,01	
FDD 12	699,0	25,00	100,0%	0,466	0,230	0,23017	4,92	5,00	20	5,63	11,91	11,98	5,63	

Band	Frequency (MHz) (Lowest Frequency)	Maximum conducted output power (per tune-up) (dBm)	Duty cycle (%)	Antenna gain (dBi)	FCC/IC MPE limit (mW/cm ²)	FCC ERP limit (W)	IC ERP limit (W)	FCC/IC ERP limit (W)	Evaluation distance for compliance with MPE limits (cm)	$S = \frac{PG}{4\pi R^2}$ (mW/cm ²)	MPE Ratio (S/MPE limit)
GSM 850	824,0	33,50	25,0%	3,64	0,25756	11,48	11,50	11,48	20	0,25744	0,99952
EGPRS850	824,0	33,50	25,0%	3,64	0,25756	11,48	11,50	11,48	20	0,25744	0,99952
WCDMA Band V	820,0	25,00	100,0%	3,64	0,25671	11,48	11,50	11,48	20	0,14546	0,56662
FDD 5	820,0	25,00	100,0%	3,64	0,25671	11,48	11,50	11,48	20	0,14546	0,56662
FDD 4	1710,0	25,00	100,0%	5,00	0,42419	1,00	1,00	1,00	20	0,19894	0,46899
WCDMA Band IV	1710,0	25,00	100,0%	5,00	0,42419	1,00	1,00	1,00	20	0,19894	0,46899
DCS 1900	1850,0	30,50	25,0%	2,51	0,44763	2,00	2,00	2,00	20	0,09946	0,22220
EGPRS1900	1850,0	30,50	25,0%	2,51	0,44763	2,00	2,00	2,00	20	0,09946	0,22220
WCDMA Band II	1850,0	25,00	100,0%	2,51	0,44763	2,00	2,00	2,00	20	0,11213	0,25050
FDD 2	1850,0	25,00	100,0%	2,51	0,44763	2,00	2,00	2,00	20	0,11213	0,25050
FDD 7	2500,0	25,00	100,0%	8,01	0,54991	2,00	2,00	2,00	20	0,39786	0,72351
FDD 12	699,0	25,00	100,0%	5,63	0,23017	4,92	5,00	4,92	20	0,23000	0,99926

Yours sincerely,
P.A.



By: **Ken Bednasz**
Title: **VP Application Engineering - Americas**
Company: **Telit Communications S.p.A.**
Telephone: **+1-919-415-1517**
e-mail: **Ken.Bednasz@telit.com**