



Test report No:
 NIE: 60375RRRF.001

Test report
REFERENCE STANDARD:
USA FCC Part 27
CANADA RSS-130

(*) Identification of item tested	LTE Module CAT M and NB-IOT
(*) Trademark	Telit
(*) Model and /or type reference	ME910C1-WW
Other identification of the product	FCC ID: RI7ME910C1WW IC: 5131A-ME910C1WW IMEI TAC: 35308109
(*) Features	LTE CATM/NB-IOT /Quad Band 2G
Applicant	Telit Communications S.p.A Via Stazione di Prosecco 5/B, 34010 Sgonico, Trieste - ITALY
Test method requested, standard	USA FCC Part 27 10-1-18 Edition. CANADA RSS-130 Issue 1, Oct. 2013. ANSI C63.26 – 2015.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	A. Llamas RF Lab. Manager
Date of issue	2019-06-24
Report template No	FDT08_22 (*) "Data provided by the client"

Index

Competences and guarantees	3
General conditions	3
Uncertainty	3
Data provided by the client.....	4
Usage of samples	4
Test sample description	4
Identification of the client.....	7
Testing period and place.....	7
Document history	7
Environmental conditions	7
Remarks and comments	8
Testing verdicts.....	9
Summary	9
Appendix A: Test results for FCC Part 27 / RSS-130. CAT M.	10

Competences and guarantees

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

Uncertainty

Uncertainty (factor k=2) was calculated according to the DEKRA Testing and Certification internal document PODT000.

Data provided by the client

The sample consist of a LTE module CAT M and NB-IOT with 2G Fallback.

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples undergoing test have been selected by: the client.

Sample S/01 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
57536/047	Module	ME910C1-WW	IMEI: 353081090002109	2018-09-25
53445B/017	Cradle	---	113990005439	2017-06-28
55696/011	Antenna	---	---	2017-11-16

1. Sample S/01 has undergone the following test(s):

All radiated tests indicated in appendix A.

Sample S/02 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
57536/047	Module	ME910C1- WW	IMEI: 353081090002109	2018-09-25
53445B/017	Cradle	---	113990005439	2017-06-28

1. Sample S/02 has undergone the following test(s):

All conducted tests indicated in appendix A.

Test sample description

Ports..... :	Port name and description	Cable			
		Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
Supplementary information to the ports..... :							
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input checked="" type="checkbox"/>	DC: 3.8 Vdc.					
<input type="checkbox"/>	DC:						
Rated Power							
Clock frequencies							
Other parameters..... :							
Software version	M0B.800004						
Hardware version..... :	0.0						
Dimensions in cm (W x H x D).... :							
Mounting position..... :	<input type="checkbox"/>	Table top equipment					
	<input type="checkbox"/>	Wall/Ceiling mounted equipment					
	<input type="checkbox"/>	Floor standing equipment					
	<input type="checkbox"/>	Hand-held equipment					
	<input checked="" type="checkbox"/>	Other: Module					
Modules/parts	Module/parts of test item		Type	Manufacturer			
Accessories (not part of the test item)..... :	Description		Type	Manufacturer			

Documents as provided by the applicant.....:	Description	File name	Issue date

Identification of the client

TELIT COMMUNICATIONS
Via Stazione di Prosecco 5/B, 34010 Sgonico,
Trieste – ITALY

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2019-02-06
Date (finish)	2019-06-13

Document history

Report number	Date	Description
60375RRRF.001	2019-06-24	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 35 %

Remarks and comments

The tests have been performed by the technical personnel: José Alberto Aranda.

Used instrumentation:

Conducted Measurements

	Last Cal. date	Cal. due date
1. Spectrum analyser Agilent E4440A	2017/10	2019/10
2. Vector signal analyzer Rohde & Schwarz FSQ8	2018/08	2020/08
3. Climatic chamber HERAEUS VM 04/35	2018/06	2020/06
4. DC power supply R&S NGPE 40/40	2018/02	2021/02
5. Universal Radio communication Tester R&S CMW50	2019/02	2020/02

Radiated Measurements

	Last Cal. date	Cal. due date
1. Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2. BiconicalLog antenna ETS LINDGREN 3142E	2017/09	2020/09
3. Multi Device Controller MESSTECHNIK DAV-RR	N.A.	N.A.
4. Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2018/01	2021/01
5. Spectrum analyser Rohde & Schwarz FSV40	2018/02	2020/02
6. EMI Test Receiver R&S ESR7	2018/10	2020/10
7. RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-3A	2019/04	2020/04

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

FCC PART 27 / RSS-130 PARAGRAPH		
Requirement – Test case	Verdict	Remark
Clause 27.50 / RSS-130 Clause 4.4.: RF output power	P	
Clause 2.1047 / RSS-130 Clause 4.1.: Modulation characteristics	P	
Clause 27.54 / RSS-130 Clause 4.3.: Frequency stability	P	
Clause 2.1049: Occupied Bandwidth	P	
Clause 27.53 / RSS-130 Clause 4.6.: Spurious emissions at antenna terminals	P	
Clause 27.53 / RSS-130 Clause 4.6.: Radiated emissions	P	
<u>Supplementary information and remarks:</u>		
None.		

Appendix A: Test results for FCC Part 27 / RSS-130. CAT M.

INDEX

TEST CONDITIONS.....	12
RF Output Power	13
Frequency Stability	20
Modulation Characteristics	24
Occupied Bandwidth	27
Spurious emissions at antenna terminals.....	35
Spurious emissions at antenna terminals at Block Edges.....	44
Radiated emissions.....	51

TEST CONDITIONS

Power supply (V):

Vnominal = 3.8 Vdc

Vmax = 4.37 Vdc

Vmin = 3.23 Vdc

The subscripts nom, min and max indicate voltage test conditions (nominal, minimum and maximum respectively, as declared by the applicant).

Type of power supply = DC Voltage from external power supply

Type of antenna = External antenna.

Declared Gain for antenna = 2.14 dBi.

TEST FREQUENCIES:

LTE. QPSK AND 16QAM MODULATION (BAND 12)

	Channel (Frequency. MHz)			
	BW = 1.4 MHz	BW = 3 MHz	BW = 5 MHz	BW = 10 MHz
Lowest	23017 (699.7)	23025 (700.5)	23035 (701.5)	23060 (704.0)
Middle	23095 (707.5)	23095 (707.5)	23095 (707.5)	23095 (707.5)
Highest	23173 (715.3)	23165 (714.5)	23155 (713.5)	23130 (711.0)

LTE. QPSK AND 16QAM MODULATION (BAND 13)

	Channel (Frequency, MHz)	
	BW = 5 MHz	BW = 10 MHz
Lowest	23205 (779.5)	N/A
Middle	23230 (782.0)	23230 (782.0)
Highest	23255 (784.5)	N/A

RF Output Power

SPECIFICATION

FCC §27.50 (c) (10).

Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band. and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

FCC §27.50 (b) (10).

Portable stations (hand-held devices) transmitting in the 746-757 MHz. 776-788 MHz. and 805-806 MHz bands are limited to 3 watts ERP.

RSS-130 Clause 4.4.

The e.i.r.p. shall not exceed 50 watts (46.99 dBm) for mobile equipment or for outdoor fixed subscriber equipment nor shall it exceed 5 watts (36.99 dBm) for portable equipment or for indoor fixed subscriber equipment.

The peak-to-average power ratio (PAPR) of the transmission shall not exceed 13 dB.

METHOD

The conducted RF output power measurements were made at the RF output terminals of the EUT using the power meter of the Universal Radio Communication tester R&S CMW500, selecting maximum transmission power of the EUT and different modes of modulation.

The maximum equivalent isotropically radiated power (e.i.r.p.) is calculated by adding the declared maximum antenna gain (dBi).

The maximum effective radiated power e.r.p. is calculated from the maximum equivalent isotropically radiated power (e.i.r.p.) by subtracting 2.15 dB:

$$E.R.P. = E.I.R.P. - 2.15 \text{ dB}$$

The peak-to-average power ratio (PAPR) is measured using an attenuator, power splitter and spectrum analyser with a Complementary Cumulative Distribution Function implemented.


The EUT was controlled via the Universal Radio Communication tester R&S CMW500 selecting maximum transmission power of the EUT and different modes of modulation.

TEST SETUP

Conducted average power.



Peak-to-average power ratio (PAPR)



RESULTS

MAXIMUM OUTPUT POWER (CONDUCTED).

LTE. BAND 12.

Preliminary measurements determined the narrow band = 1 and nominal bandwidth of 1.4 MHz as the worst case. The results in the next tables shows the results for this configuration.

Narrow band = 1

BANDWIDTH (MHz)	CHANNEL	FREQUENCY (MHz)	MODULATION	RB SIZE	RB OFFSET	AVERAGE POWER (dBm)	PAPR (dB)
1.4	23017	699.7	QPSK	1	0	22,76	5.71
			16-QAM	6	0	21,84	
	23095	707.5	QPSK	1	0	22,23	6.19
			16-QAM	5	0	22	
	23173	715.3	QPSK	1	0	22,82	5.64
			16-QAM	6	0	21,9	
23173	715.3	QPSK	1	0	22,32	6.23	
		16-QAM	5	0	21,98		
23173	715.3	QPSK	1	0	22,86	5.53	
		16-QAM	6	0	21,84		
23173	715.3	QPSK	1	0	22,11	6.14	
		16-QAM	5	0	21,88		

LTE. BAND 13.

Preliminary measurements determined the narrow band = 1 and nominal bandwidth of 5 MHz as the worst case. The results in the next tables shows the results for this configuration.

Narrow band = 1

BANDWIDTH (MHz)	CHANNEL	FREQUENCY (MHz)	MODULATION	RB SIZE	RB OFFSET	AVERAGE POWER (dBm)	PAPR (dB)
5	23205	779.5	QPSK	1	0	22,93	4.94
			16-QAM	6	0	22,46	
	23230	782.0	QPSK	1	0	22,93	5.82
			16-QAM	5	0	22,18	
	23230	782.0	QPSK	1	0	22,96	4.92
			16-QAM	6	0	22,53	
23255	784.5	QPSK	1	0	22,95	5.69	
		16-QAM	5	0	22,22		
23255	784.5	QPSK	1	0	22,94	4.9	
		16-QAM	6	0	22,52		
23255	784.5	QPSK	1	0	22,94	5.95	
		16-QAM	5	0	22,21		


PEAK-TO-AVERAGE POWER RATIO (PAPR).

LTE. BAND 12.


Preliminary measurements determined the narrow band = 1, nominal bandwidth of 1.4 MHz, 16-QAM modulation and 5 RB size offset 0 as the worst case. The results in the next tables shows the results for this configuration.

Bandwidth = 1.4 MHz. Modulation 16-QAM. RB Size: 5. RB Offset: 0.


Channel Low:



Channel Middle:



Channel High:




LTE. BAND 13.


Preliminary measurements determined the narrow band = 1, nominal bandwidth of 5 MHz, 16-QAM modulation and 5 RB size offset 0 as the worst case. The results in the next tables shows the results for this configuration

Bandwidth = 5 MHz. Modulation 16 QAM. RB Size: 5. RB Offset: 0.


Channel Low:



Channel Middle:



Channel High:



LTE BAND 12.

Channel	Measured maximum average power (dBm) at antenna port	Maximum declared antenna gain (dBi)	Maximum equivalent isotropically radiated power (E.I.R.P.) (dBm)	Maximum effective radiated power E.R.P. (dBm)	PAPR (dB)
Lowest	22.18	2.14	24.32	22.17	5.71
Middle	22.27	2.14	24.41	22.26	5.64
Highest	22.15	2.14	24.29	22.14	6.14
Measurement uncertainty (dB)	<±1.11				

LTE BAND 13.

Channel	Measured maximum average power (dBm) at antenna port	Maximum declared antenna gain (dBi)	Maximum equivalent isotropically radiated power (E.I.R.P.) (dBm)	Maximum effective radiated power E.R.P. (dBm)	PAPR (dB)
Lowest	22.48	2.14	24.62	22.47	5.82
Middle	22.48	2.14	24.62	22.47	5.69
Highest	22.54	2.14	24.68	22.53	5.95
Measurement uncertainty (dB)	<±1.11				

Verdict: PASS

Frequency Stability

SPECIFICATION

FCC §2.1055 and §27.54.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

RSS-130. Clause 4.3.

The applicant shall ensure frequency stability by showing that f_L minus the frequency offset and f_H plus the frequency offset shall be within the frequency range in which the equipment is designed to operate.

METHOD

The frequency tolerance measurements over temperature variations were made over the temperature range of -30°C to $+50^{\circ}\text{C}$. The EUT was placed inside a climatic chamber and the temperature was raised hourly in 10°C steps from -30°C up to $+50^{\circ}\text{C}$.

The supply voltage was varied between 85% and 115% of nominal voltage.

The EUT was set in "Radio Resource Control (RRC) mode" in the middle channel using the Universal Radio Communication tester R&S CMW500 and the maximum frequency error was measured using the built-in calibrated frequency meter.


The worst case LTE mode for conducted power was used for the test.

In order to check that the frequency stability is sufficient such that the fundamental emissions stay within the authorized bands of operation, a reference point is established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and highest channel of operation are identified as f_L and f_H respectively. The worst-case frequency offset determined in the above methods is added or subtracted from the values of f_L and f_H to check that the resulting frequencies remain within the band.


The reference point measurements were made at the RF output terminals of the EUT using an attenuator, power splitter and spectrum analyser. The EUT was controlled via the Universal Radio Communication tester R&S CMW500 selecting maximum transmission power of the EUT and different modes of modulation.

TEST SETUP

Frequency tolerance.



Reference points f_L and f_H .



RESULTS

Frequency stability over temperature variations.

LTE Band 12. QPSK MODULATION. BW = 5 MHz. Narrow band: 1. Channel: 707.5 MHz.

Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
+50	1.17	0.00165371
+40	0.54	0.000763251
+30	1.27	0.001795053
+20	1.34	0.001893993
+10	1.73	0.00244523
0	1.49	0.002106007
-10	1.39	0.001964664
-20	1.40	0.001978799
-30	0.62	0.000876325

LTE Band 13. QPSK MODULATION. BW = 5 MHz. Narrow band: 1. Channel: 782 MHz

Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
+50	0.43	0.000549872
+40	0.44	0.00056266
+30	1.02	0.001304348
+20	1.04	0.001329923
+10	0.86	0.001099744
0	1.13	0.001445013
-10	0.49	0.000626598
-20	-0.29	-0.000370844
-30	-1.13	-0.001445013

Frequency stability over voltage variations.

LTE Band 12

Battery Supply voltage	Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
Vmax	4.37	0.8	0.001130742
Vmin	3.23	1.29	0.001823322

LTE Band 13

Battery Supply voltage	Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
Vmax	4.37	1.13	0.001445013
Vmin	3.23	1.19	0.001521739

Reference points established at the applicable unwanted emissions limit (worst case):

	LTE Band 12
f_L (MHz)	699.071
f_H (MHz)	715.989

	LTE Band 13
f_L (MHz)	777.063
f_H (MHz)	786.927

Reference points f_L and f_H with the worst-case frequency offsets added or subtracted:

	LTE Band 12
f_L (MHz)	699.071
f_H (MHz)	715.989

	LTE Band 13
f_L (MHz)	777.063
f_H (MHz)	786.927

The reference frequency points stay within the authorized blocks.

Verdict: PASS

Modulation Characteristics

SPECIFICATION


FCC §2.1047

RSS-130. Clause 4.1. Equipment certified under this standard shall use digital modulation.

METHOD

For LTE the EUT operates with QPSK and 16QAM modulation modes in which the information is digitised and coded into a bit stream. The RF transmission is multiplexed using *Orthogonal Frequency Division Multiplexing (OFDM)* using different possible arrangement of subcarriers (Resource Blocks RB).


TEST SETUP




RESULTS

The following plot shows the modulation schemes in the EUT.


LTE MODULATION (Band 12). QPSK.




LTE MODULATION (Band 12). 16QAM.



LTE MODULATION (Band 13). QPSK.



LTE MODULATION (Band 13). 16QAM.



Occupied Bandwidth


SPECIFICATION

§2.1049

METHOD

The occupied bandwidth measurement was performed at the output terminals of the EUT using an attenuator, power splitter and spectrum analyser. The EUT was controlled via the Universal Radio Communication tester R&S CMW500 selecting maximum transmission power of the EUT and different modes of modulation. The 99% occupied bandwidth and the -26 dBc bandwidth were measured directly using the built-in bandwidth measuring option of spectrum analyser.

TEST SETUP



RESULTS (see next plots)

The worst case of occupied bandwidth corresponds to all Resource Blocks (RB) offset 0 regardless either the Narrow band position or the nominal bandwidth selected.

LTE QPSK MODULATION. BW = 1.4 MHz (Band 12). Narrow band: 1.

Channel	Lowest	Middle	Highest
99% Occupied bandwidth (KHz)	1108.7	1110.1	1115.8
-26 dBc bandwidth (KHz)	1273	1280	1282
Measurement uncertainty (kHz)	<±16.67		

LTE 16QAM MODULATION. BW = 1.4 MHz (Band 12). Narrow band: 1.

Channel	Lowest	Middle	Highest
99% Occupied bandwidth (KHz)	952.609	940.132	951.608
-26 dBc bandwidth (KHz)	1164	1132	1177
Measurement uncertainty (kHz)	<±16.67		

LTE QPSK MODULATION. BW = 5 MHz (Band 13). Narrow band: 1.


Channel	Lowest	Middle	Highest
99% Occupied bandwidth (KHz)	1182.5	1575.1	1138.9
-26 dBc bandwidth (KHz)	1701	1815	1510
Measurement uncertainty (kHz)	<±16.67		

LTE 16QAM MODULATION. BW = 5 MHz (Band 13). Narrow band: 1.


Channel	Lowest	Middle	Highest
99% Occupied bandwidth (KHz)	1009.5	988.842	979.61
-26 dBc bandwidth (KHz)	1752	1833	1774
Measurement uncertainty (kHz)	<±16.67		

LTE QPSK MODULATION. BW = 1.4 MHz (Band 12)


Lowest Channel



Middle Channel




Highest Channel




LTE 16QAM MODULATION. BW = 1.4 MHz (Band 12)


Lowest Channel



Middle Channel




Highest Channel




LTE QPSK MODULATION. BW = 5 MHz (Band 13)


Lowest Channel



Middle Channel




Highest Channel




LTE 16QAM MODULATION. BW = 5 MHz (Band 13)


Lowest Channel



Middle Channel



Highest Channel



Spurious emissions at antenna terminals

SPECIFICATION

FCC §27.53 (g).

For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC §27.53 (c).

On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.

On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

RSS-130 Clause 4.6.

The power of any unwanted emissions in any 100 kHz bandwidth on any frequency outside the frequency range(s) within which the equipment is designed to operate shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB.

The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment.

At P_o transmitting power, the specified minimum attenuation becomes $43+10 \log (P_o)$, and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mwatts}) - 30] = -13 \text{ dBm.}$$

At P_o transmitting power, the specified minimum attenuation becomes $65+10 \log (P_o)$, and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [65 + 10 \log (P_o \text{ in mwatts}) - 30] = -35 \text{ dBm.}$$

METHOD


The EUT RF output connector was connected to a spectrum analyser and to the Universal Radio Communication tester R&S CMW500 (selecting maximum transmission power of the EUT and different modes of modulation) using a 50 ohm attenuator and a power divider.

The spectrum was investigated from 9 kHz to 8 GHz for LTE Band 12 and Band 13.

The reading of the spectrum analyser is corrected with the attenuation loss of connection between output terminal of EUT and input of the spectrum analyser.

The configuration of Resource Blocks and modulation which is the worst case for conducted power was used.

TEST SETUP



RESULTS (see plots in next pages)

LTE Band 12

1. CHANNEL: LOWEST

No spurious signals were found at less than 20dB respect to the limit in all the range.

2. CHANNEL: MIDDLE

No spurious signals were found at less than 20dB respect to the limit in all the range.

3. CHANNEL: HIGHEST

No spurious signals were found at less than 20dB respect to the limit in all the range.

LTE Band 13

1. CHANNEL: LOWEST

Frequency (MHz)	Level (dBm)	Limit (dBm)
773.963	-41.47	-35

2. CHANNEL: MIDDLE

Frequency (MHz)	Level (dBm)	Limit (dBm)
774.963	-48.13	-35

3. CHANNEL: HIGHEST


Frequency (MHz)	Level (dBm)	Limit (dBm)
774.495	-53.11	-35
793.267	-50.02	-35

Verdict: PASS

LTE Band 12

1. CHANNEL: LOWEST


Frequency Range 9 kHz – 8 GHz



Note: The peak above the limit is the carrier frequency.

2. CHANNEL: MIDDLE


Frequency Range 9 kHz – 8 GHz



Note: The peak above the limit is the carrier frequency.

3. CHANNEL: HIGHEST

Frequency Range 9 kHz – 8 GHz




Note: The peak above the limit is the carrier frequency.

LTE Band 13


1. CHANNEL: LOWEST

Frequency Range 9 kHz – 8 GHz




Note: The peak above the limit is the carrier frequency.

Frequency Range 763 MHz - 775 MHz




Frequency Range 793 MHz - 806 MHz




2. CHANNEL: MIDDLE

Frequency Range 9 kHz – 8 GHz




Note: The peak above the limit is the carrier frequency.

Frequency Range 763 MHz - 775 MHz




Frequency Range 793 MHz - 806 MHz




3. CHANNEL: HIGHEST

Frequency Range 9 kHz – 8 GHz




Note: The peak above the limit is the carrier frequency.

Frequency Range 763 MHz - 775 MHz



Frequency Range 793 MHz - 806 MHz



Spurious emissions at antenna terminals at Block Edges

SPECIFICATION

FCC §27.53 (c) & (g). RSS-130 Clause 4.6.

According to specification. the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. P in watts.

At P_o transmitting power. the specified minimum attenuation becomes $43+10\log (P_o)$. and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mwatts}) - 30] = -13 \text{ dBm}$$

METHOD

The EUT RF output connector was connected to a spectrum analyser and to the Universal Radio Communication tester R&S CMW500 (selecting maximum transmission power of the EUT and different modes of modulation) using a 50 ohm attenuator and a power splitter.


The reading of the spectrum analyser is corrected with the attenuation loss of connection between output terminal of EUT and input of the spectrum analyser.

The configuration of modulation which is the worst case for conducted power was used.

For LTE Band12. as indicated in FCC part 27.53 (g) /RSS-130 Clause 4.6., in the 100 kHz bands immediately outside and adjacent to the licensee's frequency block or band. a resolution bandwidth of 30 kHz may be employed.

For LTE Band 13. as indicated in FCC part 27.53 (c) (5) /RSS-130 Clause 4.6., in the 100 kHz bands immediately outside and adjacent to the licensee's frequency block or band. a resolution bandwidth of 30 kHz may be employed.

TEST SETUP



RESULTS (see plots in next pages)

LTE. BAND 12.

The results in the next tables shows the results for the worst case.

(Channels in Band 12):	RB=1. Offset=0. Narrow band = 1 BW=5 MHz	RB= All. Offset=0. Narrow band = 1 BW=3 MHz
Maximum measured level at lowest Block Edge at antenna port (dBm)	-29.92	-30.82

(Channels in Band 12):	RB= 1. Offset=Max. Narrow band = 1 BW=3 MHz	RB= All. Offset=0. Narrow band = 1 BW=5 MHz
Maximum measured level at highest Block Edge at antenna port (dBm)	-22.00	-24.09

LTE. BAND 13.

The results in the next tables shows the results for the worst case.

(Channels in Band 13):	RB=1. Offset=0. Narrow band = 1 BW=5 MHz	RB= All. Offset=0. Narrow band = 1 BW= 5 MHz
Maximum measured level at lowest Block Edge at antenna port (dBm)	-21.32	-24.37

(Channels in Band 13):	RB= 1. Offset=Max. Narrow band = 1 BW=5 MHz	RB= All. Offset=0. Narrow band = 1 BW=10 MHz
Maximum measured level at highest Block Edge at antenna port (dBm)	-20.27	-25.88


Measurement uncertainty = ± 1.20 dB.

Verdict: PASS

LTE. BAND 12.

Narrow band = 1. RB = 1. Offset = 0. BW = 5 MHz


CHANNEL LOWEST



NOTE: The equipment transmits at the maximum output power

Narrow band = 1. RB = 1. Offset = Max. BW = 3 MHz


CHANNEL HIGHEST



NOTE: The equipment transmits at the maximum output power

Narrow band = 1. RB = All. Offset = 0. BW = 3 MHz


CHANNEL LOWEST



NOTE: The equipment transmits at the maximum output power

Narrow band = 1. RB = All. Offset = 0. BW = 5 MHz

CHANNEL HIGHEST




NOTE: The equipment transmits at the maximum output power

Verdict: PASS

LTE. BAND 13.

Narrow band = 1. RB = 1. Offset = 0. BW = 5 MHz


CHANNEL LOWEST



NOTE: The equipment transmits at the maximum output power

Narrow band = 1. RB = 1. Offset = Max. BW = 5 MHz


CHANNEL HIGHEST



NOTE: The equipment transmits at the maximum output power

Narrow band = 1. RB = Max. Offset = 0. BW = 5 MHz


CHANNEL LOWEST.



NOTE: The equipment transmits at the maximum output power

Narrow band = 1. RB = Max. Offset = 0. BW = 10 MHz

CHANNEL HIGHEST.



NOTE: The equipment transmits at the maximum output power

Verdict: PASS

Radiated emissions

SPECIFICATION

FCC §27.53 (g).

For operations in the 600 MHz band and the 698-746 MHz band. the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation. measured in watts. by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However. in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block. a resolution bandwidth of at least 30 kHz may be employed

FCC §27.53 (c) & (f).

On any frequency outside the 776-788 MHz band. the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.

On all frequencies between 763-775 MHz and 793-805 MHz. by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment. for mobile and portable stations.

For operations in the 746-758 MHz. 775-788 MHz. and 805-806 MHz bands. emissions in the band 1559-1610 MHz shall be limited to -70 dBW (-40 dBm)/MHz equivalent isotropically radiated power (EIRP) for wideband signals. and -80 dBW (-50 dBm) EIRP for discrete emissions of less than 700 Hz bandwidth.

RSS-130 Clause 4.6.

The power of any unwanted emissions in any 100 kHz bandwidth on any frequency outside the frequency range(s) within which the equipment is designed to operate shall be attenuated below the transmitter power. P (dBW). by at least $43 + 10 \log_{10} p$ (watts). dB.

The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power. P (dBW). by at least $65 + 10 \log_{10} p$ (watts). dB. for mobile and portable equipment.

The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW (-40 dBm) /MHz for wideband signal and -80 dBW (-50 dBm) for discrete emission with bandwidth less than 700 Hz.

At P_o transmitting power. the specified minimum attenuation becomes $43+10 \log (P_o)$. and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mwatts}) - 30] = -13 \text{ dBm.}$$

At P_o transmitting power. the specified minimum attenuation becomes $65+10 \log (P_o)$. and the level in dBm relative P_o becomes:

$$P_o \text{ (dBm)} - [65 + 10 \log (P_o \text{ in mwatts}) - 30] = -35 \text{ dBm.}$$

METHOD

The measurement was performed with the EUT inside an anechoic chamber. The spectrum was scanned from 30 MHz to at least the 10th harmonic of the highest frequency generated within the equipment.


The EUT was placed on a non-conductive stand at a 3 meter distance from the measuring antenna for measurements below 1 GHz and at 1 m distance for measurements above 1 GHz.

Detected emissions were maximized at each frequency by rotating the EUT and adjusting the measuring antenna height and polarization. The maximum meter reading was recorded.


Each detected emission at less than 20 dB respect to the limit is substituted by the Substitution method in accordance with the ANSI/TIA-603-E: 2016.

TEST SETUP

Radiated measurements below 1 GHz.



Radiated measurements above 1 GHz.



RESULTS

LTE. BAND 12.

A preliminary scan determined the QPSK 1.4 MHz bandwidth, Narrow band =1, RB = 1, as the worst case.

The following tables and plots show the results for this configuration.

1. CHANNEL: LOWEST

Frequency range 30 MHz-1000 MHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

Frequency range 1 GHz-8 GHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

2. CHANNEL: MIDDLE

Frequency range 30 MHz-1000 MHz.

No radiated spurious signals were detected.

Frequency range 1 GHz-8 GHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

3. CHANNEL: HIGHEST

Frequency range 30 MHz-1000 MHz.

No radiated spurious signals were detected.

Frequency range 1 GHz-8 GHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

LTE. BAND 13.

A preliminary scan determined the QPSK 5 MHz bandwidth, Narrow band =1, RB = 1, as the worst case.

The following tables and plots show the results for this configuration.

1. CHANNEL: LOWEST

Frequency range 30 MHz-1000 MHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

Frequency range 1 GHz-8 GHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

Frequency range 1559 MHz-1610 MHz.

Frequency (MHz)	Instrument reading (dBm)	Polarization	RBW	(1) Generator output (dBm)	(2) Cable loss (dB)	(3) Substitution antenna gain G_i (respect to isotropic radiator) (dB)	E.I.R.P. (dBm) = (1) – (2) + (3)
1563.2441	-38.32	Horizontal	1 MHz	-51.40	0.79	8.27	-43.92

No discrete signals were detected. Only wideband signals were detected.

2. CHANNEL: MIDDLE

Frequency range 30 MHz-1000 MHz.

No radiated spurious signals were detected.

Frequency range 1 GHz-8 GHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

Frequency range 1559 MHz-1610 MHz.

Substitution method data

Frequency (MHz)	Instrument reading (dBm)	Polarization	RBW	(1) Generator output (dBm)	(2) Cable loss (dB)	(3) Substitution antenna gain Gi (respect to isotropic radiator) (dB)	E.I.R.P. (dBm) = (1) – (2) + (3)
1560.6278	-41.09	Horizontal	1 MHz	-54.17	0.79	8.25	-46.70
1568.3186	-45.12	Horizontal	1 MHz	-58.22	0.79	8.29	-50.72

No discrete signals were detected. Only wideband signals were detected.

3. CHANNEL: HIGHEST

Frequency range 30 MHz-1000 MHz.

No radiated spurious signals were detected.

Frequency range 1 GHz-8 GHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit.

Frequency range 1559 MHz-1610 MHz.

Frequency (MHz)	Instrument reading (dBm)	Polarization	RBW	(1) Generator output (dBm)	(2) Cable loss (dB)	(3) Substitution antenna gain Gi (respect to isotropic radiator) (dB)	E.I.R.P. (dBm) = (1) – (2) + (3)
1565.7669	-38.06	Horizontal	1 MHz	-51.15	0.79	8.28	-43.66
1573.201	-38.58	Horizontal	1 MHz	-51.68	0.79	8.31	-44.17


No discrete signals were detected. Only wideband signals were detected

Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.


LTE Band 12

CHANNEL: LOWEST




Note: The peak above the limit is the carrier frequency.

CHANNEL: MIDDLE



Note: The peak above the limit is the carrier frequency.


CHANNEL: HIGHEST



Note: The peak above the limit is the carrier frequency.


LTE Band 13

CHANNEL: LOWEST




Note: The peak above the limit is the carrier frequency.

CHANNEL: MIDDLE



Note: The peak above the limit is the carrier frequency.


CHANNEL: HIGHEST




Note: The peak above the limit is the carrier frequency.

LTE Band 12. Frequency range 1 GHz to 8 GHz.


CHANNEL: LOWEST



CHANNEL: MIDDLE




CHANNEL: HIGHEST




LTE Band 13. Frequency range 1 GHz to 8 GHz.


CHANNEL: LOWEST



CHANNEL: MIDDLE




CHANNEL: HIGHEST




LTE Band 13. Frequency range 1559 MHz to 1610 MHz.

CHANNEL: LOWEST



CHANNEL: MIDDLE



CHANNEL: HIGHEST

