



Report No.: RZA2010-1428RF02



Part 24

TEST REPORT

Product Name	H9 USB MODEM
Model Name	H9
FCC ID	R17TELITH9
Client	Dai Telecom Ltd

TA Technology (Shanghai) Co., Ltd.



GENERAL SUMMARY

Product Name	H9 USB MODEM	Model Name	H9
FCC ID	R17TELITH9		
Report No.	RZA2010-1428RF02		
Client	Dai Telecom Ltd		
Manufacturer	SHANGHAI SIMCOM LTD		
Reference Standard(s)	<p>FCC CFR47 Part 2 (2009-12) Frequency Allocations And Radio Treaty Matters;General Rules And Regulations</p> <p>FCC CFR47 Part 24E (2009-12) Personal Communications Services</p> <p>ANSI/TIA-603-C(2004) Land mobile FM or PM Communications Equipment Measurements and Performance Standards.</p>		
Conclusion	<p>This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 2 of this test report are below limits specified in the relevant standards.</p> <p>General Judgment: Pass</p> <div style="text-align: right;">  <p>(Stamp) Date of issue: November 1st, 2010</p> </div>		
Comment	The test result only responds to the measured sample.		

Approved by 杨伟中
Yang Weizhong

Revised by 徐凯
Xu Kai

Performed by 杜如蔚
Du Ruwei

TABLE OF CONTENT

1. General Information	4
1.1. Notes of the test report	4
1.2. Testing laboratory	4
1.3. Applicant Information	5
1.4. Manufacturer Information	5
1.5. Information of EUT	6
1.6. Test Date	6
2. Test Information	7
2.1. Summary of test results	7
2.2. RF Power Output	8
2.3. Effective Isotropic Radiated Power	10
2.4. Occupied Bandwidth	12
2.5. Band Edge Compliance	18
2.6. Frequency Stability	23
2.7. Spurious Emissions at Antenna Terminals	25
2.1. Radiates Spurious Emission	32
3. Main Test Instruments	40
ANNEX A: EUT Appearance and Test Setup	41
A.1 EUT Appearance	41
A.2 Test Setup	42

TA Technology (Shanghai) Co., Ltd. Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 4 of 42

1. General Information

1.1. Notes of the test report

TA Technology (Shanghai) Co., Ltd. guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at TA Technology (Shanghai) Co., Ltd. at the time of execution of the test.

TA Technology (Shanghai) Co., Ltd. is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. This report only refers to the item that has undergone the test.

This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of **TA Technology (Shanghai) Co., Ltd.** and the Accreditation Bodies, if it applies.

1.2. Testing laboratory

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Yang Weizhong
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: yangweizhong@ta-shanghai.com

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 5 of 42

1.3. Applicant Information

Company: Dai Telecom Ltd

Address: 3 Nirim st

City: Tel-Aviv

Postal Code: 67060

Country: Israel

Contact: Vadim Zukovsky

Telephone: +972543042360

Fax: +97237914008

1.4. Manufacturer Information

Company: SHANGHAI SIMCOM LTD

Address: SIM Technology Building A, No.633, Jinzhong Road, Changning District, Shanghai, P.R.China, 200335

City: Shanghai

Postal Code: 200335

Country: P.R. China

Telephone: 021-32523464

Fax: 021-32523019

TA Technology (Shanghai) Co., Ltd.

Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 6 of 42

1.5. Information of EUT

General information

Name of EUT:	H9 USB MODEM		
IMEI:	351602000330570		
Hardware Version:	UW621BL-T-MB V2.00		
Software Version:	QCT_30_V16_0_090827_V30.20.3_for_PCL_H9		
Antenna Type:	Internal Antenna		
Device Operating Configurations:			
Operating Mode(s):	GSM1900: (tested)		
Test Modulation:	GMSK		
GPRS Multislot Class:	10		
EGPRS Multislot Class:	10		
Maximum E.I.R.P.	20.87dBm		
Rated Power Supply Voltage:	5.0V		
Extreme Voltage:	Minimum: 4.9V Maximum: 5.1V		
Extreme Temperature:	Lowest: -10°C Highest: +55°C		
Test Channel: (Low - Middle - High)	512 - 661 - 810 (GSM 1900) (tested)		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM1900	1850.2 ~ 1909.8	1930.2 ~ 1989.8
Used Host Product:	IBM T61		

Equipment Under Test (EUT) is H9 USB MODEM with internal antenna. The EUT supports GSM1900 in this report.

The sample under test was selected by the Client.

Components list please refer to documents of the manufacturer.

1.6. Test Date

The test is performed from October 29, 2010 to October 31, 2010.

2. Test Information

2.1. Summary of test results

Number	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Isotropic Radiated power	24.232	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	24.238	PASS
5	Frequency Stability	2.1055 / 24.235	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 24.238	PASS
7	Radiates Spurious Emission	2.1053 / 24.238	PASS

2.2. RF Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation. These measurements have been tested at following channels: 512,661,810 for GSM 1900.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$. $U = 0.4$ dB.

TA Technology (Shanghai) Co., Ltd.

Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 9 of 42

Test Results

	Channel	Frequency (MHz)	RF Output Power (dBm)	
			1 Down 1Up	1 Down 2Up
GSM 1900	512	1850.2	30.14	
	661	1880.0	30.12	
	810	1909.8	29.94	
GSM 1900+GPRS	512	1850.2	1 Down 1Up	30.10
			1 Down 2Up	30.04
	661	1880.0	1 Down 1Up	30.11
			1 Down 2Up	30.03
	810	1909.8	1 Down 1Up	29.91
			1 Down 2Up	29.85
GSM 1900+EGPRS	512	1850.2	1 Down 1Up	26.68
			1 Down 2Up	26.63
	661	1880.0	1 Down 1Up	26.65
			1 Down 2Up	26.6
	810	1909.8	1 Down 1Up	26.49
			1 Down 2Up	26.45

2.3. Effective Isotropic Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Test procedure:

The measurement was done according to TIA/EIA 603C.

Step 1:


The measurement is carried out in a fully anechoic chamber. EUT was placed on a 0.8 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used while RBW and VBW are both set to 3MHz. During the measurement, the highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna moved up and down over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.

Step 2:

A dipole antenna shall be substituted in place of the EUT. The antenna will be driven by a signal generator with a known power S.G. applied through a Tx cable. Then the maximum Analyzer reading is recorded while the antenna was moving up and down. The E.R.P. /E.I.R.P. of the EUT can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

The correction factor (in dB)=S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading – 2.15. Then the EUT's E.R.P. was calculated with the correction factor, E.R.P. = LVL + Correction factor. The measurement will be conducted at three channels No.512, No.661 and No.810 of GSM 1900.

Test Setup



Limits

Rule Part 24.232(b) specifies that "Mobile/portable stations are limited to 2 watts EIRP. Peak power" and Rule Part 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage".

Limit (EIRP)	$\leq 2\text{ W}$ (33 dBm)
--------------	----------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$. $U = 1.19\text{ dB}$

Test Results:Pass

	Channel	Frequency (MHz)	P_{er} (EUT)	P_{in}	Gain (dBi)	Cable Loss	P_r (dBm)	Path loss (dBm)	E.I.R.P. (dBm)
GSM 1900	512	1850.2	-36.0556	0	1.9173	18.1801	-71.2084	54.9456	18.89
	661	1880.0	-35.9207	0	1.94	18.2744	-71.6851	55.3507	19.43
	810	1909.8	-35.3683	0	1.9	18.3003	-72.0286	55.6283	20.26
GSM 1900+GPRS	512	1850.2	-35.9356	0	1.9173	18.1801	-71.2084	54.9456	19.01
	661	1880.0	-35.4907	0	1.94	18.2744	-71.6851	55.3507	19.86
	810	1909.8	-34.7583	0	1.9	18.3003	-72.0286	55.6283	20.87
GSM1900 +EGPRS	512	1850.2	-35.9856	0	1.9173	18.1801	-71.2084	54.9456	18.96
	661	1880.0	-35.7807	0	1.94	18.2744	-71.6851	55.3507	19.57
	810	1909.8	-35.3383	0	1.9	18.3003	-72.0286	55.6283	20.29

2.4. Occupied Bandwidth


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz,VBW is set to 10kHz on spectrum analyzer.99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits


No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$. $U = 624\text{Hz}$.

Test Result

	Channel	Frequency (MHz)	99% Power Bandwidth (kHz)	-26dBc Bandwidth(kHz)
GSM 1900	512	1850.2	245.339	310.524
	661	1880.0	237.375	304.496
	810	1909.8	245.363	296.762
GSM 1900+GPRS	512	1850.2	242.925	316.548
	661	1880.0	247.124	312.301
	810	1909.8	241.443	316.747
GSM 1900+EGPRS	512	1850.2	245.661	310.007
	661	1880.0	242.530	306.012
	810	1909.8	245.850	308.845



GSM1900 CH512 Occupied Bandwidth


TA Technology (Shanghai) Co., Ltd.

Test Report


Registration Num:428261

Report No.: RZA2010-1428RF02


Page 14 of 42




GSM 1900 CH661 Occupied Bandwidth




GSM 1900 CH810 Occupied Bandwidth




GSM1900 GPRS CH512 Occupied Bandwidth




GSM 1900 GPRS CH661 Occupied Bandwidth




GSM 1900 GPRS CH810 Occupied Bandwidth



GSM1900 EGPRS CH512 Occupied Bandwidth



GSM 1900 EGPRS CH661 Occupied Bandwidth



GSM 1900 EGPRS CH810 Occupied Bandwidth

2.5. Band Edge Compliance


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The Average detector is used and RBW is set to 3kHz, VBW is set to 10kHz on spectrum analyzer. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U=0.684$ dB.

TA Technology (Shanghai) Co., Ltd. Test Report


Registration Num:428261

Report No.: RZA2010-1428RF02


Page 19 of 42

Test Result:


	Carrier frequency (MHz)	Reference value (dBm)	Limit	Conclusion
GSM 1900	1850.2	-16.34	-13	PASS
	1909.8	-23.73	-13	PASS
GSM 1900+GPRS	1850.2	-18.33	-13	PASS
	1909.8	-19.54	-13	PASS
GSM 1900+EGPRS	1850.2	-28.39	-13	PASS
	1909.8	-25.79	-13	PASS



GSM 1900 512 Channel



GSM1900 810 Channel



GSM 1900 GPRS 512 Channel


TA Technology (Shanghai) Co., Ltd.

Test Report


Registration Num:428261

Report No.: RZA2010-1428RF02

Page 21 of 42



GSM1900 GPRS 810 Channel




GSM 1900 EGPRS 512 Channel

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 22 of 42



GSM1900 EGPRS 810 Channel

2.6. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,
 (1) With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

2. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 4.9 V and 5.1 V, with a nominal voltage of 5.0V.

Test setup



Limits

No specific frequency stability requirements in part 24.235

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$. $U = 0.01\text{ppm}$.

Test Result

Temperature (° C)	Test Results (ppm) / 5.0 V Power supply
	GSM 1900 Channel 661
-30	0.068
-20	0.051
-10	0.044
0	0.040
10	0.036
20	0.032
30	0.046
40	0.052
50	0.070

Voltage (V)	Test Results(ppm) / 20° C
	Channel 661
4.9	0.026
5.0	0.032
5.1	0.036

2.7. Spurious Emissions at Antenna Terminals


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. RBW and VBW are set to 100 kHz, Sweep is set to ATUO.

Test setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.”

Limit	-13 dBm
-------	---------


Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-12.75GHz	1.407 dB

Test Result

CH 512



Note: The signal beyond the limit is carrier:1850.2 MHz
GSM 1900 Channel 512 30MHz ~18GHz



GSM 1900 Channel 512 18GHz ~20GHz

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261


Report No.: RZA2010-1428RF02

Page 27 of 42


Harmonic	TX ch.512 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	3700.9	-52.394	-13	39.394
3	5550.6	Nf	-13	/
4	7400.8	Nf	-13	/
5	9251	Nf	-13	/
6	11101.2	Nf	-13	/
7	12951.4	Nf	-13	/
8	14801.6	Nf	-13	/
9	16651.8	Nf	-13	/
10	18502	Nf	-13	/
Nf: noise floor				

Note: The other Spurious RF conducted emissions level is no more than noise floor.

CH 661



Note: The signal beyond the limit is carrier:1880 MHz
GSM 1900 Channel 661 30MHz ~18GHz



GSM 1900 Channel 661 18GHz ~20GHz

TA Technology (Shanghai) Co., Ltd.

Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02


Page 29 of 42

Harmonic	TX ch.661 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	3760	Nf	-13	/
3	5640	Nf	-13	/
4	7520	Nf	-13	/
5	9400	Nf	-13	/
6	11280	Nf	-13	/
7	13160	Nf	-13	/
8	15040	Nf	-13	/
9	16920	Nf	-13	/
10	18800	Nf	-13	/


Nf: noise floor

Note: The other Spurious RF conducted emissions level is no more than noise floor.

CH 810



Note: The signal beyond the limit is carrier:1909.8 MHz
GSM 1900 Channel 810 30MHz ~18GHz



GSM 1900 Channel 810 18GHz ~20GHz

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 31 of 42

Harmonic	TX ch.810 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	3819.75	-53.299	-13	40.299
3	5729.4	Nf	-13	/
4	7639.2	Nf	-13	/
5	9549	Nf	-13	/
6	11458.8	Nf	-13	/
7	13368.6	Nf	-13	/
8	15278.4	Nf	-13	/
9	17188.2	Nf	-13	/
10	19098	Nf	-13	/

Nf: noise floor

Note: The other Spurious RF conducted emissions level is no more than noise floor.

TA Technology (Shanghai) Co., Ltd.

Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 32 of 42

2.1. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The measurements procedures in TIA -603C are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The measurement will be conducted at channels 512,661,810 of GSM1900.

The procedure of Radiates Spurious Emission is as follows:

1. Pre-calibration

In an fully anechoic chamber, A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted at a 3 meter test distance from the receive antenna. An RF signal source is connected to the dipole with a Tx cable that has been constructed to not interfere with radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to input of dipole, and the power received (P_r) is recorded from the spectrum analyzer.

“Reference Path loss” is established as $P_{in} - P_r - \text{Tx cable loss} + \text{Substitution antenna gain}$.



2. EUT Test

EUT was placed on a 1.5 meter high non – conductive table at a 3 meter test distance from the receive antenna. The height of receiving antenna is 1.5 m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the table and adjusting the receiving antenna polarization. The measurement is carried out using a spectrum analyzer .The radiated emission measurements of all non-harmonic and harmonic of the transmit frequency from 30MHz to the 10th harmonic were measured with peak detector. RBW is set to 100kHz and VBW is set to 300kHz for 30MHz to 1GHz. RBW is set to 100kHz,VBW is set to 30kHz for the carrier frequency, RBW is set to 1MHz and VBW is set to 3MHz for other frequency above 1GHz. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency. If the harmonic could not be detected above the noise floor, the ambient level was recorded.


The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

Calculation procedure:

$$RSE = Rx \text{ (dBm)} + \text{Reference Path loss}$$

Rx: reading of the receiver

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis) and docking mode. The worst emission was found in stand-up position (Z axis) and the worst case was recorded.



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”


Limit	-13 dBm
-------	---------

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U=3.16$ dB.

Test Result


CH 512



Note: The signal beyond the limit is carrier.
GSM 1900 Channel 512 30MHz~3GHz




GSM 1900 Channel 512 3GHz ~18GHz




GSM 1900 Channel 512 18GHz ~20GHz

Harmonic	TX ch.512 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3700.125	-41.158	-13	28.158	135


CH 661



Note: The signal beyond the limit is carrier.
GSM 1900 Channel 661 30MHz~3GHz




GSM 1900 Channel 661 3GHz ~18GHz




GSM 1900 Channel 661 18GHz ~20GHz

Harmonic	TX ch.661 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3759.75	-42.995	-13	29.995	0
7	13159.375	-46.495	-13	33.495	90


CH 810



Note: The signal beyond the limit is carrier.
GSM 1900 Channel 810 30MHz~3GHz



GSM 1900 Channel 810 3GHz ~18GHz



GSM 1900 Channel 810 18GHz ~20GHz

Harmonic	TX ch.810 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3819.375	-46.136	-13	33.136	90
6	11459	-46.575	-13	33.575	45
7	13368.75	-44.738	-13	31.738	180

TA Technology (Shanghai) Co., Ltd.
Test Report

Registration Num:428261

Report No.: RZA2010-1428RF02

Page 40 of 42

3. Main Test Instruments

No.	Name	Type	Manufacturer	Serial Number	Calibration Date	Valid Period
01	Base Station Simulator	CMU200	R&S	118133	2010-05-27	One year
02	Signal Analyzer	FSV	R&S	100815	2010-06-28	One year
03	Signal generator	SMR27	R&S	1606.6000.02	2010-06-28	One year
04	EMI Test Receiver	ESCI	R&S	100948	2010-07-01	One year
05	Trilog Antenna	VUBL 9163	SCHWARZB ECK	9163-201	2010-06-29	Two years
06	Horn Antenna	HF907	R&S	100126	2009-07-02	Two years
07	Power Splitter	11667A	Agilent	52960	NA	NA
08	DC Power Supply	GPS-3030D	GM	E877677	NA	NA
09	Climatic Chamber	ESS-SDH401	YIN HE	2006001	2010-02-22	One year
10	Semi-Anechoic Chamber	9.6*6.7*6.6m	ETS-Lindgren	NA	NA	NA
11	EMI test software	ES-K1	R&S	NA	NA	NA

*****END OF REPORT BODY*****

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance



Picture 1 EUT and Auxiliary

A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup