

# **FCC Test Report**

FCC ID : RID-LS134

Equipment : LoRa® Smoke and Heat Detector

Model No. : LS-134XX

(X can be any alphanumeric character for marketing

purpose)

Brand Name : GlobalSat

Applicant : GlobalSat WorldCom Corporation

Address : 16F., No.186, Jian 1st Rd., Zhonghe Dist., New

Taipei City, 23553, Taiwan

Standard : 47 CFR FCC Part 15.247

Received Date : Sep. 19, 2017

Tested Date : Jun. 05 ~ Jun. 15, 2018

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen Assistant Manager Gary Chang / Manager

Testing Laboratory

Report No.: FR791901-01 Page: 1 of 34



# **Table of Contents**

1	GENERAL DESCRIPTION	4
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	7
1.4	The Equipment List	
1.5	Test Standards	9
1.6	Measurement Uncertainty	g
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	
3	TRANSMITTER TEST RESULTS	11
3.1	6dB and Occupied Bandwidth	11
3.2	RF Output Power	14
3.3	Power Spectral Density	15
3.4	Unwanted Emissions into Restricted Frequency Bands	17
3.5	Emissions in Non-Restricted Frequency Bands	31
4	TEST LABORATORY INFORMATION	34



# **Release Record**

Report No.	Version	Description	Issued Date
FR791901-01	Rev. 01	Initial issue	Sep. 13, 2018

Report No.: FR791901-01 Page: 3 of 34



# **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	Note	N/A
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 955.38MHz 42.25 (Margin -3.75dB) - PK	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 18.65	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass
15.247(d)	Antenna-port Conducted Emission	Meet the requirement of limit	Pass

Note: The EUT consumes DC power, so the test is not required.

Report No.: FR791901-01 Page: 4 of 34



# 1 General Description

## 1.1 Information

## 1.1.1 Specification of the Equipment under Test (EUT)

	RF General Information							
Frequency Range (MHz)	Ch. Freq. (MHz)	Channel Number	Physical bit rate (bit/s)	Spread Factor	Channel Bandwidth (kHz)			
902 ~ 928	902.9 ~ 927.5	1 ~ 42 [42]	21900	7	500			

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.

Note 2: The device uses FSK modulation.

#### 1.1.2 Antenna Details

Ant. No. Type		Connector	Gain (dBi)	
1	chip	N/A	1.6	

# 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3Vdc from battery
-------------------	-------------------

#### 1.1.4 Accessories

	Accessories					
No.	Equipment	Description				
1	Lithium battery	Brand: Panasonic Model: CR123A Power Rating: 3Vdc				
2	Sensor Programmable Cable	1m non-shielded without core.				

Report No.: FR791901-01 Page: 5 of 34



## 1.1.5 Channel List

Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	902.9	17	912.5	33	922.1
2	903.5	18	913.1	34	922.7
3	904.1	19	913.7	35	923.3
4	904.7	20	914.3	36	923.9
5	905.3	21	914.9	37	924.5
6	905.9	22	915.5	38	925.1
7	906.5	23	916.1	39	925.7
8	907.1	24	916.7	40	926.3
9	907.7	25	917.3	41	926.9
10	908.3	26	917.9	42	927.5
11	908.9	27	918.5		
12	909.5	28	919.1		
13	910.1	29	919.7		
14	910.7	30	920.3		
15	911.3	31	920.9		
16	911.9	32	921.5		

# 1.1.6 Test Tool and Duty Cycle

Test Tool Real Term, version: 2.0.0.70	
Duty cycle	94.86 %

# 1.1.7 Power Setting

Madulation Mada	Test Frequency (MHz)			
Modulation Mode	902.9	914.9	927.5	
FSK	7	7	7	


Report No.: FR791901-01 Page: 6 of 34



# 1.2 Local Support Equipment List

	Support Equipment List						
No. Equipment Brand		Model	FCC ID	Remarks			
1	Notebook	DELL	Latitude E6440	DoC			

# 1.3 Test Setup Chart



Report No.: FR791901-01 Page: 7 of 34



# 1.4 The Equipment List

Took Cite	Radiated Emission						
Test Site	966 chamber1 / (03CH01-WS)						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	R&S	FSV40	101498	Dec. 04, 2017	Dec. 03, 2018		
Receiver	R&S	ESR3	101658	Nov. 20, 2017	Nov. 19, 2018		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 25, 2017	Jul. 24, 2018		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 20, 2017	Dec. 19, 2018		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 23, 2017	Nov. 22, 2018		
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2017	Nov. 12, 2018		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 07, 2017	Dec. 06, 2018		
Preamplifier	EMC	EMC02325	980225	Jul. 28, 2017	Jul. 27, 2018		
Preamplifier	Agilent	83017A	MY39501308	Oct. 06, 2017	Oct. 05, 2018		
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 07, 2017	Dec. 06, 2018		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 07, 2017	Dec. 06, 2018		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 07, 2017	Dec. 06, 2018		
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	16052	Dec. 07, 2017	Dec. 06, 2018		
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 07, 2017	Dec. 06, 2018		
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 07, 2017	Dec. 06, 2018		
Measurement Software AUDIX e3 6.120210g NA NA							

Test Item	RF Conducted							
Test Site	(TH01-WS)							
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101486	Nov. 21, 2017	Nov. 20, 2018			
Power Meter	Anritsu	ML2495A	1241002	Oct. 16, 2017	Oct. 15, 2018			
Power Sensor	Anritsu	MA2411B	1207366	Oct. 16, 2017	Oct. 15, 2018			
AC POWER SOURCE	APC	AFC-500W	F312060012	Dec. 01, 2017	Nov. 30, 2018			
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA			
Note: Calibration Inte	Note: Calibration Interval of instruments listed above is one year.							

Report No.: FR791901-01 Page: 8 of 34



### 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 ANSI C63.10-2013 FCC KDB 558074 D01 15.247 Meas Guidance v05 FCC KDB 453039

# 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty					
Parameters	Uncertainty				
Bandwidth	±34.134 Hz				
Conducted power	±0.808 dB				
Power density	±0.463 dB				
Conducted emission	±2.670 dB				
AC conducted emission	±2.90 dB				
Radiated emission ≤ 1GHz	±3.66 dB				
Radiated emission > 1GHz	±5.63 dB				

Report No.: FR791901-01 Page: 9 of 34



# 2 Test Configuration

# 2.1 Testing Condition

Test Item Test Site		Ambient Condition	Tested By		
Radiated Emissions	03CH01-WS	24°C / 61%	Akun Chung Vincent Yeh Roger Lu		
RF Conducted	TH01-WS	22°C / 65%	Felix Sung		

FCC Designation No.: TW2732
 FCC site registration No.: 181692
 IC site registration No.: 10807A-1

## 2.2 The Worst Test Modes and Channel Details

Test item	Test Frequency (MHz)	Channel Bandwidth (kHz)	Modulation / SF	Test Configuration
Maximum Output Power 6dB Bandwidth				
Power Spectral Density Radiated Emissions ≤1GHz Radiated Emissions >1GHz	902.9 / 914.9 / 927.5	500	FSK / 7	

#### Note:

Report No.: FR791901-01 Page: 10 of 34

<sup>1.</sup> The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.



# 3 Transmitter Test Results

## 3.1 6dB and Occupied Bandwidth

#### 3.1.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

#### 3.1.2 Test Procedures


#### 6dB Bandwidth

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

### **Occupied Bandwidth**

- 1. Set resolution bandwidth (RBW) = 10kHz, Video bandwidth = 30kHz.
- Detector = Peak, Trace mode = max hold.
- 3 Sweep = auto couple, Allow the trace to stabilize.
- 4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

#### 3.1.3 Test Setup




Report No.: FR791901-01 Page: 11 of 34



# 3.1.4 Test Result of 6dB and Occupied Bandwidth


Modulation / SF	Freq. (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
FSK / 7	902.9	0.768	0.5
FSK / 7	914.9	0.759	0.5
FSK / 7	927.5	0.757	0.5



Report No.: FR791901-01 Page: 12 of 34



Modulation / SF	Freq. (MHz)	99% Occupied Bandwidth (MHz)
FSK / 7	902.9	0.627
FSK / 7	914.9	0.621
FSK / 7	927.5	0.615



Report No.: FR791901-01 Page: 13 of 34



# 3.2 RF Output Power

### 3.2.1 Limit of RF Output Power


Conducted power shall not exceed 1Watt.

Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

#### 3.2.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

### 3.2.3 Test Setup



### 3.2.4 Test Result of Maximum Output Power

Modulation / SF	Freq. (MHz)	PK Output Power (mW)	PK Output Power (dBm)	Limit (dBm)
FSK / 7	902.9	73.28245	18.65	30
FSK / 7	914.9	72.94575	18.63	30
FSK / 7	927.5	72.77798	18.62	30

Modulation / SF	Freq. (MHz) AV Output Powe		AV Output Power (dBm)
FSK / 7	902.9	71.61434	18.55
FSK / 7	914.9	71.28530	18.53
FSK / 7	927.5	71.12135	18.52

Note: Average power is reference only.

Report No.: FR791901-01 Page: 14 of 34



# 3.3 Power Spectral Density


### 3.3.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

#### 3.3.2 Test Procedures

- 1. Set the RBW = 3 kHz, VBW = 10 kHz.
- 2. Detector = Peak, Sweep time = auto couple.
- 3. Trace mode = max hold, allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

#### 3.3.3 Test Setup




Report No.: FR791901-01 Page: 15 of 34



# 3.3.4 Test Result of Power Spectral Density

Modulation / SF	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
FSK/7	902.9	5.81	8.00
FSK / 7	914.9	5.99	8.00
FSK / 7	927.5	6.14	8.00



Report No.: FR791901-01 Page: 16 of 34



### 3.4 Unwanted Emissions into Restricted Frequency Bands

### 3.4.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit							
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)				
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300				
0.490~1.705	24000/F(kHz)	33.8 - 23	30				
1.705~30.0	30	29	30				
30~88	100	40	3				
88~216	150	43.5	3				
216~960	200	46	3				
Above 960	500	54	3				

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:** 

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.4.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR791901-01 Page: 17 of 34




## 3.4.3 Test Setup



Report No.: FR791901-01 Page: 18 of 34



### 3.4.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR791901-01 Page: 19 of 34



Modulation / SF	FSK / 7	Test Freq. (MHz)	902.9
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV		Remark	ANT High cm	Turn Table deg
1	223 03	26.56	16 00	_19 //	37.18	-10.62	Peak		
_									
2	314.21	27.07	46.00	-18.93	34.36	-7.29	Peak		
3	396.66	30.00	46.00	-16.00	35.04	-5.04	Peak		
4	439.34	31.23	46.00	-14.77	35.27	-4.04	Peak		
5	667.29	35.39	46.00	-10.61	35.21	0.18	Peak		
6	955.38	41.96	46.00	-4.04	37.03	4.93	Peak		

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR791901-01 Page: 20 of 34



Modulation / SF	FSK	FSK / 7					q. (M	914.9					
Polarization	Hori	Horizontal											
90 Le	vel (dBuV/m)							_					
80—													
80													
70—					+			+					
60—													
										FCC CL	ASS-B		
50													
40					_		5		6				
			,	3 4	.		ا						
30													
20					$\vdash$			+					
10													
030	100. 20	0. 30	0. 4	00.	500		0.	700.	800.	900.	1000		
						ncy (MHz)							
	Freq. I	Emission	Limit	Marg			Fact	or	Remar				
	MHz	level dBuV/m	dBuV/	n dB		reading dBuV	g dE	2		Hig cm	h Table deg		
	14112	ubuv/III	ubuv/i	ii ub		ubuv	uL	,		CIII	ueg		
1	203.63	28.74	43.50	-14.7	6	39.53	-10.	79	Peak				
2	307.42	29.16	46.00	-16.8	4	36.62	-7.	46	Peak				
3		29.94				34.32	-4.		Peak				
4	470.38					33.72	-3.		Peak				
5	645.95	34.98	46.00	-11.0	2	35.15	-0.	1/	Peak				

2.15

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

778.84 37.36 46.00 -8.64 35.21

Report No.: FR791901-01 Page: 21 of 34



Modulation / SF	FSK / 7	Test Freq. (MHz)	914.9
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	270.56	24.58	46.00	-21.42	33.06	-8.48	Peak		
2	329.73	27.10	46.00	-18.90	34.01	-6.91	Peak		
3	439.34	31.37	46.00	-14.63	35.41	-4.04	Peak		
4	490.75	32.89	46.00	-13.11	35.90	-3.01	Peak		
5	621.70	34.15	46.00	-11.85	34.58	-0.43	Peak		
6	955.38	42.25	46.00	-3.75	37.32	4.93	Peak		

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR791901-01 Page: 22 of 34



Modulation / SF	FSK	( / 7			Test I	req	927.	927.5				
Polarization	Horizontal											
90 Leve	l (dBuV/m)				1						_	
80												
00												
70						+						
60												
									FCC	CLAS	S-B	
50												
40					_	_	6				_	
30		1	3 4		5 		Ĭ					
30		2										
20												
10												
0 <mark></mark>	100. 20	00. 30	00.		00.	600.	700.	800.	90	00.	1000	
	-			-	ency (M		<b>.</b> .			NIT	_	
	Freq.	tmission level	n Limi	t Margi	n SA read		Factor	Remark		NNT High	Turn Table	
	MHz	dBuV/m	dBuV	/m dB	dBu	_	dB			m :	deg	
1	205.57			0 -13.43	40.		-10.79	Peak				
2	283.17			0 -19.75	34.		-8.01	Peak				
3	326.82			0 -17.28	35.		-6.98	Peak				
4 5	374.35 559.62			0 -17.01 0 -12.93			-5.70 -1.53	Peak Peak				
6				0 -12.95 0 -10.95	35.		-0.25	Peak Peak				

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR791901-01 Page: 23 of 34



Modulation / SF	FS	FSK / 7					Test Freq. (MHz)				
Polarization	Vertical										
90 Lev	el (dBuV/m)										
80											
00											
70					+						
60										ļ	
50									FCC	CLAS	SS-B
50											5
40					_			- 5			
30			1 2	3	4						
			ÍΙ								
20					$\dagger$						
10											
0											
030	100.	200. 3	00.	400. Fre	500	). 60 cy (MHz)	0. 70	0. 80	0. 9	000.	1000
	Enoa	Emissio	n limit				Factor	Rema	nk	ANT	Turn
	11 04.	level		- mun g		reading		ricina		High	Table
	MHz	dBuV/m	ı dBuV/	m dB		dBuV	dB			cm	deg
			45.00		_						
1 2	301.6 367.5			-18.9 -17.9		34.62 33.91	-7.60 -5.89				
3	439.3			) -14.3	_	35.88	-4.04				
4		4 32.23				35.49					
5		3 37.17				35.14	2.03				
6	955.3	8 42.07	46.00	-3.9	93	37.14	4.93	Peak			

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR791901-01 Page: 24 of 34



### 3.4.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR791901-01 Page: 25 of 34






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR791901-01 Page: 26 of 34






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR791901-01 Page: 27 of 34





\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR791901-01 Page: 28 of 34



Modulation / SF		FSK	/7			Test Fre	927.5					
Polarization	Horizontal											
_												
90	Level	(dBuV/m)										
80-												
									FCC CLAS	SS-B		
70												
60								ECC	CLASS-B (A	WG)		
50			2					rcc	CLASS-D (A	400)		
50			1		4				5			
40												
30-					1							
20												
20												
10												
0	1000	2000.	3000.	4000.	5000.	6000.	7000.	8000.	9000.	10000		
	1000	2000.	3000.	4000.		ency (MHz)		8000.	9000.	10000		
		Freq. E	mission	Limit	Margi	n SA	Factor	Remark		Turn		
			level			readin			High	Table		
		MHz	dBuV/m	dBuV/ı	n dB	dBuV	dB		cm	deg		
1		2782.50	45.89	54.00	-8.11	47.94	-2.05	Average	117	266		
2		2782.50	50.97	74.00	-23.03	53.02	-2.05	Peak	117	266		
3		4637.50	33.51	54.00	-20.49	30.52	2.99	Average	100	188		
4		4637.50						Peak	100	188		
5		9275.00	43.62		-10.38	31.85	11.77	Average	≥ 100	129		
_												

11.77

Peak

100

129


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor , cable loss and amplifier gain

9275.00 56.10 74.00 -17.90 44.33

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR791901-01 Page : 29 of 34





\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR791901-01 Page: 30 of 34



# 3.5 Emissions in Non-Restricted Frequency Bands

### 3.5.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

#### 3.5.2 Test Procedures


#### Reference level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Use the peak marker function to determine the maximum PSD level

#### **Emission level measurement**

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Scan Frequency range is up to 25GHz
- 4. Use the peak marker function to determine the maximum amplitude level


#### 3.5.3 Test Setup



Report No.: FR791901-01 Page: 31 of 34




## 3.5.4 Unwanted Emissions into Non-Restricted Frequency Bands



Report No.: FR791901-01 Page: 32 of 34





Report No.: FR791901-01 Page: 33 of 34



# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

#### Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

#### Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FR791901-01 Page: 34 of 34