

Report No. : AD019292-3 Date : 2003 November 04

Client : Team Caliber, Inc.

4606 Roush Place

Concord, North Carolina,

U.S.A.

Sample Description : One(1) submitted sample stated to be <u>1/64 R/C Car – 49 MHz</u>

of Model No. 64RCTRANS49.

Rating : 2.4 V Rechargeable Battery

No. of sample(s) : Two(2) sets

Date Received : 2003 October 27.

Test Period : 2003 October 27 – 2003 November 03.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – May 2002

ANSI C63.4 – 1992

Test Result : See attached sheet(s) from page 2 to 10.

Conclusion : The submitted sample was found to comply with requirement of FCC

Part 15 Subpart B.

For and on behalf of

CMA Testing and Certification Laboratories

Authorized Signature : Page 1 of 10

Darlay Chui EMC Engineer - EL. Division

FCC ID: RIO-64RCRECEI49



Report No. : AD019292-3 Date : 2003 November 04

Table of Contents

1	G	eneral Information	
	1.1	General Description	3
	1.2	Related Submittal Grants	
	1.3	Location of the test site	
	1.4	List of measuring equipment	
2	D	escription of the radiated emission test	
	2.1	Test Procedure	
	2.2	Test Result	<i>€</i>
	2.3	Radiated Emission Measurement Data	7
3	D	escription of the Line-conducted Test	8
	3.1	Test Procedure	8
	3.2	Test Result	
	3.3	Graph and Table of Conducted Emission Measurement Data	
4	Pł	hotograph	_
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	
	4.2	Photographs of the External and Internal Configurations of the EUT	
5	Su	pplementary document	
	5.1	Bandwidth	
	6	Appendices	



Report No. : AD019292-3 Date : 2003 November 04

1 General Information

1.1 General Description

The equipment under test (EUT) is a superregenerative receiver for 1/64 R/C Car – 49 MHz operating at 49.860 MHz which is controlled by a LRC circuit. The EUT is powered by 2.4 V rechargeable battery, and it has an external antenna in the back of the receiver. When received forward or backward signal, it will go forward or backward. When received left of right signal, it will turn left or right.

The brief circuit description is listed as follows:

- Q7 and associated circuit act as super regenerative
- Q3-Q6 and associated circuit act as motor control
- Q1-Q2 and associated circuit act as L/R control
- RX2 and associated circuit act as decoder
- R3 and associated circuit act as oscillator for RX2
- U2 and associated circuit act as power supply

1.2 Related Submittal Grants

This is a single application for certification of a receiver. The transmitter for this receiver is authorized by Certification procedure.



Report No. : AD019292-3 Date : 2003 November 04

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. A double shielded room is located at :

Roof Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AD019292-3 Date : 2003 November 04

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



Report No. : AD019292-3 Date : 2003 November 04

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to "cohere" the characteristic broadband emissions from the receiver.

2.2 Test Result

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR qusai-peak detector.

It was found that the EUT meet the FCC requirement.



Report No. : AD019292-3 Date : 2003 November 04

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV/m)	Antenna and Cable factor (dB)	Field Strength (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
46.784	V	16.7	11.4	28.1	40.0	-11.9
47.292	V	15.6	11.4	27.0	40.0	-13.0
47.809	V	15.7	11.4	27.1	40.0	-12.9
50.625	V	17.1	8.9	26.0	40.0	-14.0
52.923	V	15.2	8.9	24.1	40.0	-15.9
92.823	V	13.8	10.0	23.8	43.5	-19.7
93.599	V	13.7	10.0	23.7	43.5	-19.8
97.679	V	14.0	10.0	24.0	43.5	-19.5
137.603	V	11.0	13.2	24.2	43.5	-19.3
190.029	V	13.8	10.5	24.3	43.5	-19.2



Report No. : AD019292-3 Date : 2003 November 04

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



Report No. : AD019292-3 Date : 2003 November 04

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExtPho1.jpg to ExtPho2.jpg and IntPho1.jpg to IntPho2.jpg.

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmpl.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

N.A.



Report No. : AD019292-3 Date : 2003 November 04

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of External Configurations	1 page
A3.	Photos of Internal Configurations	1 page
A4.	ID Label/Location	1 page
A5.	Block Diagram	1 page
A6.	Schematics	1 page
A7.	User Manual	1 page
A8.	Operation Description	1 page

***** End of Report *****