
FCC Part 90 Test Report

Report No.: AGC02X121201-2F2

FCC ID : RIQAM-580
PRODUCT DESIGNATION : Land Mobile Radio
BRAND NAME : ADI
MODEL NAME : AM-580
CLIENT : Access Device Integrated Communications Corp.
DATE OF ISSUE : Dec.28, 2012
STANDARD(S) : FCC Part 90 Rules
REPORT VERSION : V 1.0

Attestation of **Global Compliance (Shenzhen) Co., Ltd.**

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

VERIFICATION OF COMPLIANCE

Applicant:	Access Device Integrated Communications Corp.
	No. 193, Sec. 1, Chungching Road, Taya, Taichung City 42862, Taiwan (R.O.C.)
Manufacturer:	Access Device Integrated Communications Corp.
	No. 193, Sec. 1, Chungching Road, Taya, Taichung City 42862, Taiwan (R.O.C.)
Product Designation:	Land Mobile Radio
Brand Name:	ADI
Model Name:	AM-580
Report No.:	AGC02X121201-2F2
Date of Test:	Dec.26, 2012 to Dec.28, 2012

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2003. The sample tested as described in this report is in compliance with the FCC Rules Part 90 requirements

The test results of this report relate only to the tested sample identified in this report.

Tested by Wall Huang
Wall Huang Dec.28, 2012

Checked By Forrest Lei
Forrest Lei Dec.28, 2012

Authorized By Solger Zhang
Solger Zhang Dec.28, 2012

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.3 TEST METHODOLOGY	6
1.4 TEST FACILITY	6
1.5 SPECIAL ACCESSORIES	6
1.6 EQUIPMENT MODIFICATIONS	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 GENERAL TECHNICAL REQUIREMENTS	7
2.4 CONFIGURATION OF TESTED SYSTEM	7
3. SUMMARY OF TEST RESULTS	8
4. DESCRIPTION OF TEST MODES	9
5. CONDUCTED LIMITS	10
5.1 PROVISIONS APPLICABLE	10
5.2 MEASUREMENT PROCEDURE	10
5.3 TEST SETUP BLOCK DIAGRAM	11
5.4 TEST EQUIPMENT USED	11
5.5 TEST RESULT	12
6. FREQUENCY TOLERANCE	13
6.1 PROVISIONS APPLICABLE	13
6.2 MEASUREMENT PROCEDURE	13
6.3 TEST SETUP BLOCK DIAGRAM	14
6.4 TEST EQUIPMENT USED:	14
6.5 TEST RESULT	15
7. EMISSION BANDWIDTH	21
7.1 PROVISIONS APPLICABLE	21
7.2 MEASUREMENT PROCEDURE	21
7.3 TEST SETUP BLOCK DIAGRAM	21
7.4 MEASUREMENT EQUIPMENT USED:	21
7.5 MEASUREMENT RESULT:	22
8. UNWANTED RADIATION	24
8.1 PROVISIONS APPLICABLE	24
8.2 MEASUREMENT PROCEDURE	24

8.3 TEST SETUP BLOCK DIAGRAM.....	25
8.4 MEASUREMENT EQUIPMENT USED:.....	27
8.5 MEASUREMENT RESULTS:.....	27
9. MODULATION CHARACTERISTICS	32
9.1 PROVISIONS APPLICABLE.....	32
9.2 MEASUREMENT METHOD	32
9.3 MEASUREMENT INSTRUMENTS	32
9.4 MEASUREMENT RESULT	33
10. MAXIMUM TRANSMITTER POWER (CONDUCTED OUTPUT POWER).....	36
10.1 PROVISIONS APPLICABLE.....	36
10.2 TEST PROCEDURE.....	36
10.3 TEST INSTRUMENTS.....	36
10.4 TEST CONFIGURATION	36
10.5 TEST RESULT.....	36
10.6 CONDUCT SPURIOUS PLOT	37
11. TRANSMITTER FREQUENCY BEHAVIOR	40
11.1 PROVISIONS APPLICABLE.....	40
11.2 TEST METHOD	40
11.3 TEST INSTRUMENTS	40
11.4 DESCRIBE LIMIT LINE OF TRANSMITTER FREQUENCY BEHAVIOR.....	41
11.5 MEASURE RESULT	43
12. RADIATED EMISSION ON RECEIVING MODE.....	44
12.1 PROVISIONS APPLICABLE.....	44
12.2 TEST METHOD	44
12.3 TEST INSTRUMENTS.....	44
12.4 MEASURE RESULT (MEASURED AT 3M USING FCC PART15 B LIMITS).....	45
13. AUDIO LOW PASS FILTER RESPONSE	47
13.1 LIMITS	47
13.2. METHOD OF MEASUREMENTS	47
13.3 TEST DATA.....	47
APPENDIX I.....	50
PHOTOGRAPHS OF SETUP	50
APPENDIX II.....	51
EXTERNAL VIEW OF EUT.....	51

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a Land Mobile Radio designed for voice communication. It is designed by way of utilizing the FM modulation achieves the system operating.

A major technical description of EUT is described as following:

Communication Type	Voice / Tone only	
Type of Modulation	F3E	
Emission Bandwidth	7.79KHz for VHF(max) 7.61KHZ for UHF(max)	
Peak Frequency Deviation	1.78 KHz	
Audio Frequency Response	11.03dB	
Maximum Transmitter Power	46.96dBm for VHF(max) 45.42dBm for UHF(max)	
Rating Power	46.99dBm for VHF(max) 45.44dBm for UHF(max) (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Antenna Designation	Detachable	
Power Supply	DC 13.8V by DC source	
Limiting Voltage	DC 11.73V	
Operation Frequency Range and Channel	Frequency Range:136MHz to 174MHz & 400MHz to 520MHz Channel Separation: 12.5KHz	
	136MHz to 174MHz: Top Channel: 173.975MHz, Centre Channel: 155.000MHz, Bottom Channel: 136.025MHz	400MHz to 520MHz: Top Channel: 519.975MHz, Centre Channel: 460.000MHz, Bottom Channel: 400.025MHz
Frequency Tolerance	0.471ppm for VHF for VHF(max) 0.502ppm for UHF for UHF(max)	

Note: VHF (136MHz to 174MHz)
UHF (400MHz to 520MHz)

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: RIQAM-580**, filing to comply with the FCC Part 90 requirements.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2009; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located on the address of Attestation of Global Compliance (Shenzhen) Co., Ltd. 2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003 and IC requirements in documents RS212.

FCC register No.: 259865

1.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

1.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

- (1). Section 15.207: Conducted Limits
- (2). Section 90.205: Maximum ERP is dependent upon the station's antenna HAAT and required service area
- (3). Section 90.207: Modulation Characteristic
- (4). Section 90.209: Occupied Bandwidth
- (5). Section 90.210: Emission Mask
- (6). Section 90.213: Frequency Tolerance
- (7). Section 90.214: Transient Frequency Behavior
- (8). Section 15.109: Radiated Emission

2.4 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Model No.	Identifier	Note
1	Land Mobile Radio	AM-580	FCC ID: RIQAM-580	EUT

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207	Conducted Emission	N/A
§90.205	Maximum Transmitter Power	Compliant
§90.207	Modulation Characteristic	Compliant
§90.209	Occupied Bandwidth	Compliant
§90.210	Emission Mask	Compliant
§90.213	Frequency Tolerance	Compliant
§90.214	Transient Frequency Behavior	Compliant
§15.209	Radiated Emission	Compliant

NOTE:

1. N/A- Not Applicable.

4. DESCRIPTION OF TEST MODES

RF TEST MODES

The EUT (Land Mobile Radio) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation (12.5 KHz).

No.	TEST MODES	CHANNEL SEPARATION
1	Low Channel	12.5 KHz
2	Middle Channel	12.5 KHz
3	High Channel	12.5 KHz

EMC TEST MODES

No.	TEST MODES
1	Standby Mode

Note: Only the result of the worst case was recorded in the report.

5. CONDUCTED LIMITS

5.1 PROVISIONS APPLICABLE

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the, the radio frequency voltage that is conducted back onto the AC power line on any frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50uH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.


Frequency of Emission (MHz)	Conducted Limit(dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency.

5.2 MEASUREMENT PROCEDURE

- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per ANSI C63.4.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- (4) The EUT received power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- (5) All support equipments received AC power from a second LISN, if any.
- (6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (7) Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
During the above scans, the emissions were maximized by cable manipulation.

5.3 TEST SETUP BLOCK DIAGRAM



5.4 TEST EQUIPMENT USED

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	N/A	07/18/2012	07/17/2013
LISN	R&S	ESH3-Z5	N/A	07/18/2012	07/17/2013

5.5 TEST RESULT

N/A

6. FREQUENCY TOLERANCE

6.1 PROVISIONS APPLICABLE

- a). According to FCC Part 2 Section 2.1055(a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- b). According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- c). According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5KHz channel separation.

6.2 MEASUREMENT PROCEDURE


6.2.1 Frequency stability versus environmental temperature

1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz and Frequency Span to 50KHz. Record this frequency as reference frequency.
3. Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT shall be powered by DC 13.8V
2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 KHz and Video Resolution Bandwidth to 1KHz. Record this frequency as reference frequency.
3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 TEST SETUP BLOCK DIAGRAM



6.4 TEST EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
Receiver	R&S	ESCI	N/A	07/18/2012	07/17/2013
Climate Chamber	EXPERY	TN-400	N/A	07/18/2012	07/17/2013

6.5 TEST RESULT

VHF TEST RESULTS

(1) Frequency stability versus input voltage (Supply nominal voltage is 13.8V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	136.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 13.8 V	136.025044	0.323
40	DC 13.8 V	136.025035	0.257
30	DC 13.8 V	136.025029	0.213
20	DC 13.8 V	136.025019	0.140
10	DC 13.8 V	136.025026	0.191
0	DC 13.8 V	136.025031	0.228
-10	DC 13.8 V	136.025042	0.309
-20	DC 13.8 V	136.025047	0.346
-30	DC 13.8 V	136.025051	0.375

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	155.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 13.8 V	155.000051	0.329
40	DC 13.8 V	155.000042	0.271
30	DC 13.8 V	155.000035	0.226
20	DC 13.8 V	155.000021	0.135
10	DC 13.8 V	155.000034	0.219
0	DC 13.8 V	155.000039	0.252
-10	DC 13.8 V	155.000042	0.271
-20	DC 13.8 V	155.000048	0.310
-30	DC 13.8 V	155.000053	0.342

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 13.8 V	173.975046	0.264
40	DC 13.8 V	173.975038	0.218
30	DC 13.8 V	173.975026	0.149
20	DC 13.8 V	173.975017	0.098
10	DC 13.8 V	173.975025	0.144
0	DC 13.8 V	173.975036	0.207
-10	DC 13.8 V	173.975041	0.236
-20	DC 13.8 V	173.975047	0.270
-30	DC 13.8 V	173.975053	0.305

(2) Frequency stability versus input voltage (Battery limiting voltage is 11.73V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	136.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 11.73 V	136.025049	0.360
40	DC 11.73 V	136.025026	0.191
30	DC 11.73 V	136.025029	0.213
20	DC 11.73 V	136.025022	0.162
10	DC 11.73 V	136.025033	0.243
0	DC 11.73 V	136.025041	0.301
-10	DC 11.73 V	136.025052	0.382
-20	DC 11.73 V	136.025059	0.434
-30	DC 11.73 V	136.025064	0.471

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	155.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 11.73 V	155.000056	0.361
40	DC 11.73 V	155.000047	0.303
30	DC 11.73 V	155.000031	0.200
20	DC 11.73 V	155.000023	0.148
10	DC 11.73 V	155.000031	0.200
0	DC 11.73 V	155.000043	0.277
-10	DC 11.73 V	155.000055	0.355
-20	DC 11.73 V	155.000064	0.413
-30	DC 11.73 V	155.000073	0.471

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 11.73 V	173.975057	0.328
40	DC 11.73 V	173.975046	0.264
30	DC 11.73 V	173.975038	0.218
20	DC 11.73 V	173.975025	0.144
10	DC 11.73 V	173.975031	0.178
0	DC 11.73 V	173.975043	0.247
-10	DC 11.73 V	173.975052	0.299
-20	DC 11.73 V	173.975066	0.379
-30	DC 11.73 V	173.975074	0.425

(3) Frequency stability versus input voltage (Battery Fully Charged voltage is 15.87V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	136.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 15.87 V	136.025049	0.360
40	DC 15.87 V	136.025037	0.272
30	DC 15.87 V	136.025028	0.206
20	DC 15.87 V	136.025019	0.140
10	DC 15.87 V	136.025026	0.191
0	DC 15.87 V	136.025033	0.243
-10	DC 15.87 V	136.025039	0.287
-20	DC 15.87 V	136.025045	0.331
-30	DC 15.87 V	136.025056	0.412

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	155.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 15.87 V	155.000055	0.355
40	DC 15.87 V	155.000042	0.271
30	DC 15.87 V	155.000033	0.213
20	DC 15.87 V	155.000024	0.155
10	DC 15.87 V	155.000032	0.206
0	DC 15.87 V	155.000041	0.265
-10	DC 15.87 V	155.000052	0.335
-20	DC 15.87 V	155.000066	0.426
-30	DC 15.87 V	155.000071	0.458

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 15.87 V	173.975063	0.362
40	DC 15.87 V	173.975051	0.293
30	DC 15.87 V	173.975036	0.207
20	DC 15.87 V	173.975025	0.144
10	DC 15.87 V	173.975033	0.190
0	DC 15.87 V	173.975045	0.259
-10	DC 15.87 V	173.975061	0.351
-20	DC 15.87 V	173.975072	0.414
-30	DC 15.87 V	173.975082	0.471

UHF TEST RESULTS

(1) Frequency stability versus input voltage (Supply nominal voltage is 13.8V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	400.025	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 13.8 V	400.025157	0.392
40	DC 13.8 V	400.025144	0.360
30	DC 13.8 V	400.025135	0.337
20	DC 13.8 V	400.025123	0.307
10	DC 13.8 V	400.025133	0.332
0	DC 13.8 V	400.025142	0.355
-10	DC 13.8 V	400.025156	0.390
-20	DC 13.8 V	400.025171	0.427
-30	DC 13.8 V	400.025182	0.455

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	460.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 13.8 V	460.000177	0.385
40	DC 13.8 V	460.000162	0.352
30	DC 13.8 V	460.000156	0.339
20	DC 13.8 V	460.000136	0.296
10	DC 13.8 V	460.000151	0.328
0	DC 13.8 V	460.000162	0.352
-10	DC 13.8 V	460.000175	0.380
-20	DC 13.8 V	460.000183	0.398
-30	DC 13.8 V	460.000198	0.430

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	519.975	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 13.8 V	519.975196	0.377
40	DC 13.8 V	519.975174	0.335
30	DC 13.8 V	519.975155	0.298
20	DC 13.8 V	519.975133	0.256
10	DC 13.8 V	519.975157	0.302
0	DC 13.8 V	519.975179	0.344
-10	DC 13.8 V	519.975192	0.369
-20	DC 13.8 V	519.975202	0.388
-30	DC 13.8 V	519.975215	0.413

(2) Frequency stability versus input voltage (Battery limiting voltage is 11.73V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	400.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 11.73 V	400.025187	0.467
40	DC 11.73 V	400.025166	0.415
30	DC 11.73 V	400.025148	0.370
20	DC 11.73 V	400.025129	0.322
10	DC 11.73 V	400.025141	0.352
0	DC 11.73 V	400.025159	0.397
-10	DC 11.73 V	400.025171	0.427
-20	DC 11.73 V	400.025187	0.467
-30	DC 11.73 V	400.025193	0.482

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	460.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 11.73 V	460.000188	0.409
40	DC 11.73 V	460.000171	0.372
30	DC 11.73 V	460.000149	0.324
20	DC 11.73 V	460.000128	0.278
10	DC 11.73 V	460.000145	0.315
0	DC 11.73 V	460.000158	0.343
-10	DC 11.73 V	460.000173	0.376
-20	DC 11.73 V	460.000196	0.426
-30	DC 11.73 V	460.000203	0.441

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	519.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 11.73 V	519.975195	0.375
40	DC 11.73 V	519.975173	0.333
30	DC 11.73 V	519.975154	0.296
20	DC 11.73 V	519.975132	0.254
10	DC 11.73 V	519.975158	0.304
0	DC 11.73 V	519.975177	0.340
-10	DC 11.73 V	519.975189	0.363
-20	DC 11.73 V	519.975199	0.383
-30	DC 11.73 V	519.975206	0.396

(3) Frequency stability versus input voltage (Battery Fully Charged voltage is 15.87V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	400.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 15.87 V	400.025188	0.470
40	DC 15.87 V	400.025166	0.415
30	DC 15.87 V	400.025143	0.357
20	DC 15.87 V	400.025127	0.317
10	DC 15.87 V	400.025141	0.352
0	DC 15.87 V	400.025163	0.407
-10	DC 15.87 V	400.025182	0.455
-20	DC 15.87 V	400.025202	0.505
-30	DC 15.87 V	400.025211	0.527

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	460.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 15.87 V	460.000186	0.404
40	DC 15.87 V	460.000163	0.354
30	DC 15.87 V	460.000142	0.309
20	DC 15.87 V	460.000128	0.278
10	DC 15.87 V	460.000139	0.302
0	DC 15.87 V	460.000152	0.330
-10	DC 15.87 V	460.000174	0.378
-20	DC 15.87 V	460.000189	0.411
-30	DC 15.87 V	460.000198	0.430

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	519.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 15.87 V	519.975191	0.367
40	DC 15.87 V	519.975174	0.335
30	DC 15.87 V	519.975156	0.300
20	DC 15.87 V	519.975131	0.252
10	DC 15.87 V	519.975152	0.292
0	DC 15.87 V	519.975176	0.338
-10	DC 15.87 V	519.975191	0.367
-20	DC 15.87 V	519.975205	0.394
-30	DC 15.87 V	519.975216	0.415

7. EMISSION BANDWIDTH


7.1 PROVISIONS APPLICABLE

According to FCC Part 90 Section 90.209: The authorized bandwidth shall be 11.25 KHz for 12.5 KHz

7.2 MEASUREMENT PROCEDURE

- 1). The EUT was placed on a turntable which is 0.8m above ground plane.
- 2). The EUT was modulated by 2.5 KHz Sine wave audio signal, The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing).
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW= 300 Hz, Span =50 KHz.
- 4). Set SPA Max hold. Mark peak, -26 dB.

7.3 TEST SETUP BLOCK DIAGRAM



7.4 MEASUREMENT EQUIPMENT USED:


NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/18/2012	07/17/2013
MODULATION ANALYZER	HP	8920B	3104A03367	07/18/2012	07/17/2013
BROADBAND ANT.	A.H.	SAS-521-4	A0304224	07/18/2012	07/17/2013

7.5 MEASUREMENT RESULT:

VHF TEST RESULTS

26 dB Bandwidth Measurement Result			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	7.76KHz	11.25 KHz	Pass
155.000MHz	7.79KHz	11.25 KHz	Pass
173.975MHz	7.75KHz	11.25 KHz	Pass


Occupied bandwidth of Middle Channel (Maximum) @ 12.5KHz Channel Separation



UHF TEST RESULTS

26 dB Bandwidth Measurement Result			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	7.54KHz	11.25 KHz	Pass
460.000MHz	7.61KHz	11.25 KHz	Pass
519.975MHz	7.57KHz	11.25 KHz	Pass

Occupied bandwidth of Middle Channel (Maximum) @ 12.5KHz Channel Separation



8. UNWANTED RADIATION

8.1 PROVISIONS APPLICABLE

8.1.1 According to Section 90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with 12.5 KHz channel bandwidth:

- (1). On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 KHz removed from f_0 : Zero dB
- (2). On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 5.625 KHz but no more than 12.5 KHz: At least $7.27(f_d - 2.88 \text{ KHz})$ dB
- (3). On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_0 of more than 12.5 KHz: At least $50 + 10 \log(P)$ dB or 70 dB, which ever is lesser attenuation.

8.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.


- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- (14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- (15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by

the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.

(16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.


(17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

8.3 TEST SETUP BLOCK DIAGRAM




SUBSTITUTION METHOD: (Radiated Emissions)

Radiated Below 1GHz



Radiated Above 1 GHz



8.4 MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/18/2012	07/17/2013
TEST RECEIVER	R&S	ESIC	A0304218	07/18/2012	07/17/2013
LOOP ANTENNA	A.H.	SAS-562B	A0304220	07/18/2012	07/17/2013
HORN ANT.	EM	EM-AH-10180	100150	07/18/2012	07/17/2013
BROADBAND ANT.	A.H.	SAS-521-4	A0304224	07/18/2012	07/17/2013

8.5 MEASUREMENT RESULTS:

Measurement Result for 12.5 KHz Channel Separation-50W

On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_o of more than 12.5 KHz: At least $50+10 \log(P)$ dB or 70 dB, which ever is lesser attenuation.

Limit: At least $50+10 \log(P) = 50+10 \log(50) = 67$ (dB)

Measurement Result for 12.5 KHz Channel Separation-35W

On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_o of more than 12.5 KHz: At least $50+10 \log(P)$ dB or 70 dB, which ever is lesser attenuation.

Limit: At least $50+10 \log(P) = 50+10 \log(35) = 65$ (dB)

VHF TEST RESULTS

Measurement Result for 12.5 KHz Channel Separation @ 136.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
136.025	v	0		pass
272.050	v	95.36(-47.58dBm)	67	pass
408.08	v	99.25(-51.47dBm)	67	pass
544.100	v	102.23(-54.45dBm)	67	pass
680.125	v	108.56	67	pass
816.150	v	109.25	67	pass
952.175	v	109.87	67	pass
1088.200	v	110.22	67	pass
1224.225	v	110.84	67	pass
1360.250	v	114.33	67	pass

Measurement Result for 12.5 KHz Channel Separation @ 155.000MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
155.000	v	0		pass
310.000	v	97.82(-50.04dBm)	67	pass
465.000	v	100.25(-52.47dBm)	67	pass
620.000	v	103.48	67	pass
775.000	v	104.82	67	pass
930.000	v	105.62	67	pass
1085.000	v	107.28	67	pass
1240.000	v	108.74	67	pass
1395.000	v	109.63	67	pass
1550.000	v	111.85	67	pass

Measurement Result for 12.5 KHz Channel Separation @ 173.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
173.975	v	0		pass
347.950	v	99.88(-52.10dBm)	61	pass
521.925	v	104.74	61	pass
695.900	v	106.47	61	pass
869.875	v	106.85	61	pass
1043.850	v	107.44	61	pass
1217.825	v	107.96	61	pass
1391.800	v	110.39	61	pass
1565.775	v	111.58	61	pass
1739.750	v	112.56	61	pass

Notes: The emissions were scanned from 30 MHz to 10th harmonics.

UHF TEST RESULTS

Measurement Result for 12.5 KHz Channel Separation @ 400.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
400.025	v	0		pass
800.050	v	96.63(-48.85dBm)	65	pass
1200.08	v	99.52(-51.74dBm)	65	pass
1600.100	v	102.33(-54.55dBm)	65	pass
2000.125	v	105.89	65	pass
2400.150	v	106.77	65	pass
2800.175	v	107.32	65	pass
3200.200	v	109.44	65	pass
3600.225	v	110.23	65	pass
4000.250	v	111.57	65	pass

Measurement Result for 12.5 KHz Channel Separation @ 460.000MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
460.000	v	0		pass
920.000	v	99.36(-51.58dBm)	65	pass
1380.000	v	100.23(-52.45dBm)	65	pass
1840.000	v	103.35	65	pass
2300.000	v	104.75	65	pass
2760.000	v	105.21	65	pass
3220.000	v	106.39	65	pass
3680.000	v	108.77	65	pass
4140.000	v	110.25	65	pass
4600.000	v	111.57	65	pass

Measurement Result for 12.5 KHz Channel Separation @ 519.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
519.975	v	0		pass
1039.950	v	100.52(-52.74dBm)	65	pass
1559.925	v	103.77	65	pass
2079.900	v	105.96	65	pass
2599.875	v	106.52	65	pass
3119.850	v	107.43	65	pass
3639.825	v	108.92	65	pass
4159.800	v	109.77	65	pass
4679.775	v	111.99	65	pass
5199.750	v	113.57	65	pass

Notes: The emissions were scanned from 30 MHz to 10th harmonics.


8.6 EMISSION MASK PLOT

The detailed procedure employed for Emission Mask measurements are specified as following:

- The transmitter shall be modulated by a 2.5 kHz audio signal,
- The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing)


VHF TEST RESULTS

The Worst Emission Mask for 12.5 KHz channel Separation (50W)



UHF TEST RESULTS

The Worst Emission Mask for 12.5 KHz channel Separation (35W)



9. MODULATION CHARACTERISTICS

9.1 PROVISIONS APPLICABLE

According to CFR 47 section 2.1047(a), for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

9.2 MEASUREMENT METHOD

9.2.1 Modulation Limit

- (1). Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1KHz using this level as a reference (0dB) and vary the input level from -20 to +20dB. Record the frequency deviation obtained as a function of the input level.
- (2). Repeat step 1 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

9.2.2 Audio Frequency Response

- (1). Configure the EUT as shown in figure 1.
- (2). Adjust the audio input for 20% of rated system deviation at 1 KHz using this level as a reference (0 dB).
- (3). Vary the Audio frequency from 100 Hz to 10 KHz and record the frequency deviation.
- (4). Audio Frequency Response = $20\log_{10}(\text{Deviation of test frequency}/\text{Deviation of 1 KHz reference})$.




Figure 1: Modulation characteristic measurement configuration

9.3 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
Modulation Analyzer	HP	8920B	3104A03367	07/18/2012	07/17/2013


NOTE: 8920B can generate audio modulation frequency.

9.4 MEASUREMENT RESULT

(A). MODULATION LIMIT:

Middle Channel @ 12.5 KHz Channel Separations

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz	Peak Freq. Deviation At 1000 Hz	Peak Freq. Deviation At 1500 Hz	Peak Freq. Deviation At 3000 Hz
-20	0.26	0.85	0.88	0.90
-15	0.35	0.94	0.96	1.06
-10	0.42	1.23	1.31	1.38
-5	0.55	1.36	1.42	1.47
0	0.66	1.50	1.55	1.58
+5	0.72	1.65	1.68	1.83
+10	0.84	1.74	1.75	1.86
+15	0.91	1.67	1.72	1.77
+20	0.87	1.59	1.66	1.71




(B). AUDIO FREQUENCY RESPONSE:

Middle Channel @ 12.5 KHz Channel Separations

Frequency (Hz)	Deviation (KHz)	Audio Frequency Response(dB)
100	--	--
200	--	--
300	0.11	-13.15
400	0.15	-10.46
500	0.24	-6.38
600	0.26	-5.68
700	0.29	-4.73
800	0.35	-3.10
900	0.43	-1.31
1000	0.52	0.34
1200	0.59	1.44
1400	0.66	2.41
1600	0.74	3.41
1800	0.88	4.91
2000	0.97	5.76
2400	1.27	8.10
2500	1.43	9.13
2800	1.66	10.42
3000	1.78	11.03
3200	1.73	10.78
3600	1.51	9.60
4000	1.11	6.93
4500	0.92	5.30
5000	0.77	3.75
5500	0.55	0.83
6000	0.18	-8.87
6500	0.06	-18.42
7000	0.02	-27.96
7500	0.01	-33.98
9000	--	--
10000	--	--
14000	--	--
18000	--	--
20000	--	--
30000	--	--

Frequency Response of Middle Channel



10. MAXIMUM TRANSMITTER POWER (CONDUCTED OUTPUT POWER)

10.1 PROVISIONS APPLICABLE

Per FCC §2.1046 and §90.205 AND RSS 119 Part 4.1: Maximum ERP is dependent upon the station’s antenna HAAT and required service area.


10.2 TEST PROCEDURE

The RF output of Two-way Radio was conducted to a spectrum analyzer through an appropriate attenuator.

10.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/18/2012	07/17/2013

10.4 TEST CONFIGURATION



10.5 TEST RESULT

The maximum Conducted Power (CP) is
60 W for 12.5 KHz Channel Separation

Calculation Formula: $CP = R + A + L$

* Note:

- CP: The final Conducted Power
- R : The reading value from spectrum analyzer
- A : The attenuation value of the used attenuator
- L : The loss of all connection cables

VHF TEST RESULTS

Conducted Power Measurement Results		
Channel Separation	Channel	Measurement Result (dBm)
		For 46.99dBm(50W)
12.5 KHz	Bottom(136.025MHz)	46.91
	Middle(155.000MHz)	46.96
	Top (173.975MHz)	46.94


UHF TEST RESULTS

Conducted Power Measurement Results		
Channel Separation	Channel	Measurement Result (dBm)
		For 45.44dBm(35W)
12.5 KHz	Bottom(400.025MHz)	45.39
	Middle(460.000MHz)	45.42
	Top (519.975MHz)	45.41


10.6 CONDUCT SPURIOUS PLOT

VHF TEST RESULTS

Conducted Spurious Emission (worst) @ 155.000MHz (30MHz-1GHz)




Conduct Spurious Emission (worst) @ 155.000MHz (1GHz-12.75GHz)




UHF TEST RESULTS

Conducted Spurious Emission (worst) @ 460.000MHz (30MHz-1GHz)



Conduct Spurious Emission(worst) @ 460.000MHz (1GHz-12.75GHz)



NOTE: Only the worst data recorded in the report.

11. TRANSMITTER FREQUENCY BEHAVIOR

11.1 PROVISIONS APPLICABLE

Section 90.214

Time intervals ^{1, 2}	Maximum frequency difference ³	All equipment	
		150 to 174 MHz	421 to 512 MHz
Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels			
t ₁ ⁴	± 25.0 kHz	5.0 ms	10.0 ms
t ₂	± 12.5 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 25.0 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels			
t ₁ ⁴	± 12.5 kHz	5.0 ms	10.0 ms
t ₂	± 6.25 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 12.5 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels			
t ₁ ⁴	± 6.25 kHz	5.0 ms	10.0 ms
t ₂	± 3.125 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 6.25 kHz	5.0 ms	10.0 ms

¹ t_{on} is the instant when a 1 kHz test signal is completely suppressed, including any capture time due to phasing.

t₁ is the time period immediately following t_{on}.

t₂ is the time period immediately following t₁.

t₃ is the time period from the instant when the transmitter is turned off until t_{off}.

t_{off} is the instant when the 1 kHz test signal starts to rise.

² During the time from the end of t₂ to the beginning of t₃, the frequency difference must not exceed the limits specified in § 90.213.

³ Difference between the actual transmitter frequency and the assigned transmitter frequency.

⁴ If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.

11.2 TEST METHOD

TIA/EIA-603 2.2.19

11.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
Signal Generator	AGILENT	E4412B	LR114196	07/18/2012	07/17/2013
Storage Oscilloscope	Tektronix	TDS3052	B017447		2013.07

11.4 DESCRIBE LIMIT LINE OF TRANSMITTER FREQUENCY BEHAVIOR


ton: The switch-on instant of a transmitter is defined by the condition when the output power, measured at the antenna terminal, exceeds 0,1 % of the full output power (-30 dBc).


t1: period of time starting at ton and finishing according to above 11.1

t2: period of time starting at the end of t1 and finishing according to above 11.1

toff: switch-off instant defined by the condition when the output power falls below 0,1 % of the full output power (-30 dBc).

t3: period of time that finishing at toff and starting according to above 11.1







11.5 MEASURE RESULT

VHF test results(WORST)

Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation--Off to On



Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation--On to Off



12. RADIATED EMISSION ON RECEIVING MODE

12.1 PROVISIONS APPLICABLE

FCC Part 15 Subpart B Section 15.209


12.2 TEST METHOD

ANSI C 63.4: 2003

12.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/18/2012	07/17/2013
TEST RECEIVER	R&S	ESIC	A0304218	07/18/2012	07/17/2013
LOOP ANTENNA	A.H.	SAS-562B	N/A	07/18/2012	07/17/2013
HORN ANT.	EM	EM-AH-10180	100150	07/18/2012	07/17/2013
BROADBAND ANT.	A.H.	SAS-521-4	A0304224	07/18/2012	07/17/2013


12.4 MEASURE RESULT (MEASURED AT 3M USING FCC PART15 B LIMITS)
RADIATED EMISSION TEST RESULTS – HORIZONTAL



Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation	Power:	Humidity: 60 %
EUT: Land Mobile Radio	Distance: 3m	
M/N: AM-580		
Mode: Mode 1		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
									cm	degree	
1		97.9000	16.51	13.24	29.75	43.50	-13.75	peak			
2		287.0500	19.18	17.13	36.31	46.00	-9.69	peak			
3	*	351.7167	20.15	19.06	39.21	46.00	-6.79	peak			
4		388.8999	17.99	17.72	35.71	46.00	-10.29	peak			
5		484.2832	13.20	21.95	35.15	46.00	-10.85	peak			
6		776.8999	8.66	28.04	36.70	46.00	-9.30	peak			

RADIATED EMISSION TEST RESULTS – VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Land Mobile Radio
M/N: AM-580
Mode: Mode 1
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		136.6999	23.29	10.91	34.20	43.50	-9.30	peak			
2		159.3333	24.73	9.95	34.68	43.50	-8.82	peak			
3		354.9499	18.24	19.08	37.32	46.00	-8.68	peak			
4	*	388.8999	19.56	19.06	38.62	46.00	-7.38	peak			
5		658.8832	11.90	25.76	37.66	46.00	-8.34	peak			
6		776.8999	7.60	27.19	34.79	46.00	-11.21	peak			

13. AUDIO LOW PASS FILTER RESPONSE

13.1 LIMITS

2.1047(a): Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.

90.242(b)(8): Recommended audio filter attenuation characteristics are given below:

Audio band	Minimum Attenuation Rel. to 1 KHz Attenuation
3 –20 KHz 20 – 30 KHz	$60 \log_{10}(f/3)$ dB where f is in KHz 50dB

13.2. METHOD OF MEASUREMENTS


The rated audio input signal was applied to the input of the audio low-pass filter (or of all modulation stages) using an audio oscillator, this input signal level and its corresponding output signal were then measured and recorded using the FFT Digital Spectrum Analyzer. Tests were repeated at different audio signal frequencies from 0 to 50 KHz.

13.3 TEST DATA


12.5 KHZ CHANNEL SPACING, F3E, FREQUENCY OF ALL MODULATION STATES

Frequency (KHz)	Audio In (dBV)	Audio out (dBV)	Attenuation (Out_In) dB	Attenuation Rel. to 3 KHz (dB)	Recommended Attenuation (dB)
0.1	-74.38	-30.33	46.3	-35.4	
0.2	-74.38	-18.79	55.8	-26.9	
0.4	-74.38	-5.45	71.5	-13.5	
0.6	-74.38	0.67	75.8	-6.8	
0.8	-74.38	4.11	79.7	-3.5	
1.0	-74.38	6.47	81.8	0.0	
1.5	-74.38	8.68	83.6	2.1	
2.0	-74.38	8.72	84.5	1.5	
2.5	-74.38	7.54	82.7	0.8	
3.0	-74.38	5.47	81.2	-1.5	0
3.5	-74.38	2.23	77.3	-4.2	-5
4.0	-74.38	-2.76	73.7	-9.5	-8
4.5	-74.38	-8.57	67.3	-15.3	-13
5.0	-74.38	-14.23	61.6	-20.6	-15
6.0	-74.38	-22.44	53.2	-29.3	-19
7.0	-74.38	-30.63	45.8	-37.6	-24
8.0	-74.38	-38.76	36.2	-45.8	-28
9.0	-74.38	-63.00	14.5	-66.4	-29
10.0	-74.38	-63.00	14.5	-66.9	-32
12.0	-74.38	-63.00	14.5	-66.9	-37
14.0	-74.38	-63.00	14.5	-66.9	-41
16.0	-74.38	-63.00	14.5	-66.9	-45
18.0	-74.38	-63.00	14.5	-66.9	-48
20.0	-74.38	-63.00	14.5	-66.9	-50
25.0	-74.38	-63.00	14.5	-66.9	-50
30.0	-74.38	-63.00	14.5	-66.9	-50
35.0	-74.38	-63.00	14.5	-66.9	-50
40.0	-74.38	-63.00	14.5	-66.9	-50
45.0	-74.38	-63.00	14.5	-66.9	-50
50.0	-75.76	-61.00	14.5	-66.9	-50

Note: Due to the difficulty of measuring the Frequency Response of the internal low-pass filter, the Frequency Response of All Modulation States is performed to show the roll-off at 3 KHz in comparison with the recommended audio filter attenuation.



APPENDIX I
PHOTOGRAPHS OF SETUP
RADIATED TEST SETUP




APPENDIX II
EXTERNAL VIEW OF EUT
WHOLE VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT




FRONT VIEW OF EUT



BACK VIEW OF EUT




LEFT VIEW OF EUT




RIGHT VIEW OF EUT




OPEN VIEW-1 OF EUT




OPEN VIEW-2 OF EUT



INTERNAL VIEW-1 OF EUT




INTERNAL VIEW-2 OF EUT




INTERNAL VIEW-3 OF EUT




INTERNAL VIEW-4 OF EUT




INTERNAL VIEW-5 OF EUT



INTERNAL VIEW-6 OF EUT



INTERNAL VIEW-7 OF EUT



----END OF REPORT----