

INTERTEK TESTING SERVICES

Analysis Report

The equipment under test (EUT) is a PDA operating at 915.95MHz – 927.00MHz. The EUT was powered by DC 3.0V (UM-3 / R6 / AA 1.5V*2). For more detail information pls. refer to the user manual.

Modulation Type: FSK

Antenna Type: Integral antenna

Antenna Gain: 0dBi

The nominal conducted output power specified: 7.0dBm (Tolerance: +/- 2dB)

According to the KDB 447498:

The maximum conducted output power for the EUT is 7.58dBm in the frequency 921.80MHz which is within the production variation.

The minimum conducted output power for the EUT is 7.56dBm in the frequency 915.95MHz which is within the production variation.

The maximum conducted output power specified is 9.0dBm = 7.94mW

The source- based time-averaging conducted output power
= $7.94 * \text{Duty cycle mW} < 7.94$ (Duty Cycle<100%)

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$
= $3.0 * 5 / \sqrt{0.927}$ mW
= 15.6 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.