



Bondale Electronics Ltd.

博 钜 电 子 有 限 公 司

Unit11, 12/F, BLK B Veristrong ind. Ctr, 34-36 Au Pui Wan Street, Fo Tan Shatin, N.T. HK

Tel: 852 2345 0215 Fax: 852 27978191

Email: antenna@bondale.com

Website: www.bondale.com



COVER OF SPECIFICATION 规 格 书

No.: AN03445

CUSTOMER'S NAME :

客户名称

金 进

CUSTOMER'S MODEL NO. :

客户型号

CUSTOMER'S PART NO. :

客户料号

E02520

PRODUCT NAME :

产品名称

Rubber Antenna

OUR MODEL NO. :

本公司型号

G-RA0025179005-SZ478

This Specification is Composed of Under Listed (Samples be attached)

本规格书由以下内容组成(样品另附) :

NO.	Items(项目)	Pages(页码)
1	Certificate Of Conformance ROHS(环保证明书)	1
2	Product Drawing (产品图)	1
3	Specification of Product (规格书内容)	1
4	Capability Test Report (性能测试报告)	3
Total pages(包含本页)		共 7 页

Please fax back this brefile page with authorized signature and company chop as customer's approval on samples,Thanks! (如果此产品得到您的确认,请传回本页给我们.)

Customer Sign 客户签名		Customer Company Chop 客户公章	
-----------------------	--	----------------------------------	--



Bondale Electronics Ltd.

博钜电子有限公司

Unit11, 12/F, BLK B Veristrong ind. Ctr, 34-36 Au Pui Wan Street, Fo Tan Shatin, N.T. HK

Tel: 852 2345 0215 Fax: 852 27978191

Email: antenna@bondale.com

Website: www.bondale.com

TO: 金 进

DATE: 2023-03-10

File NO.: AN03445

CERTIFICATE OF CONFORMANCE ROHS

Customer Part No. : E02520

Bondale Part No. : G-RA0025179005-SZ478

Description : Rubber Antenna

We, Bondale Electronics Ltd. assured that the above mentioned item: G-RA0025179005-SZ478 is fully comply with the EU directive 2011/65/EU, (EU)2015/863 and packaging directive 94/62/EC and that its content of hazardous substances is below the values as listed:

ROHS critical values:

*Cadmium(Cd)			under 100 ppm
*Lead (Pb)	Generally		under 1,000 ppm
	Be Exempted	Products that contain Copper alloy components	under 40,000 ppm
		Product that contain Steel alloy components	under 3,500 ppm
		Product that contain aluminum alloy components	under 4,000 ppm
*Mercury (Hg)			under 1,000 ppm
*Hexavalent Chormium (Cr6+)			under 1,000 ppm
*PBBs			under 1,000 ppm
*PBDEs			under 1,000 ppm
*DEHP			under 1,000 ppm
*BBP			under 1,000 ppm
*DBP			under 1,000 ppm
*DIBP			under 1,000 ppm

Packaging directive 94/62/EC critical values:

*Packaging (Pb + Cd +Hg +Cr6+) under 100 ppm

Expemted below:

If the above mentioned item is reprocessed by customer, we wouldn't promise and assure the content of hazardous substances of the product item.

On behalf of

Bondale Electronics Ltd.

ROHS green chop and GPMS spokesman sign(Rohs綠色印章 + GPMS負責人簽名): 潘卫青


Yours sincerely,

---GREEN PRODUCT MANAGEMENT SYSTEM (GPMS)---

---綠色產品管理系統---




REV.	ISSUE FOR	OLD DRAWING NO.	APPROVED	80<L<=250	±0.50
①	根据实际情况把透明PVC胶管的长度由48.0 ^{+5.0} _{-0.0} 改为15.0 ^{+5.0} _{-0.0} MM.	G-RA0025179005-SZ478(A)	曹新学	25<L<=80	±0.40
②	用客户机壳重新调试频率,芯线长度由 69.0±2.0改为80.5±2.0.	G-RA0025179005-SZ478(B)	陸 東	8<L<=25	±0.30
③	应客户要求,将频率由915±10MHz改为915±15MHz.	G-RA0025179005-SZ478(C)	陸 東	L<=8	±0.20
				線性尺寸L	未注尺寸偏差
				未注明公差	



注：

1. 工作頻率為:915±15MHz.
2. 同軸線線芯外露部分套一截透明PVC膠管以保護芯线,長度為15.0^{+5.0}_{-0.0} mm
3. ▲ 為重點管控尺寸.
4. ⊕ 為做FAI尺寸.
5. 客户PARTNO:E02520



TITLE	Rubber Antenna	版次	SCALE	1 : 1	DRAWN	陆 东	14/03-23
PART NAME	G-RA0025179005-SZ478	D	MATERIAL		INSPECTED	陈 东	14/13-23
BONDALE ELECTRONICS LTD.			HANDLING		APPROVED		
			PROJECTION (視角)	☐	☉	SHEET	

RUBBER ANTENNA SPECIFICATION

Customer : 金 进
Specification No.: AN03445
Model No.: G-RA0025179005-SZ478

1, Application

The antenna specified in this specification is applicable for the radio-communication

2, Dimensions

As per Drawing No. G-RA0025179005-SZ478 attached.

3, Materials

As specified in drawing No. G-RA0025179005-SZ478


4, Electrical Characteristics

- i) Resonate Frequency : 915±15 MHz
- ii) Impedance : 50 ohm Nominal
- iii) Radiation Pattern : Omni Directional
- iv) Polarization : Vertical
- v) Standing Wave Ratio (S.W.R): 2.0 or less
- vi) Insulation resistance : 500 M ohm at DC 500V

5, Others:

Any modification of this specification has to be agreed by us

Prepared By:



Checked By:




Approval:





Capability Test Report


Specification NO.: AN03445
Model NO.: G-RA0025179005-SZ478



增益测试



增益测试



	增益测试数据	
频率	增益(dBi)	效率
900MHz	-0.74	44.52%
905MHz	-0.21	50.13%
910MHz	0.09	52.26%
915MHz	0.22	51.99%
920MHz	0.17	50.81%
925MHz	-0.02	48.42%
930MHz	-0.28	45.44%